

The diagram is a large square grid composed of smaller squares. The grid is divided into several distinct regions:

- Top-Left Region:** A square area with a checkerboard pattern of light gray and white squares.
- Top-Right Region:** A square area with a checkerboard pattern of dark gray and light gray squares.
- Bottom-Left Region:** A square area with a checkerboard pattern of light gray and white squares.
- Bottom-Right Region:** A square area with a checkerboard pattern of dark gray and light gray squares.
- Central Region:** A large square area with a diagonal pattern of light gray and white squares.

A green zigzag line is drawn across the central region, starting from the top-left corner and ending at the bottom-right corner. The line follows a path that zigzags between the diagonal and the edges of the central square.

On the right side of the grid, there are vertical labels for each row, numbered 1 through 9, indicating the row index.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).