

The image shows a 10x10 grid with several distinct patterns. The top-left 5x5 area contains a checkerboard pattern of gray and white squares. The top-right 5x5 area contains a checkerboard pattern of gray and white squares. The bottom-left 5x5 area contains a checkerboard pattern of gray and white squares. The bottom-right 5x5 area contains a checkerboard pattern of gray and white squares. The central 10x10 area is filled with diagonal lines. A green zigzag line runs vertically through the center of the grid, starting from the top and ending at the bottom. The grid is divided into four quadrants by a vertical line at column 5 and a horizontal line at row 5.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).

--