

The diagram consists of a large grid. The left portion of the grid has a gray and white checkerboard pattern. A vertical column of gray squares separates this from the right portion. The right portion has a white background with a black grid. A prominent green zigzag line runs vertically through the center of the right portion. To the right of this is another vertical column of gray squares, followed by a final column of numbers 1 through 9, repeated twice. The numbers are arranged in two columns: the first column contains 1, 2, 3, 4, 5, 6, 7, 8, 9 from bottom to top, and the second column contains 9, 8, 7, 6, 5, 4, 3, 2, 1 from bottom to top.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).