

The diagram consists of a large grid. The background is a checkerboard pattern of gray and white squares. A central vertical band is filled with a dense pattern of green zigzag lines. To the left of this band, there are several vertical columns of diagonal lines. On the right side, a vertical column of numbers (1 through 9) is aligned with the grid lines. The numbers are arranged in a specific pattern, with some numbers appearing multiple times in a column. The overall structure suggests a technical drawing or a puzzle, possibly related to a specific field like architecture or engineering.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).