

The diagram consists of a large grid. The background is a checkerboard pattern of gray and white squares. Overlaid on this are several features:

- A vertical column of gray squares on the left side, spanning from the bottom to the top.
- A small 3x3 gray square located in the bottom right corner.
- Diagonal lines running from the top-left to the bottom-right across the grid.
- Green zigzag lines forming a series of vertical columns, primarily in the center and right portions of the grid.
- A vertical axis on the far right, labeled with numbers 1 through 9, corresponding to the rows.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).