

A 10x10 grid with various patterns. The grid is labeled with numbers 1-9 on the right side. The patterns are as follows:

- Top-left (rows 1-4, columns 1-4):** Checkerboard pattern (alternating light and dark gray squares).
- Top-right (rows 1-4, columns 5-10):** Diagonal line pattern (alternating light and dark gray squares along the diagonal).
- Center (rows 5-8, columns 5-10):** Green zigzag pattern (alternating light and dark gray squares along the diagonal).
- Bottom-right (rows 9-10, columns 5-10):** Solid gray pattern (all squares are dark gray).

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).