

The diagram is a large grid composed of several distinct regions:

- Top-Left Region:** A square grid of alternating light and dark gray squares, forming a checkerboard pattern.
- Top-Middle Region:** A square grid where each small square is further divided into four smaller triangles by a diagonal line from the top-left to the bottom-right. The triangles are shaded in a repeating pattern.
- Top-Right Region:** A square grid of alternating light and dark gray squares, similar to the top-left region.
- Bottom-Left Region:** A square grid of alternating light and dark gray squares, similar to the top-left region.
- Bottom-Middle Region:** A square grid where each small square is further divided into four smaller triangles by a diagonal line from the top-left to the bottom-right. The triangles are shaded in a repeating pattern.
- Bottom-Right Region:** A square grid of alternating light and dark gray squares, similar to the top-right region.

A prominent green zigzag line runs vertically through the center of the grid, starting from the bottom and extending towards the top. The line is composed of many small, sharp, triangular peaks and valleys, creating a complex, jagged path. The line is colored a bright green and stands out against the gray and white background.

Color in the QR code modules. If a module contains only a diagonal line, color only the upper left half. Only color in modules that lie on the green line.

For each (interleaved) data digit (4 consecutive bits along the green line), fill it inside the block table. Interpret squares with a diagonal line as inverted.

0 : 0000	8 : 1000
1 : 0001	9 : 1001
2 : 0010	A : 1010
3 : 0011	B : 1011
4 : 0100	C : 1100
5 : 0101	D : 1101
6 : 0110	E : 1110
7 : 0111	F : 1111

[illegible][illegible][illegible][illegible]

Now, decode the data. Read the data block-by-block, essentially concatenating the blocks. The first digit indicates the encoding mode: 1 for numeric, 2 for alphanumeric, 4 for byte. If it's not byte, this tutorial will not work - sorry! The next two digits represent the number of characters to read. After, each two digits together form a number from 0 to 255, representing the ASCII values. It's easy to memorize: 31 (hex) is '1', 41 is 'A', 61 is 'a', 2E is '.', 2F is '/', and 3A is ':' (full table on page 7).