

Stainless Steel Cam Locks and Hatch Fasteners

Order numbers • 316 Stainless steel hatch fasteners, flush type with separate key

Installation: Drill hole: 22.5 mm Ø / 7/8" Back set to center hole: 30 mm – 1 3/16"

To order sets with clearance:









Hatch fastener sets complete: Set: Ix housing, Ix mounting plate, Ix cam. Operating Keys to be ordered separately


43.206 6 mm - ½" 43.218 18 mm - ¾" 43.222 22 mm 7/8" 43.228 28 mm 1 1/8"	(18 mm body) (18 mm body) (18 mm body) (18 mm body)	#43.206	#43.218	#43.222	#43.228
43.224 24 mm - 1" 43.236 36 mm 1 3/8" 43.240 40 mm 1 13/16 43.246 46 mm 1 3/4"	(36 mm body) (36 mm body) (36 mm body) (36 mm body)	#43.224	36	#43.240	#43.246
43.238 38 mm	(50 mm body) (50 mm body) (50 mm body) (50 mm body)	38	50	50 51 31 31 31 31 31 31 31 31 31 31 31 31 31	#43.260
43.268 2 11/16" 68 mm 43.281 3 1/8" - 80 mm 43.284 3 1/4" - 84 mm 43.290 3 1/2" - 90 mm	(3 1/8" size body) (3 1/8" size body) (3 1/8" size body) (3 1/8" size body)				




43.687K Hatch fastener, key operated 18 mm body



#43.280; 80 mm body (3 1/8")






#43.687K Key operated 18 mm body 8 mm max. material thickness.

Olperating Keys









#43.180 Key zamac Mounting plate with holes 43.295