


























Order number	Material	Backset	Specifics	Finish
		 1  2  3 standard is round corners; specify square or 3/8" radius otherwise	 Thickness lock case 5/8" or 15 mm	
14.220.266	Bbrass	55 mm	Latch uses 9x9 mm spindle	Polished Chrome Plated
				
14.251	Brass		Strike plate passage lip 29 mm	Chrome plate brass
14.2511	Brass		Strike plate passage lip cut and bend 17 mm	Chrome plate brass
		 1  2  3 standard is round corners; specify square or 3/8" radius otherwise	  Insert #22.7000 with rose #16.954 thumb-turn #16.90W and indicator #16.91W	
14.17W	Stainless steel	55 mm	Works with Thumb-turn	Satin or Polished Stainless steel
		 1  2  3 standard is round corners; specify square or 3/8" radius otherwise		
14.17Z.508	Stainless steel	55 mm	Works with Profile Cylinder	Satin Stainless steel
14.17Z.308	Stainless steel			Polished Stainless steel
				
14.242.508	Stainless steel		Strike plate dead bolt	Satin Stainless Steel
14.242.308	Stainless steel		Strike plate dead bolt	Polished Stainless Steel

For different options like finish and other configurations, please contact our office sales@izerwaren.com