


Practical 1 - Empirical Analysis

ThreeSumA - Timing experiments

Algorithm	Input	Time	Number of Triples
ThreeSumA	8ints.txt	0.0	4
	1Kints.txt	0.256	70
	2Kints.txt	1.923	528
	4Kints.txt	15.967	4039
	8Kints.txt	138.605	32074

ThreeSumA Timing Graph

Three Sum A - Timing




ThreeSumB - Timing Experiments


Algorithm	Input	Time	Number of Triples
ThreeSumA	8ints.txt	0.001	4
	1Kints.txt	0.032	70
	2Kints.txt	0.114	528

	4Kints.txt	0.443	4039
	8Kints.txt	1.483	32074

ThreeSumB Timing Graph



ThreeSumA versus ThreeSum B - timing graph



Questions:

Which algorithm performs better (i.e. take less time in relation to the size of the input)?

ThreeSumB performs better, with the exception of the 8ints input.

Why do you think this is the case?

In ThreeSumA, the algorithm uses three nested for loops in order to find the triplets.

As we can see in the above timing graph, while the solution could work for smaller inputs (see 8ints), it is not maintainable for larger inputs.

In ThreeSumB, the triplets are found using a binary search. It is interesting to see that this algorithm takes longer for the smallest N (8 ints). This is because the array needs to be sorted in order to be able to perform a binary search. For that reason, it makes sense to use the algorithm ThreeSumB for larger inputs, where the sorting is justified. The binary search allows for far quicker output and it is scalable, as opposed to the ThreeSumA algorithm.