```
Hermes[@T.I]
ROLE: SYSTEM
  Frag SystemPrompt[@T]                                                    ] 1
// Config-supplied conversation turns (prefill_messages_file)
Frag PrefillMessages[@T]                                                   ] 2
// Replaces the middle of the transcript with one summary row.
◇ If sys.number_of_compactions[@T] == 1:                                   ]
  Frag ProtectedFirstMessages[@T]                                          ] 3
// The summary row's role is chosen so user/assistant alternation stays valid on both sides of it.
Frag CompactionSummary[@T]                                                 ]
// ── REPLAYED HISTORY (completed turns) ──────────────────────────────
// A turn is one run_conversation() call: one inbound ask, a run of sub-steps, and a closing row that may be absent.
Name C := sys.last_compaction_turn[@T] // 0 while no compaction has occurred ]
// ── remaining replayed turns ──                                          ]
↻ ForEach t : @C + 1...@T                                                  ]
  ROLE: USER                                                               ]
    ◇ If @t == @C + 1:                                                     ]
      Frag FirstTurnAfterCompaction[@t]                                    ]
    ◇ Else:                                                                ]
      Frag InputMemoriesAndPlugins[@t]                                     ]
  // one HistoryStep per model response that did not close the turn; only the permanent kinds
  (tool_round, continuation, user_correction) survive into a completed turn ] 4
  ↻ ForEach i : @t.substeps                                                ]
    Frag HistoryStep[@t, i]                                                ]
  // absent when the turn was stopped before any model reply; the next ask then follows directly and the
  two user rows are merged on the wire                                     ]
  ◇ If sys.turn_has_closing_reply[@t]:                                     ]
    Frag TurnClosingReply[@t]                                              ]
// ── CURRENT TURN ────────────────────────────────────────────────────
// the inbound ask, composed live; the composed bytes are stamped on the row and are what Mark 4 replays on
later turns                                                                ] 5
ROLE: USER                                                                 ]
  Frag InputMemoriesAndPlugins[@T]                                         ]
↻ ForEach i : @T.substeps[:-1]                                             ]
  Frag HistoryStep[@T, i]                                                  ] 6
```