HistoryStep[@t, i] RolesFrag

◇ If sys.substep_kind[@t.i] == tool_round:

Frag ToolRound[@t, i]

◇ Else:

⎇ Switch sys.substep_kind[@t.i]:

// the reply hit the output cap, the fragment is model output until the cap

Case continuation:

ROLE: ASSISTANT

resp.fragment[@t.i]

ROLE: USER

◆ CONTINUATION_PROMPT(sys.dropped_tool_names[@t.i])

// the user typed /steer while the model was replying

// only the in-flight request is cancelled; what was on screen is kept, then the correction lands as a real user row

Case user_correction:

ROLE: ASSISTANT

resp.visible_text_before_interruption[@t.i]

ROLE: USER

env.user_correction[@t.i]

// the model tried to stop and a stop-gate sent it back

// live turn only: on later turns the nudge is gone

Case provisional_answer:

◇ If (@t == @T):

ROLE: ASSISTANT

resp.provisional_answer[@t.i]

⎇ Switch sys.stop_gate[@T.i]:

// edited code with no passing verification newer than the edit

Case unverified_edits:

ROLE: USER

◆ VERIFY_BEFORE_STOPPING_NUDGE(sys.files_changed_this_turn[@T])

Case open_kanban_task:

ROLE: USER

◆ CLOSE_KANBAN_TASK_NUDGE

// the model returned nothing after a tool round

Case empty_reply:

◇ If (@t == @T):

ROLE: ASSISTANT

◆ EMPTY_REPLY_PLACEHOLDER

ROLE: USER

◆ EMPTY_REPLY_NUDGE

// finish_reason=tool_calls but the tool_calls array was empty

Case dropped_tool_call:

◇ If (@t == @T):

ROLE: ASSISTANT

resp.visible_text[@t.i]

ROLE: USER

◆ DROPPED_TOOL_CALL_NUDGE