SystemPrompt[@t] `StrFrag`

```
// ── SETUP ──────────────────────────────────────────────────────────
// The system prompt is built once per session and rebuilt only at a compaction boundary (a resumed session restores the same bytes from the session DB).
// $B is the turn of that build: anything indexed [@$B] was read then, not on the current turn; anything unindexed is fixed for the agent's lifetime.
  Name B :=
  sys.system_prompt_build_turn[@t] // 1 until the first compaction, then the latest compacti
// ── stable tier ──
// SOUL.md persona file when present, else the hardcoded identity.
  ◇ If sys.soul_md_loaded[@B]:
    sys.soul_md_identity[@B]
  ◇ Else:
    ◆ DEFAULT_AGENT_IDENTITY
// Two variants; the skill-pointer one needs both the skill_view tool and the hermes-agent skill in the skills index rendered below.
  ◇ If sys.skill_view_tool_enabled
       and sys.hermes_agent_skill_in_skills_index[@B] :
    ◆ HERMES_AGENT_HELP_GUIDANCE // docs URL + skill_view pointer
  ◇ Else:
    ◆ HERMES_AGENT_HELP_GUIDANCE_NO_SKILLS // docs URL only
// config agent.task_completion_guidance
  ◇ If sys.task_completion_guidance_enabled:
    ◆ TASK_COMPLETION_GUIDANCE // finish the job / no fabrication
// config agent.parallel_tool_call_guidance
  ◇ If sys.parallel_tool_call_guidance_enabled:
    ◆ PARALLEL_TOOL_CALL_GUIDANCE // batch independent tool calls
// Tool-aware guidance blocks, each gated on its own tool being in the toolset.
  ◇ If sys.memory_tool_enabled:
    ◇ If sys.memory_store_enabled:
      ◆ MEMORY_GUIDANCE // MEMORY.md / USER.md write rules
    ◇ ElseIf sys.user_profile_enabled:
      ◆ USER_PROFILE_GUIDANCE // narrower USER.md-only variant
  ◇ If sys.session_search_tool_enabled:
    ◆ SESSION_SEARCH_GUIDANCE
  ◇ If sys.skill_manage_tool_enabled:
    ◆ SKILLS_GUIDANCE
// only when spawned by the kanban dispatcher
  ◇ If sys.kanban_worker:
    ◆ KANBAN_GUIDANCE // worker/orchestrator lifecycle
  ◇ If sys.tools_loaded:
    ◆ STEER_CHANNEL_NOTE // how /steer text arrives mid-turn
// config agent.tool_use_enforcement
  ◇ If sys.tool_use_enforcement_selected:
    ◆ TOOL_USE_ENFORCEMENT_GUIDANCE // call tools, don't narrate them
      ◇ If sys.model_family == google:
        ◆ GOOGLE_MODEL_OPERATIONAL_GUIDANCE
// config agent.execution_guidance
  ◇ If sys.execution_guidance_selected:
    // execution_guidance_text(valid_tool_names)
    ◆ EXECUTION_GUIDANCE(sys.valid_tool_names)
// Alibaba returns a wrong model name
  ◇ If sys.provider == alibaba:
    ◆ MODEL_IDENTITY_OVERRIDE(sys.model)
// build_environment_hints() (WSL, Termux…)
sys.environment_hints
// coding_system_prompt_parts(): brief, then the workspace snapshot, then operator instructions — the same order whether or not a snapshot exists.
  ◇ If sys.coding_posture_active:
    ◆ CODING_OPERATING_BRIEF
    // ── context tier ──
      ◇ If sys.workspace_snapshot[@B]:
        sys.workspace_snapshot[@B] // git state / workspace summary
      ◇ If sys.coding_operator_instructions:
        ◆ CODING_OPERATOR_INSTRUCTIONS(sys.coding_operator_instructions) // from co
// tools/env_probe.get_environment_probe_line(); empty when the local Python toolchain is default
sys.python_toolchain_probe_line[@B]
// only in a bot's canonical "Bot Chat" session
  ◇ If sys.bot_mode_session:
    ◆ BOT_MODE_TEAMMATE_PROTOCOL
    sys.capability_epoch_line[@B]
// names the active Hermes profile + its paths
◆ ACTIVE_PROFILE_NOTE(sys.active_profile, sys.hermes_home)
// per-platform hint (built-in, plugin-registered, or config-supplied)
sys.platform_hint
// caller-supplied system_message argument
  ◇ If sys.caller_system_message:
    sys.caller_system_message
// Project context files; subagents set skip_context_files.
  ◇ If not sys.skip_context_files:
    // first match wins: HERMES.md, AGENTS.md, CLAUDE.md, .cursorrules (from the context cwd; the Hermes install tree is refused as a fallback cwd)
      Name projectFile := firstPresentContextFile(sys.context_cwd)[@B]
      ◇ If projectFile:
        ◆ PROJECT_CONTEXT_HEADER
        // the body is scanned for injection patterns before it can enter the prompt
          ◇ If injectionPatternsFound(projectFile.content):
            ◆ CONTEXT_FILE_BLOCKED_PLACEHOLDER(projectFile.Name)
          ◇ Else:
            truncate(projectFile.content, sys.context_length)
// ── volatile tier ──
// skills index rendered at the build (skills can change during a session)
  ◇ If sys.skills_tools_enabled:
    buildSkillsIndex(sys.valid_tool_names, sys.skills_dirs)[@B]
// MEMORY.md / USER.md snapshots taken at the build
  ◇ If sys.memory_store_enabled:
    sys.memory_md_block[@B]
  ◇ If sys.user_profile_enabled:
    sys.user_md_block[@B]
// external memory provider block
  ◇ If sys.memory_manager_present:
    sys.memory_provider_block[@B]
// plugin sections rendered at the build (after_memory anchor)
  ↻ ForEach section : sys.plugin_prompt_sections[@B]
    section.framed_content
// Bot Chat sessions get the zone only, no dates.
  ◇ If sys.bot_mode_session:
    ◆ TIMEZONE_LINE(sys.timezone)
  ◇ Else:
    // day precision, with zone/offset
    ◆ CONVERSATION_STARTED_LINE(sys.session_start_date, sys.timezone)
    // only when the build fell on a later day than the session start
      ◇ If sys.date[@B] ≠ sys.session_start_date:
        ◆ TODAY_AS_OF_REBUILD_LINE(sys.date[@B])
  ◇ If sys.pass_session_id:
    ◆ SESSION_ID_LINE(sys.session_id)
◆ MODEL_PROVIDER_PLATFORM_LINES(sys.model, sys.provider, sys.platform)
// Not part of the [@$B] build: appended to the cached prompt on every request. A subagent's task brief rides here (see the subagent note after Mark 6).
  ◇ If sys.ephemeral_system_prompt:
    sys.ephemeral_system_prompt
```