

CC2 - Week 5 - Spiral 2 Submission

Nolan Downey - ndowney@nd.edu

Changes from Spiral 1 to Spiral 2 are marked in red. Everything I found in common between Professor Morrison's solution and mine stayed in black, and unnecessary elements were removed

Problem 3 - Nolan Downey

1) Identify Objectives

- a. Create a class which contains the four different elements
 - i. URL - string
 - ii. Website Header - string
 - iii. Date Visited - string
 - iv. Time Visited - string
- b. Create a main driver which reads in the information from a text file and stores it in the class
- c. Use a data structure to store the classes, then overload the ostream operator to print out the elements in the specific order required

2) Identify Risks and Alternatives

- a. Risk: Use a Hash Table to easily store the information
- b. Alternative: Have to keep the elements in the order that they are accessed
- c. Risk: Do not know how many websites are going to be entered
- d. Alternative: Store the websites into a data structure that can handle an unknown number - **can't use an array**
- e. Risk: Need to know whether the characters are in Unicode or ASCII
- f. Alternative: We can assume the characters will be in ASCII because they will be run on the Notre Dame computers
- g. Risk: Ensure that the right number of arguments is run on the command line
- h. Alternative: Write a function that ensures the right number of arguments is given
- i. Risk: Duplicates can be given in a browser history
- j. Alternative: Use a data structure that can take in multiple versions of similar elements

3) Product Testing and Development

- a. Use a `std::vector` to store the class Site
- b. **Create an empty `std::vector`**
- c. The class Site should contain a constructor and an overloaded operator to store the elements from the text file and then a private element for each data type of the elements of the browsing history
- d. As the elements are read from the data file, they are stored into the class Site, then each class is pushed into the vector using the `.push_back()` method
- e. The following testing method displays the logic behind the approach
- f. Also the elements will be stored in the order that they are accessed
- g. **Use smart iterator to print the results in order**

Vector	
0	Element 1 - Class Site - URL

	<ul style="list-style-type: none"> - Website Header - Date Visited - Time Visited
1	Next Element - Class Site <ul style="list-style-type: none"> - URL - Website Header - Date Visited - Time Visited
...7	...std::vector has initial size of 8

Problem 1 - Connor Ruff

1) Identify Objectives

- Create a class which contains the five different elements
 - Song ID - unsigned int
 - Artist/Band Name - string
 - Song Title - string
 - Album Name - string
 - Year Recorded - unsigned int
- Create a main driver which reads in the information from a text file and stores it in the class
- Use a data structure to store the classes, then overload the ostream operator to print out the elements in the specific order required

2) Identify Risks and Alternatives

- Risk: Use a Hash Table to easily store the information
- Alternative: Have to keep the elements in the order that they are accessed
- Risk: Do not know how many websites are going to be entered
- Alternative: Store the playlist into a data structure that can handle an unknown number - **can't use an array**
- Risk: Need to know whether the characters are in Unicode or ASCII
- Alternative: We can assume the characters will be in ASCII because they will be run on the Notre Dame computers
- Risk: Ensure that the right number of arguments is run on the command line
- Alternative: Write a function that ensures the right number of arguments is given
- Risk: Duplicates can be given in a playlist
- Alternative: Use a data structure that can take in multiple versions of similar elements

3) Product Testing and Development

- Use a std::vector to store the class Music
- Create an empty std::vector**
- The class Music should contain a constructor and an overloaded operator to store the elements from the text file and then a private element for each data type of the elements of the playlist
- As the elements are read from the data file, they are stored into the class Music, then each class is pushed into the vector using the .push_back() method
- The following testing method displays the logic behind the approach
- Also the elements will be stored in the order that they are accessed
- Use smart iterator to print the results in order**

Vector	
--------	--

0	Element 1 - Class Music - Song ID - Artist/Band Name - Song Title - Album Name - Year Recorded
1	Next Element - Class Music - Song ID - Artist/Band Name - Song Title - Album Name - Year Recorded
...7	...std::vector has a initial size of 8

Problem 2 - Kelly Buchanan

4) Identify Objectives

- a. Create a class which contains the four different elements
 - i. Item ID - unsigned int
 - ii. Manufacturer Name - string
 - iii. Item Name - string
 - iv. Cost - string
- b. Create a main driver which reads in the information from a text file and stores it in the class
- c. Use a data structure to store the classes, then overload the ostream operator to print out the elements in the specific order required

5) Identify Risks and Alternatives

- a. Risk: Use a Hash Table to easily store the information
- b. Alternative: Have to keep the elements in the order that they are accessed
- c. Risk: Do not know how many items are going to be entered
- d. Alternative: Store the websites into a data structure that can handle an unknown number - **can't use array**
- e. Risk: Need to know whether the characters are in Unicode or ASCII
- f. Alternative: We can assume the characters will be in ASCII because they will be run on the Notre Dame computers
- g. Risk: Ensure that the right number of arguments is run on the command line
- h. Alternative: Write a function that ensures the right number of arguments is given
- i. Risk: Duplicates can be given in a receipt
- j. Alternative: Use a data structure that can take in multiple versions of similar elements
- k. **Risk: Can't use floats for money since precise, not accurate**
- l. **Alternative: Must create a Money class with long unsigned int for Dollars, and int for Cents**

6) Product Testing and Development

- a. Use a std::vector to store the class Receipt
- b. **Create an empty std::vector**
- c. The class Receipt should contain a constructor and an overloaded operator to store the elements from the text file and then a private element for each data type of the elements of the receipt
- d. As the elements are read from the data file, they are stored into the class Receipt, then each class is pushed into the vector using the .push_back() method

- e. The following testing method displays the logic behind the approach
- f. Also the elements will be stored in the order that they are accessed
- g. Use smart iterator to print the results in order

Vector	
0	Element 1 - Class Receipt - Item ID - Manufacturer Name - Item Name - Cost
1	Next Element - Class Receipt - Item ID - Manufacturer Name - Item Name - Cost
...7	...std::vector has initial size of 8