

TEI ROCK DRILLS

HEM

HYDRAULIC EXCAVATOR MOUNT

The HEM (Hydraulic Excavator Mount) is the most popular drilling attachment manufactured at TEI Rock Drills. The stable excavator base with long boom combine to form an excellent drilling platform. The HEM receives hydraulic power from the excavator's hammer circuit; no additional hydraulic plumbing is required. TEI solely uses their patented hydraulic drifters and feed systems to build the HEM. These technically advanced drifters have an Automatic Stroke Adjustment or ASA. This feature brings the hammer into an idle mode when the drill string is not engaged. When the operator puts down pressure on the drill string the ASA automatically brings the hammer up to full power. The built-in swivel accepts air, water or grout for all types of drilling including the installation of the popular hollow bars.



HYDRAULIC EXCAVATOR MOUNT

HEM 360 WITH TE360 DRIFTER			HEM 350R WITH RDS350 ROTARY		
	U.S.	Metric		U.S.	Metric
HYDRAULIC FLOW	36 gpm	136 lpm	HYDRAULIC FLOW	30 gpm	114 lpm
HYDRAULIC PRESSURE	2250 psi	155 bar	HYDRAULIC PRESSURE	3000 psi	207 bar
HOLE SIZE	1 3/8” to 3”	35 mm-76 mm	HOLE SIZE	2 3/4” to 8”	70 mm-203 mm
TOTAL LENGTH	16 ft	4.9 meters	TOTAL LENGTH	16 ft	4.9 meters
DRILL TRAVEL	11.75 ft	3.6 meters	DRILL TRAVEL	11.75 ft	3.6 meters
PULLBACK	7,350 lbf	33 kN	PULLBACK	7,350 lbf	33 kN
APPROX. WEIGHT	3,290 lbs	1,492 kgs	APPROX. WEIGHT	3,175 lbs	1,440 kgs
MINIMUM EXCAVATOR SIZE	13 ton	13 ton	MINIMUM EXCAVATOR SIZE	13 ton	13 ton

HEM 760 WITH TE760 DRIFTER			HEM 550R WITH RDS550 ROTARY		
	U.S.	Metric		U.S.	Metric
HYDRAULIC FLOW	47 gpm	178 lpm	HYDRAULIC FLOW	40 gpm	152 lpm
HYDRAULIC PRESSURE	2500 psi	172 bar	HYDRAULIC PRESSURE	3000 psi	207 bar
HOLE SIZE	2” to 5”	52 mm-127 mm	HOLE SIZE	4” to 12”	102 mm-305 mm
TOTAL LENGTH	16 ft	4.9 meters	TOTAL LENGTH	16 ft	4.9 meters
DRILL TRAVEL	11.75 ft	3.6 meters	DRILL TRAVEL	11.75 ft	3.6 meters
PULLBACK	7,350 lbf	33 kN	PULLBACK	7,350 lbf	33 kN
APPROX. WEIGHT	3,750 lbs	1,700 kgs	APPROX. WEIGHT	4,800 lbs	2,177 kgs
MINIMUM EXCAVATOR SIZE	20 ton	20 ton	MINIMUM EXCAVATOR SIZE	20 ton	20 ton



Specifications subject to change without notice.
TEI technical specifications consider a 40% hydraulic power loss.

QUALITY POLICY

CONTINUAL IMPROVEMENT OF CUSTOMER VALUE THROUGH INNOVATION, EFFICIENCY AND INTEGRITY

TEI08.010.B
REV. 07/22/2022