-
-

`Ctrl + F`

> `Ctrl + F`

>

> ⚠️

>

>

`frontend/`

`kosu/` `hozen_another/`

>

> `/api/`

> `/api/kosu/`

>

>

> `https`

{

"name": "山田", "age": 30 }

https://example.com/login

/login

---

npm start python manage.py runserver

`npm install`

`node-v22.17.1`

`npm install` `npm start` `npm run build`

`pip install`

>

>

> `npm run build` `frontend/build/`

> `npm start`

> `pip install -r requirements.txt`

> `SECRET_KEY` `DB_PASSWORD`

`.env`

`localhost` `http://localhost:3000` `8000`

.git

休憩変更時の工数消去バグ修正

`master` `main`

`master`

`git add`

`git` `push`

`git pull`

> `git fetch`

> `git merge`

>

> `gh`

> `origin`

>

>

.env

...

<input type="number"> type="number"

`<p>本文</p>`

`.blue_button { ... }`

`.blue_button`

`class="blue_button"`

`.名前`

`id="numberInput"`

`#名前`

`margin: 0 auto`

`border: 1px solid #ddd`

`box-sizing: border-box`
`width`

`display: flex` `justify-content`
`align-items` `gap`

`row` `column`
`column`

`justify-content` `align-items` `center`

`:` `:hover` `:focus`

`::` `::before` `::after` `content` ⚠️

`:root { --heading1: ...; }` `var(--heading1)`

`clamp(最小, 推奨, 最大)`

`calc(100% - 60px)`

`px` `%` `rem` `vw`

@media (max-width: 768px) { ... }

clamp

○ ○.module.css className={styles["名前"]}

class className for htmlFor { }

.tsx

const name = "山田" name

const let

handleSubmit

Number(employee_no)

employee_no

Number("5") 5

{ name: "山田",

age: 30 }

[1, 2, 3] ["P", "R", "W1"]

if (条件) { ... }

07

for

async

await

onClick

onClick onChange onSubmit

null
undefined
null
undefined

true
false

"山田太郎" "
'

30 3.14 <input
type="number"> Number()
"30"
30

<Login />

KosuList MemberList

const [値, 値を変える関数] = useState(初期値) setNumber

`useState` `useEffect`

`/login` `/kosu`

index.tsx

<Link to="/help"> <a>

Pagination

`manage.py`

`employee_no = models.IntegerField('従業員番号')` `IntegerField` `CharField` `DateField` `BooleanField`

`SELECT * FROM member`

`member.objects.filter(shop='P')`

`member.objects.all()` `objects` `.all()` `.filter()`

`.get()`

`.all()`

`.filter(条件)` `.get(条件)`

`python manage.py makemigrations`

`python manage.py migrate`

`kosu/views/`

`kosu_views` `member_views`

`/api/kosu/`

`kosu/urls.py`

localhost:3000

localhost:8000

@○○ @login_required

@

`signals.py`

`hozen_another/wsgi.py`

`manage.py runserver`

`python manage.py`

`collectstatic` `staticfiles/`

`python manage.py qcluster` `tasks.py`

`python manage.py runserver` `migrate` `makemigrations`

`hozen_another/settings.py`

`kosu/models.py`

models.py

<input type="number">

Number()

models.py shop_list P R W1 W2 T1 T2 A1 A2 J その他 異動・退社

tyoku2

break_time1 break_time6

time_work max_length=288

detail_work

max_length=32676

Business_Time_graph def_ver2

work_day2

`break_time1`　　`max_length=9`

休憩変更時の工数消去バグ修正

⚠️

`over_time`

`authority`　　`administrator`　　`true`　`false`

AsyncTask History
signals.py

pop_up1 pop_up5 pop_up_id1
通知誤削除修正

break_check
true false

---

frontend/src/tests/

npm test npm run test:run

`npm run test:ui`

`it("...", () => { ... })`

`expect(...)` `expect(結果).toBe(期待値)` `.toBe(...)`

> `DEBUG` `False`

> `True`
> `False`

`//`		
`/* */`		
`#`		
`{ }`		
`[ ]`		
`( )`		
`=>`		
`===`		
`==`		`===`
`&&`		
`||`		
`!`		
`?`		
`=`		
`@`		`@login_required`
`.`		`member.objects`
`:`		
`;`		
`$`		`${ }`
`...`		

> `Login.tsx:42`

> `Cannot read properties of undefined (reading 'name')`
>
> `name`

`Ctrl + Shift + F`

-
- `Business_Time_graph`

>

>

`break_time1`

> ⚠️

- `Ctrl + F`
- `/login`
- `.env`

-
-

`member`