Extended bonus campaign with jackpot information

- Create extended bonus campaign request
  - 1. Introduction
  - 2. Non-functional requirements
  - 3. Functional requirements
    - Request sample
    - Request (filters)
    - Bonus Rules Settings
    - Trigger Rules Settings
- List Of Available Bets
- Generate JWT Bearer token
- Jackpot information
  - 1. Introduction
  - 2. Non-functional requirements
  - 3. Functional requirements
    - Query parameters
    - Response for type = active_jackpots
    - Response for type = list_of_winners
    - Response for type = jackpots_with_winners
    - Possible errors and some message examples:

Create extended bonus campaign request

1. Introduction

Call to create bonus campaign

2. Non-functional requirements

3. Functional requirements

POST `https://<domain>/api/v1/b2b/bonuses/extended_campaign`

Header:

- Content-Type: application/json
- Accept: application/json
- b2b-client-id: Unique identifier of B2B company in provider system (uuid)
- Authorization: Bearer <token> (see how to generate token below)

Request sample

```
{
  "b2b_campaign_id": "string",
  "name": "string",
  "valid_from": "2023-01-23T14:21:33.228Z",
  "valid_until": "2023-01-23T14:21:33.228Z",
  "description": "string",
  "b2c": [
    {
```

```
      "id": "1234",
      "int_id": 12345
    }
  ],
  "game_ids": [
    "string"
  ],
  "currency": "string",
  "type": "wheel_of_fortune",
  "rule_settings": "please read section Bonus Rules Settings",
  "trigger_settings": "please read section Trigger System Settings"
}
```

Request (filters)

Parameter	Required	Restrictions	Description
`b2b_campaign_id`	+	String	Unique identifier of campaign in b2b system
`name`	+	String	Name of b2b campaign
`valid_from`	-	DateTime	Date and time of start of campaign in UTC 0 **Note:** if `valid_from` is not specified, the company is effective from the moment of creation
`valid_until`	+	DateTime	Date and time of the end of campaign in UTC 0
`description`	-	String	Description
`b2c`	+	Array (object) count(array) = 1	Unique identifier of the player to whom the campaign will be credited. This array cannot be empty.
`b2c.id`	+	string	String user id
`b2c.int_id`	-	int	If you used int user id

`game_ids`	+	String array count(array) >= 1	Unique identifier of games in provider system which are participating in the campaign. This array cannot be empty.
`currency`	+	String	Currency code for setting free spins ISO 4217 for fiat currencies or crypto
`type`	+	String	The type of bonus campaign being created Valid values: • free_spins • golden_dragon • treasure_chest • wheel_of_fortune
`rule_settings`	+	Object	Bonus specific settings. Please read more in the section “Bonus Rules Settings”
`trigger_settings`	+	Object	Triggers settings. Please read more in the section “Trigger Rules Settings”

Response:

```
{
  "b2b_campaign_id": "string",
}
```

Parameter	Required	Restrictions	Description
`b2b_campaign_id`	+	string	Unique identifier of campaign in b2b system

Possible errors and some message examples:

200: `success`

400: `validation errors`, `bonus campaign already exists`

401: `invalid bearer token`

403: `b2b company is banned` `game_id is not allowed for b2b company`

500: `internal error`

Bonus Rules Settings

Each type of bonuses has own settings.

1. **Bonus Free Spins.** You need to pass amount of free spins and bet per line parameter (it is NOT in currency, it is in coins).

Object content — rule_settings:

Parameter	Required	Restrictions	Description
bet_id	+	String	Unique identifier if total bet received in response to **List Of Available Bets** request
free_spin_amount	+	Integer	Amount of free spins to be given
instant_games_min_cashout_multiplier	-	Float	Required for games with **game_type = Instant** The game's **game_type** is returned in the `type` field of the **Get game list** request The value must be greater than or equal to **1.3**

Example:

```
"rule_settings": {
 "bet_id": "4qwerty",
 "free_spin_amount": 10,
 "instant_games_min_cashout_multiplier": 1.5
}
```

Freespin Price can be get from List Of Available Bets request

instant_games_min_cashout_multiplier does not affect the awarded bet amount. Instead, it affects the payout of each round.

With a value of 1.5 :

- Losing rounds pay 0 .
- Winning rounds can only be cashed out if the multiplier reaches at least 1.5x .
- Multipliers below 1.5x result in a payout of 0 .
- Any successful cashout will occur at a multiplier of 1.5x or higher.

2. **Golden Dragon**
   This bonus is using Weight System. Basically it's a setup for prize probabilities. For Golden Dragon you can pass 1-100 prizes only in money (free spins are not allowed here) with different probabilities.

Object content — rule_settings:

Parameter		Required	Restrictions	Description
weight_lines		+	Array of Objects	An array of weight values assigned to paylines to determine their occurrence frequency and hit rate.
	prize_type	+	Integer	Type of the prize. it should be 1 for Golden Dragon
	value	+	Integer	Amount in the current currency
	weight	+	Integer	Weight of this prize, if it's 0 player will never get it

Example:

```
//in that example Golden Dragon has only 3 prizes: 15, 1, 100 (let's assume
```

```
it's EUR)
//15 EUR has ~16.67% probablitily to be given(10+50+0 = 60 is a total weights.
10/60*100=16.67%)
//1 EUR has ~83.33% probablitily to be given(10+50+0 = 60 is a total weights.
50/60*100=83.33%)
//100 EUR has 0% probability to be given
"rule_settings": {
    "weight_lines": [
      {
        "prize_type": 1,
        "value": 15,
        "weight": 10
      },
      {
        "prize_type": 1,
        "value": 1,
        "weight": 50
      },
      {
        "prize_type": 1,
        "value": 100,
        "weight": 0
      }
    ]
}
```

3. **Treasure Chest**

   This bonus is using Weight System too. Here you can pass **strictly 16 prizes** only in money (free spins are not allowed here) with different probabilities.

Object content — rule_settings:

Parameter		Required	Restrictions	Description
weight_lines		+	Array of Objects	An array of weight values assigned to paylines to determine their occurrence frequency and hit rate.
	prize_type	+	Integer	Type of the prize. it should be 1 for Treasure Chest
	value	+	Integer	Amount in the current currency
	weight	+	Integer	Weight of this prize, if it's 0 player will never get it

Example:

```
//in that example Treasure Chest has 16 prizes: 15, 1, 100, 10, 20,
1000, 11,
45, 67, 21, 22, 78, 35, 36, 2, 5 (let's assume it's EUR)
//for all prizes we are using same weight (1) then probability for
each prize
will be the same: 16%
"rule_settings": {
    "weight_lines": [
      {
        "prize_type": 1,
        "value": 15,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 1,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 100,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 10,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 20,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 1000,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 11,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 45,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 67,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 21,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 22,
        "weight": 1
      },
      {
```

```
        "prize_type": 1,
        "value": 78,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 35,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 36,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 2,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 5,
        "weight": 1
      }
    ]
}
```

4. **Wheel of Fortune**

   This bonus is using Weight System too. Here you can pass strictly 16 prizes in money or free spins with different probabilities.

Object content — rule_settings:

Parameter		Required	Restrictions	Description
weight_lines		+	Array of Objects	An array of weight values assigned to paylines to determine their occurrence frequency and hit rate.
	prize_type	+	Integer	Type of the prize: 1 - money 2 - free spins
	value	+	Integer	Amount in the current currency or amount of free spins

	bet_per_line	-	Integer	Bet per line in coin, not in currency
	weight	+	Integer	Weight of this prize, if it's 0 player will never get it

Example:

```
//in that example Wheel of Fortune has 16 prizes: 15, 1, 100, 10, 20, 1000, 11,
45, 67, 21, 22, 78, 35, 36, 2, 5 (let's assume it's EUR)
//for all prizes we are using same weight (1) then probability for each prize
will be the same: 16%
//for 1 prize (second one) we are using Free Spins as a prize
"rule_settings": {
    "weight_lines": [
      {
        "prize_type": 1, //type of the prize. 1 - money, 2 - free spins
        "value": 15, //amount in the current currency (if type is 1)
        "weight": 1 //weight of this prize. should be int. if it's 0 player
will never get it
      },
      {
        "prize_type": 2, // type is free spins
        "value": 10, //10 free spins will be given
        "bet_per_line": 1, //free spins will be given for bet per line = 1 (in
coins)
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 100,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 10,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 20,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 1000,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 11,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 45,
```

```
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 67,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 21,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 22,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 78,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 35,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 36,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 2,
        "weight": 1
      },
      {
        "prize_type": 1,
        "value": 5,
        "weight": 1
      }
    ]
}
```


Trigger Rules Settings

In all our bonuses you must to define at least one trigger. Trigger is a nice way to define when the player should get the bonus. We have 4 triggers:

1. First launch trigger - player will get the bonus once he opened a game. This is a most common trigger. Once player open the game he will get a bonus.

2. Bet amount trigger - player will get the bonus once he bet for X amount of money. You can setup if it’s for all games together or per game. Also you can setup many triggers within this type.

3. Amount of Spins in session - player will get the bonus if he did from X to Y amount of spins (the bet amount is not relevant here). Also you can setup many triggers within this type.

4. Loss trigger - player will get the bonus once his loss will be X amount of money (here we are considering a winnings). For example: we setup a loss trigger for 10 EUR. Player bet 1 EUR, then win 10 EUR, then bet 5 EUR, won 0 and then bet 20 EUR with 1 EUR win. 1-10+5-0+20-1 = total loss is 15 EUR - player will get a bonus.

You can put many triggers together, just be careful, because player will get a bonus for each type of trigger!

Object content — trigger_settings:

Parameter			Required	Restrictions	Description
first_game_launch_trigger			+	Boolean	First game launch trigger: true - Enable false - Disenable
game_bet_amount_trigger			-	Object	Game bet amount trigger
	bet_settings		-	Array of Objects	Bet settings
		trigger_bet_amount	-	Decimal	How much total bet player should do
		single_bet_amount	-	Boolean	Counting in all games together or per game
session_spin_amount_trigger			-	Object	Session spin amount trigger
	spin_settings		-	Array of Objects	Spin settings

		min_spin_amount	-	Integer	How many spins as minimum player should do
		max_spin_amount	-	Integer	How many spins as maximum player should d
loss_money_trigger			-	Object	Loss money trigger
		loss_amount	-	Decimal	How much player should lose

Example with all triggers together:

```
"trigger_settings": {
    "first_game_launch_trigger": true,
    "game_bet_amount_trigger": {
      "bet_settings": [
        {
          "trigger_bet_amount": 50.0,
          "single_bet_amount": true
        },
        {
          "trigger_bet_amount": 75.0,
          "single_bet_amount": false
        }
      ]
    },
    "session_spin_amount_trigger": {
      "spin_settings": [
        {
          "min_spin_amount": 10,
          "max_spin_amount": 20
        },
        {
          "min_spin_amount": 25,
          "max_spin_amount": 50
        }
      ]
    },
    "loss_money_trigger": {
      "loss_amount": 100.5
    }
}
```

Another example with just 2 triggers:

```
"trigger_settings": {
     "first_game_launch_trigger": true, // just true or false or you
can avoid this
     "game_bet_amount_trigger": {
       "bet_settings": [
         {
         "triger_bet_amount": 75.0,
         "single_bet_amount": false
         }
```

```
        ]
    }
```

Let’s put all together.

This example is creating campaign with name "SuperDooper Compaign" for 2 games, for 1 player in EUR currency. This campaign will start 11.11.2025 (time you can see in a timestamp) and will end 15.11.2025. ID of that campaign in Yprovider system is “11111111“. Player will get Golden Dragon bonus twice: when they opened games 32001 or 42001 and when they lose 100.5 EUR. They can get 2 prizes: 1.5 EUR or 10 EUR. 1 EUR they will get with probability 90% and 10 EUR with 10% probability.

Request example:

```
{
    "b2b_campaign_id": "11111111",
    "name": "SuperDooper Compaign",
    "valid_from": "2025-11-11T14:21:33.228Z"
    "valid_until": "2025-11-11T14:21:33.228Z"
    "description": "some description",
    "b2c_id": ["string" or int],
    "game_ids": ["32001"],
    "currency": "EUR",
    "campaign_type": "golden_dragon",
    "rule_settings": {
      "weight_lines": [
         {
         "prize_type": 1,
         "value": 1.5,
         "weight": 90,
         },
         {
         "prize_type": 1,
         "Value": 10,
         "Weight": 10,
         }
   ]
 }
    },
    "trigger_settings": {
      "first_game_launch_trigger": true,
       "loss_money_trigger": {
       "loss_amount": 100.5
     }
    },
}
```

List Of Available Bets

Call to get the available bets for a particular game and currency used to create a bonus campaign

POST `https://<domain-for-mechanics>/api/v1/b2b/bonuses/bet-ranges`

Header:

- Content-Type: application/json

- Accept: application/json
- b2b-client-id: Unique identifier of B2B company in provider system (uuid)
- Authorization: Bearer <token> (see how to generate token below)

Body:

Parameter	Required	Restrictions	Description
`game_id`	+	string	Unique identifier of game in provider system
`currency`	+	string	Currency code for setting free spins ISO 4217 for fiat currencies or crypto

Response:

```
[{
      "id": "string",
      "bet": 10.01
}]
```

Parameter	Mandatory	Restrictions	Description
`id`	-	string	Unique identifier if total bet
`bet`	-	float up to 131072	Bet size by game and currency

Mandatory

Array is empty if there is no restrictions for free spin bets

Possible errors and some message examples:

200: `success`

400: `validation errors`

401: `invalid bearer token`

403: `b2b company is banned` `game_id is not allowed for b2b company`

500: `internal error`

Generate JWT Bearer token

Call to get generated JWT from provider system (to authorize)

If you do not have an API key, generate it in the provider system admin panel.

POST `https://<domain>/api/v1/b2b/token`

Header:

- Content-Type: application/json
- Accept: application/json

Body:

```
{
  "b2b_id": string,
  "api_key": string
}
```

Parameter	Required	Restrictions	Description
`b2b_id`	+	string(36)	Unique identifier of B2B company in provider system (uuid)
`api_key`	+	string(255)	B2B Company active API Key generated in provider system

Response:

```
{
    "token":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJiMmJfaWQiOiIwYzg0YjRlOC00ZmJiLTExZWQtYmRjMy0wMjQyYWMxMjAwMDIiLCJleHBpcmVkX2F0IjoiMjAyMi0xMS0yMlQxMjowNTozNC41ODAzOTQyOTUrMDM6MDAifQ.vo78-_DLcyIT6M7MrBPm7l5dFrjfx3rbaTgpu9H4P7c",
    "expired_at": {
```

```
        "seconds": 1669107934,
        "nanos": 580439874
    }
}
```

Parameter	Required	Restrictions	Description
`token`	+	string	JWT
`expired_at.seconds`	+	int64	Represents seconds of UTC time since Unix epoch Default: JWT expires 24 hours after generation
`expired_at.nanos`	+	int32	Non-negative fractions of a second at nanosecond resolution. Negative second values with fractions must still have non-negative nanos values that count forward in time. Must be from 0 to 999,999,999

Possible errors and some message examples:

200: `success`

400: `validation errors`

403: `b2b company is banned`

500: `internal error`

Jackpot information

1. Introduction

Called to get active jackpot data and winner lists by timeframe.

2. Non-functional requirements

3. Functional requirements

GET `https://<domain>/api/v1/b2b/bonuses/jackpot_info?type=type&date_from=date_from`

Header:

- Content-Type: application/json
- Accept: application/json
- b2b-client-id: Unique identifier of B2B company in provider system (uuid)
- vendor-id: Unique identifier of the vendor in provider system
- Authorization: Bearer <token>

Query parameters

Parameter	Required	Restrictions	Description
`type`	+	string	Type of requested information ℹ Valid values: • active_jackpots • list_of_winners • jackpots_with_winners
`date_from`	-	integer	The start date for filtering winners up to the current moment. A parameter representing the time in Unix format. ℹ Required parameter for type = list_of_winners

Response for type = active_jackpots


```
{
  "active_jackpot_list": [
    {
      "jackpot_name": "Mega Jackpot",
      "jackpot_id": "a1571321952b57072669014c16876155",
      "amount": 10041.75,
      "currency": "USD",
      "game_id": "87166291-127f-4927-a759-5798d43605a8"
    }
```

```
  ]
}
```

Parameter		Required	Restrictions	Description
`active_jackpot_list`		+	Object array	Object array with information about active jackpots
	`jackpot_name`	+	string	Jackpot name
	`jackpot_id`	+	string	Unique identifier of the jackpot
	`amount`	+	float	Jackpot amount
	`currency`	+	string	Currency
	`game_id`	+	string	Unique identifier of the game

Response for type = list_of_winners

```
{
  "winner_list": [
    {
      "jackpot_name": "Mega Jackpot",
      "jackpot_id": "a1571321952b57072669014c16876155",
      "amount": 10041.75,
      "currency": "USD",
      "b2c_id": "2674dnvw",
      "date_time": "2024-07-03T15:23:57.371Z"
    }
  ]
}
```

Parameter		Required	Restrictions	Description
`winner_list`		+	Object array	Object array with information about jackpots winners
	`jackpot_name`	+	string	Jackpot name
	`jackpot_id`	+	string	Unique identifier of the jackpot

	`amount`	+	float	Jackpot amount
	`currency`	+	string	Currency
	`b2c_id`	+	string	Unique identifier of the jackpot winner
	`date_time`	+	string	Date and time of winning

Response for type = jackpots_with_winners


```
{
  "active_jackpot_list": [
    {
      "jackpot_name": "Mega Jackpot",
      "jackpot_id": "a1571321952b57072669014c16876155",
      "amount": 10041.75,
      "currency": "USD",
      "game_id": "87166291-127f-4927-a759-5798d43605a8"
    }
  ],
  "winner_list": [
    {
      "jackpot_name": "Mega Jackpot",
      "jackpot_id": "a1571321952b57072669014c16876155",
      "amount": 10041.75,
      "currency": "USD",
      "b2c_id": "2674dnvw",
      "date_time": "2024-07-03T15:23:57.371Z"
    }
  ]
}
```


Parameter		Required	Restrictions	Description
`active_jackpot_list`		+	Object array	Object array with information about active jackpots
	`jackpot_name`	+	string	Jackpot name
	`jackpot_id`	+	string	Unique identifier of the jackpot
	`amount`	+	float	Jackpot amount
	`currency`	+	string	Currency
	`game_id`	+	string	Unique identifier of the game

`winner_list`		+	Object array	Object array with information about jackpots winners
	`jackpot_name`	+	string	Jackpot name
	`jackpot_id`	+	string	Unique identifier of the jackpot
	`amount`	+	float	Jackpot amount
	`currency`	+	string	Currency
	`b2c_id`	+	string	Unique identifier of the jackpot winner
	`date_time`	+	string	Date and time of winning

Possible errors and some message examples:

200: `success`

400: `validation errors`

401: `token is invalid`

403: `B2B company is banned`

500: `Internal error`