

File Format of FileReferences.dat

UPDATES

Version	Authors	Actions	Revision	Date	Distribution
1.0	JCW	Creation		20/07/2017	
1.1	JS	V12 format		25/04/2018	

Information in this document is subject to change without notice and does not represent a commitment on the part of the supplier. The software described in this document is furnished under a license agreement. The software may be used or copied only in accordance with the terms of the agreement. It is against the law to copy software on any medium except as specifically allowed in the license agreement. The purchaser may make one copy of the software for backup purposes. No part of this manual may be reproduced or transmitted in any form or by any means, without the express permission of the supplier.

Whilst the utmost care is taken to ensure the accuracy of the data contained herein, it is provided on the understanding that the supplier shall under no circumstances, be liable for any injuries, expenses, or losses which may be in any way attributable to the use or adaptation of such data.

All trademarks duly acknowledged.

CONTENTS

Location of the configuration file	4
The format in the configuration file	5

Location of the configuration file

The file references configuration file "FileReferences.DAT" is saved in the subfolder C of the project folder.

The format in the configuration file

No	Description	T	Size (bytes)	Value
1	Entry header	C	7	FILEREF
2	Name	C	255	
3	Version number	N	2	2
4	File type	N	2	0: Worksheet
5	Path name Can be a full path or a path relative to TP project folder	C	260	
6	Default null value	N	2	0: Empty 1: NULL 2: Custom null value
7	Custom null value	C	10	Meaningful when the field 6 is 2
8	Reserved	N	2	Must be 0
9	Use in expression engine	N	1	0: Not used 1: Used
10	Load type for expression engine	N	2	Meaningful when the field 9 is 1 0: at startup 1: On call
11	Unload type for expression engine	N	2	Meaningful when the field 9 is 1 0: When leaving 1: After a delay
12	Unload delay	N	2	Meaningful when the field 11 is 1
13	Description	C	255	
14	Output formatting – Default column separator	C	1-2	All single character (except "), \t (carriage return), \n (tabulation)

15	Output formatting – Default row separator	C	1-2	All single character (except "), \t (carriage return), \n (tabulation)
----	---	---	-----	--