



2.6 — Why functions are useful, and how to use them effectively

👤 [ALEX](#)¹ 🕒 JANUARY 25, 2023

Now that we've covered what functions are and some of their basic capabilities, let's take a closer look at why they're useful.

Why use functions?

New programmers often ask, "Can't we just put all the code inside the *main* function?" For simple programs, you absolutely can. However, functions provide a number of benefits that make them extremely useful in programs of non-trivial length or complexity.

- Organization -- As programs grow in complexity, having all the code live inside the *main()* function becomes increasingly complicated. A function is almost like a mini-program that we can write separately from the main program, without having to think about the rest of the program while we write it. This allows us to reduce a complicated program into smaller, more manageable chunks, which reduces the overall complexity of our program.
- Reusability -- Once a function is written, it can be called multiple times from within the program. This avoids duplicated code ("Don't Repeat Yourself") and minimizes the probability of copy/paste errors. Functions can also be shared with other programs, reducing the amount of code that has to be written from scratch (and retested) each time.
- Testing -- Because functions reduce code redundancy, there's less code to test in the first place. Also because functions are self-contained, once we've tested a function to ensure it works, we don't need to test it again unless we change it. This reduces the amount of code we have to test at one time, making it much easier to find bugs (or avoid them in the first place).
- Extensibility -- When we need to extend our program to handle a case it didn't handle before, functions allow us to make the change in one place and have that change take effect every time the function is called.
- Abstraction -- In order to use a function, you only need to know its name, inputs, outputs, and where it lives. You don't need to know how it works, or what other code it's dependent upon to use it. This lowers the amount of knowledge required to use other people's code (including everything in the standard library).

Effectively using functions

One of the biggest challenges new programmers encounter (besides learning the language) is understanding when and how to use functions effectively. Here are a few basic guidelines for writing functions:

- Groups of statements that appear more than once in a program should generally be made into a function. For example, if we're reading input from the user multiple times in the same way, that's a great candidate for a function. If we output something in the same way in multiple places, that's also a great candidate for a function.
- Code that has a well-defined set of inputs and outputs is a good candidate for a function, (particularly if it is complicated). For example, if we have a list of items that we want to sort, the code to do the sorting would make a great function, even if it's only done once. The input is the unsorted list, and the output is the sorted list. Another good prospective function would be code that simulates the roll of a 6-sided dice. Your current program might only use that in one place, but if you turn it into a function, it's ready to be reused if you later extend your program or in a future program.
- A function should generally perform one (and only one) task.
- When a function becomes too long, too complicated, or hard to understand, it can be split into multiple sub-functions. This is called **refactoring**. We talk more about refactoring in lesson [3.10 -- Finding issues before they become problems](#)².

Typically, when learning C++, you will write a lot of programs that involve 3 subtasks:

1. Reading inputs from the user
2. Calculating a value from the inputs
3. Printing the calculated value

For trivial programs (e.g. less than 20 lines of code), some or all of these can be done in function *main*. However, for longer programs (or just for practice) each of these is a good candidate for an individual function.

New programmers often combine calculating a value and printing the calculated value into a single function. However, this violates the "one task" rule of thumb for functions. A function that calculates a value should return the value to the caller and let the caller decide what to do with the calculated value (such as call another function to print the value).



[Next lesson](#)

2.7 [Forward declarations and definitions](#)

3



[Back to table of contents](#)

4



[Previous lesson](#)

2.5 [Introduction to local scope](#)

5

[B](#) [U](#) [URL](#) [INLINE CODE](#) [C++ CODE BLOCK](#) [HELP!](#)




Leave a comment...

 Name* Email* | 

Notify me about replies:



POST COMMENT

 Find a mistake? Leave a comment above! Avatars from <https://gravatar.com/>⁹ are connected to your provided email address.

115 COMMENTS

Newest ▼

**IceFloe** February 20, 2024 3:43 am

I think it's not worth making the code too modular and complicating where it's enough to add a couple of lines to the main function.

Everything is fine in moderation, and with parameters and copying values, it is still worth figuring out what depends on what and how to use it most effectively.

By the way, another interesting question is, is it possible to create two functions with the same name, but which will have different arguments and take different parameters, returning different values? example:

```
1 | int Sum ( int x, int y)
2 | {
3 |     return x+y;
4 | }
5 | int Sum (int z, int v, int c)
6 | {
7 |     return z+v+c;
8 | }
```

 Last edited 2 months ago by IceFloe



0



Reply

**Alex**

Author

Reply to [IceFloe](#)¹⁰ ⓘ February 22, 2024 1:36 pm

1. Mostly agree, but we're illustrating good practices here on short, simple problems. These practices will be more useful later as programs get more complex.
2. Yes, this is called function overloading. We have lessons on this later.



3



Reply

**Pocket**

ⓘ February 15, 2024 6:17 am

```
1  #include <iostream>
2
3
4  int givAdd(int a, int b)
5  {
6      return a + b;
7  }
8  int givSub(int a, int b)
9  {
10     return a - b;
11 }
12 int givMul(int a, int b)
13 {
14     return a * b;
15 }
16 int givDiv(int a, int b)
17 {
18     return a / b;
19 }
20
21 int main()
22 {
23     std::cout
24         << "Two Numbers for math: ";
25     int getA{};
26     int getB{};
27     int pickOpp{};
28
29     std::cin
30         >> getA
31         >> getB;
32
33     std::cout
34         << "What kinda maths, 1 = add, 2 = sub, 3 = mul, 4 = div.\n"
35         << "All other numbers will Div.\n";
36
37     std::cin
38         >> pickOpp;
39
40     if (pickOpp <= 1)
41     {
42         std::cout
43             << givAdd(getA, getB);
44     }
45     else if (pickOpp == 2)
46     {
47         std::cout
48             << givSub(getA, getB);
49     }
50     else if (pickOpp == 3)
51     {
52         std::cout
53             << givMul(getA, getB);
54     }
55     else
56     {
57         std::cout
58             << givDiv(getA, getB);
59     }
60
61     return 0;
62 }
```

👍 0

↩ Reply

**Pocket**↩ Reply to [Pocket](#)¹¹ ⌚ February 15, 2024 6:17 am

It's the perfect calculator.

👍 0

↩ Reply

**alb**

⌚ January 28, 2024 3:43 am

// I know this very obviously produces undefined behavior I am just curious as to why I can not use functions this way

```
#include <iostream>
```

```
int userIn()
```

```
{
```

```
std::cout << "Enter a number: " << "\n";
```

```
int x{};
```

```
std::cin >> x;
```

```
return x;
```

```
}
```

```
int userOut()
```

```
{
```

```
int x{};
```

```
int doubleNum();
```

```
std::cout << x << " doubled is : " << doubleNum() << "\n";
```

```
return doubleNum();
```

```
}
```

```
int doubleNum()
```

```
{
```

```
int x{};
```

```
return x * 2;
```

```
}
```

```
int main()
```

```
{
```

```
int userIn();
```

```
int doubleNum();

int userOut();

std::cout << userIn() << doubleNum() << userOut() << '\n';

return 0;

}
```

👍 0 ➡ Reply



Patrick

🗨 Reply to [alb](#) ¹² ⌚ January 31, 2024 11:55 am

```
int doubleNum()
{
    int x{};

    return x * 2;
}
```

You double x without defining it to be some value, in some systems this will automatically format the variable to a default value. Essentially you can think of it as saying you want to double a number but don't tell me what number you want to double. How can I double a number that I don't know the value of?

👍 0 ➡ Reply



BillMai

⌚ December 21, 2023 12:54 am

Thanks!!!

📝 Last edited 4 months ago by BillMai

👍 1 ➡ Reply



thisisfun

⌚ November 8, 2023 9:43 am

Didnt follow the DRY rule. Here i am still tho this is fun still i could have done namespace but i like this better

```

1  #include <iostream>
2
3
4
5  // Making a calculator...
6  int main()
7  {
8      int x;
9      int y;
10     int z;
11     int m;
12     int n;
13     int o;
14     int p;
15     int q;
16     std::cout << "Today we will be making a Calculator... That goes to + - *
17 / in a line...";
18     std::cout << "+" << '\n';
19     std::cin >> x;
20     std::cin >> y;
21     std::cout << "-" << '\n';
22     std::cin >> z;
23     std::cin >> m;
24     std::cout << "*" << '\n';
25     std::cin >> n;
26     std::cin >> o;
27     std::cout << "/" << '\n';
28     std::cin >> p;
29     std::cin >> q;
30     std::cout << "Adding...: " << x + y << " Added!" << '\n';
31     std::cout << "Now the -: " << z - m << '\n';
32     std::cout << "Now the multiplying: " << n * o << '\n';
33     std::cout << "Now the dividing: " << p / q << '\n';
34     return 0;
}

```

This is Really fun making this

👍 3 ➡ Reply



Jason E

🗨 Reply to [thisisfun](#) ¹³ 🕒 December 30, 2023 12:26 am

```
1 | int x, y, z, m, n, o, p, q;
```

This, I think would make it read better than initializing them all down a line, a lot faster to write as well.

👍 2 ➡ Reply



Gripes

🗨 Reply to [Jason E](#) ¹⁴ 🕒 January 11, 2024 6:10 pm

Good suggestion! By the way, how do you make your text appear as though it's in an

IDE?

 Last edited 3 months ago by Grippe

 0

 Reply



aaa

 Reply to Grippe¹⁵  January 19, 2024 10:27 am

The built in terminal

 1

 Reply




Dedi

 October 23, 2023 11:03 pm

can we make a function as another file? and how to connect to that function file?

 0

 Reply



Alex Author

 Reply to Dedi¹⁶  October 24, 2023 9:59 am


Keep reading. Covered in lesson <https://www.learncpp.com/cpp-tutorial/programs-with-multiple-code-files/>

 2

 Reply



Serif

 October 1, 2023 12:55 am

Why do we need to know the input and outputs of a function to use it, as its said on abstraction part, i probably didnt understand that well, what do we mean by knowing its outputs and inputs?

 0

 Reply



Alex Author

 Reply to Serif¹⁷  October 2, 2023 1:11 pm

Inputs are the values you give to the function to work with.

Outputs are the values that the function gives back to you.

To use a function, you need to know what kind of inputs it takes, and what those inputs actually mean. Same with the outputs.

To use an analogy, think of a vending machine. In order to use the machine, you need to know what kind of money it takes and what the denominations of the money is. You also

have to know how the vending machine is going to return the item you're purchasing back to you as well. If you don't know any of these things you're going to have trouble using the vending machine in any sort of meaningful way.

👍 2 ➡ Reply

**vstar**

🕒 August 6, 2023 8:46 pm

哈哈太棒了，就好比什是，什是，反正我得那就是天，作者我解了天

👍 4 ➡ Reply

**Kvicala**

🕒 May 1, 2023 2:36 am

It's nice that they're explaining why functions are useful. I wish someone did that when I was learning Java, to this day I have no goddamn clue as to what is interfaces', abstract methods' and abstract classes' purpose. I feel that there are just some legacy control tool, which you can handle by documentation.

👍 1 ➡ Reply

**Taste**

🕒 April 5, 2023 10:21 am

This is really cool, here I split up all the work to be in functions, leaving only 4 lines in my main function.

Loving this course

```
1  #include <iostream>
2
3  int getNum()
4  {
5      int num{ };
6      std::cout << "Enter a number: ";
7      std::cin >> num;
8
9      return num;
10 }
11
12 int doubleNumber(int x)
13 {
14     return x * 2;
15 }
16
17
18 void printMath(int x, int y)
19 {
20     std::cout << x << " doubled is " << doubleNumber(x) << '\n'
21             << y << " doubled is " << doubleNumber(y) << '\n';
22 }
23
24 int main()
25 {
26     int x{ getNum() };
27     int y{ getNum() };
28     printMath(x, y);
29
30     return 0;
31 }
```

 Last edited 1 year ago by Taste

 8

 Reply



Docksie

 Reply to [Taste](#)¹⁸  April 26, 2023 10:43 pm

could reduce it by 2 more lines:

```
printMath(getNum(), getNum());
```

 4

 Reply



dyderf

 Reply to [Docksie](#)¹⁹  June 21, 2023 12:38 pm

Although in this example it doesn't matter that much, this is actually undefined behavior. The first number typed by the user could be printed as the second and vice versa.

 1

 Reply

**resident of flavourtown**Reply to [dyderf](#)²⁰ September 3, 2023 9:24 am

Could you explain why that is? To me, it seems that the first input would always be x, and so always be printed first; though I may be missing something.

0 Reply

**Alex** AuthorReply to [resident of flavourtown](#)²¹ September 5, 2023 12:25 pm

Discussed in lesson <https://www.learncpp.com/cpp-tutorial/operator-precedence-and-associativity/>

1 Reply

**Wanderer above the Sea of Fog**Reply to [resident of flavourtown](#)²¹ September 5, 2023 5:40 am

by using this
"printMath(getNum(), getNum());"

this instead of this

```
"int x{ getNum() };  
int y{ getNum() };  
printMath(x, y);"
```

in the main function x and y are not created and initialized.

1 Reply

**Krishnakumar**

January 23, 2023 1:54 am

Ridiculously minor nitpick:

>making it much easier to find bugs (or avoid them in the first place).

Experience suggests that for any non-trivial function, we can never fully **avoid** bugs (such is life), but can attempt to minimize them as much as reasonably possible by following such good practices.

0 Reply

**Emeka Daniel**Reply to [Krishnakumar](#)²² ⌚ March 17, 2023 5:50 am

You must have read that wrong or maybe it's just based on how to understand the word avoid.

👍 0 ➡ Reply

**Krishnakumar**Reply to [Emeka Daniel](#)²³ ⌚ August 24, 2023 1:15 am


Indeed. Re-reading it helped!

👍 0 ➡ Reply

**Emeka Daniel**Reply to [Krishnakumar](#)²⁴ ⌚ August 24, 2023 3:00 am

Okay.

👍 0 ➡ Reply

**Alex** AuthorReply to [Krishnakumar](#)²² ⌚ January 25, 2023 11:02 am

Hmmm, I read that as "making it easier to... avoid them in the first place", which doesn't imply they can all be avoided.

👍 6 ➡ Reply

**Krishnakumar**Reply to [Alex](#)²⁵ ⌚ May 25, 2023 4:39 pm

Thanks. That helps

👍 0 ➡ Reply

**silent**

⌚ December 14, 2022 5:13 am

"Extensibility -- When we need to extend our program to handle a case it didn't handle before, functions allow us to make the **change in one place** and have that change take effect every time the function is called."


"Make the change" where exactly? In the function itself or in the new piece of code that is affected by this function, or both? What kind of change? Same for the "take effect" part.



0



Reply

**Alex** AuthorReply to [silent](#)²⁶ 🕒 December 17, 2022 4:25 pm

Make the change in the body of the function. Whenever the function is executed, the change will be executed transparently to the caller.

For example, consider this function

```
1 void foo()
2 {
3 }
```

When called, it does nothing. Now let's add a change:

```
1 void foo()
2 {
3     std::cout << "Moo";
4 }
```

Now whenever it is called, it will print "Moo". The code on the caller's side doesn't need to change at all.



6



Reply

**Tiziano**

🕒 November 11, 2022 1:45 pm

Great tutorial Alex! Thanks!


I have a question: is the standard library available to be opened to look inside its code? if yes, how?



2



Reply

**Alex** AuthorReply to [Tiziano](#)²⁷ 🕒 November 13, 2022 5:44 pm

Only partially. You can open the header files and see what's inside those (they will probably not be very intelligible). The code defined inside .cpp files is precompiled into a format that's non-viewable.



1



Reply

**Krishnakumar**Reply to [Alex](#)²⁸ 🕒 May 25, 2023 4:43 pm

Here's the source code for the standard library of one conforming C++ compiler implementation: <https://github.com/llvm/llvm-project/tree/main/libcxx/> . You can take a look at the implementation details of all the standard library functions.

 Last edited 10 months ago by Krishnakumar

 1  Reply




South

 April 26, 2022 1:28 am

Not sure if the way I think isn't normal but functions I think are the best way to go. A dice roll function can be used by a game to calculate random damage to the player or mob but can also be used in any other program where a random number is desired.

I see functions as modules to be plugged in as needed and accessed. I see coding in general as a group of modules working together through linking code in the main to produce a result.

 8  Reply



Alex Author


 Reply to [South](#)²⁹  April 26, 2022 9:37 am

Exactly. If you're smart about how you design your "modules" they will be reusable across many different programs. This is maximized by separating the logic of your program (which is specific to your program) from the reusable components (functions and types that can be used in any program).

 13  Reply



KKW

 December 24, 2021 6:45 am

so like the brawl star figures, they were made using functions and if else so they will attack when the attack button is pressed, right? and the COC troops keep attacking and don't attack when walking is also because of the use of functions and if else, right?

 5  Reply



Ankes

 Reply to [KKW](#)³⁰  August 29, 2022 3:52 am

yeah you are right

 1  Reply

**MWAR**Reply to [KKW](#)³⁰ ⌚ March 3, 2022 7:54 pm

Not sure what you're referring to. But keep it up! Learning by relating to things you already know is one of the best ways to retain information! I use the ADEPT method :
<https://betterexplained.com/articles/adept-method/>

👍 4 ➡ Reply

**Jean Peter T. Paredes**

⌚ August 26, 2021 6:23 pm

"Statements that appear more than once in a program should generally be made into a function. For example, if we're reading input from the user multiple times in the same way, that's a great candidate for a function. If we output something in the same way multiple times, that's also a great candidate for a function."

Would like to add that

Statements that appeared once BUT has a high probability of being used multiple times in the future should generally be made into a function
just like the get user input from our previous lessons

👍 10 ➡ Reply

**Nitin**

⌚ August 22, 2021 9:27 pm

isn't it okay to use "using namespace std;" than using every time std: with in-build functions.

👍 1 ➡ Reply

**Alex** AuthorReply to [Nitin](#)³¹ ⌚ August 25, 2021 12:44 pm

This question is addressed in lesson <https://www.learncpp.com/cpp-tutorial/using-declarations-and-using-directives/>

👍 10 ➡ Reply

**Ni3**Reply to [Alex](#)³² ⌚ August 26, 2021 1:38 am

Okay thank you sir

👍 4 ➡ Reply

**lil pump**

🕒 February 20, 2021 7:36 am

[C++]

#include iostream

```
int main(){
    std::cout << "Hello world" << std::endl;
}
```

[/C++]

👍 0

➡ Reply

**seaque**🗨 Reply to [lil pump](#)³³ 🕒 June 1, 2021 6:40 am

the correct use is

```
1 | #include iostream
2 |
3 | int main(){
4 |     std::cout << "Hello world" << std::endl;
5 | }
```

👍 0

➡ Reply

**Vinorosso**🗨 Reply to [seaque](#)³⁴ 🕒 June 21, 2021 2:03 am

The code should be like this tho:

```
1 | #include <iostream>
2 |
3 | int main()
4 | {
5 |     std::cout << "Hello world\n";
6 |
7 |     return 0;
8 | }
```

Copy

👍 0

➡ Reply

**seaque**🗨 Reply to [seaque](#)³⁴ 🕒 June 1, 2021 6:58 am

sorry, i meant (code) (/code)

change the parenthesis with []



1



Reply



RHOULAN DHAMAR WANTO

🕒 November 21, 2020 11:12 pm

please help Alex

please help me with this

(Equilateral Triangle validation and perimeter) Implement the following two functions:

// Returns true if all the sides of the triangle

// are same.

bool isValid(double side1, double side2, double side3)

// Returns the perimeter of an equilateral triangle.

double perimeter(double side1)

The formula for computing the perimeter is $\text{perimeter} = 3 * \text{side}$. Write a test program that reads three sides for a triangle and computes the perimeter if the input is valid. Otherwise, display that the input is invalid.



0



Reply



Anon

🗨️ Reply to [RHOULAN DHAMAR WANTO](#)³⁵ 🕒 December 17, 2020 10:56 am

```
#include <iostream>
```

```
bool isValid(double side1, double side2, double side3)
```

```
{
```

```
    //if side1 == side2 then they have the same length, and if side2 and side 3 have the same length,
```

```
    //it follows that side1 == side2 == side3 and therefore it is equilateral
```

```
    return (side1 == side2) && (side2 == side3);
```

```
}
```

```
double perimeter(double side1)
```

```
{
```

```
    return side1 * 3;
```

```
}
```

```
int main()
```

```
{
```

```
    //you could refactor a way to take the input for all 3 sides as a function
```

```
    std::cout << "Please enter side1 of your triangle:";
```

```
    double side1{};
```

```
std::cin >> side1;
std::cout << "Please enter side2 of your triangle:";
double side2{};
std::cin >> side2;
std::cout << "Please enter side3 of your triangle:";
double side3{};
std::cin >> side3;
if (isValid(side1, side2, side3))
{
    std::cout << "The perimeter of an equilateral triangle with side length " << side1 << " is
" << perimeter(side1) << ".";
} else
{
    std::cout << "The triangle is not equilateral.";
}
return 0;
}
```

👍 2 ➡ Reply



John

🕒 November 10, 2020 6:13 am

for practice purposes:

```
1  #include <iostream>
2
3  int get_value()
4  {
5      int v{};
6
7      std::cout << "Enter a Number: ";
8      std::cin >> v;
9
10     return v;
11 }
12
13 char get_operator()
14 {
15     char o{};
16
17     std::cout << "Enter operator: ";
18     std::cin >> o;
19
20     return o;
21 }
22
23 int main()
24 {
25     int a{ get_value() };
26     char op{ get_operator() };
27     int b{ get_value() };
28
29     switch (op)
30     {
31         case '*':
32             std::cout << a * b << "\n";
33             break;
34         case '/':
35             std::cout << a / b << "\n";
36             break;
37         case '+':
38             std::cout << a + b << "\n";
39             break;
40         case '-':
41             std::cout << a - b << "\n";
42             break;
43     }
44
45     return 0;
46 }
```



4



Reply

**lettuceMan**Reply to [John](#)³⁶ February 14, 2022 7:37 am

nice



2



Reply

**Mathari**

🕒 May 9, 2020 9:00 pm

Hello

Are there any tutorials or exercises accompanying each lesson?

👍 0

➡ Reply

**José**🗨 Reply to [Mathari](#) 🕒 May 19, 2020 6:46 am

If you search on the internet, maybe you'll find something

👍 0

➡ Reply

**nascardriver**

Sub-admin

🗨 Reply to [Mathari](#) 🕒 May 10, 2020 3:23 am

Not for each lesson. There's a quiz every now and then.

👍 0

➡ Reply

**you're using a function provided by the standard library**

🕒 May 5, 2020 8:43 am

- 1 | "Although it doesn't look like it, every time you use `operator<<` or `operator>>` to do input or output, you're using a function provided by the standard library that meets all of the above criteria."

I found this part very interesting. Can we reach in this tutorial to a point where we can start writing user-defined functions with such characteristic you mentioned in the quote?

I mean I hadn't had any idea `std::cout`, could be a function!

👍 0

➡ Reply

**nascardriver**

Sub-admin

🗨 Reply to [you're using a function provided by the standard library](#) 🕒 May 6, 2020 6:40 am

`std::cout` is a variable, the function is `<<`. We show how to write those functions in the chapter about operator overloading.

👍 1

➡ Reply

**ColdCoffee**

🕒 April 7, 2020 11:02 am

"A function should generally perform one (and only one) task."

If function always performs one and only one task then why do you use "generally" ?

👍 0

➡ Reply

**Gabe**🗨 Reply to [ColdCoffee](#) 🕒 April 9, 2020 1:32 pm

The idea is to use a function that only solves a single computational. No more. If you have a function that not only computes the sum of two parameters passed as arguments, but also prints out the result in the same function, that only shows that you can separate the two as their own functions. Functions should be short and sweet and binds to the name of the function.

👍 1

➡ Reply

**Jonas**

🕒 June 9, 2019 12:58 am

Found a typo at the first point of 'Effectively using functions' (incorrect word is marked with asterisks and already corrected):

Statements that *appear* more than once in a program should generally be made into a function.

👍 0

➡ Reply

**Rowan**

🕒 February 28, 2019 12:16 pm

do you know why 0 does not move

```
#include <iostream>
```

```
#include <conio.h>
```

```
using namespace std;
```

```
bool gameover;
```

```
const int width = 20;
```

```
const int height = 20;
```

```
int x, y, fruitX,fruitY, score;
```

```
enum eDirection { STOP = 0, LEFT, RIGHT, UP, DOWN};
```

```
eDirection dir;
```

```
void Setup() {
```

```
    gameover = false;
```

```
    dir = STOP;
    x = width / 2;
    y = height / 2;
    fruitX = rand() % width;
    fruitY = rand() % height;
    score = 0;
}

void Draw() {

    system("cls");
    for (int i = 0; i < width; i++)
        cout << "#";
    cout << endl;

    for (int i = 0; i < height; i++)
    {
        for (int j = 0; j < width; j++)
        {
            if (j == 0)

                cout << "#";
            if (i == y && j == x)
                cout << "0";

            else if (i == fruitY && j == fruitX)
                cout << "F";

            else

                cout << " ";
            if (j == width + 2)
                cout << "#";
        }
        cout << endl;
    }

    for (int i = 0; i < width+2; i++)
        cout << "#";
    cout << endl;

}

void input() {
```

```
if (_kbhit())
{
    switch (_getch()) {
        case 'a':
            dir = LEFT;
            break;
        case 'd':
            dir = RIGHT;
            break;
        case 'w':
            dir = UP;
            break;
        case 's':
            dir = DOWN;
            break;
        case 'x':
            gameover = true;
            break;
    }
}

void Logic()
{
    switch (eDirection())
    {
        case STOP:
            break;
        case LEFT:
            break;
        case RIGHT:
            break;
        case UP:
            break;
        case DOWN:
            break;
        default:
            break;
    }
    if (x > width || x < 0 || y > height || y < 0)
        gameover = true;
}

int main()
{
```



```
Setup();
while (!gameover)
    Draw();
input();
Logic();

return 0;
}
```

👍 0

➡ Reply

**Julius**🗨 Reply to [Rowan](#) ⌚ March 31, 2019 7:28 am

I did not read in detail through all of it but one problem I found was that the GameLoop in Main (while(!gameover))

only calls your draw function, not the input and Logic functions. They only get called once the gameLoop is over.

I would suggest moving the input and Logic function calls into the GameLoop and see what happens

(change this)

```
1 while(!gameover) {
2     Draw();
3 }
4 input();
5 Logic();
```

to this

```
1 while(!gameover) {
2     input();
3     Logic();
4     Draw();
5 }
```

👍 0

➡ Reply

**Anonymous**

⌚ November 8, 2018 5:11 am

I combined all the things I learnt so far up to this point

Is there anything I could improve on in this code or so far so good?

```
#include <iostream>
```

```
void doNothing(const int &q)
{
```

```
}

int getValueFromUser()
{
    std::cout << "Enter a number: " << std::endl;
    int a;
    std::cin >> a;
    return a;
}

void doRendering()
{
    std::cout << "Rendering..." << std::endl;
}

void doConfiguring()
{
    std::cout << "Configuring..." << std::endl;
}

void doRenderAndConfigure()
{
    doRendering();
    doConfiguring();
}

void printValue(int x, int y)
{
    std::cout << x << std::endl;
    std::cout << y << std::endl;
}

int add(int x, int y)
{
    return x + y;
}

int multiply(int x, int y)
{
    return x * y;
}

int doubleNumber(int x)
{
    return x * 2;
}
```

```
int Return5()
{
    return 5;
}

int main()
{
    int x = getValueFromUser();
    int y = getValueFromUser();
    int z;
    doNothing(z);
    doRenderAndConfigure();
    std::cout << "Hello World!\nYour numbers are: " << add(doubleNumber(x), y) << std::endl;
    std::cout << z << std::endl;
    printValue(Return5(), multiply(Return5(), 2));
    return 0;
}
```

👍 0 ➡ Reply



nascar driver

🗨 Reply to [Anonymous](#) ⌚ November 8, 2018 7:46 am

- "q" is a poor variable name. Avoid abbreviations unless they're obvious.

Other than that there's not much to say, because this is lesson 1.4b. You'll learn about other improvements in future lessons.

When you're done with lesson 2.7, there should two improvements you can make to your code. If you don't find them, feel free to repost your code or leave a reply here.

👍 0 ➡ Reply



Dhruv Tyagi

⌚ April 19, 2018 12:39 pm

Dear Alex, I made a small calculator to add, subtract, multiply and devidetwo integers...Can you edit the code such that it can calculate the decimals too?


```

1  #include "stdafx.h"
2  #include <iostream>
3
4  int add(int x, int y) // add two numbers
5  {
6      return x + y;
7  }
8
9  int multiply(int x, int y) // multiply two numbers
10 {
11     return x * y;
12 }
13
14 int subtract(int x, int y) // subtract two numbers
15 {
16     return x - y;
17 }
18
19 int devide(int x, int y) // devide two numbers
20 {
21     return x / y;
22 }
23
24 int req1() //choose the first number
25 {
26     int a;
27     std::cout << "Enter the first variable: " << std::endl;
28     std::cin >> a;
29     return a;
30 }
31
32 int req2() //choose the second number
33 {
34     int b;
35     std::cout << "Enter the second variable: " << std::endl;
36     std::cin >> b;
37     return b;
38 }
39
40 int req3() //choose the operator
41 {
42     int op;
43     std::cout << "Enter the mathematical operator: (1 = + , 2 = - , 3 = * ,
44 4 = /) " << std::endl;
45     std::cin >> op;
46     return op;
47 }
48
49 void calculate() { //calculate
50     int p, q, r;
51     p = req1(); // number 1
52     q = req2(); //number 2
53     r = req3(); // operator
54     if (r == 1) { // add
55         std::cout << p << " + " << q << " = " << add(q, p) << std::endl;
56     }
57     else if (r == 2) { // subtract
58         std::cout << p << " - " << q << " = " << subtract(p, q) <<
59 std::endl;
60     }
61     else if (r == 3) { //multiply
62         std::cout << p << " * " << q << " = " << multiply(p, q) <<
63 std::endl;
64     }
65     else if (r == 4) { // devide
66         std::cout << p << " / " << q << " = " << devide(p, q) << std::endl;

```

```
66         std::cout << p << " / " << q << " = " << calculate(p, q) << std::endl;
67     }
68     else { // invalid operator
69         std::cout << "Enter a valid operator..." << std::endl;
70     }
71 }
int main() {
    calculate();
}
```

Thanks

👍 0

➡ Reply



codePhobia

🗨 Reply to [Dhruv Tyagi](#) ⌚ December 25, 2022 3:21 pm



```

1  #include <iostream>
2
3  double getNum()
4  {
5      double inp{};
6      std::cin >> inp;
7      return inp;
8  }
9
10 int main()
11 {
12     std::cout << "Enter the first variable: ";
13     double num1{ getNum() };
14     std::cout << "Enter the second variable: ";
15     double num2{ getNum() };
16     std::cout << "Enter the mathematical operator: (1 = +, 2 = -, 3
17 = *, 4 = /\n";
18     int op{};
19     std::cin >> op;
20
21     switch (op)
22     {
23         case 1:
24             std::cout << num1 << " + " << num2 << " = " << num1 +
25 num2;
26             break;
27         case 2:
28             std::cout << num1 << " - " << num2 << " = " << num1 -
29 num2;
30             break;
31         case 3:
32             std::cout << num1 << " * " << num2 << " = " << num1 *
33 num2;
34             break;
35         case 4:
36             std::cout << num1 << " / " << num2 << " = " << num1 /
37 num2;
38             break;
39         default:
40             std::cout << "Enter a valid operator...\n";
41     }
42
43     return 0;
44
45     /*
46     if (op == 1)
47     {
48         std::cout << num1 << " + " << num2 << " = " << num1 + num2;
49     }
50     else if (op == 2)
51     {
52         std::cout << num1 << " - " << num2 << " = " << num1 - num2;
53     }
54     else if (op == 3)
55     {
56         std::cout << num1 << " * " << num2 << " = " << num1 * num2;
57     }
58     else if (op == 4)
59     {
60         std::cout << num1 << " / " << num2 << " = " << num1 / num2;
61     }
62     else
63     {
64         std::cout << "Enter a valid operator...\n";
65     }
66     */

```



```
}
```

 0 Reply**nascardriver** Reply to [Dhruv Tyagi](#)  April 20, 2018 8:36 am

Hi Dhruv!

Use 'double' instead of 'int'.

References

Lesson 2.1 - Fundamental variable definition, initialization, and assignment

Lesson 2.5 - Floating point numbers

 0 Reply**Singh** Reply to [nascardriver](#)  June 18, 2019 10:08 am

Hi there, How's it going?

Can you please look into my case. Please check with line number 11 and 56.

1. Unable to use double to get decimal value on a division of number.
2. Not able to clear screen if not a valid input from a user.


```

1 //Program is to use different functions to get the results.
2
3 #include <iostream>
4
5 int addfunction(int a, int b)
6     { return a+b; }
7
8 int multi(int a, int b)
9     { return a*b; }
10
11 int division(int a, int b) //not getting result even using
12 double.
13     { double c=a/b;
14       std::cout<<"Division of both A & B is: " <<c;
15       return c; }
16
17 int main()
18     {
19         std::cout<<"Program is to add, mulitply or divide the
20 numbers.\n";
21         int x{};
22         std::cout<<"Please select the function.\nTo ADD:
23 1\nTo MUL: 2\nTo DIV: 3\n\nInput: ";
24         std::cin>>x;
25
26         // And how can I use the below set of code in new
27         // function which can be called in if Statements?
28         //only after condition check whereas it has to run
29         //every time. But its working fine If I put
30         //"else if(x==4)" condition as "if(x==4)" below
31         //(before a & b declaration.) Such as Below:
32         //    if(x==4)
33         //    {
34         //        std::cout<<"Please input valid number.\n";
35         //        std::cin.clear();
36         //        main();
37         //    }
38         //    Is it a good approach or do we have any
39         //    solution to it. */
40
41         int a, b;
42         std::cout<<"\nPlease enter the numbers.";
43         std::cout<<"A: ";
44         std::cin>>a;
45         std::cout<<"B: ";
46         std::cin>>b;
47
48         if(x==1)
49         {
50             std::cout<<addfunction(a,b);
51         }
52         else if(x==2)
53         {
54             std::cout<<multi(a,b);
55         }
56         else if(x==3)
57         {
58             std::cout<<division(a,b);
59         }
60         else if(x==4)
61         {
62             std::cout<<"Please input valid
63 number.\n";
64             system("cls"); //how to perform clear
65             screen and again it goes back to main after screen went
66             black not working with cls

```

```
01 | BLACK. NOT WORKING WITH C++
    |
    |     main();
    | }
    |
    |     return 0;
    | }
    |
```



0



Reply

**nascar driver**
 Reply to [Singh](#) June 19, 2019 3:24 am

- Use your editor's auto-formatting feature.
- `main` cannot be used. You need a loop, loops are covered later.
- Don't use `system`, it won't work on other platforms.

> Line 12

`c`'s type doesn't matter. You're dividing an `int` by an `int`, the result is an `int`, which is then converted to a `double`. You need to copy `a` or `b` or both into a double and divide that. (You'll learn about casts later, you don't need an extra variable then).

> Line 56

There is no universal way to clear the console/terminal. You can try hiding the previous output by printing a lot of line feeds.

```
1 | std::cout << std::string(1024, '\n'); // Repeats '\n'
2 | 1024 times.
   | // I made up 1024. There is no universal way of
   | retrieving the terminal height.
```



1



Reply

**Henry**

April 4, 2018 7:38 am

Hi Alex, please what does these three statements do:

```
"std::cin.clear();
std::cin.ignore(32767, '\n');
std::cin.get();" ????
```



0



Reply

**Anonymous**
 Reply to [Henry](#) April 20, 2018 8:04 am

you can use double instead of int to define all the variables and you will be able to do

decimal calculations as well.

👍 0 ➡ Reply



nascardriver

👤 Reply to [Henry](#) ⌚ April 4, 2018 7:46 am

Hi Henry!

This is covered in lesson 5.10.

@std::cin.clear clears @std::cin's error flag

@std::cin.ignore ignores all characters in the input stream until '\n' is found, but a maximum of 32767 characters.

@std::cin.get reads one character from the input stream

👍 0 ➡ Reply



Henry

👤 Reply to [nascardriver](#) ⌚ April 4, 2018 11:46 pm

Thank you for this tutorial.

I used to be scared of programming before now, but this tutorial has changed that.

👍 0 ➡ Reply



ScarLet

⌚ July 6, 2017 8:49 pm

Is in a program only contain one function main() or can be more in a program?

👍 0 ➡ Reply



Alex Author

👤 Reply to [ScarLet](#) ⌚ July 6, 2017 11:19 pm

A program can only contain one main() function, but may contain as many other functions as you want.

👍 0 ➡ Reply



Kamran

⌚ July 6, 2017 3:38 am

I want to learn c++

👍 1 ➡ Reply

**UncleMi**Reply to [Kamran](#) ⌚ July 7, 2017 8:35 am

You are in the right place then



1



Reply

Links

1. <https://www.learncpp.com/author/Alex/>
2. <https://www.learncpp.com/cpp-tutorial/finding-issues-before-they-become-problems/>
3. <https://www.learncpp.com/cpp-tutorial/forward-declarations/>
4. <https://www.learncpp.com/>
5. <https://www.learncpp.com/cpp-tutorial/introduction-to-local-scope/>
6. <https://www.learncpp.com/why-functions-are-useful-and-how-to-use-them-effectively/>
7. <https://www.learncpp.com/cpp-tutorial/range-based-for-loops-for-each/>
8. <https://www.learncpp.com/cpp-tutorial/null-pointers/>
9. <https://gravatar.com/>
10. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-593854>
11. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-593650>
12. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-592978>
13. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-589534>
14. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-591514>
15. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-592206>
16. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-589059>
17. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-588012>
18. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-579034>
19. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-579838>
20. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-582239>

21. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-586517>
22. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-576575>
23. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-578473>
24. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-586043>
25. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-576703>
26. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-575265>
27. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-574626>
28. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-574664>
29. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-568076>
30. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-563811>
31. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-560489>
32. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-560593>
33. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-500748>
34. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-536527>
35. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-482250>
36. <https://www.learncpp.com/cpp-tutorial/why-functions-are-useful-and-how-to-use-them-effectively/#comment-480000>