



## 1.8 — Whitespace and basic formatting

👤 ALEX<sup>1</sup> 🕒 JANUARY 23, 2024

**Whitespace** is a term that refers to characters that are used for formatting purposes. In C++, this refers primarily to spaces, tabs, and newlines. Whitespace in C++ is generally used for 3 things: separating certain language elements, inside text, and for formatting code.

### Some language elements must be whitespace-separated

The syntax of the language requires that some elements are separated by whitespace. This mostly occurs when two keywords or identifiers must be placed consecutively, so the compiler can tell them apart.

For example, a variable declaration must be whitespace separated:

```
1 | int x; // int and x must be whitespace separated
```

If we typed `intx` instead, the compiler would interpret this as an identifier, and then complain it doesn't know what identifier `intx` is.

As another example, a function's return type and name must be whitespace separated:

```
1 | int main(); // int and main must be whitespace separated
```

When whitespace is required as a separator, the compiler doesn't care how much whitespace is used, as long as some exists.

The following variable definitions are all valid:

```
1 | int x;  
2 | int          y;  
3 |           int  
4 | z;
```

In certain cases, newlines are used as a separator. Single-line comments are terminated by a newline.

As an example, doing something like this will get you in trouble:

```
1 | std::cout << "Hello world!"; // This is part of the comment and  
2 | this is not part of the comment
```

Preprocessor directives (e.g. `#include <iostream>`) must be placed on separate lines:

```
1 | #include <iostream>
2 | #include <string>
```

## Quoted text takes the amount of whitespace literally

Inside quoted text, the amount of whitespace is taken literally.

```
1 | std::cout << "Hello world!";
```

is different than:

```
1 | std::cout << "Hello      world!";
```

Newlines are not allowed in quoted text:

```
1 | std::cout << "Hello
2 |     world!"; // Not allowed!
```

Quoted text separated by nothing but whitespace (spaces, tabs, or newlines) will be concatenated:

```
1 | std::cout << "Hello "
2 |     "world!"; // prints "Hello world!"
```

## Using whitespace to format code

Whitespace is otherwise generally ignored. This means we can use whitespace wherever we like to format our code in order to make it easier to read.

For example, the following is pretty hard to read:

```
1 | #include <iostream>
2 | int main(){std::cout<<"Hello world";return 0;}
```

The following is better (but still pretty dense):

```
1 | #include <iostream>
2 | int main() {
3 |     std::cout << "Hello world";
4 |     return 0;
5 | }
```

And the following is even better:

```
1 | #include <iostream>
2 |
3 | int main()
4 | {
5 |     std::cout << "Hello world";
6 |
7 |     return 0;
8 | }
```

Statements may be split over multiple lines if desired:

```
1 | #include <iostream>
2 |
3 | int main()
4 | {
5 |     std::cout
6 |         << "Hello world"; // works fine
7 |     return 0;
8 | }
```

This can be useful for particularly long statements.

---

## Basic formatting

Unlike some other languages, C++ does not enforce any kind of formatting restrictions on the programmer. For this reason, we say that C++ is a whitespace-independent language.

This is a mixed blessing. On one hand, it's nice to have the freedom to do whatever you like. On the other hand, many different methods of formatting C++ programs have been developed throughout the years, and you will find (sometimes significant and distracting) disagreement on which ones are best. Our basic rule of thumb is that the best styles are the ones that produce the most readable code, and provide the most consistency.

Here are our recommendations for basic formatting:

1. It's fine to use either tabs or spaces for indentation (most IDEs have a setting where you can convert a tab press into the appropriate number of spaces). Developers who prefer spaces tend to do so because it ensures that code is precisely aligned as intended regardless of which editor or settings are used. Proponents of using tabs wonder why you wouldn't use the character designed to do indentation for indentation, especially as you can set the width to whatever your personal preference is. There's no right answer here -- and debating it is like arguing whether cake or pie is better. It ultimately comes down to personal preference.

Either way, we recommend you set your tabs to 4 spaces worth of indentation. Some IDEs default to 3 spaces of indentation, which is fine too.

2. There are two conventional styles for function braces.

Many developers prefer putting the opening curly brace on the same line as the statement:

```
1 | int main() {  
2 |     // statements here  
3 | }
```

The justification for this is that it reduces the amount of vertical whitespace (as you aren't devoting an entire line to an opening curly brace), so you can fit more code on a screen. This enhances code comprehension, as you don't need to scroll as much to understand what the code is doing.

However, in this tutorial series, we'll use the common alternative, where the opening brace appears on its own line:

```
1 | int main()  
2 | {  
3 |     // statements here  
4 | }
```

This enhances readability, and is less error prone since your brace pairs should always be indented at the same level. If you get a compiler error due to a brace mismatch, it's very easy to see where.

- Each statement within curly braces should start one tab in from the opening brace of the function it belongs to. For example:

```
1 | int main()  
2 | {  
3 |     std::cout << "Hello world!\n"; // tabbed in one tab (4 spaces)  
4 |     std::cout << "Nice to meet you.\n"; // tabbed in one tab (4 spaces)  
5 | }
```

- Lines should not be too long. Typically, 80 characters has been the de facto standard for the maximum length a line should be. If a line is going to be longer, it should be split (at a reasonable spot) into multiple lines. This can be done by indenting each subsequent line with an extra tab, or if the lines are similar, by aligning it with the line above (whichever is easier to read).

```
1 | int main()  
2 | {  
3 |     std::cout << "This is a really, really, really, really, really, really,  
4 | really, "  
5 |         "really long line\n"; // one extra indentation for continuation line  
6 |  
7 |     std::cout << "This is another really, really, really, really, really,  
8 | really, really, "  
9 |         "really long line\n"; // text aligned with the previous  
10 | line for continuation line  
  
    std::cout << "This one is short\n";  
}
```

This makes your lines easier to read. On modern wide-screen monitors, it also allows you to place two windows with similar code side by side and compare them more easily.

## Best practice

Consider keeping your lines to 80 chars or less in length.

## Tip

Many editors have a built-in feature (or plugin/extension) that will show a line (called a “column guide”) at a given column (e.g. at 80 characters), so you can easily see when your lines are getting too long. To see if your editor supports this, do a search on your editor’s name + “Column guide”.

5. If a long line is split with an operator (eg. `<<` or `+`), the operator should be placed at the beginning of the next line, not the end of the current line

```
1 | std::cout << 3 + 4
2 |   + 5 + 6
3 |   * 7 * 8;
```

This helps make it clearer that subsequent lines are continuations of the previous lines, and allows you to align the operators on the left, which makes for easier reading.

6. Use whitespace to make your code easier to read by aligning values or comments or adding spacing between blocks of code.

Harder to read:

```
1 | cost = 57;
2 | pricePerItem = 24;
3 | value = 5;
4 | numberOfItems = 17;
```

Easier to read:

```
1 | cost           = 57;
2 | pricePerItem   = 24;
3 | value          = 5;
4 | numberOfItems  = 17;
```

Harder to read:

```
1 | std::cout << "Hello world!\n"; // cout lives in the iostream library
2 | std::cout << "It is very nice to meet you!\n"; // these comments make the
3 | code hard to read
   | std::cout << "Yeah!\n"; // especially when lines are different lengths
```

Easier to read:

```
1 | std::cout << "Hello world!\n";           // cout lives in the
2 | iostream library
3 | std::cout << "It is very nice to meet you!\n"; // these comments are easier
   | to read
   | std::cout << "Yeah!\n";                 // especially when all lined
   | up
```

Harder to read:

```
1 | // cout lives in the iostream library
2 | std::cout << "Hello world!\n";
3 | // these comments make the code hard to read
4 | std::cout << "It is very nice to meet you!\n";
5 | // especially when all bunched together
6 | std::cout << "Yeah!\n";
```

Easier to read:

```
1 | // cout lives in the iostream library
2 | std::cout << "Hello world!\n";
3 |
4 | // these comments are easier to read
5 | std::cout << "It is very nice to meet you!\n";
6 |
7 | // when separated by whitespace
8 | std::cout << "Yeah!\n";
```

We will follow these conventions throughout this tutorial, and they will become second nature to you. As we introduce new topics to you, we will introduce new style recommendations to go with those features.

Ultimately, C++ gives you the power to choose whichever style you are most comfortable with, or think is best. However, we highly recommend you utilize the same style that we use for our examples. It has been battle tested by thousands of programmers over billions of lines of code, and is optimized for success.

One exception: If you are working in someone else's code base, adopt their styles. It's better to favor consistency than your preferences.

### Best practice

When working in an existing project, be consistent with whatever style has already been adopted.

## Automatic formatting

Most modern IDEs will help you format your code as you type it in (e.g. when you create a function, the IDE will automatically indent the statements inside the function body).

However, as you add or remove code, or change the IDE's default formatting, or paste in a block of code that has different formatting, the formatting can get messed up. Fixing the formatting for part or all of a file can be a headache. Fortunately, modern IDEs typically contain an automatic formatting feature that will reformat either a selection (highlighted with your mouse) or an entire file.

### For Visual Studio users

In Visual Studio, the automatic formatting options can be found under *Edit > Advanced > Format Document* and *Edit > Advanced > Format Selection*.

### For Code::Blocks users

In Code::Blocks, the automatic formatting options can be found under *Right mouse click > Format use AStyle*.

For easier access, we recommend adding a keyboard shortcut to auto-format the active file.

There are also external tools that can be used to automatically format code. [clang-format](https://clang.llvm.org/docs/ClangFormat.html) (<https://clang.llvm.org/docs/ClangFormat.html>)<sup>2</sup> is a popular one.

### Best practice

Using the automatic formatting feature is highly recommended to keep your code's formatting style consistent.

## Style guides

A **style guide** is a concise, opinionated document containing (sometimes arbitrary) programming conventions, formatting guidelines, and best practices. The goal of a style guide is to ensure that all developers on a project are programming in a consistent manner.

Some commonly referenced C++ style guides include:

- [C++ Core Guidelines](#)<sup>3</sup>, maintained by Bjarne Stroustrup and Herb Sutter.
- [Google](#)<sup>4</sup>.
- [LLVM](#)<sup>5</sup>
- [GCC/GNU](#)<sup>6</sup>

We generally favor the C++ Core Guidelines, as they are up to date and widely applicable.

## [Next lesson](#)

1.9 [Introduction to literals and operators](#)

7

## [Back to table of contents](#)

8

## [Previous lesson](#)

1.7 [Keywords and naming identifiers](#)

9

10



**B** **U** **URL** **INLINE CODE** **C++ CODE BLOCK** **HELP!**

Leave a comment...

Name\*

Email\*

Notify me about replies: ☐

POST COMMENT

Find a mistake? Leave a comment above!

Avatars from <https://gravatar.com/><sup>13</sup> are connected to your provided email address.

192 COMMENTS

Newest



**Young**

April 10, 2024 7:34 pm

Is it normal for ClangFormat to turn a single tab into two spaces? (I use Clion and I clicked "Enable ClangFormat (only for C/C++/Objective-C)" in the code style setting)

0

Reply

**Thomas**

April 2, 2024 10:47 am

Just saw that there is a "Code Cleanup" in VS Code 2022. Tools -> Options -> Code Cleanup. Checkmark Run Code Cleanup profile on save, and configure it. For some reason for C++, I needed to remove the Format Document and add the Format Document C++ in Profile 1. You can adjust the multiple options but I kept the default profile 1 and just switched Format Document to Format Document C++.

Hope this helps others. Such a great website, thank you!

0

Reply

**Ryan Rawlings**

February 23, 2024 7:05 am

Almost anyone who says they "always use tabs", or "always use spaces" is knowingly or unknowingly just inserting their favorite indentation character into documents that use the other one. Every IDE worth using has an option to render white space characters, and if everyone turned that option on, it'd be a lot harder to create a mixed indentation mess.

0

Reply

**IceFloe**

February 18, 2024 4:30 pm

which is better: `int x {25}` or `int x {25 }`?

Should I indent a space if there are several functions?

And finally, what if a function is inside a function? It turns out that the operator of the nested function needs another tab in 4 spaces? It will turn out to be a ladder, which may make it difficult to read the code

0

Reply

**Alex** AuthorReply to [IceFloe](#)<sup>14</sup> February 18, 2024 9:26 pm

`int x { 25 }` is more readable than `int x{25}` or `int x {25}`, imo. But any are fine.

> Should I indent a space if there are several functions?

Not sure what you mean here

Functions can't be nested inside each other. But generally we tab in each time we have something that is nested (e.g. a block inside a function, a function inside a namespace, etc...)

👍 0    ➡ Reply

**IceFloe**Reply to [Alex](#)<sup>15</sup> February 18, 2024 9:33 pm

thank you for the answer)

👍 0    ➡ Reply

**Krishnakumar**

January 12, 2024 1:51 am

Other popular style guides that are used by `clang-format` include:

- [Chromium coding style](#)<sup>16</sup>
- [Mozilla coding style](#)<sup>17</sup>
- [Webkit coding style](#)<sup>18</sup>
- [microsoft coding style](#)<sup>19</sup>

👍 4    ➡ Reply

**Erik**

January 8, 2024 12:02 am

Hi Alex,

"The Google C++ style guide recommends putting the opening curly brace on the same line as the statement:"

If I understand correctly the C++ Core Guidelines recommends the same:

<https://isocpp.github.io/CppCoreGuidelines/CppCoreGuidelines#RI-knr>

I was just wondering if you try to follow those guidelines in these lessons? What is your take on it?

I realize it can generate a lot of work, but maybe it is worth referencing and discussing them in this chapter?

👍 0    ➡ Reply



**Alex** Author

Reply to Erik<sup>20</sup> January 8, 2024 3:56 pm

> but maybe it is worth referencing and discussing them in this chapter?

Both options are presented in this very lesson.

For beginners, I think having the opening and closing braces indented to the same level is easier to read and debug.

Once you become more experienced, you may very well want to switch to preserve vertical space, and that's fine.

👍 1    ➡ Reply



**Erik**

Reply to Alex<sup>21</sup> January 9, 2024 12:53 am

I meant why don't you reference the C++ Core Guidelines, but you do the Google guidelines. As a beginner I am thinking the 'official' guidelines must be better than some company's (well, they are in interwebs business for some time now... ;)).


I just came across those C++ guidelines reading about if-statements and was a bit confused when I saw another layout than I learned here. Actually, in your example you use a function block, but the C++ GL differentiate:

"Note The { for a class and a struct is not on a separate line, but the { for a function is."

I think you are right, using a separate line for the opening brace is a bit more easy to read. Which is best for beginners. But then again, I guess I just assumed you mostly followed the C++ GL, or at least inform us when you defer from them for good reasons. Maybe the Google GL are preferable? That's what I meant by discussing them, when do you follow which guidelines and what is the reason. Doesn't have to be a long discussion obviously.

Anyway, it is just a detail and not impacting the high quality of the lessons :)

👍 0    ➡ Reply



**Alex** Author

Reply to Erik<sup>22</sup> January 9, 2024 11:15 pm

Added a "style guides" section to this lesson, linking some of the more commonly mentioned style guides.

This tutorial series doesn't follow a particular style guide, though I tend to generally align with the C++ Core Guidelines. Whenever possible, if there are multiple common conventions, I'll try to mention them.



2



Reply

**Erik**Reply to [Alex](#)<sup>23</sup>

January 10, 2024 12:28 am

Thanks a lot, as always very clearly described (the added section and adjusted examples).



0



Reply


**Aaron**

December 30, 2023 6:20 pm

I don't see the option for automatic formatting in Visual Studio, I go Edit -> Advanced and nothing is there!



0



Reply

**Tekksage**

December 24, 2023 12:20 pm

not sure how valid this is but this example " #include <iostream>

```
int main()
```

```
{
```

```
std::cout
```

```
<< "Hello world"; // works fine
```

```
return 0;
```

```
} " doesn't serve its role as an example very well i suggest you make it longer to display the usefulness of sectioning a statement to make it more readable. if I'm mistaken about what that code was an example for then please ignore this.
```



0



Reply

**Te0\_faN**Reply to [Tekksage](#)<sup>24</sup>

December 29, 2023 1:01 pm

```
std::cout << "Hello world";
```

is already readable so you don't need to use a separate line.

"Typically, 80 characters has been the de facto standard for the maximum length a line should be".

 0 Reply**AbeerOrTwo**

December 13, 2023 8:33 pm

Very helpful beginning chapter

 0 Reply**Makis**

December 8, 2023 9:52 am

Also I really appreciate these tutorials being free!!! I had tried a lot of other languages but failed and each time I felt I had the same problem. I didn't know what to do and search and I failed. but it is different with C++. These tutorials are the only reason I even know a programming language. Thank you.

 1 Reply

## Links

1. <https://www.learncpp.com/author/Alex/>
2. <https://clang.llvm.org/docs/ClangFormat.html>
3. <http://isocpp.github.io/CppCoreGuidelines/CppCoreGuidelines>
4. <https://google.github.io/styleguide/cppguide.html>
5. <https://llvm.org/docs/CodingStandards.html>
6. <https://gcc.gnu.org/codingconventions.html>
7. <https://www.learncpp.com/cpp-tutorial/introduction-to-literals-and-operators/>
8. <https://www.learncpp.com/>
9. <https://www.learncpp.com/cpp-tutorial/keywords-and-naming-identifiers/>
10. <https://www.learncpp.com/whitespace-and-basic-formatting/>
11. <https://www.learncpp.com/wordpress/hyperlinking-your-wordpress-header-image/>
12. <https://www.learncpp.com/cpp-programming/6-ways-to-write-better-code/>
13. <https://gravatar.com/>
14. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-593790>
15. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-593802>
16. <https://chromium.googlesource.com/chromium/src/+/refs/heads/main/styleguide/styleguide.md>
17. [https://firefox-source-docs.mozilla.org/code-quality/coding-style/coding\\_style\\_cpp.html](https://firefox-source-docs.mozilla.org/code-quality/coding-style/coding_style_cpp.html)
18. <https://www.webkit.org/code-style-guidelines/>

19. <https://learn.microsoft.com/en-us/dotnet/fundamentals/code-analysis/code-style-rule-options>
20. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-591944>
21. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-591989>
22. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-592023>
23. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-592095>
24. <https://www.learncpp.com/cpp-tutorial/whitespace-and-basic-formatting/#comment-591326>