

# Polyethylene-LLDPE

## CLEAN CU \_AMC\_LLDPE



### METERIAL SAFETY DATE SHEET

#### 1. identification

product name: AMC LLDPE  
Company: CLEANCU  
Add: 85, Taeri-ro 179beon-gil, Gochon-eup, Gimpo-si,  
Gyeonggi-do, Republic of Korea  
Tel: (+82)31-998-5991  
Fax: (+82)31-998-5997  
Emergency Tel: (+82)31-998-5991

#### 2. Composition / Information on ingredients

Thermoplastic polyurethane elastomer: This product does not contain any hazardous  
Ingredients

- ☐ All additives are physically bounded (excapsulated) in the compound. This product  
Is not expected to create any hazard when it is used, handled, and processed.

Composition	CAS No.	Mass Ratio
Polyethylene	9002-88-4	Confidential
Copper	7440-50-8	Confidential

#### 3. Hazards Summarizing

- ☐ This product is not considered harzardous at ambient conditions and there are no  
Known or expected health effects.
- ☐ Processing temperatures(100~250°C) may generate fumes and vapors sufficient to  
Cause eye, skin and upper respiratory trect irritation if ventilation is inadequate.
- ☐ Molten polymer may cause thermal burns to skin and serious burns to eyes.

# Polyethylene -LLDPE

## CLEAN CU \_AMC\_LLDPE



In case of spillage, it is possible risk of slipping.

Chronic Health Effects: unknown.  
Routes of exposure/Entry: Inhalation of process vapors. Eye and/or skin contact  
Of molten polymer.  
Carcinogenic Status: Not listed or regulated by IARC.

#### 4. First Aid Measures

Inhalation:	if processing vapors or decomposition products are Inhaled, remove person to fresh air. If irritation Develops or persists, obtain medical attention.
Eye contact:	Flush eyes with water, mechanical effects only
Skin contact:	Wash the affected area thoroughly with plenty of water the and soap. If molten polymer contacts the skin, cool the skin rapidly with water or ice. Sea a physician for removal of any adhering material and for treatment of the burn.
Ingestion:	No ingestion effects known

## 5. Fire Fighting Measures

Combustion products:	Under fire conditions, polymer decomposition Generates smoke and unidentified toxic and irritating Compounds (see section 10)..
Extinguish media:	Small fire Use dry chemical, CO2, water spray or Regular foam. Large fire. Use water spray, water fog or regular foam. Do not use straight streams.
Firefighting instructions:	Fire fighters should wear positive pressure self-contained breathing apparatus and should be equipped with protective clothing. Keep people away and isolated fire area.

## 6. Accidental Release Measures

- ☐ In case of spill, sweep up material and place in containers for re-use or disposal

# Polyethylene -LLDPE

## CLEAN CU \_AMC\_LLDPE

## 7. Handling and Storage

- ☐ Avoid processing material above recommended thermal processing temperatures.  
Good general ventilation should be sufficient for most conditions, Consider the use  
Of local exhaust ventilation at processing emission points.
- ☐ Avoid breathing thermal processing fumes and vapors.
- ☐ Mechanical handling equipment can cause formation of dust Avoid breathing dust.,



- ☐ Use proper grounding techniques when handling this product to avoid electrostatic Charges.

Pellets on the floor may be slippery and cause falls.

Storage recommendations: To maintain product quality, store product in a cool, Dry area. Keep in a tightly sealed container.

#### 8. Exposure controls / Personal protection

Respiratory protection: For most conditions, no respiratory protection should Be needed.

- ☐ When processing at elevated temperatures without sufficient ventilation, use an Approved air-purifying respirator.

Eye protection: Use safety glasses if there is a potential risk for Exposure to particles. Use safety glasses if vapor Exposure causes eye discomfort.

Skin protection: Wear gloves for handling hot material during processing.

#### 9. Physical and Chemical Properties

Appearance: Spherical pellets or granules.

Odor: Not noticeable.

Boiling point / range: Not applicable.

Melting point / range: At temperatures between 50°C and 200°C.

Flash point: Not applicable.

Auto ignition: No data.

Vapor pressure: Not applicable.

Density at 23°C: 1.1~1.3 g/cm<sup>3</sup>.

Solubility (in water): Insoluble.

## Polyethylene -LLDPE

### CLEAN CU \_AMC\_LLDPE

#### 10. Stability and Reactivity

- ☐ Product is stable at room temperature. Hazardous polymerization will not occur.
- ☐ Volatiles from melt processing are expected to be water vapor, carbon dioxide and Other decomposition products.
- ☐ Hazardous decomposition products: These potential decomposition gases have not Been fully determined but may include CO, CO<sub>2</sub>, and small amounts of hydrogen,



Cyanide, oxide of nitrogen, hydrocarbons, isocyanate, water vapor and/or  
Combinations of the previous, and smoke, substances listed under thermal  
Processing emissions may also be present.

- ☐ The specific materials generated will vary depending on temperature, time and  
Other immediate environmental factors.

Conditions to avoid:                      Temperature above 260°C.

#### 11. Toxicological information

Inhalation:                                      At room temperature, exposure to dust and vapors is  
Unlikely. High processing temperatures may generate  
Vapors, which may cause irritation and sensitization.

Eyes:    Solid or dust may cause irritation due to mechanical  
Action. Elevated temperatures may generate vapors  
Sufficient to cause eye irritation.

Skin contact:                                      At room temperature essentially non-irritating to skin.  
At high temperature vapors may cause sensitization.

- ☐ No toxicity studies have been conducted.

#### 12. Ecological Information

- ☐ Not expected adverse effects from this product as furnished.
- ☐ This product has not been tested.
- ☐ Material expected to have low aquatic toxicity because of its insolubility in water.

#### 13. Disposal Considerations

- ☐ The unused product is not considered a hazardous waste.
- ☐ Do not dump into any sewers on the ground or into any body of water.
- ☐ Incinerate or Landfill waste in a properly permitted facility in accordance with  
federal, state and local regulations.

## Polyethylene - LLDPE

### CLEAN CU \_AMC\_ LLDPE



#### 14. Transport Information

- ☐ This product is Not REGULATED for domestic and international transportation.

#### 15. Regulatory Information

- ☐ This product does not need to be labeled according to Chinese regulations.

EINECS status:                                      All starting raw materials of this product are listed on  
EINECS.

TSCA status: All ingredients are on the TSCA inventory

Korea: All components of this product are included on the Korean inventory.

#### Disclaimer of Responsibility

- ☐ The information provided in this document is generated for the purpose of Distributing health safety and environmental data. Information contained herein is given in good faith and believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied
- ☐ The conditions or method of handling, storage, use and disposal of the product are beyond our control and we do not assume responsibility and expressly disclaim liability for loss, damage or expense connected with them.
- ☐ Compliance with all applicable state and local laws and local regulations remains the responsibility of the user.