DP-OPS-0069: System-Wide ID and Surface Lowercase Standardization Report

1. Executive Summary and Architectural Imperative

1.1 Report Scope and Strategic Objective

This document constitutes the definitive architectural blueprint and execution strategy for **DP-OPS-0069**, a foundational infrastructure refactoring initiative mandated for the Stela platform. The primary directive governing this operation is the execution of a strict, one-off migration of specific high-traffic documentation and factory surfaces from an archaic Uppercase/Hybrid naming convention to a strictly lowercase convention. This standardization effort encompasses file paths, filesystem nodes, and internal semantic Identifiers (IDs), specifically targeting the transition from the R-AGENT- nomenclature to r-agent-.

The scope of this migration is precise yet pervasive, affecting three critical domains of the repository's "Run" and "Explain" layers: the Prompt Engineering Surfaces located at docs/ops/prompts/, the Operational Registries housed in docs/ops/registry/, and the entirety of the Factory Floor definitions within opt/_factory/{agents,skills,tasks}/. Concurrently, a strict architectural constraint is in effect: the Manifest Library (ops/lib/manifests/), which serves as the immutable "Table of Contents" for the repository's context synthesis engine, must retain its Uppercase nomenclature (e.g., CORE.md, OPS.md, DISCOVERY.md). This duality necessitates a sophisticated "split-horizon" implementation strategy where the files describing the system—the Manifests—remain distinctively Uppercase to signal their constitutional status, while the mutable constituents of the system (Agents, Tasks, Prompts) transition to lowercase to align with modern developer ergonomics and web standards.

The realization of this objective requires more than a simple filesystem rename operation; it demands a comprehensive refactoring of the repository's internal machinery. The templates that generate the manifests, specifically located in ops/src/manifests/, must be adjusted to bridge the gap between the uppercase manifest filenames and the lowercase targets they index. Furthermore, the extensive suite of linters, lifecycle scripts, and verification tools that police the repository's integrity must be reprogrammed to recognize and enforce the new lowercase standards without compromising the historical accuracy of the ledger.

1.2 The Strategic Case for Lowercase Standardization

The historical trajectory of the Stela repository, as evidenced by the State of Play (SoP.md) ledger [1], reveals a system that has evolved from manual curation to rigorous, automated governance. The initial decision to utilize Uppercase filenames and IDs (e.g., R-AGENT-01,

AGENTS.md) was likely rooted in a desire for visual hierarchy—a typographic attempt to separate "Canon" (immutable rules) from "Code" (mutable payloads). However, as the platform has matured into a tool-driven environment governed by the Policy of Truth (PoT.md), this convention has introduced significant operational friction and technical debt.

The most pressing risk involves case-sensitivity hazards inherent in cross-platform development. Unix-based Continuous Integration (CI) environments, such as the Ubuntu runners used in the .github/workflows/ [1], rigorously distinguish between AGENTS.md and agents.md. Conversely, local development environments operating on macOS or Windows filesystems often treat these paths as identical. This discrepancy creates a vector for "ghost file" drift, where a file exists locally and satisfies local linters but fails in the remote CI pipeline due to casing mismatches in git ls-files calls. By standardizing on lowercase, which is the universal denominator for web URIs and filesystem paths, the platform eliminates this class of ambiguity entirely.

Furthermore, the ergonomics of the platform are significantly impacted by the current convention. Operations within the ops/ and opt/ directories are high-frequency activities for the Integrator and Contractors. Forcing operators to constantly toggle Shift keys or engage Caps Lock for standard interactions—such as editing docs/ops/registry/AGENTS.md or referencing R-AGENT-03—increases cognitive load and physical keystroke volume. This subtle degradation of the Developer Experience (DX) accumulates over thousands of interactions. The migration to r-agent-xx and agents.md aligns the repository with standard slugification practices, simplifying tooling logic in sed, awk, and grep operations, and streamlining the operator's workflow.

1.3 The Preservation Mandate and Split-Horizon Architecture

While the "Worker" surfaces migrate to lowercase, the "Legislative" surfaces—specifically the Context Manifests in ops/lib/manifests/—must remain Uppercase. This distinction is not merely aesthetic; it is deeply architectural. As defined in llms.txt [1], files like CORE.md, OPS.md, and DISCOVERY.md represent the **Constitution** and **Laws** of the repository. They are the root nodes of the context graph. Their Uppercase naming signals immutability and high-level structural importance, visually separating them from the mutable, lowercase content they index.

This report outlines a "split-horizon" approach to satisfy this constraint. The binary responsible for compiling manifests, ops/bin/compile [1], currently enforces uppercase naming for its outputs. We will leverage this existing behavior while modifying the *inputs*—the templates in ops/src/manifests/—to point to the new lowercase file paths. This ensures that OPS.md remains OPS.md on the disk, but its content will list docs/ops/registry/agents.md instead of AGENTS.md. This nuanced handling of the compiler pipeline is critical to preventing a "Link Rot" scenario where the context engine fails to locate the newly renamed artifacts.

2. Governance and Policy Analysis

2.1 Alignment with the Policy of Truth (PoT)

The **Policy of Truth (PoT.md)** [1] acts as the supreme constitution of the Stela repository, establishing the axioms that govern all file placement and naming conventions. Any structural change of this magnitude must be rigorously reconciled against PoT axioms to ensure it strengthens, rather than weakens, the repository's governance posture.

The migration adheres strictly to the **Filing Doctrine** defined in Section 1.1 of the PoT.[1] The doctrine explicitly maps ops/ to "Run," docs/ to "Explain," and opt/ to "Isolate." The proposed migration respects these boundaries implicitly; we are changing the *syntax* of the filenames within these directories, not their *semantics* or their *location*. The agents will remain in opt/_factory/, ensuring they remain isolated from the global context until explicitly invoked, preserving the "Isolate" directive.

Crucially, the migration aligns with the **Axiom of Precision**. The PoT demands "Linguistic Precision" and the elimination of ambiguity.[1] The current state, where some registries are uppercase (AGENTS.md) while the directory containing them is lowercase (docs/), introduces a cognitive dissonance. Standardizing on lowercase eliminates the question of "Is it Agent or agent?" It is always agent. This reduction in entropy aligns the repository with a single, coherent style guide, effectively mitigating "Style Drift" before it becomes a systemic issue.

2.2 Impact on the State of Play (SoP)

The **State of Play (SoP.md)** ledger [1] serves as the immutable history of the platform. This migration represents a watershed moment that must be recorded with precision. Previous entries referencing R-AGENT or AGENTS.md will become historical artifacts, reflecting the state of the repository *at the time of their writing*.

It is imperative that we do not rewrite the history of the SoP. The integrity of the ledger depends on its append-only nature. Old SoP entries will continue to reference Uppercase IDs, and this is acceptable. However, the SoP entry for **DP-OPS-0069** must explicitly detail the cutover, establishing a "Before" and "After" state to prevent confusion during future forensic audits. All future entries, starting from the merge of DP-OPS-0069, must strictly use lowercase identifiers (r-agent-, b-task-). This demarcation ensures that the history remains accurate while the active context evolves.

2.3 Proof of Work (PoW) Requirements

The **Proof of Work (PoW.md)** ledger [1] requires strict evidentiary standards for any state-changing maintenance. A migration that touches potentially hundreds of files carries a

high risk of breaking links, particularly in a pointer-first architecture where every file relies on explicit references to others. The PoW for DP-OPS-0069 must be the most robust in the system's history.

The verification strategy must include **Zero-Drift Verification**, proving that the git ls-files output matches the expected allowlist exactly, with no "ghost" uppercase files remaining. It must demonstrate **Link Integrity**, proving that all internal pointers—such as {{@include:...}} directives in templates and registry lookups in scripts—have been updated to lowercase. Finally, it must prove **Toolchain Validity**, demonstrating that critical binaries like ops/bin/compile and tools/lint/factory.sh function correctly in the new lowercase environment. The failure of any one of these checks would constitute a system failure state, requiring an immediate rollback.

---

3. Comprehensive Current State Assessment (As-Is Audit)

Before executing the migration, we must establish a rigorous inventory of the target surfaces. This section details the specific files targeted for renaming and the internal IDs targeted for refactoring, based on the file lists provided in the full dump.[1]

3.1 Target Domain: Prompt Engineering (docs/ops/prompts/)

The docs/ops/prompts/ directory currently houses the definitional files for operator stances. These files are critical for the "Explain" layer, guiding the behavior of the AI contractor. The current naming convention uses Uppercase prefixes, likely to denote their status as "Entities" within the system.

Current State Inventory: The repository dump [1] confirms the existence of the following files:

- docs/ops/prompts/E-PROMPT-01.md: Gatekeeper Stance.
- docs/ops/prompts/E-PROMPT-02.md: Hygiene Stance.
- docs/ops/prompts/E-PROMPT-03.md: Architect Stance.
- docs/ops/prompts/E-PROMPT-04.md: Analyst Stance.
- docs/ops/prompts/README.md: The index for the prompts directory.

Migration Target State: The objective is to convert these filenames to lowercase and their internal IDs to lowercase to match. The README.md presents a unique case; while industry convention often retains the uppercase README, the specific instruction for a "strict one-off lowercase migration" implies a total standardization. However, given the primary function of README.md as a directory index often rendered specially by git hosting interfaces, we must weigh this against the strictness of the mandate. The mandate lists docs/ops/prompts/ as a target. To ensure absolute compliance with the "strict" directive, we will migrate README.md

to readme.md. If the platform requires README.md for display, the ops/bin/map tool [1] should be updated to prioritize readme.md.

Transformation Logic:

The files will be renamed to e-prompt-01.md, e-prompt-02.md, etc. Internally, the ID E-PROMPT-01 found in the headers or content of these files must be sed-replaced to e-prompt-01.

3.2 Target Domain: Operational Registries (docs/ops/registry/)

The docs/ops/registry/ directory contains the authoritative lists of system components. These files are heavily referenced by the linter suite (tools/lint/*.sh) to validate the existence of agents, tasks, and skills. The current convention uses ALL CAPS filenames, emphasizing their role as "Ledgers."

Current State Inventory:

- docs/ops/registry/AGENTS.md: Registry of R-AGENT entities.
- docs/ops/registry/BINARIES.md: Registry of OPS-BIN entities.
- docs/ops/registry/LINT.md: Registry of LINT entities.
- docs/ops/registry/PROJECTS.md: Registry of active projects.
- docs/ops/registry/PROMPTS.md: Registry of E-PROMPT entities.
- docs/ops/registry/SCRIPTS.md: Registry of SCRIPT entities.
- docs/ops/registry/SKILLS.md: Registry of S-LEARN entities.
- docs/ops/registry/TASKS.md: Registry of B-TASK entities.
- docs/ops/registry/TEST.md: Registry of TEST entities.
- docs/ops/registry/TOOLS.md: Registry of TOOL entities.

Migration Target State: All files must be renamed to their lowercase equivalents (e.g., agents.md, binaries.md). This is a high-impact change because tools/lint/factory.sh [1] explicitly hardcodes variables like AGENTS_REGISTRY="docs/ops/registry/AGENTS.md". Failing to update the linters concurrently with the rename will result in immediate CI failure. The content within these registries—specifically the columns listing IDs—must also be updated to reflect the new lowercase ID syntax (r-agent-, b-task-).

3.3 Target Domain: The Factory Floor (opt/_factory/)

The opt/_factory/ directory is the heart of the "Isolate" layer, containing the actual definitions of the agents, skills, and tasks. The current structure is a hybrid: the directories are lowercase (agents/, skills/), but the files and the local ledgers are Uppercase.

Sub-Target: Factory Ledgers

These files act as local indexes for the factory components.

- opt/_factory/AGENTS.md -> opt/_factory/agents.md
- opt/_factory/SKILLS.md -> opt/_factory/skills.md
- opt/_factory/TASKS.md -> opt/_factory/tasks.md
- opt/_factory/INDEX.md -> opt/_factory/index.md

Sub-Target: Factory Definitions

These are the files that define the logic for each entity.

- opt/_factory/agents/R-AGENT-01.md through R-AGENT-06.md.
- opt/_factory/skills/S-LEARN-01.md through S-LEARN-06.md.
- opt/_factory/tasks/B-TASK-01.md through B-TASK-06.md.

Transformation Logic: The renaming here is straightforward: R-AGENT-01.md becomes r-agent-01.md. However, the internal content of these files is critical. For example, opt/_factory/tasks/B-TASK-06.md [1] contains references to R-AGENT-03 (doc-updater). This reference must be updated to r-agent-03. Furthermore, the task definition contains a section ## Provenance with fields like **DP-ID:**. While DP-ID is an identifier, the mandate specifically targets R-AGENT, B-TASK, and S-LEARN IDs. We should preserve DP-OPS- IDs in uppercase as they refer to the immutable PoW/SoP ledgers which are not part of this lowercase migration scope.

---

4. Technical Implementation Plan and Tooling Refactor

The complexity of DP-OPS-0069 lies not in the filesystem operations (mv), but in the ripple effects through the ops/ and tools/ ecosystem. The repository is a tightly coupled graph of pointers; changing the nodes requires updating every edge.

4.1 Refactoring the Compiler (ops/bin/compile)

The ops/bin/compile binary [1] is responsible for generating the manifests in ops/lib/manifests/. An analysis of its source code reveals a critical piece of logic regarding filename casing:

Bash

```
local output_name="${template_file%.tpl}"
if [[ "$output_name" == *.md ]]; then
  local output_stem="${output_name%.md}"
  output_name="$(printf '%s.md' "$(printf '%s' "$output_stem" | tr '[:lower:]' '[:upper:]')")"
else
```

```
    output_name="$(printf '%s' "$output_name" | tr '[:lower:]' '[:upper:]')"
fi
```

Insight: The script explicitly forces the output filename to Uppercase using tr '[:lower:]' '[:upper:]'. This confirms that the preservation of CORE.md, OPS.md, etc., is already baked into the compiler's logic. We do *not* need to modify ops/bin/compile to preserve the uppercase manifest filenames; it will continue to produce OPS.md even if we feed it a lowercase template file.

The Template Disconnect: However, ops/bin/compile uses git ls-files to resolve the entries listed *inside* the templates. The function resolve_template_members parses the template content. If ops/src/manifests/ops.md.tpl [1] currently lists - docs/ops/registry/AGENTS.md, and we rename that file to agents.md, the compiler will fail to find the file and abort.

Action Plan:

We must edit the *.tpl files in ops/src/manifests/ to reference the new lowercase file paths. This satisfies the user's specific instruction to "adjust ops/src/manifests/*.tpl content."

- **Target:** ops/src/manifests/ops.md.tpl -> Update references to docs/ops/registry/*.md and docs/ops/prompts/*.md.
- **Target:** ops/src/manifests/discovery.md.tpl -> Update reference to opt/_factory/index.md.
- **Target:** ops/src/manifests/context.md.tpl -> Update reference to tools/lint/context.sh (already lowercase, but verify consistency).

4.2 Refactoring the Linter Suite (tools/lint/*.sh)

The linters are the enforcement mechanism of the repository. They currently enforce the Uppercase convention and will block the migration if not refactored first.

4.2.1 tools/lint/agent.sh

This script [1] validates the agent definitions.

- **Registry Variable:** It defines AGENTS_REGISTRY="docs/ops/registry/AGENTS.md". This must be updated to docs/ops/registry/agents.md.
- **ID Regex:** It likely contains regex validation for the ID format. We must locate patterns like R-AGENT-[0-9]{2,} and update them to r-agent-[0-9]{2,}.
- **Pointer Logic:** The script checks that the agent file contains valid pointers. It must now accept lowercase pointers to other agents (e.g., r-agent-02) while still enforcing Uppercase pointers to the Constitution (PoT.md, TASK.md).

4.2.2 tools/lint/task.sh

This script [1] is the sole enforcer of the TASK schema.

- **Registry Variable:** TASKS_REGISTRY must point to docs/ops/registry/tasks.md.

- **Directory Variable:** TASKS_DIR="opt/_factory/tasks" remains valid, but the globbing for *.md will now pick up the lowercase files.
- **ID Regex:** The pattern B-TASK-[0-9]{2,} must be updated to b-task-[0-9]{2,}.
- **Content Logic:** It checks for "Primary Agent" fields. The validation logic must be updated to expect r-agent-xx instead of R-AGENT-XX.

4.2.3 tools/lint/factory.sh

This script [1] ensures synchronization between the registries and the files on disk. It is the most fragile component regarding this migration.

- **Registry Paths:** Updates required for AGENTS_REGISTRY, SKILLS_REGISTRY, and TASKS_REGISTRY.
- **Parsing Logic:** The script uses awk to parse the pipe-delimited tables in the registry files.
  Bash
  awk -F'|' '... { id=$2... path=$4... } '

  It then verifies that path exists on disk. Since we are renaming both the file on disk and the path in the registry, this logic will hold *provided* the update is atomic.
- **Ghost Check:** It scans the directories for files not in the registry. It derives the ID from the filename (basename "$rel_path".md). If the filename is r-agent-01.md, the derived ID is r-agent-01. It then checks if this ID exists in the registry map. This implies that the IDs in the registry *must* be lowercased to match the filenames, confirming the need for a comprehensive update.

4.2.4 tools/lint/project.sh

This script [1] validates STELA.md files in the projects/ directory.

- **Regex Scan:** It scrapes STELA.md for R-AGENT-[0-9]{2,}, B-TASK-[0-9]{2,}, etc.
- **Validation:** It cross-references these findings against the registries.
- **Action:** The regex must be updated to look for r-agent-, b-task-, etc. Crucially, this script highlights that the migration impacts the *projects* as well. If a project STELA.md references R-AGENT-01, and we change the registry to r-agent-01, this linter will flag a "Dead Pointer." Therefore, projects/ content must also be sed-replaced to maintain system integrity, consistent with the PoT jurisdiction over projects/.

4.3 Refactoring Lifecycle Scripts (ops/lib/scripts/*.sh)

These scripts are responsible for harvesting and promoting new entities. They must be updated to produce lowercase outputs by default.

4.3.1 ops/lib/scripts/agent.sh

- **ID Generation:** The script likely uses printf to format new IDs. printf 'R-AGENT-%02d'

must be changed to printf 'r-agent-%02d'.
- **Filename Generation:** The variable constructing the filename "${AGENTS_DIR}/R-AGENT-${id}.md" must be updated to use lowercase.
- **Header Generation:** The markdown header # R-AGENT-XX written to the file must be lowercased.

4.3.2 ops/lib/scripts/task.sh & skill.sh

- Similar updates are required for B-TASK and S-LEARN generation logic.
- **Heuristics:** The ops/lib/scripts/heuristics.sh library [1] contains functions like check_semantic_collision. If this function relies on Uppercase matching, it must be adjusted to be case-insensitive or expect lowercase.

4.4 Refactoring the Template Engine (ops/bin/template)

The binary ops/bin/template [1] renders the .tpl files.

- **Frontmatter:** It parses template_id. If ops/src/definitions/agent.md.tpl has template_id: agent, this is already lowercase and fine.
- **Logic:** It does not appear to enforce casing on the output file *path* (that is controlled by the caller, e.g., ops/bin/draft or the lifecycle scripts).
- **Conclusion:** ops/bin/template likely requires no internal code changes, but the templates it consumes (ops/src/definitions/*.tpl) must be updated if they contain hardcoded Uppercase text (e.g., # Task Draft: {{TASK_NAME}} is fine, but if it had # TASK:, it might need review).

---

5. Migration Execution Strategy

The execution of DP-OPS-0069 requires a precise sequence of operations to avoid leaving the repository in a broken state. We cannot simply rename the files; we must first prepare the tooling to accept the new names, then perform the content refactoring, and finally move the files.

5.1 The "Git Move" Protocol

A critical technical challenge is the handling of case-only renames on case-insensitive filesystems (common in macOS and Windows environments). Git often ignores mv FILE file, leading to index corruption or "ghost file" issues.

Protocol:

To ensure the index correctly registers the change, we will employ a two-step move strategy:

1. git mv FILE FILE_tmp
2. git mv FILE_tmp file

This forces the filesystem and git index to acknowledge the change explicitly.

5.2 The "Sed" Transformation Strategy

We require a robust sed expression to capture the specific IDs without corrupting other text. The goal is to replace specific ID prefixes while leaving other Uppercase terms (like PoT, SoP, CORE) touched.

- **Target Pattern 1:** R-AGENT- -> r-agent-
- **Target Pattern 2:** B-TASK- -> b-task-
- **Target Pattern 3:** S-LEARN- -> s-learn-
- **Target Pattern 4:** E-PROMPT- -> e-prompt-

Scope of Text Replacement:

The replacement must be applied to:

- ops/ (binaries, scripts, manifests, templates)
- docs/ (registries, manuals, specs)
- opt/ (factory definitions, ledgers)
- projects/ (payloads referencing platform entities)
- tools/ (linters, tests)

Exclusions:

We must strictly exclude .git and storage. Additionally, we must be careful with SoP.md and PoW.md. While we generally want to preserve history, if we change the *keys* (IDs) used to reference entities, the history becomes disconnected from the present. However, changing the *historical* log entries in SoP.md violates the "immutable history" principle.

Decision: We will apply the replacement to *active* pointers (e.g., in TASK.md, projects/, and source code) and *future* templates. We will *not* rewrite the text of historical SoP.md entries unless they contain active links that would break. Given the "strict" nature of the request and the fact that these are text IDs, updating them in SoP might be cleaner for grep-ability, but the safest path for governance is to treat SoP as immutable. *However*, for tools/lint scripts and ops/lib scripts, the replacement is mandatory.

5.3 Updates to ops/src/manifests/*.tpl (Preservation Logic)

This is the mechanism that satisfies the user's specific preservation requirement.

- **File:** ops/src/manifests/context.md.tpl
  - Current content likely references tools/lint/context.sh (already lowercase). We verify it.
- **File:** ops/src/manifests/ops.md.tpl
  - Current: - docs/ops/registry/AGENTS.md
  - Target: - docs/ops/registry/agents.md

    - Current: - docs/ops/prompts/E-PROMPT-01.md
    - Target: - docs/ops/prompts/e-prompt-01.md
- **File:** ops/src/manifests/discovery.md.tpl
    - Current: - opt/_factory/INDEX.md
    - Target: - opt/_factory/index.md

By updating these templates, when ops/bin/compile runs, it will search for the lowercase files (which will exist after the rename) and generate the Uppercase manifests (OPS.md) because of the internal tr logic in the binary.

---

6. Detailed Implementation Steps (The Runbook)

Step 1: Tooling Refactor (The Enablers)

We define the new reality in the verification tools first.

A. Update tools/lint/agent.sh

Bash

```
sed -i 's|docs/ops/registry/AGENTS.md|docs/ops/registry/agents.md|g' tools/lint/agent.sh
sed -i 's|R-AGENT-|r-agent-|g' tools/lint/agent.sh
```

B. Update tools/lint/task.sh

Bash

```
sed -i 's|docs/ops/registry/TASKS.md|docs/ops/registry/tasks.md|g' tools/lint/task.sh
sed -i 's|B-TASK-|b-task-|g' tools/lint/task.sh
```

C. Update tools/lint/factory.sh

Bash

```
sed -i 's|docs/ops/registry/AGENTS.md|docs/ops/registry/agents.md|g' tools/lint/factory.sh
sed -i 's|docs/ops/registry/SKILLS.md|docs/ops/registry/skills.md|g' tools/lint/factory.sh
sed -i 's|docs/ops/registry/TASKS.md|docs/ops/registry/tasks.md|g' tools/lint/factory.sh
```

D. Update Lifecycle Scripts (ops/lib/scripts/*.sh)

Apply the ID regex change to agent.sh, skill.sh, and task.sh to ensure they generate r-agent-xx instead of R-AGENT-XX.

Step 2: Content Refactoring (The References)

We perform the text replacement across the repository.

Bash

```
# Define the replacement scope (excluding git and storage)
find ops docs opt tools projects -type f -not -path '*/.git/*' | xargs sed -i 's/R-AGENT-/r-agent-/g'
find ops docs opt tools projects -type f -not -path '*/.git/*' | xargs sed -i 's/B-TASK-/b-task-/g'
find ops docs opt tools projects -type f -not -path '*/.git/*' | xargs sed -i 's/S-LEARN-/s-learn-/g'
find ops docs opt tools projects -type f -not -path '*/.git/*' | xargs sed -i 's/E-PROMPT-/e-prompt-/g'
```

Note: This command implicitly updates ops/src/manifests/*.tpl if they contain the IDs or filenames, fulfilling the preservation requirement. We must manually double-check ops/src/manifests/ops.md.tpl to ensure the filename extensions (like AGENTS.md -> agents.md) are also lowercased in the list.

Explicit Manifest Template Update:

Bash

```
sed -i 's/AGENTS.md/agents.md/g' ops/src/manifests/ops.md.tpl
sed -i 's/SKILLS.md/skills.md/g' ops/src/manifests/ops.md.tpl
sed -i 's/TASKS.md/tasks.md/g' ops/src/manifests/ops.md.tpl
sed -i 's/PROMPTS.md/prompts.md/g' ops/src/manifests/ops.md.tpl
#... repeat for all registry files
sed -i 's/INDEX.md/index.md/g' ops/src/manifests/discovery.md.tpl
```

Step 3: The File Renaming (The Structure)

We execute the directory-by-directory rename using the safe two-step protocol.

Batch 1: Prompts (docs/ops/prompts/)

Bash

```
cd docs/ops/prompts
for f in E-PROMPT-*.md; do
  new_name=$(echo "$f" | tr '[:upper:]' '[:lower:]')
  git mv "$f" "${new_name}_tmp"
  git mv "${new_name}_tmp" "$new_name"
done
git mv README.md readme.md_tmp
git mv readme.md_tmp readme.md
```

Batch 2: Registry (docs/ops/registry/)

Bash

```
cd docs/ops/registry
for f in *.md; do
  new_name=$(echo "$f" | tr '[:upper:]' '[:lower:]')
  git mv "$f" "${new_name}_tmp"
  git mv "${new_name}_tmp" "$new_name"
done
```

Batch 3: Factory (opt/_factory/)

Bash

```
cd opt/_factory
```

```
# Rename Ledgers
git mv AGENTS.md agents.md_tmp && git mv agents.md_tmp agents.md
git mv SKILLS.md skills.md_tmp && git mv skills.md_tmp skills.md
git mv TASKS.md tasks.md_tmp && git mv tasks.md_tmp tasks.md
git mv INDEX.md index.md_tmp && git mv index.md_tmp index.md

# Rename Definition Files
cd agents
for f in R-AGENT-*.md; do
  new_name=$(echo "$f" | tr '[:upper:]' '[:lower:]')
  git mv "$f" "${new_name}_tmp"
  git mv "${new_name}_tmp" "$new_name"
done
# Repeat for skills/ and tasks/
```

Step 4: Verification & Compilation

The final step is to run the compiler. This confirms that the templates (updated in Step 2) correctly point to the new files (renamed in Step 3).

Bash

```
./ops/bin/compile
```

If successful, ops/lib/manifests/OPS.md will be regenerated. Its content will list docs/ops/registry/agents.md, but its filename will remain OPS.md, preserving the architecture.

---

7. Verification & Proof of Work (PoW)

The PoW.md entry for DP-OPS-0069 will be the authoritative record of this transformation.

7.1 Verification Commands

The worker must run the following to prove the migration is complete and coherent:

1. **File Existence Check:**
   Bash
   ```
   test -f docs/ops/registry/agents.md && echo "OK: Registry Renamed"
   test -f opt/_factory/agents/r-agent-01.md && echo "OK: Agent Renamed"
   test -f docs/ops/prompts/readme.md && echo "OK: Prompt Index Renamed"
   ```

2. **Manifest Preservation Check:**
   Bash
   ```
   test -f ops/lib/manifests/CORE.md && echo "OK: CORE.md Preserved"
   test -f ops/lib/manifests/OPS.md && echo "OK: OPS.md Preserved"
   ```

3. **Content Consistency Check:**
   Bash
   ```
   grep "r-agent-01" opt/_factory/agents/r-agent-01.md && echo "OK: ID Refactored"
   grep "docs/ops/registry/agents.md" ops/lib/manifests/OPS.md && echo "OK: Manifest Content Updated"
   ```

4. **Tooling Functional Check:**
   Bash
   ```
   bash tools/lint/factory.sh
   # Must pass without "Ghost" or "Dead End" errors.
   ```

7.2 Safety Invariants

- **No Orphaned Pointers:** Every {{@include}} in ops/bin/template logic must be checked to ensure it does not point to a dead Uppercase path.
- **No Mixed Casing:** A scan for [A-Z]-AGENT- should return 0 results (excluding the ledger history in SoP.md if we decided to preserve it).

---

8. Conclusion

DP-OPS-0069 represents a significant maturation of the Stela platform's governance hygiene. By migrating to a lowercase standard for worker-facing surfaces (prompts, registry, factory), we eliminate a class of cross-platform compatibility bugs and improve developer ergonomics. Crucially, by strictly preserving the Uppercase convention for the ops/lib/manifests/ layer, we maintain the architectural distinction between the system's "Constitution" (Manifests) and its "Citizens" (Agents/Tasks).

The execution plan relies on a precise sequence: **Refactor Tooling -> Update Content Pointers -> Rename Files -> Recompile Manifests**. This order ensures that at no point is the repository in an invalid state where the compiler cannot find the files listed in the templates. The adjustment of ops/src/manifests/*.tpl content is the linchpin that allows the new lowercase reality to coexist with the immutable Uppercase manifest generation logic. The resulting state is a more robust, web-standard-compliant repository that honors its constitutional filing doctrine while evolving its operational syntax.

Appendix: Detailed Breakdown of Renaming Targets

A.1 docs/ops/prompts/

Current Filename	Target Filename	ID Transformation
E-PROMPT-01.md	e-prompt-01.md	E-PROMPT-01 -> e-prompt-01
E-PROMPT-02.md	e-prompt-02.md	E-PROMPT-02 -> e-prompt-02
E-PROMPT-03.md	e-prompt-03.md	E-PROMPT-03 -> e-prompt-03
E-PROMPT-04.md	e-prompt-04.md	E-PROMPT-04 -> e-prompt-04
README.md	readme.md	N/A

A.2 docs/ops/registry/

Current Filename	Target Filename
AGENTS.md	agents.md
BINARIES.md	binaries.md
LINT.md	lint.md
PROJECTS.md	projects.md
PROMPTS.md	prompts.md

SCRIPTS.md	scripts.md
SKILLS.md	skills.md
TASKS.md	tasks.md
TEST.md	test.md
TOOLS.md	tools.md

A.3 opt/_factory/

Current Filename	Target Filename	ID Transformation
AGENTS.md	agents.md	N/A
SKILLS.md	skills.md	N/A
TASKS.md	tasks.md	N/A
INDEX.md	index.md	N/A
agents/R-AGENT-01.md	agents/r-agent-01.md	R-AGENT-01 -> r-agent-01
agents/R-AGENT-02.md	agents/r-agent-02.md	R-AGENT-02 -> r-agent-02
agents/R-AGENT-03.md	agents/r-agent-03.md	R-AGENT-03 -> r-agent-03
agents/R-AGENT-04.md	agents/r-agent-04.md	R-AGENT-04 -> r-agent-04
agents/R-AGENT-05.md	agents/r-agent-05.md	R-AGENT-05 -> r-agent-05
agents/R-AGENT-06.md	agents/r-agent-06.md	R-AGENT-06 -> r-agent-06
skills/S-LEARN-01.md	skills/s-learn-01.md	S-LEARN-01 -> s-learn-01

skills/S-LEARN-02.md	skills/s-learn-02.md	S-LEARN-02 -> s-learn-02
skills/S-LEARN-03.md	skills/s-learn-03.md	S-LEARN-03 -> s-learn-03
skills/S-LEARN-04.md	skills/s-learn-04.md	S-LEARN-04 -> s-learn-04
skills/S-LEARN-05.md	skills/s-learn-05.md	S-LEARN-05 -> s-learn-05
skills/S-LEARN-06.md	skills/s-learn-06.md	S-LEARN-06 -> s-learn-06
tasks/B-TASK-01.md	tasks/b-task-01.md	B-TASK-01 -> b-task-01
tasks/B-TASK-02.md	tasks/b-task-02.md	B-TASK-02 -> b-task-02
tasks/B-TASK-03.md	tasks/b-task-03.md	B-TASK-03 -> b-task-03
tasks/B-TASK-04.md	tasks/b-task-04.md	B-TASK-04 -> b-task-04
tasks/B-TASK-05.md	tasks/b-task-05.md	B-TASK-05 -> b-task-05
tasks/B-TASK-06.md	tasks/b-task-06.md	B-TASK-06 -> b-task-06

This list comprises the definitive Scope of Work for the migration script. Any file present in these directories but not listed here (e.g., future agents) must also be migrated dynamically by the script logic to ensure 100% coverage.

Works cited

1. dump-full-main-f3d6b2e4.txt