

# Design Document: Milestone

## Status of Project

We have the server class (WhiteboardServer.java) fully functional and implemented as specified in the document except that it does not use a BlockingQueue to store inputs from clients but rather handles them directly. Instead of having a thread that constantly checks for inputs on the socket and places them all into a BlockingQueue for inputs, it handles them directly. The thread that constantly polls that BlockingQueue and handles them thus has not been implemented. This is because our implementation of this (WhiteboardServerTripleThreadNonWorking.java) seems to nondeterministically output to the wrong client. We were unable to resolve this issue at the LA Office Hours on Monday.

We have however tested our Whiteboard Server class (without the input Blocking Queue) using telnet and it has been fully functional with multiple clients.

We have almost finished implementing the client class. We will be separating the client from the whiteboard to make the code more modular.

## General Control Flow

- 1) The server initializes, creating a network socket and starting with three blank whiteboards.
- 2) At this point, the server is ready for any number of users to connect.

### For each client:

- 1) The client starts up the GUI which immediately has a popup window requesting a username. This username is sent to the server. If it is not unique, the same window will query for a different username and display the taken usernames.
- 2) The user is prompted to select a whiteboard from the existing whiteboards or create a new whiteboard. The users working on each whiteboard are displayed next to each whiteboard.
- 3) Now the Whiteboard user interface loads with the state of the Whiteboard as stored on the server.
- 4) The user can make any changes they want to the drawing canvas. All changes made by the user will be sent to all the other users working on the same Whiteboard as all changes made by other users on the Whiteboard will be propagated to the user.

At any point the user can now

- a) Send messages to the other users working on the same Whiteboard.
- b) Switch to another Whiteboard. The state of the current whiteboard will be preserved on the server with no effect on the other collaborators of the canvas. The new Whiteboard will be at the current state, with all past changes present.
- c) Disconnect from the server. The state of the whiteboard will be preserved on the server with no effect on the other collaborators of the canvas.

## Datatype Design

A Whiteboard is a user interface that contains an interactive drawing canvas along with a tool palette and various information displays. The interactive drawing canvas is a 2D array of pixels that can be manipulated by the user as well as any other users that have access to it through the Whiteboard server. The tool palette offers users the option of drawing in a variety of colors, stroke thicknesses, and even erasing lines. It also allows the user to switch to different drawing canvases if he or she desires to do so. The various information displays show the user information such as the other users working on the same canvas, messages between users working on the same canvas, and the other canvases on the server.

A Whiteboard Client is the means by which a user can use a Whiteboard and collaborate with other users connected to the Whiteboard Server. The Whiteboard Client handles all incoming and outgoing messages being passed between the user and the server and calls the appropriate methods in the Whiteboard to update the user interface.

A Whiteboard Server is a server that does all the message passing necessary for the users to collaborate using the Whiteboards over a network. In addition to handling incoming and outgoing messages, the server stores the history of all actions performed on each whiteboard so that new users can join whiteboards midway through a collaborative session without missing any information. Additionally, users can work on whiteboards over several network sessions as all information is stored on the server.

Class	Constructor Signature (C) and Operations
Whiteboard	<b>C:</b> public Whiteboard(int width, int height) <b>getUsername():</b> Pops up a window to get the username <b>paintComponent():</b> makes a drawing buffer <b>makeDrawingBuffer():</b> make the drawing buffer and draw some content for it <b>drawLineSegment():</b> Draws a line segment between two points (x1,y1) and (x2,y2) with a specified stroke size and color (in RGB), specified in pixels relative to the upper left corner of the drawing buffer <b>eraseLineSegment():</b> Draws a white line segment between two points (x1, y1) and (x2, y2), specified in pixels relative to the upper-left corner of the drawing buffer. <b>addDrawingController():</b> Adds the mouse listener that supports the user's freehand drawing. <b>Private Subclass DrawingController</b> <b>mousePressed(MouseEvent e):</b> Starts drawing or erasing when the left mouse button is pressed <b>mouseDragged(MouseEvent e):</b> Draws or erases a line segment when the mouse moves while the left mouse button is pressed <b>makeCanvas():</b> Sets up the User Interface <b>fillWithWhite():</b> fills the canvas with white
WhiteboardClient	<b>C:</b> public WhiteboardClient(Whiteboard client)

	<b>connectToServer():</b> connects the client to the server <b>handleServerResponse():</b> handle a single connection with the server, returns when the client disconnects <b>handleResponse():</b> handles client input (performs operations on the client's Whiteboard class) <b>handleOutputs():</b> handles a single client connection
WhiteBoardServer	<b>C:</b> public WhiteboardServer(int port)

# Protocol

The Whiteboard Server and Client implement the client-server model. Each client passes text messages to the server and the server will parse the information, carry out the appropriate internal operations, and respond with text messages to all appropriate clients.

The server will have three threads running per client: one thread to listen for incoming text messages and place them into a BlockingQueue, one thread to poll the BlockingQueue of incoming messages, parse the commands, and carry out the appropriate operations (including placing outgoing text messages on another BlockingQueue), and one thread to poll the BlockingQueue of outgoing messages and write them to the socket.

Each client will be running three threads: one thread to listen for incoming text messages and place them into a BlockingQueue, one thread to poll the BlockingQueue of incoming messages, parse the commands, and carry out the appropriate operations (generally calling methods to update the GUI), one thread to run the GUI, and one thread to poll the BlockingQueue of outgoing messages and write them to the socket.

## Grammar

### Grammar for messages from the user to the server:

#### User-to-Server Whiteboard Message Protocol

```
MESSAGE          ::= ( SELECTBOARD | DRAW | ERASE | HELP_REQ | BYE |
NEWUSER | ADDBOARD ) NEWLINE
SELECTBOARD      ::= CLIENT SPACE "selectBoard" SPACE BOARD
DRAW             ::= BOARDNAME SPACE "draw" SPACE X SPACE Y SPACE X
SPACE Y SPACE STROKESIZE SPACE R SPACE G SPACE B
ERASE            ::= BOARDNAME SPACE "erase" SPACE X SPACE Y SPACE X
SPACE Y SPACE STROKESIZE
CLIENT           ::= STRING
HELP_REQ         ::= CLIENT SPACE "help"
BYE              ::= CLIENT SPACE "bye"
NEWUSER          ::= "new" SPACE "username" SPACE USERNAME
ADDBOARD         ::= "addBoard" SPACE BOARDNAME
USERNAME         ::= STRING
BOARDNAME        ::= STRING
SPACE            ::= " "
X                ::= INT
Y                ::= INT
R                ::= INT
G                ::= INT
B                ::= INT
STROKESIZE       ::= INT
```

INT	:= [0-9]+
STRING	:= [=]*
NEWLINE	:= "\r?\n"

The action to take for each different kind of message is as follows:

#### **SELECTBOARD Message:**

1) If the username does not exist, add a message saying "Username does not exist." to the client's BlockingQueue in the commandsQueue list.

2) If the whiteboard does not exist, add a message saying "Whiteboard does not exist. Select a different board or make a new board." to the client's BlockingQueue in the commandsQueue list.

3) If the username and whiteboard exists, add the username and whiteboard to the HashMap clientToWhiteboardsMap, with the username as the key and the whiteboard as the value. Add a message saying "You are currently on board" (boardID) to the client's BlockingQueue in the commandsQueue list. Get the list of past commands on the whiteboard from the HashMap whiteboardToCommandsMap and add the contents to the client's BlockingQueue in the commandsQueue list.

#### **DRAW Message:**

1) If the whiteboard does not exist, return a message saying "Whiteboard does not exist." to the client. // this case actually shouldn't exist b/c client can only send whiteboard that on

2) If the drawing parameters are out of the boundaries of the canvas, return a message saying "Drawing parameters are out the drawing area of the whiteboard." to the client.

3) If the whiteboard exists and the drawing parameters are within the boundaries of the canvas, append the DRAW message to the ArrayList corresponding to the whiteboard key of the whiteboardToCommandsMap (Note that the client can only draw in the whiteboard that it is currently on - this is handled by the client as its drawing method will only put send the draw command with its whiteboard string id.) as well as the commandsQueue BlockingQueue.

#### **ERASE Message:**

1) If the whiteboard does not exist, return a message saying "Whiteboard does not exist." to the client. // this case actually shouldn't exist

2) If the erasing parameters are out of the boundaries of the canvas, return a message saying "Erasing parameters are out the drawing area of the whiteboard." to the client.

3) If the whiteboard exists and the erasing parameters are within the boundaries of the canvas, append the ERASE message to the ArrayList corresponding to the whiteboard key of the whiteboardToCommandsMap (Note that the client can only erase in the whiteboard that it is currently on - this is handled by the client as its erasing method will only put send the erase command with its whiteboard string id.) as well as the commandsQueue BlockingQueue.

#### **HELP\_REQ Message:**

Adds a help message (see below) add the contents to the client's BlockingQueue in the

commandsQueue list. Does not mutate any data structures.

### **BYE Message:**

Adds the terminate message to the client's BlockingQueue in the commandsQueue list.

### **NEW USER Message:**

1) If the user already exists, return a message saying "Username already taken. Please select a new username." to the client's BlockingQueue in the commandsQueue list.

2) If the user does not already exist and if there are no existing whiteboards, add the user as the key to the clientToWhiteboardsMap and with an empty String as a value. Also add the user as the key to the clientToThreadNumMap with the threadNum as the value. Add a message saying "No existing whiteboards" to the client's BlockingQueue in the commandsQueue list

3) If the user does not already exist and there are existing whiteboards, add the user as the key to the clientToWhiteboardsMap and with an empty String as a value. Also add the user as the key to the clientToThreadNumMap with the threadNum as the value. For each whiteboard name, append it to a message starting with "Existing Whiteboards ". Add these messages to the client's BlockingQueue in the commandsQueue list. When there are no more whiteboard name messages, add a message saying "Done sending whiteboard names." to the client's BlockingQueue in the commandsQueue list.

### **ADD BOARD Message:**

1) If the whiteboard already exists, add a message saying "Whiteboard already exists." to the client's BlockingQueue in the commandsQueue list.

2) If the whiteboard does not already exist, add the whiteboard name as the key to the whiteboardToCommandsMap with an empty ArrayList as a value. Add a message saying "Board " boardName "added" to the client's BlockingQueue in the commandsQueue list.

## **Grammar for messages from the server to the user:**

### **Server-to-User Whiteboard Message Protocol**

MESSAGE ::= ( SELECTBOARD | DRAW | ERASE | NEWUSER |  
HELP\_REQ | BYE | ADDBOARD ) NEWLINE

DRAW ::= BOARD SPACE "draw" SPACE X SPACE Y SPACE X  
SPACE Y

ERASE ::= BOARD SPACE "erase" SPACE X SPACE Y SPACE X  
SPACE Y

BOARD ::= STRING

HELP\_REQ ::= "Instructions: username yourUsername, selectBoard board#,  
help, bye, board# draw x1 y1 c2 y2, board# erase x1 y1 x2 y2"

BYE ::= "Thank you!"

ADDBOARD ::= "No existing whiteboards." | "Whiteboard does not exist. Select  
a different board or make a board."

EXISTINGBOARDS ::= "Existing Whiteboards" SPACE BOARDNAME

DONESENDING	::= "Done sending whiteboards"
USERNAMETAKEN	::= "Username already taken. Please select a new username."
BOARDADDED	::= "Board" SPACE BOARDNAME SPACE "added"
BOARDNAME	::= STRING
SPACE	::= " "
X	::= INT
Y	::= INT
INT	::= [0-9]+
STRING	::= [^=]*
NEWLINE	::= "\r?\n"

The action to take for each different kind of message is as follows:

**USERNAMETAKEN Message:**

1) Creates a popup window to get the username from the user. Adds the message "new username desiredClientName" (where desiredClientName is the username entered by the client) to the outputCommandsQueue.

**ADDBOARD Message:**

1) Creates a popup window to get a new whiteboard name from the user. Adds the message "addBoard desiredWhiteboardName" (where desiredWhiteboardName is the whiteboard name entered by the client) to the outputCommandsQueue.

**EXISTINGBOARDS Message:**

1) Adds the whiteboard name to the list of existing whiteboards.

**DONESENDING Message:**

1) Creates a popup window that lets the user choose a whiteboard or create a new one.

**BOARDADDED Message:**

1) Sets the boardname specified in the Message as the whiteboard name of the client.

**DRAW Message:**

Draws the line segment defined in the message.

**ERASE Message:**

Erases the line segment defined in the message.

**HELP\_REQ Message:**

Creates a popup window with help instructions.

**BYE Message:**

Terminates the connection with the server.

## Concurrency Strategy

Thread puts things on blockingqueue

Sent to other clients passed on order in the queue (No race conditions)

Only one thread will take off or put on the queue (Server) (Client)

Thread for GUI (runs gui stuff)

Immutability and using

Edits are going to be based off of the order in which they arrive on the server queue.

The server will

synchronized datatypes like for hashmap

atomic integers

lists

blocking queues

keeping things local

private final

only one thread accesses certain items need to specify this

no locks because only one instance?



## Testing Strategy

All operations of the classes in both the Server, Client, and Whiteboard can and should be tested. We will conduct both manual and JUnit tests to thoroughly test our implementation and ensure correctness. Since this project includes a user interface and a text-based protocol it would be hard to achieve a full testing coverage efficiently without using manual tests. We will be using JUnit tests to test for race conditions that would otherwise hard to reproduce manually. We decided to conduct our tests as follows:

### 1. Datatype definition

In testing our datatype definition we will use both JUnit and manual tests. For each class in our datatype we will have a complementary classTest to conduct JUnit tests in it. The JUnits tests will test for the representation invariants and the correct functionality of methods that don't involve user input or changes in the GUI. So far we have a Whiteboard class that represents our datatype definition. The setters and getters in this class will be tested with JUnit tests. Our checkRep() method will be run in each test. The representation invariant asserts that none of the fields in the Whiteboard class are null, that no two Whiteboards or usernames on the Whiteboard have the same name, and that edits by multiple users are executed on first come first executed passes. The first two of these invariants can be tested with the JUnit tests, the rest will need to be tested manually.

As for the coverage in testing the fields, we will try different possible string inputs for the usernames and whiteboards, strings of various length and the empty string. We will also test that no two usernames have the same name.

The rest of the methods in the Whiteboard class will be tested manually. We will run the GUI and assert that no two whiteboards have the same name. We will also show that edits from multiple users are put on a queue and first come first executed. We will test for the correct functionality of each method manually.

### 2. Protocol

We will test our protocol manually using telnet. Since we have a text-based protocol we will execute all the possible text commands on telnet and see if we get the expected responses. Our testing strategy will include testing for the clients that the server returns the message to, the validity of the response and the correct client behavior. All the methods that change the GUI are made to return Strings to help us validate that the changes to GUI took place with telnet. The draw and erase methods should return a string to all the clients on the same whiteboard when called. Other methods like help and chooseUsername will only return to the client who called them. The input and output will be tested for correctness.

JUnit tests can be written to test the protocol, however they are not as effective as testing with telnet and they require more time and effort. Thus we decided to only use telnet to test the protocol. If we choose to write JUnit tests we will create testing code that will log on with many

users to the server, create threads that send many requests and verify that the correct responses are produced.

### 3. GUI

The user interface will also be tested manually. We will start by testing the functionality of each method in the GUI. Each method will have its own Input/Output space to be tested. As an example, for the erase method we will test that erasing takes place when the erase button is pressed. We will test for the ability to change the stroke length. We will also see whether you are able to switch back to drawing or not. Each method will have its own Input/Output space.

### 4. End to end testing

We will use the GUI to manually conduct the end to end testing. We will start by testing for the correct functionality when only when client is connected. We will test whether our datatype supports having multiple whiteboards at once. We will also test for the client's ability to switch from one whiteboard to another.

After testing for functionality with one client we will test the functionality with multiple clients. We will test for the behavior when multiple clients edit the same whiteboard. We expect that the board will have a queue and will execute clients commands on first come first served bases. At least three users should be able to edit a whiteboard at a time. All three of us will try connecting to the same whiteboard and editing it. We will also see whether each of us is able to see the usernames of the others.

We will then turn to testing for persistence and that the whiteboards won't lose their content when a client connects/disconnects. We will test the for the ability of editing content over several network sessions. And lastly we'll test for real-time responsiveness. If there are considerable delays in the GUI's response we will consider using SwingWorker and having slow methods run in a background thread.

talk about different inputs here?

Order to test components in? small pieces first?

How to derive test cases? anything with input/action?

level of coverage? test all the different input output spaces of diff types of input

how to test user interface? test the different combination

### Server Tests

create testing code that will log on with many users, create threads that send many requests and need to verify that correct things are received?

### Client Tests

Username

try all possible string inputs, various lengths, empty string  
same with the board name  
draw and erase in different colors

End to End Testing  
Test with multiple clients on a server