FORMULA 1

Podium Prediction Analytical Report

Data-engineering answers, pre-race features, and limitations

Target: podium finish (positionOrder <= 3).
Prediction cutoff: after qualifying and before race start.
Unit: one driver entering one race.

Generated from the executed notebook: 2026-10-17 13:05 UTC

1. Answers to the three data-engineering questions

1.1 Front-row starts and circuit podium conversion

Qualifying positions 1-2 and final grid slots 1-2 are compared separately because penalties can change the starting grid. The comparison uses 490 races with both definitions observed, excluding 87 races without complete front-row support. Recorded nonstarters are excluded from the start denominator. Circuit-era rankings require adequate support and are descriptive.

Compared 490 races from 1994-2024 with both front-row definitions observed; excluded 87 races with incomplete front-row support. Recorded nonstarters are removed before eligibility is checked (138 driver entries in this window). 1994-2013 Grid 1-2: Suzuka Circuit, 76.9% (20/26); 1994-2013 Qualifying 1-2: Suzuka Circuit, 76.9% (20/26); 2014-2024 Grid 1-2: Yas Marina Circuit, 86.4% (19/22); 2014-2024 Qualifying 1-2: Circuit de Barcelona-Catalunya, 81.8% (18/22). The largest supported absolute grid-conversion change is Circuit de Spa-Francorchamps: +27.7 percentage points; its common-circuit rank changed from 5 to 1. Front-row membership differs for 72 driver-race records, so qualifying and grid must not be conflated. Ranks are descriptive, with ties and wide intervals possible; changes cannot be attributed causally to hybrid regulations.

Figure 1. Circuit podium conversion from qualifying and actual grid front rows, with uncertainty intervals.





Figure 2. Change in front-row conversion across the 2014 era boundary for circuits with common support.




1.2 Home-country podium association after grid control

Home-country status is based on an explicit mapping from recorded driver nationality to circuit country. Home and away rates are standardized over the same observed exact-grid-position by era strata. Whole races are resampled for uncertainty, preserving dependence among competitors. This controls observed starting position and broad era, not driver or team strength.

In 1994-2024, crude home podium rate is 12.5% versus 14.1% away. After standardizing exact grid x era, home is 11.4% versus 13.9% away: difference -2.53 percentage points (95% race-bootstrap interval -4.42 to -0.49). Shared support retains 11,043/12,358 rows (89.4%) across 40 strata; 0 rows are excluded for unavailable mapping/country/grid. The unit is a driver entry; recorded nonstarters remain non-podiums for this pre-race association. 964/1,000 adjusted bootstrap draws retained all strata. The adjusted interval excludes zero, supporting an observed association in this target population. Nationality is a proxy for home, and unmeasured driver/team/circuit differences prevent causal interpretation.

Figure 3. Crude and grid/era-standardized home and away podium rates with race-bootstrap intervals.




1.3 Constructor mechanical retirements by era

The denominator is race starts; the numerator requires an explicit mechanical component cause and fewer recorded laps than the winner as an early-end proxy. Crash, driver-caused, and regulatory outcomes are excluded from the mechanical numerator. Positive-lap withdrawals remain starts. Strict and broader cause maps are compared for 2014-2021 and 2022-2024.

2014-2021: Lotus F1 has the highest supported strict rate, 17.3% (13/75), 95% Wilson interval 10.4%-27.4%; the broad-map leader is Lotus F1 (24.0%); 2022-2024: Alfa Romeo has the highest supported strict rate, 12.5% (11/88), 95% Wilson interval 7.1%-21.0%; the broad-map leader is Alfa Romeo (12.5%). Excluded 28 recorded nonstarters from both numerator and denominator. Withdrawal/nonqualifying labels exclude only entries without positive laps; positive-lap withdrawals remain starts. Both cause maps require laps below winner distance as an early-end proxy; 1 full-distance component-status row(s) are flagged and excluded from both retirement numerators, while remaining in the start denominator. 10 remaining zero-lap mechanical/ambiguous rows have uncertain start status; the exported table reports a sensitivity excluding these. The numerator excludes explicit crash/damage, driver-health and regulatory outcomes while these started entries remain in the denominator. Rankings use at least 40 starts and recorded constructor IDs, so a rename does not automatically inherit its predecessor's rate. Wilson intervals and unequal exposure mean that the largest observed rate is not necessarily evidence of the least reliable constructor.

Figure 4. Constructor mechanical-retirement rates by era, with strict and broad definitions and uncertainty intervals.



2. Selected features and pre-race validity

The prediction cutoff is after qualifying and before the race starts. Every selected predictor is available by that cutoff or is derived solely from completed earlier races. Current-race results, points, status, laps, pit stops, and post-race standings are excluded. Driver and constructor histories are shifted so the current race cannot contribute to its own features.

Feature selection combines training-period exploratory evidence with domain reasoning. The table lists every selected input, its motivation, and the information available at the cutoff. The accompanying figures show training-only associations and feature effects; these are exploratory evidence, not causal effects or proof that a feature improves the final model.

Selected feature rationale and cutoff availability

feature	group	motivation	availability
grid	Grid	Starting opportunity is expected to constrain podium chances.	Final published starting grid before race start; zero is treated as missing.
grid_unassigned	Grid	Distinguishes pit-lane/unrecorded grid from an ordinary midfield start.	Final published starting grid before race start; zero is treated as missing.
qualifying_position	Qualifying	Reflects weekend pace while allowing penalties to change the actual grid.	Current qualifying positions and completed qualifying lap times before start.
qualifying_gap_pct	Qualifying	Normalizes lap duration across circuits, while acknowledging session-condition differences.	Current qualifying positions and completed qualifying lap times before start.
driver_form_podium_rate	Form	Recent results summarize competitiveness using only completed races.	Only earlier completed Grand Prix results; driver entry rolling mean and team race aggregation shifted once.
driver_form_points	Form	Provides a graded recent-performance measure beyond a binary podium.	Only earlier completed Grand Prix results; driver entry rolling mean and team race aggregation shifted once.
driver_form_finish	Form	Adds recent finishing consistency, including non-podium outcomes.	Only earlier completed Grand Prix results; driver entry rolling mean and team race aggregation shifted once.
driver_prior_starts	Form	Represents experience and distinguishes debut from a missing form value.	Only earlier completed Grand Prix results; driver entry rolling mean and team race aggregation shifted once.
constructor_form_podium_rate	Form	Captures recent team strength without leaking a current-race teammate outcome.	Only earlier completed Grand Prix results; driver entry rolling mean and team race aggregation shifted once.
constructor_form_points	Form	Summarizes recent team competitiveness without favoring larger historical lineups.	Only earlier completed Grand Prix results; driver entry rolling mean and team race aggregation shifted once.
driver_standing_points	Standings	Summarizes current-season performance available before the current race.	Snapshot after previous Grand Prix in same season; round one has zero points and missing rank.
driver_standing_position	Standings	Adds relative current-season competitiveness alongside absolute points.	Snapshot after previous Grand Prix in same season; round one has zero points and missing rank.
constructor_standing_points	Standings	Represents accumulated team strength before the current race.	Snapshot after previous Grand Prix in same season; round one has zero points and missing rank.
constructor_standing_position	Standings	Adds the team's relative position under the current scoring system.	Snapshot after previous Grand Prix in same season; round one has zero points and missing rank.
driver_age	Context	Exploratory experience/context hypothesis, tested by context ablation.	Scheduled year/round, birth date, sporting nationality/circuit country, and earlier circuit races.
is_home	Context	Tests the observed home-country association without treating it as causal.	Scheduled year/round, birth date, sporting nationality/circuit country, and earlier circuit races.
circuit_prior_podium_rate	Context	Historical field-size/circuit context is an exploratory hypothesis.	Scheduled year/round, birth date, sporting nationality/circuit country, and earlier circuit races.
year	Context	Represents broad eras and scoring/format changes, with extrapolation limits.	Scheduled year/round, birth date, sporting nationality/circuit country, and earlier circuit races.
round	Context	Allows season progression to modify other competitiveness signals.	Scheduled year/round, birth date, sporting nationality/circuit country, and earlier circuit races.

Figure 5. Training-only missingness and univariate association evidence for selected features.





Figure 6. Observed feature effects and podium rates used to motivate feature groups.



3. Known limitations

Historical qualifying coverage is sparse and uneven. Analyses that require qualifying data use supported periods and common coverage, while the modeling sensitivity compares a shorter training window. Historical coverage and timing conventions may still change the observed relationships.

Formula 1 rules, cars, calendars, scoring systems, constructor identities, and field composition change across eras. The 2014 boundary is a useful descriptive comparison, not an isolated causal experiment. A model trained on past seasons may transfer poorly after regulatory changes or to new drivers and teams.

The archived final grid is treated as information available before the race. The archive does not provide a publication timestamp for every grid update; live use requires a genuine pre-start snapshot. Historical form and standings are only valid when constructed from completed earlier races.

Home-country status is a nationality-based proxy, not residence or personal identification. The three data-engineering analyses are observational; unmeasured driver, team, circuit, and selection differences remain. Mechanical retirement labels and recorded lap counts are imperfect proxies, and constructor IDs do not automatically unify renamed teams.

These limitations constrain interpretation and transfer. Plots and feature associations describe the supplied archive; they do not establish causes or guarantee future prediction performance.

FORMULA 1 / MILESTONE 1

Technical Report

Part II - Data quality, predictive modeling, experiments and explainability

Companion to the Analytical Report (Part I). Together, the two reports document the historical questions, pre-race feature validity and complete computational evidence from the run-all notebook.

Report	Contents
Part I: Analytical Report	The three relational data-engineering answers and six figures; the 19 selected features and cutoff validity; historical/archive limitations.
Part II: Technical Report	The remaining 18 figures; cleaning/audits; chronological split; all-model metrics; learning curves; ablation/order experiments; global/local XAI; inference and evaluation limitations.

Prediction unit: one driver entering one race. Target: positionOrder <= 3. Prediction cutoff: after qualifying and final published grid, before the Grand Prix starts.

Read Part I for the substantive answers to Q1-Q3. Read Part II for how data quality, validation, model behavior and inference support the predictive task. The accompanying notebook remains the executable source of the calculations.

Evidence status: this document summarizes the existing corrected run; its creation is not a new blind test. Model choice and thresholds use validation data. The reused 2022-2024 test-period limitation is stated explicitly in Section 16.

Prepared 18 October 2026

1. Raw data and initial EDA

All 14 relational CSVs are loaded as strings before automatic missing-value conversion. This preserves literal \N sentinels for counting, alongside blank cells and full-row duplicates. Raw inputs are hashed; cleaning is performed on copies.

The archive contains 26,759 result records across 1950-2024. Season volume varies with calendar length and field composition, so row counts cannot be interpreted as a fixed-size panel. Race outcomes support retrospective analyses; they are excluded from current-race predictors.




Figure T1. Raw sentinel and blank counts across all 14 tables. Qualifying-session absence is substantial and must be distinguished from an observed zero.




Figure T2. Raw result records by season. Historical volume changes motivate calendar-aware comparisons and chronological evaluation.

2. Grain correction and missing values

The prediction grain is one (raceId, driverId) pair. For a duplicated pair, retain the smallest positive grid position, then smallest resultId; if all grids are absent/nonpositive, retain the smallest resultId. This deterministic entry-based rule avoids choosing by finishing outcome, while retaining an audit of ambiguous shared drives.

Removing 91 extra rows across 85 pairs leaves 26,668 historical driver-race rows. The small prevalence change is measured rather than assumed harmless. In modeling, grid zero becomes missing and grid_unassigned records that state.




Figure T3. Deduplication changes historical row count and podium prevalence. The modeling table is subsequently restricted to 1994-2024.




Figure T4. Placeholder conversion preserves the observed missingness pattern; it changes representation without inventing measured values.

3. Semantic typing and integrity

IDs/counts use nullable integers; measurements use numeric types; race/session dates and birth dates become datetimes. Qualifying, lap and pit durations become numeric seconds. Race result strings beginning with + are gaps, not total race durations, and are not coerced into elapsed time. Q2/Q3 absence often reflects elimination.

Audit	Observed result
Primary keys	14 table checks: no null or duplicate primary-key rows.
Foreign keys	23 relationships: no null or unmatched required references.
Semantic parsing	87 conversion audit rows: zero unexpected nonmissing values lost.
Source integrity	All 14 raw CSV hashes match before and after notebook execution.




Figure T5. Observed qualifying coverage varies sharply across seasons. Historical absence is retained and represented through training-derived missingness indicators.




Figure T6. Qualifying Q1 duration in seconds. The 99th-percentile display truncation improves visibility; it does not delete raw observations.

4. Chronology, preprocessing and features

Train on 1994-2018, validate on 2019-2021 and evaluate on 2022-2024. Every driver from a race stays in one partition. Histories may use earlier completed races within validation/test, matching sequential pre-race deployment; model weights and preprocessing remain frozen.

Partition	Years	Rows	Races	Podiums
train	1994-2018	9,799	449	1347
validation	2019-2021	1,200	60	180
test	2022-2024	1,359	68	204

Fit medians and StandardScaler on training only. Append 11 training-derived missingness indicators to the 19 original inputs. Part I documents every input and its cutoff validity. Driver histories are shifted; constructor outcomes are aggregated by team/race before shifting; standings come from the previous round of the same season.




Figure T7. Whole-race chronological partitions and class prevalence. Random driver-row splitting would mix race conditions and future seasons across partitions.




Figure T8. Training-only feature correlations. Related qualifying, grid, form and standings signals motivate regularization and grouped ablation; they are not independent causal effects.

5. Models, selection and complete metrics

Primary selection metric: validation average precision (AP), appropriate for a minority podium class. Secondary decision metric: F1, used to select a probability threshold on validation only. ROC-AUC summarizes ranking; precision and recall expose decision trade-offs. AP uses recall-weighted precision; trapezoidal PR-AUC interpolates the PR curve. Both are reported. Brier measures probability error.

Attempt	Mechanism / selected settings	Main limitation
LR baseline	Regularized additive log-odds. C=0.1; no class weighting. Six candidates.	Cannot automatically learn nonlinear interactions.
RF	Bootstrap trees with random feature subsets. Unrestricted maximum depth, minimum leaf 12. Four candidates.	Can overfit historical relationships and drift.
Shallow NN	One 32-unit ReLU layer, sigmoid output; L2=0.01, Adam 0.003, batch 256. Three candidates.	Limited historical sample, temporal drift and validation sensitivity.

All three attempts use identical rows, the same 19 original features and the same fitted preprocessing. Validation AP selects the NN (0.748718); its validation-F1 threshold is 0.347110. Weights remain training-only; choices are frozen before corrected holdout scoring.

Model	Split	ROC-AUC	AP	PR-AUC	F1	Precision	Recall	Brier	Thresh.
LR	train	0.9219	0.6441	0.6437	0.6288	0.5045	0.8344	0.0709	0.2064
LR	validation	0.9327	0.7146	0.7128	0.7225	0.6345	0.8389	0.0655	0.2064
LR	test	0.9358	0.7094	0.7084	0.6769	0.5549	0.8676	0.0707	0.2064
RF	train	0.9608	0.7990	0.7989	0.7256	0.6803	0.7773	0.0558	0.3682
RF	validation	0.9417	0.7432	0.7408	0.7352	0.6842	0.7944	0.0627	0.3682
RF	test	0.9373	0.6967	0.6953	0.6826	0.6133	0.7696	0.0700	0.3682
NN	train	0.9283	0.6641	0.6639	0.6502	0.5988	0.7112	0.0695	0.3471
NN	validation	0.9375	0.7487	0.7476	0.7352	0.6842	0.7944	0.0646	0.3471
NN	test	0.9383	0.7110	0.7097	0.6682	0.6425	0.6961	0.0700	0.3471

LR = logistic regression; RF = random forest; NN = shallow neural network. Thresholds maximize each model's validation F1, with the larger threshold breaking ties. Test scores never determine the chosen model or threshold in the current code.

6. Neural learning and baseline comparison

Keras Sequential uses one hidden ReLU layer and one sigmoid output, binary cross-entropy loss and Adam. A callback computes exact validation AP after each epoch before EarlyStopping reads it; the best-AP weights are restored. Validation is the explicit 2019-2021 partition, not a random row split.




Figure T9. Training/validation loss and exact validation AP from Keras History. Checkpoint selection uses validation AP, not the final test period.

Attempt	Validation AP	Change from LR	Validation F1
LR	0.714582	+0.000000	0.722488
RF	0.743172	+0.028590	0.735219
NN	0.748718	+0.034136	0.735219

The selected NN restores epoch 140 from 160 trained epochs. Its validation AP improves on logistic regression by 0.034136; the RF also improves over that baseline. This supports the extra flexibility in this validation era, while repeated trials can still adapt to that era. Loss/learning curves do not establish future performance.

7. Frozen-model holdout performance

The 2022-2024 partition spans the regulation change. The selected NN has ROC-AUC 0.938333, AP 0.711050, trapezoidal PR-AUC 0.709687 and F1 0.668235 at threshold 0.347110. Precision is 0.642534 and recall 0.696078. A high ROC-AUC does not imply that nearly every podium prediction is correct.




Figure T10. ROC and precision-recall curves for all three frozen models. The dashed PR reference is test podium prevalence; model choice remains based on validation AP.




Figure T11. Selected NN at its frozen validation threshold: 142 true positives, 79 false positives, 62 false negatives and 1,076 true negatives.

The NN has the highest test AP of these three models, but RF has slightly higher test F1 (0.682609). Different ranking and decision metrics can disagree; switching models after seeing that test result would compromise evaluation. These are corrected retrospective results on a reused test period, not a new blind test.

8. Feature-group ablation

Remove one group at a time, refit preprocessing on training rows for the remaining features, and retrain logistic regression with its selected configuration fixed. Keep training/validation rows unchanged. AP is threshold-free; each reported F1 uses the candidate's validation-selected threshold.

Removed group	Features left	Validation AP	AP change	F1
None (all features)	19	0.714582	+0.000000	0.722488
grid	17	0.697207	-0.017375	0.711779
qualifying	17	0.710377	-0.004205	0.723618
form	13	0.707218	-0.007364	0.724409
standings	15	0.715147	+0.000566	0.726343
context	14	0.724931	+0.010349	0.727273




Figure T12. Every declared group is retrained against the full-feature logistic baseline. Negative changes mean removal hurts; positive changes are retained honestly.

Removing grid hurts most (AP -0.017375); form and qualifying removals also reduce AP. Removing context improves AP by 0.010349, and removing standings improves it by 0.000566. Correlation and regularization permit substitution between inputs. These findings apply to the logistic ablation estimator; they do not establish that dropping context improves the selected NN. The primary comparison retains its predeclared full feature set.

9. Two preprocessing-order experiments

Comparison A changes median-impute then scale to scale observed values then impute in scaled units. StandardScaler ignores missing values during fitting, so fitting its variance before filling can alter the transformed data. Comparison B changes clip-impute-scale to impute-scale-clip, using training 1st/99th percentiles for continuous features only.

Order	Validation AP	F1	Threshold
A0: impute > scale (baseline)	0.714582	0.722488	0.206441
A1: scale > impute	0.714788	0.721228	0.336444
B0: clip > impute > scale	0.703887	0.723404	0.209226
B1: impute > scale > clip	0.704881	0.724936	0.367379




Figure T13. Observed transformations for A (qualifying_gap_pct) and B (driver_prior_starts). All bounds, medians and scales come from training only.

A changes validation AP by +0.000206; B's second order changes AP by +0.000994 relative to its first order. qualifying_gap_pct has 1,987 missing training values; the maximum A1/A0 transformed difference is 10.2573. All 13 binary/indicator columns are protected from clipping. The 120-row value-effect table records ranges, dispersion and changed values for every input/order. These small validation differences are diagnostic, not proof of general superiority; the primary comparison keeps impute-then-scale.

10. Historical-coverage sensitivity

Refit the same selected logistic configuration on 2003-2018 instead of 1994-2018. Retain the same feature definitions and 2019-2021 validation rows, and refit preprocessing only on the shorter training window. Earlier completed events may still supply lagged histories.

Training window	Rows	Qualifying missing	Validation AP	F1
1994-2018	9,799	18.99%	0.714582	0.722488
2003-2018	6,411	0.33%	0.716418	0.723716




Figure T14. Shortening the training window reduces qualifying-position missingness while changing both training size and era. Validation rows/configuration remain fixed.

The shorter window changes validation AP from 0.714582 to 0.716418 (+0.001836), while the training sample falls from 9,799 to 6,411 rows. Qualifying-position missingness falls from 18.99% to 0.33%. Cars, entrants and rules also change, so this experiment does not isolate a causal effect of missing qualifying. The primary training window remains 1994-2018.

11. Global permutation importance

Explain the validation-selected NN. Permute one original validation input at a time and pass the perturbed data through frozen preprocessing and the model. Importance is the decrease in AP over eight seeded repeats; error bars show the repeat standard deviation.




Figure T15. Validation AP loss after permuting each original feature. The largest losses identify inputs the fitted NN relies on under this perturbation procedure.

Leading input	Mean AP loss	Repeat SD
grid	0.142484	0.025276
qualifying_position	0.086507	0.021982
driver_prior_starts	0.028641	0.013414
driver_standing_points	0.025656	0.013539
driver_form_podium_rate	0.025652	0.026656

Grid and qualifying position dominate this ranking; prior starts and standings/form add information. Related inputs can substitute, so individual permutation may understate a redundant group. Independent permutations can create unrealistic grid/form combinations. This measures predictive reliance, not a causal effect on podium outcomes.

12. Global SHAP explanation

Kernel SHAP approximates the selected NN's podium probability using a seeded training background. The global validation sample is season-proportional: 21 rows from 2019, 17 from 2020 and 22 from 2021. Sampling uses no outcomes; any separately appended local-only case is excluded from global means and the beeswarm.




Figure T16. SHAP beeswarm for 60 validation predictions. Positive attribution raises model probability relative to the background; negative lowers it. Red/blue represent high/low standardized feature values.

Grid, qualifying position and driver_form_podium_rate lead mean absolute SHAP importance. Low grid/qualifying-position numbers generally support higher predicted podium probability; higher recent podium form can also raise it. Attributions are measured in probability units and depend on the background/approximation. Correlated inputs share information, and SHAP attributions are not causal effects.

13. Local SHAP: a single prediction

Choose the validation prediction nearest 0.5 without consulting its outcome: raceId 1027, driverId 830 (2019, round 18). Explain this same case with SHAP and LIME. Its podium probability is 0.496954, exceeding the frozen 0.347110 threshold, although its observed label is 0. An explanation of a false positive can still faithfully describe model behavior.




Figure T17. Additive attribution from expected background probability to the selected prediction. Displayed feature values are standardized inputs; contributions are probability changes.

Check	Result
Model probability	0.496953845024
SHAP reconstruction	0.496953845024
Absolute reconstruction error	1.110e-16

Qualifying position and grid are the leading positive contributions for this row; round and year are leading negative contributions. The reconstruction check verifies additive consistency for this prediction. It does not establish causal validity, a perfect approximation for every coalition, or predictive correctness.

14. Local LIME and explanation fidelity

LIME explains the same validation row using a local surrogate. Displayed conditions are in imputed original racing units; the prediction wrapper applies frozen scaling. Binary inputs and missingness flags are treated as categorical 0/1 states. Their perturbations remain binary, although independent perturbations can still break relationships such as grid and its missingness flag.




Figure T18. LIME local surrogate for the same prediction as Figure T17. Green/red bars support or oppose the local podium prediction; the title reports weighted local R-squared.

A grid of 6 or better and qualifying position of 7 or better support the local prediction under LIME's sampled neighborhood. The surrogate R-squared is 0.399350: about 39.9% of weighted neighborhood variation is explained, leaving substantial unexplained variation. Treat the displayed weights as approximate; they are not a strong stand-alone account of this network's behavior.

Local SHAP supplies an additional attribution with checked additive reconstruction. Agreement in leading grid/qualifying signals is useful, but differences between explainers reflect their neighborhoods, backgrounds and approximation methods. Neither explanation demonstrates that changing a feature would cause a podium finish.

15. Inference and saved-model verification

predict_podium(record) consumes the 19 numeric engineered pre-race inputs in the feature catalog. It is not a lookup from raw driver/race names: rolling histories and standings must already exclude the requested race. Omitted/null fields use frozen training medians and training-derived missingness flags; the response reports imputed fields.

Example	Podium probability	Binary call	Missing inputs
complete	0.595058	1	None
partially missing	0.459572	1	Qualifying + standings (6)
missing grid	0.026343	0	Grid only

All examples use the same frozen NN threshold, 0.347110. Removing six qualifying/standings inputs changes probability from 0.595058 to 0.459572; missing grid changes it to 0.026343. These examples demonstrate handling, not calibrated confidence under arbitrary missingness. Heavy imputation reduces reliability.

Input consistency

Omitted/null/nonpositive grid is treated as missing and derives grid_unassigned=1. A positive grid derives 0. Contradictory supplied flags, unknown keys, malformed numeric values and nonfinite numbers are rejected. Missing inputs must be omitted or represented as null, rather than NaN/infinity.

Native model persistence

Training-fitted medians/scaler are saved with joblib, as are the logistic/forest estimators. The NN uses native Keras serialization. The notebook verifies reloaded-model prediction parity for all three estimators. The independent local review also reloaded the delivered models and reproduced every training/validation/test metric row to numerical precision.

Run configuration

Install the project dependency files into the notebook's Python kernel. Dataset discovery searches the working directory and its ancestors for the complete 14-table Dataset folder, including when opened from Deliverables/1-Notebook. No manual path setting is needed for the delivered project layout. F1_DATA_DIR remains an optional override for custom locations; an explicit path is checked for every required CSV.

A fresh local Run All with this configuration completed all 27 code cells. This demonstrates local execution with dependencies and dataset configured; it does not verify execution on Kaggle. Fresh outputs are written under output/ in the working directory.

16. Limitations and two-report coverage

Evaluation confidence

The corrected run follows inspection of earlier test results. The same 2022-2024 period is reused, so these are corrected retrospective scores, not a new independent blind test. In the current code, candidate grids, validation-based model/checkpoint/threshold rules and split boundaries remain fixed; no test-driven fitting or selection is used. Repeated validation diagnostics can still overfit one validation era.

Transfer and interpretation

Historical qualifying coverage, rules, scoring, constructor identities and field sizes change. Final archived grid is assumed available before the start; genuine live use needs a timestamped pre-start snapshot. Qualifying gaps combine sessions/conditions. Weather, tyres and strategy are absent; probabilities are not externally calibrated, and independent binary calls need not yield exactly three podiums. Part I adds limitations specific to home-country mapping and mechanical-retirement labels.

Permutation, SHAP and LIME describe predictive associations. Correlated features, synthetic perturbations, finite SHAP sampling/background choices and low LIME fidelity constrain interpretation. Feature importance is not proof that the feature causes podium outcomes.

Where each requirement is documented

Evidence	Report / location
Q1-Q3 answers and four question plots	Part I, Section 1, pages 2-4.
Selected-feature rationale and two feature plots	Part I, Section 2, pages 5-6.
Archive/era limitations	Part I, Section 3, page 7; supplemented above.
Cleaning, EDA, split and correlation plots	Part II, Sections 1-4, Figures T1-T8.
All-model metrics and learning/evaluation plots	Part II, Sections 5-7, Figures T9-T11.
Ablation and preprocessing/coverage experiments	Part II, Sections 8-10, Figures T12-T14.
Global/local XAI and noncausal interpretation	Part II, Sections 11-14, Figures T15-T18.
Complete/partial inference and persistence	Part II, Section 15.

Together, the reports contain all 24 notebook plots: 6 in Part I and 18 in Part II. Calculations, full candidate trials and supplementary audit tables remain available in the run-all notebook and exported results. Accessible Kaggle/GitHub publication and course-form submission follow finalization of the files.

Sources: Milestone 1 brief; executed F1 Podium Prediction notebook; delivered audit/model/experiment/XAI/inference tables; exported learning-history, split, sensitivity and explanation-check evidence. Figure files are copied without alteration from those executed outputs.