

Name data: 40_Patients_Suffering_from_Leukemia

Data description: Medical and clinical lifetime data for a cohort of 40 patients suffering from blood cancer (Leukemia) has been compiled from a Saudi Arabian Ministry of Health hospital. This specific dataset is often utilized for survival analysis and statistical modeling (e.g., assessing dependent covariates). The primary purpose of this dataset is statistical modeling rather than broad epidemiological study. A summary of the dataset's clinical and demographic background from the region provides necessary context.

115, 181, 255, 418, 441, 461, 516, 739, 743, 789, 807, 865, 924, 983, 1024, 1062, 1063, 1165, 1191, 1222, 1251, 1277, 1290, 1357, 1369, 1408, 1455, 1478, 1222, 1549, 1578, 1578, 1599, 1603, 1605, 1696, 1735, 1799, 1815, 1852

Second Data

Name data: Engineering data including the breaking stress of carbon fibers measured in GPa.

Data description: The breaking stress (tensile strength) of carbon fibers typically ranges from 3.5 GPa to 7.0 GPa, depending on the precursor and manufacturing process. Engineering applications utilize various fiber grades characterized by their distinct tensile strength, modulus, and transverse properties. In engineering and quality control, breaking stress data is typically evaluated statistically (e.g., using the Weibull Distribution) due to microscopic manufacturing flaws.

115, 181, 255, 418, 441, 461, 516, 739, 743, 789, 807, 865, 924, 983, 1024, 1062, 1063, 1165, 1191, 1222, 1251, 1277, 1290, 1357, 1369, 1408, 1455, 1478, 1222, 1549, 1578, 1578, 1599, 1603, 1605, 1696, 1735, 1799, 1815, 1852