KLinterSel Manual v 0.3

Antonio Carvajal-Rodríguez
Centro de Investigación Mariña (CIM)
Departamento de Bioquímica, Genética e Inmunología
Facultad de Biología
Universidad de Vigo, Vigo 36310, Spain
Email: acraaj@uvigo.es
Web: http://acraaj.webs.uvigo.es

Table of Contents

Versions....3
Introduction....4
Pre-built Binaries Requiring No Installation....4
Installation....5
Input (Data Format)....5
Command Line Arguments....6
    Basic Command....6
    Distance option....6
    Hypergeometric k-way intersection test....7
    Intersections....7
    Kmax option....8
    No test option....8
    Number of permutations....8
    Path Specification....8
    Permissive with redundant methods....8
    Plotting....8
    Significance level....9
    Stats....9
    Uniform....9
Output....9
    HGkI Test Results Output File (HGkItest_)....9
    T_{KL} Test Results Output File (TKLtest_)....10
    Intersections Result File (INTERSEC_test_D1E4_)....10
    Plots (if enabled)....11
    Spatial uniformity ranking metric....11

Versions

Version KLinterSel 0.3 (December 2025 - June 2026):

- A new parametric test (HGkI) based on a sequentially conditioned hypergeometric distribution.

- A rank-based measure to assess deviations from uniformity in the spatial distribution of SNPs along the chromosome.

Version KLinterSel 0.2 (November 2025):

- Major speed-up of the KL computation thanks to a more efficient RelEntr implementation.

- New command-line options:

    --permissive to disable the strict redundancy filter between candidate files.

    --uniform perform resampling assuming a uniform distribution of SNPs.

- Sorted intersection output: elements within each intersection are now returned in sorted order for consistent and cleaner reporting.

- Bug fix: corrected an issue in the resampling test where the comparison of medians introduced a slight conservative bias.

Version KLinterSel 0.1 (August 2025):

- Improvements for figure customization. Multiprocessor options.

Version KLinterSel 0.0 (July 2025):

- This is the first version.

Introduction

KLinterSel is a Python project designed to assess the agreement among different methods for detecting candidate sites under selection. It implements a Monte Carlo–based test (T_{KL}) and a hypergeometric k-way intersection test (HGkI) to evaluate whether observed overlaps are closer than expected by chance. The program also computes intersections among candidates and provides complementary plotting and statistical summaries.

Pre-built Binaries Requiring No Installation

Pre-built KLinterSel binaries are available at https://github.com/noosdev0/KLinterSel/releases/tag/v0.3. Binaries are provided for Windows, Linux, and macOS (arm64) and should work on most versions of these operating systems. To run them (assuming that the files totsnps.txt, sigsmethod1.norm, sigsmethod2.tsv and sigsmethod3.norm exist and are in the same KLinterSel folder as the executable) type in the command-line interface (by default, the Monte Carlo TKL test is run; to use the hypergeometric test, simply add the --HG flag):

Linux: ./KLinterSel_U totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm --path ./ --dist 10000

macOS: ./KLinterSel_OS totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm --path ./ --perm 10000

Windows: Double click just for running the program under default options. The program will ask for the names of the files. Alternatively, you can go to the command prompt (cmd.exe) and type

C:\KLinterSel\KLinterSel.exe totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm --path ./ --dist 100

or you can also access the Run command by pressing the Windows logo key +r

then drag and drop the .exe file from your folder and add the desired arguments, e.g.

C:\KLinterSel\KLinterSel_Win.exe totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm --path ./ --perm 1000 --dist 10

Installation

Clone the KLinterSel repository or download the files. To use the KLinterSel script (KLinterSel.py), you need to have Python installed (version 3.7 or higher). To install the necessary dependencies, navigate to the folder containing the KLinterSel.py script where the requirements.txt file should also be located, and run the following command in the terminal:

```
pip install -r requirements.txt
```

This command will install all required libraries as specified in the requirements.txt file, including numpy, pandas, matplotlib, seaborn, scipy and psutil, along with any other dependencies listed.

To run the .py script type in the command-line interface (assuming that the files totsnps.txt, sigsmethod1.norm, sigsmethod2.tsv and sigsmethod3.norm exist and are in the same folder as the script):

python3 KLinterSel.py totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm

Input (Data Format)

The script requires two types of input files:

1.- Original Positions Data File: The first file contains the positions of all analyzed SNPs. A CSV, TSV or text (.txt) file with the following structure:

CHR POS

1 12345

1 12367

.

.

The first column identifies the chromosome, and the second column lists the position of the SNP within the chromosome. The original position file format is also supported in .map format, with 4 columns and no header. The first column indicates the chromosome, the second the SNP ID, the third the genetic position, and the fourth the physical position. The program will use the physical positions.

2.- Candidate Site Results Files: Files containing the candidate positions for each method. These files can have the same format as the original two column data file (CSV, TSV or txt), but in addition files with a norm extension are also accepted. These files correspond to the output files from the norm-selscan program. In this case, a single chromosome is assumed, and physical positions with a value of one in the last column are selected.

Command Line Arguments

A full description of all available command-line options can be displayed by running:

```
python3 KLinterSel.py --help
```

Below is a breakdown of the various command line arguments that can be used with the script:

- **Basic Command**

  python3 KLinterSel.py totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm

  This command processes the data without additional options it is equivalent to

  python3 KLinterSel.py totsnps.txt sigsmethod1.norm sigsmethod2.tsv sigsmethod3.norm --path . --perm 10000 --dist 10000 --SL 0.05.

- **Distance option**

  --dist 10000 Specify the distance threshold (default 10,000) for the intersection computation.

- **Hypergeometric k-way intersection test**

  --chr-id By default, when the --HG flag is used, the program computes the HGkI test for all chromosomes. If a valid chromosome number is specified using --chr-id (any integer from 1 to the last chromosome), the HGkI test and the corresponding intersections are computed only for that chromosome.

  --HG Run the hypergeometric k-way intersection test. When this option is enabled, the standard distance-based KLinterSel analysis is skipped. The window size for the hypergeometric test is defined by --W (or W = 1 if --W is not provided).

  --W It defines the size of the disjoint units used by the hypergeometric test, independently of the distance scale used by KLinterSel. When W = 1 (default), units correspond to individual SNPs (exact overlap). When W > 1, units correspond to disjoint genomic windows of size W that contain at least one SNP. Note that when --W is large, multiple candidate SNPs within the same window are collapsed into a single event for the hypergeometric test.

- **Intersections**

  --intersection Enables SNP intersection computation, which is disabled by default. When a statistical test (T_{KL} or HGkI) is performed, intersections are computed only for chromosomes identified as significant. To compute intersections for all chromosomes without performing a test, use --intersection --notest; equivalently, --intersection --SL 1 reports intersections for all chromosomes.

  --chr-id Restricts all computations to a single chromosome, specified by an integer from 1 to the total number of chromosomes. This restriction applies both to the selected statistical test and, when --intersection is enabled, to intersection computation. If a test is

performed, intersections for the selected chromosome are reported only when that chromosome is significant.

- **Kmax option**

  --Kmax undefined If defined and the number of candidate SNPs in any file is greater than Kmax, it filters SNP positions to group those that are at distance ≤ *D*, leaving only the first and last of each group.

- **No test option**

  --notest No statistical tests (T_{KL} or HGkI) are performed.

- **Number of permutations**

  --perm 10000 Number of permutations used to compute the expected distance profile (default: 10,000). Ignored when --HG is set.

- **Path Specification**

  --path ./home/KLinterSel/results/data Specify the directory where the input files are located.

- **Permissive with redundant methods**

  --permissive Disables the new default rule that removes candidate files showing high redundancy (i.e., when all or most candidate sites are identical across methods).

- **Plotting**

  --paint Only for T_{KL} test (ignored when --HG is set). Enable the generation of plots. In this case, intersection computations are skipped. The program draws two histograms: the one on the left shows the observed distances, and the one on the right shows the expected distance profile if the matches between methods were generated at random given the genomic locations of SNPs in the input data. If there are multiple chromosomes, the program displays the graph for each chromosome and, after

closing it, continues with the next chromosome. If you only want a graph for a specific chromosome, for example chromosome 7, you can specify --paint 7.

The scale of the X and Y axes can be controlled with the --max-xvalue and --max-yvalue arguments, respectively. The first is the Mb scale (--max-xvalue 20) and the second is a frequency between 0 and 1 (--max-yvalue 0.25).

- **Significance level**

  --SL 0.05 Set the significance level for the statistical tests (default 0.05).

- **Stats**

  --stats Generates statistics for each chromosome in each file, including minimum, maximum, mean, standard deviation, and median values. No other calculations are performed in this case.

- **Uniform**

  --uniform For the T_{KL} test, perform resampling assuming a uniform SNP distribution..

Output

The KLinterSel.py script generates three types of output files.

HGkI Test Results Output File (HGkItest_)

- This file reports the results of the HGkI test for each chromosome. It includes the total number of SNPs and occupied windows, the number of candidate SNPs and windows identified by each method, the observed number of overlapping windows (k_{obs}), the number expected under the null model E[k_{obs}], the associated p-value, and a rank-based measure of deviation from uniformity in the spatial distribution of SNPs along the chromosome (0 = lowest rank of deviation, 1 = highest rank of deviation), together with an independent, test-based classification derived

from Kolmogorov–Smirnov, Cramér–von Mises, and cv_counts (coefficient of variation of SNP counts) statistics (close to uniform, medium deviation, or strong deviation).

Under the null hypothesis of independent and uniformly distributed candidates across windows, the expected number of *k*-way overlapping windows is

$$E[k_{obs}] = \frac{\prod_{i=1}^{k} n_i}{N^{k-1}}$$

where n_i is the number of windows occupied by method *i* and *N* is the total number of windows in the given chromosome. This expectation ranges from 0 to the smallest number of windows reported by any method.

T_{KL} Test Results Output File (TKLtest_)

- This file reports the results of the T_{KL} test for each chromosome. It includes the total number of SNPs and the number of candidate SNPs identified by each method, a Kullback-Leibler-like discrepancy measure between the observed and expected ordered distance profiles, the associated p-value, the observed (oQ2) and expected (eQ2) medians, and a rank-based measure of deviation from uniformity in the spatial distribution of SNPs along the chromosome (0 = lowest rank of deviation, 1 = highest rank of deviation), together with an independent, test-based classification derived from Kolmogorov–Smirnov, Cramér–von Mises, and cv_counts (coefficient of variation of SNP counts) statistics (close to uniform, medium deviation, or strong deviation).

Intersections Result File (INTERSEC_test_D1E4_)

- This file contains, for each chromosome, the intersections among the different methods. The distance threshold used to define intersections is indicated in the file name; for example, _D1E4_ denotes a distance of 10 kb. Intersections are reported for all combinations of methods. For

instance, when three methods are used (K = 3), both the pairwise intersections and the three-way intersection are provided. The last column lists the genomic sites involved in the intersection across all methods.

Plots (if enabled)

- If the plotting option is enabled, the program generates graphical representations of the observed and expected distance profiles that can be saved to the user's computer.

Spatial uniformity ranking metric

In the test results output files of both HGkI and T_{KL}, the last columns report a rank-based measure of deviation from spatial uniformity together with a test-based classification derived from the Kolmogorov–Smirnov, Cramér–von Mises, and cv_counts statistics (coefficient of variation of SNP counts). The classification labels chromosomes as close to uniform, moderately deviating, or strongly deviating from uniformity.

This information is provided because both HGkI and T_{KL} explicitly account for the empirical spatial distribution of SNPs, making it useful to characterize the degree of spatial regularity of SNP positions across chromosomes. To facilitate this interpretation,the program computes a spatial uniformity ranking metric, which orders chromosomes according to the extent to which their SNP distributions depart from uniformity.

Chromosomes are ranked on a normalized scale from 0 to 1, where 0 indicates spatial uniformity and 1 indicates extreme deviation from uniformity. The ranking is based on a composite deviation score defined as the mean percentile rank across three complementary statistics: Kolmogorov–Smirnov (KS), Cramér–von Mises (CvM), and binned count heterogeneity (measured as the coefficient of variation of SNP counts across genomic bins). This procedure yields a scale-independent multivariate summary of spatial deviation from uniformity. In the program output, the

ranking score and the associated classification are reported under the headings URank and Uclasf, respectively.

The composite score emphasizes consistent deviations across multiple measures of spatial heterogeneity. Each statistic captures a different aspect of spatial structure. The Kolmogorov–Smirnov (KS) statistic is sensitive to localized departures from uniformity, highlighting sharp clustering or large gaps. The Cramér–von Mises (CvM) statistic summarizes cumulative deviations across the entire chromosome and is therefore more sensitive to broad-scale or distributed departures from uniformity. Finally, the coefficient of variation of binned SNP counts quantifies heterogeneity in local SNP density at a fixed genomic scale, capturing scale-dependent clustering or patchiness.

By combining these complementary metrics, the ranking distinguishes between localized, global, and scale-dependent forms of spatial heterogeneity. This provides a more robust characterization of SNP spatial structure and facilitates the interpretation of HGkI and T_{KL} results across chromosomes with different spatial properties.