CS 103 Lab – Variables, Expressions & Calling Functions

1 Introduction

In this lab you will gain experience writing code that uses arithmetic expressions and calls built-in functions. You will need to both submit your code electronically AND demo it for a CP/TA.

2 What you will learn

After completing this lab you should be able:

- Use cin/cout to take input from the user and print output to the user
- Use expressions, define and convert between data types, and call functions

3 Background Information and Notes

None

4 Procedure

We provide skeleton code for two of the three exercises in this lab.

Go to Lab2: Variable and Expressions in Vocareum.

You'll see the following partially completed files into your directory:

4.1 Basic I/O, Expressions, Order of Operations Calling Functions,

In calculus, a Taylor series approximates arbitrary functions by polynomials. E.g., the function sin(x) can be approximated using the series expansion:

$$\sin(x) = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} \cdots$$

Your goal is to write a program which will compute this approximation. It should take a decimal number x as input, compute the approximation given by the first four terms of the above formula, and then print it out. (This formula assumes x is in radians. Your program should do the same, so no degrees/radians conversion is necessary.)

Open compute_sin.cpp, which is a skeleton program for you to fill in and complete the contents of the main function. The comments there should help you structure your work.

Again, the formula that your program should compute is

$$x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!}$$

Last Revised: 9/1/2019

It uses exponents (like x^3) and factorials (like 3! which means $1 \cdot 2 \cdot 3 = 6$,). So, if the input is 1, the output should be $1 - 1/3! + 1/5! - 1/7! \approx 0.841468$, which is a pretty good approximation to $\sin(1) \approx 0.841471$.

- To compute powers, do not simply multiply x by itself. Also, don't use the ^ symbol (e.g. x^3), which is the XOR operator in C++. Instead, use the pow() function. It is part of the <cmath> library, which is why we need that extra #include statement at the top. The textbook explains this function, or read online at http://www.cplusplus.com/reference/cmath/pow/.
- There is no built-in factorial function in C++. However, we've provided one for you, called fact, in the skeleton code. We won't talk about defining our own functions for a couple more lectures. But *calling* the provided function is pretty straightforward: write fact(3), or any other input in place of 3.

Make sure you use parentheses where necessary, and use an appropriate datatype for your variables. Don't assume that x is a whole number, it could be a decimal number like 1.57.

You do not need to use a loop for this exercise or any other in this lab.

After you're done editing your program, remember to compile it at the terminal prompt:

Then run it with the command below.

Check the output when you input 1 (i.e. sin(1)). Ask a CP or TA for help if needed. When you're ready to check in all of your programs, demo it for a CP or TA (they'll read your code and ask you to run it on additional test cases). Submit your code on Vocareum at the end of the lab.

4.2 Casting, Expressions

2

In this exercise you will write a program to convert between two color schemes. "RGB," which corresponds to "additive" colors of light like a TV or computer screen, represents a color with 3 components Red, Green, and Blue that each range from 0 to 255. "CMYK," which corresponds to "subtractive" scheme like the wavelengths absorbed by ink, represents a color with 4 components Cyan, Magenta, Yellow, and Black that are each real values between 0.0 and 1.0. Your program will convert from RGB format to CMYK using the following conversion method:

Define
$$white = \max \left\{ \frac{red}{255}, \frac{green}{255}, \frac{blue}{255} \right\}$$

Last Revised: 9/1/2019

$$cyan = \frac{\left(white - \frac{red}{255}\right)}{white}$$

$$magenta = \frac{\left(white - \frac{green}{255}\right)}{white}$$

$$yellow = \frac{\left(white - \frac{blue}{255}\right)}{white}$$

$$black = 1 - white$$

Your program should take <u>3 integers</u>, (red, green, and blue) as input from the keyboard and output the corresponding values for cyan, magenta, yellow, and black. Fill in the provided skeleton program color_conv.cpp to achieve this.

The conversion formula includes max, which means the maximum (largest) of its inputs. The skeleton has #include <algorithm> at the top of the program, which makes C++ provide you with a function called max to do this. However, max can only compare (find the max of) two numbers at a time, so you'll have to figure out how to use this 2-input function to perform a 3 operand maximum. Here's an example of using max.

```
#include <iostream>
#include <algorithm>
using namespace std;

int main() {
  cout << max(45, 63) << endl; // prints 63, it is larger
  return 0;
}</pre>
```

Example: if you input 20 (red) 80 (green) 60 (blue), the correct output should be:

cyan: 0.75
magenta: 0
yellow: 0.25
black: 0.686275

Check other inputs by using any online RGB -> CMYK calculator site.

Hint: a common mistake in this exercise is **integer division** (see the lecture notes). You will need to demo and submit your code.

4.3 Think, Code, Test

Write a program called digits.cpp to do the following. Prompt the user for an integer between 0 and 999. (You don't need to write any code to check the input.) Write code to take the single decimal value and find the 1's digit, 10's digit, and

100's digit (in that order) and store them in three separate variables. If they enter a 1 or 2-digit decimal value you should produce 0 for the leading digits. Then output the result on three separate lines to the user.

Here is a sample run:

Enter an integer between 0 and 999: 247 1's digit is 7 10's digit is 4 100's digit is: 2

Hint: Think how you can use quotients and remainders to help you.

Demo and submit your work.

5 Review & Reflection

[Not Required – Use as a practice exercise if you have started to discuss loops.]

Take a moment and reflect on the last program. Suppose we wanted to achieve the same task of finding the separate digits of any size number (i.e. 3-, 4-, 5-, etc. digits) in ascending order (from 1's to 10's to ...) using a **while** loop? What would you do in each body/iteration? What would the condition for repeating be (i.e. the while condition)?

Write a brief English description on this paper or in a text file. You can optionally re-

check in.
-