

# Improving the robustness of motion modelling and control for mobile robots in harsh conditions

Dominic Baril (111 103 819)

December 2023

Supervised by Prof. F. Pomerleau  
and co-supervised by Prof. P. Giguère

## 1 Introduction

The field of mobile robotics has known significant advances in the last decade, leading to potentially disruptive innovations in automation for various industries. Autonomous systems are currently mature enough to be functional in controlled and structured operational environments, such as warehouses and urban areas under ideal weather. uncrewed ground vehicles (UGVs) are proving to be effective solutions to current society issues related to labor shortage, workplace security and operational efficiency. However, such issues are greater for industries industries such as agriculture, forestry, defense, mining and search and rescue, which require operation in outdoors, uncontrolled environments. In these cases, systems are subject to a higher spectrum of environmental hazards, such as harsh weather, traction variability and deployment in remote environments. However, as stated by Van Brummelen *et al.* [1], challenges inherent to these conditions remain an open question.

This work aims to extend proficiency and robustness of autonomous navigation systems to off-road environments and harsh weather. Autonomous navigation can be split into three key components: path planning, path following and localization. This work mainly focuses on path following, with some contributions to localization. For path following, the key problems related to navigating in such environments are the high variability of wheel-to-ground traction and complex vehicle dynamics. For localization, the key problems are related to navigating in Global Navigation Satellite System (GNSS)-denied conditions, low geometrical constraints and dynamic environments. In all, the research question for this work can be stated as follows:

*How to increase robustness of UGV path following and localization for off-road and winter conditions?*

A UGV motion model is a key component to compute optimal commands with respect to motion predictions and provide localization prior for localization systems. Thus, this research project is focused at minimizing motion prediction error for models, which is directly correlated with path following and localization errors. Current approaches for UGV modeling belong to two families: Model-based, divided between kinematic and dynamic models,

and Learning-based, leveraging machine learning and driving data to predict motion. Both kinematic models and learning-based approaches share the advantage that they have a low expertise requirement for deployment and require a training dataset to reduce prediction error, leading them being the most popular choice. To answer the aforementioned research question, three key issues were identified:

- 1. How does UGV behavior differ between concrete and snow-covered terrain navigating. What kinematic model behaves best for both?**
- 2. How can we standardize training dataset gathering and improve vehicle slip learning?**
- 3. What are the impacts of the boreal forest environment and winter weather on lidar-based localization?**

These key issues guide the scientific contributions that were made through this work. The remainder of this document describes the current scientific production done through this project and upcoming plan up to thesis submission. More specifically, [Section 2](#) describes the currently submitted and published research work, summarizing contributions and lessons learned for each paper. Afterwards, [Section 3](#) details the remaining research work [Section 3.4](#) and provides a schedule leading to thesis submission. Lastly, [Section 4](#) provides a brief conclusion.

## 2 Current scientific production

This section describes the current scientific done through this Ph.D. thesis work and collaborations done with other researchers. First, the three articles conducted directly for which I acted as first author. All of these scientific contributions are related to the subproblems states in [Section 1](#). Then all of the worth in which I have participated as co-author is described briefly. Since mobile robotics is a field requiring various expertise and human resources to conduct field deployments, all scientific production presented includes multiple co-authors.

### 2.1 Articles published and submitted as first author

**D. Baril, V. Grondin, S.-P. Deschenes, J. Laconte, M. Vaidis, V. Kubelka, A. Gallant, P. Giguere, and F. Pomerleau, “Evaluation of Skid-Steering Kinematic Models for Subarctic Environments”, in *2020 17th Conference on Computer and Robot Vision (CRV)*, IEEE, 2020, pp. 198–205**

The first article that I have published was submitted to the *Conference on Robot and Vision (CRV)*, in May 2020. This article aims to evaluate the performance of skid-steering mobile

robots (SSMRs) kinematic motion models on dry concrete and snow-covered terrain. For this article In this article, we collected a total of 2 km of human driving data to evaluate four kinematic models from the literature. We leverage lidar point cloud registration based on the iterative closest point (ICP) algorithm to generate ground truth localization. This work received the **Best Robot Paper Award** for the CRV conference this year. A seminar was conducted for this work.<sup>1</sup> The resulting contributions are as follows:

1. Validate SSMR kinematic motion models fitness for a heavier platform on a relatively uniform concrete terrain;
2. Evaluate SSMR kinematic motion models their performance for snow-covered terrain using more than 2 km of trajectories traveled; and
3. Highlight the impact of angular motion on the accuracy of SSMRs kinematic modeling.

The four kinematic models evaluated are the extended differential-drive asymmetrical, the extended differential-drive symmetrical [3], the full linear [4] and radius of curvature (ROC)-based [5]. We also show that models with less parameters tend to perform better for angular prediction and models with more parameters perform better for translation prediction, due to their ability to predict non-zero lateral motion. However, once trained, the performance of all models is similar for both terrain types, suggesting that all kinematic models evaluated behave similarly. The largest prediction error occurs when the vehicle's angular velocity is at its maximum, which leads to the highest amount of vehicle slip.

Additionally, training kinematic models with empirical driving data leads to significant prediction error reduction, for both concrete and snow-covered terrain. The relation between training window and prediction error is also studied in this work, clearly showing that models perform best when predicting for the same horizon for which they were trained. We show that for the same commanded angular velocity, angular velocity is higher on snow-covered terrain than concrete. This phenomenon is due to the high friction caused by the tire deformation occurring during skidding on concrete, compared to soft terrain deformation on snow-covered terrain.

The take home message for this published paper was that kinematic motion models are adequate for predicting SSMR motion, both on dry concrete and snow-covered terrain, however they require a training dataset dependent to vehicle and terrain properties. During the experimental work conducted for this paper, we imitated similar work by having a human operator to stimulate as many commands as possible, however this process lead to biased command stimulation and forward-only driving and proved to be time-consuming. Since deploying UGVs in off-road environments is a complex endeavor, reducing the time requiring to generate a motion model that is accurate enough for stable autonomous navigation is key.

---

<sup>1</sup><https://www.youtube.com/watch?v=FjrgZMmWTNI&t=25s>

D. Baril, S.-P. Deschênes, L. Coupal, C. Goffin, J. Lépine, P. Giguère, and F. Pomerleau, “Drive: Data-driven robot input vector exploration”, *ArXiv preprint, submitted to ICRA 2024*,

My second article as first author was submitted to the *International Conference on Robotics and Automation (ICRA) 2024*. It is currently under review, with a result expected in January 2024. This article aims to solve the issue discovered in our previous work by standardizing and automating the UGV training dataset gathering task. Thus, we propose Data-driven Robot Input Vector Exploration (DRIVE), a protocol allowing to automatically generate a training dataset for commercial UGVs. We also propose a novel SSMR dynamics-based slip learning model, outperforming similar models. The experimental evaluation for this work totals over 7 km of driving data, conducted through three SSMRs with weights ranging from 75 kg to 470 kg. The deployment environments include indoor tile, snow-covered terrain, dry gravel and an indoor, leveled ice rink. Again, localization is provided by our local mapping framework, based on the ICP algorithm. The code and datasets are all available online and open-source.<sup>2</sup> For this work, the contributions are as follows:

1. DRIVE, a standardized UGV characterization and motion data generation protocol allowing to train motion models on the entire vehicle input space;
2. A novel slip-based UGV motion prediction model, leveraging the accuracy of model-based approaches and the minimal system characterization requirement of learning-based approaches.

As shown in our previously published work [2], a training dataset specific to vehicle and terrain properties is key to reduce motion prediction error. Most work on UGV motion modeling includes training dataset gathering, however, there exists little-to-no guidelines available to reproduce their work. DRIVE enables automatic UGV input-space characterization and training dataset gathering by sampling uniformly through the input-space. We show that this protocol leads to significantly increased prediction performance when compared to manual driving and radius of curvature (ROC) stimulation approaches. Another key finding is that for all experiments conducted, models reach convergence with a maximum of 46 sec of driving data. This result is of high importance for field robotics operations, which are costly to deploy and for which UGV battery conservation is critical [7]. It also enables model re-training when driving conditions change drastically.

Furthermore, we propose a novel slip learning model outperforming similar learning models for SSMRs navigation in off-road terrain. Contrarily to our previous work [2], we rely on additive slip, which facilitates slip learning since slip is computed by subtracting the commanded body velocity to the observed body velocity, similarly as proposed by Seegmiller *et al.* [8]. For slip learning, we rely on Bayesian linear regression (BLR), which enable fast

---

<sup>2</sup><https://github.com/norlab-ulaval/DRIVE>

prediction and training, which is ideal for realtime UGV deployment [9]. We show that by leveraging dynamics-aware basis functions for BLR, we have significant slip prediction performance improvement over the baseline BLR learning approach, which learns vehicle acceleration. The operational limit for our model is reached on the ice rink experiments, where extreme UGV severely impacts UGV motion.

The biggest lesson learned is that DRIVE enables training dataset gathering for model convergence in 46 sec, for our slip-BLR model, which outperforms similar learning approaches. This protocol is interesting for field operations as it enables users to generate an accurate motion prediction model for any new UGV or environment configuration, effectively saving a lot of deployment resources and battery usage. As future work, we want to investigate dynamic modeling on the ice rink experiment to see if richer modeling approaches can improve prediction accuracy under dynamically complex driving conditions. This experimental dataset is also ideal to investigate the limit of adaptive modeling approaches by simulating a robot instantly changing terrain type.

**D. Baril, S.-P. Deschênes, O. Gamache, M. Vaidis, D. LaRocque, J. Laconte, V. Kubelka, P. Giguère, and F. Pomerleau, “Kilometer-scale autonomous navigation in subarctic forests: challenges and lessons learned”, *Field Robotics*, vol. 2, no. 1, pp. 1628–1660, 2022**

The third article that concludes the list of articles submitted as first author was submitted and published in the *Field Robotics* journal. In this paper, we leverage the models evaluated in our previous work with our lidar-based localization and mapping system to create the Weather-Invariant Lidar-based Navigation (WILN) autonomous navigation system and conduct 18.8 km of autonomous driving. For this work, we were awarded the **Relève Etoile Louis-Berlinguet Award** from FRQNT. We leverage the data acquired to produce a field report documenting the impact of the boreal forest biome and winter weather on lidar-based autonomous navigation. The dataset gathered in the field is available online and open-source.<sup>3</sup> A seminar was conducted for this work.<sup>4</sup> The specific contributions for this article are as follows:

1. A comprehensive study of the impact of the boreal forest biome on lidar- and GNSS-based localization and autonomous navigation;
2. An overview of the impact of snow accumulation on the reliability of lidar-based localization over multiple days; and

---

<sup>3</sup>[https://github.com/norlab-ulaval/Norlab\\_wiki/wiki/Kilometer-scale-autonomous-navigation-in-subarctic-forests-challenges-and-lessons-learned](https://github.com/norlab-ulaval/Norlab_wiki/wiki/Kilometer-scale-autonomous-navigation-in-subarctic-forests-challenges-and-lessons-learned)

<sup>4</sup><https://www.youtube.com/watch?v=VWzKZvtnInA>

3. A description of the WILN system, designed to enable wintertime autonomous navigation in a boreal forest.

While we have validated lidar-based localization and mapping is suitable for autonomous navigation the test environment, we observed particular phenomenons that can lead to navigation failure, most of which are related to lidar localization. First, when navigating in a corridor-like forest trail, under dense vegetation, the low longitudinal geometric constraints lead to localization instability, which caused the UGV to crash with vegetation in some occasions. Secondly, the snow accumulation causes the environment to change significantly, which was critical in areas where man-made structures are present to support lidar-based localization. For those issues, we have documented the impact on our localization system and highlighted the challenges to be solved to enable true year-long autonomy in boreal forests. An analysis of the quality of GNSS signal under the dense vegetation of boreal forests was also conducted, showing that it is unsuitable for navigation in tight forest trails, but functional on larger forest paths.

Since it was not the main focus for this work, an operator drove periodically with a snowmobile over the paths navigated by the UGV to tap the snow and enable large-scale navigation. We still investigated the impact of the environment on our selected kinematic path following controller [10]. Under these conditions, we show that the path following error is strongly correlated with reference path curvature, meaning that the most likely cause for path following failure is tight turning in forest trails. Qualitatively, we also show that deep snow navigation is complex for SSMRs since it significantly reduces the vehicle's ability to turn.

For this work, the main take home message is that kinematic motion modeling and lidar-based localization are suitable for wintertime navigation in boreal forests, but that challenges remain to be solved for true year-long autonomy. First, localization robustness to areas with corridor-like environments and dynamic environments should be addressed, by adapting the reference map and adding localization constraints. Secondly, kinematic path following controllers are suitable for condensed or shallow snow, but fail in deep snow. Thirdly, energy consumption estimation and prediction is complex in cold weather, however it is key to maximize UGV usage and prevent breakdown in remote areas. While those are the main challenges observed, multiple more lessons learned are highlighted in this work.

## 2.2 Articles published and submitted as co-author

S.-P. Deschenes, D. Baril, V. Kubelka, P. Giguere, and F. Pomerleau, “Lidar Scan Registration Robust to Extreme Motions”, in *2021 18th Conference on Robots and Vision (CRV)*, IEEE, 2021, pp. 17–24: This article improves point cloud registration accuracy under aggressive motion by accounting for the error related to point cloud deskewing. Deskewing is lidar scan error originating from the assumption that the

sensor is static during the sweep. Under aggressive motion, characterized by high body velocities and acceleration, this assumption is broken, leading to a high scan error. For this work, I built the experimental rig and supported for the experimental work. I have also participated in generating the results and for redaction.

**T. Rouček, M. Pecka, P. Čížek, T. Petříček, J. Bayer, V. Šalanský, T. Azayev, D. Heřt, M. Petrlík, T. Báča, V. Spurný, V. Krátký, P. Petráček, D. Baril, M. Vaidis, V. Kubelka, F. Pomerleau, J. Faigl, K. Zimmermann, M. Saska, T. Svoboda, and T. Krajník, “System for multi-robotic exploration of underground environments CTU-CRAS-NORLAB in the DARPA subterranean challenge”, *Field Robotics*, vol. 2, no. 1, pp. 1779–1818, Mar. 2022:** This article describes the system that was built for the CTU-CRAS-Norlab team at the DARPA Subterranean Challenge Urban Circuit. This is the biggest robotics competition in the world and our team managed to class third overall and first among self-funded teams. The goal was to deploy a heterogeneous robot fleet in an unknown underground environment and to detect and localize artifacts within 5 cm of their true position. For this work, I co-built the UGV that was contributed by Norlab to the competition and participated in its integration to the complete fleet. I have also post-processed the navigation data after the competition and generated the 3D maps that were used as figures in the article.

**C. Courcelle, D. Baril, F. Pomerleau, and J. Laconte, “On the Importance of Quantifying Visibility for Autonomous Vehicles Under Extreme Precipitation”, in *Towards Human-Vehicle Harmonization*, De Gruyter, 2023, pp. 239–250:** This article is a study of the impact of extreme precipitation on lidar-based localization, more precisely point cloud registration with the ICP algorithm. A novel lidar scan obstruction metric is proposed, enabling proper comparison and analysis of the impact of harsh weather. We rely on data collected with our own robot platforms and the Canadian Adverse Driving Conditions (CADC) Dataset to study the relation between this metric and lidar-based localization error, with GNSS as ground truth. The results suggest that extreme precipitation has a significant impact on the UGV’s ability to localize, however not enough data is available under such conditions. Gathering more data under extreme precipitation remains an open problem. In this work, I participated as an advisor on data analysis and experiments. I have also helped with writing the paper.

**Deschenes2023:** This article extends on the previous work on point cloud registration under aggressive motion [11]. This time, the use case is the sensor rig rolling down a steep hill, leading to gyroscope measurement saturation. Since such measurements are key to provide a prior for the ICP algorithm to converge, gyroscope saturation leads to localization failure. We leverage Gyro-free (GF)-Inertial Navigation System (INS) theory [14] to estimate body angular velocity under gyroscope saturation and show that lidar localization

and mapping then becomes robust to aggressive motions. For this work, I was responsible to design the sensor rig and co-responsible for the experimental work. I was responsible to finalize most of the figures and participated in writing the text.

### 3 Work left before submitting the thesis

The three articles written as first author presented in [Section 2](#) will consist the majority of the thesis by articles. Additionally, to maximize the value of the data gathered, especially through the work related to DRIVE, a few additional experiments will be conducted. First, an analysis of the performance improvement that can be reached through dynamic modelling for navigation on ice will be conducted. Second, an investigation of the limit of current adaptive models will be conducted by artificially mixing datasets on different terrains. Thirdly, we will study of the impact of DRIVE UGV characterization on path following performance under a realistic deployment setting. These results will be appended to the published and submitted articles in the thesis to complete it. A schedule for the remaining work and Gantt chart are presented in [Section 3.4](#)

#### 3.1 Dynamic modeling on ice

We learned through our DRIVE work that slip learning model reach their functional limit under extreme conditions, such as navigation on an ice rink, as shown in [Figure 1](#). Indeed, the low wheel-to-ground friction leads to high motion inertia, which is not modeled by slip learning. While a lot of attention is given to generate and validate dynamic motion model for high-speed driving on concrete [15] or gravel [16], not much work has focused on investigating their functionality on ice. Since we have already completed the work to collect a 20 min dataset of uniform vehicle input sampling, the time required to investigate the predictive performance of dynamic models on this dataset is much smaller.

This work could lead to contributions related to dynamic formulation for SSMRs navigating on ice, or learning dynamic model parameters through BLR to facilitate deployment of dynamic models. The evaluation pipeline for model training and prediction error over an entire dataset is already set up and ready to compare dynamic models to slip learning.<sup>5</sup> Improvements could also be made to the DRIVE protocol to sample additional dynamic variables, such as body acceleration.

---

<sup>5</sup>[https://github.com/norlab-ulaval/norlab\\_WMRD](https://github.com/norlab-ulaval/norlab_WMRD)



**Figure 1:** A photo is the Warthog, our 470kg research SSMR. Via the DRIVE protocol, we have collected a 20 min dataset of the vehicle executing a large spectrum of commands. This dataset shows the limit of our current slip learning model, motivating an investigation of dynamic model performance.

### 3.2 Adaptive motion modeling

Next, I plan to study the performance of adaptive modeling under extreme traction variation. To illustrate this challenge, [Figure 2](#) shows two use cases, namely hard and deep snow navigation, for which traction varies significantly. In the case of deep snow navigation, the SSMR almost reached immobilization, which means that switching between both conditions produces the almost the largest change in traction conditions that can be observed for a specific UGV. This is an ideal case to investigate the limits of current adaptive modeling approach, which are easy to integrate with our slip learning model.



**Figure 2:** Example of distinct terrain navigating encountered during wintertime off-road navigation with the Warthog platform. (a): Hard snow navigation, with limited slip, representing nominal navigation. (b): Deep snow navigation, with high slip, representing an edge case for SSMR motion modeling.

As proposed by McKinnon *et al.* [9], weighted BLR learning enables re-training of the model based on new traction conditions and a prior motion model. In their work, they show that weighted BLR performs well to adapt to slight changes in traction condition, both artificially generated and through slope variation. However, no study investigates the performance of adaptive modeling with respect to the degree of traction variability and what is the operational limit. By leveraging the DRIVE protocol to gather two distinct datasets, namely on hard and deep snow, we could simulate such changes in traction and analyse the performance of weighted BLR learning. In the case of failure, it will be an opportunity to develop improvements to this adaptive modeling approach, increasing its robustness to significant variation in traction.

### 3.3 DRIVE impact on path following

Lastly, we have developed a predictive control library in the context of industrial demonstrations for this project.<sup>6</sup> Such controllers are based on the Model Predictive Control (MPC) algorithm, enabling high speed path following with low tracking error. In our case, we have implemented a simplified version of the slip-aware MPC controlled proposed by Hewing *et al.* [17]. Since the motion model acts as a interchangeable module for such controllers, the prediction accuracy improvements reached through our work on the DRIVE protocol will most likely improve MPC path following performance. A last interesting result would be to quantify the path following error improvement reached through training the slip learning model with a DRIVE-gathered training dataset instead of manual driving. Typically, human driving data is limited in driving velocity since it is the first time for which the vehicle navigated the target trajectory. Our hypothesis is that by training the model through DRIVE, path following performance at high speed is improved as soon as the first time the UGV executes the desired trajectory.

### 3.4 Schedule for upcoming work

Le calendrier détaillé de la planification des objectifs pour la rédaction du prochain article de journal est située dans la ?? en annexe. Ce calendrier s'étend de novembre 2022 à mars 2023. Les différentes étapes de mes recherches y sont présentées: expériences à faire sur le terrain, génération des vérités terrains, prise en compte de l'incertitude pour ces générations, évaluation de trajectoires, et enfin rédaction de l'article de journal.


Mon article de journal rédigé, je me concentrerai sur la rédaction de ma thèse. La Figure 3 montre le calendrier de la planification des objectifs pour le dépôt final de la thèse. Je souhaite réaliser une thèse par articles. Elle en comportera trois que j'ai publiés ou soumis: CRV 2021, ICRA 2023 et Field Robotics 2023. S'il est accepté, l'article d'ICRA 2023 sera présenté à la conférence à la fin du mois de mai 2023. Pour ce qui est de l'article du journal

---

<sup>6</sup>[https://github.com/norlab-ulaval/norlab\\_controllers](https://github.com/norlab-ulaval/norlab_controllers)

Field Robotics, il sera probablement publié d'ici un an ou deux, soit en 2024 ou 2025, après les différentes rondes de révisions.

Je prévois deux mois de rédaction de thèse juste après la soumission de mon article de journal, soit en avril et mai 2023. Je ferai mon dépôt initial au mois de mai 2023. Après une période de 6 à 8 semaines, je pourrai effectuer ma défense durant le mois de juillet 2023. Si ma thèse est acceptée, il m'appartiendra de faire les corrections données par mon comité pour un dépôt final escompté au mois d'août 2023.



**Figure 3:** Diagramme de Gantt contenant les objectifs devant être accomplis d'ici au dépôt final de la thèse.

## 4 Conclusion

À travers cette proposition de thèse, un récapitulatif de mes contributions vis-à-vis de ma problématique de recherche a été présenté, et la planification de la fin de mon doctorat a été détaillée. J'ai démontré que j'avais suffisamment avancé dans mes recherches et que je serai sur le point d'effectuer mon dépôt initial d'ici à quelques mois. La problématique de ma recherche porte sur la génération précise de trajectoires de références pour les véhicules en mouvement ainsi que de leur évaluation. Deux sous-parties de ma problématique de recherche ont déjà été abordés et résolus à travers la publication de deux articles de conférence, dont un soumis en septembre dernier. Dans un premier temps, un système basé sur trois stations totales robotiques a été créé et testé sur le terrain dans le but de pouvoir générer des vérités terrains ayant une précision sub-centimétrique. Par la suite, une amélioration de

la calibration extrinsèque entre les différents référentiels de ces stations totales robotiques a été proposée et validée sur un jeu de données de plus de 30 km de trajectoires de plateformes robotiques. Mes travaux actuels portent sur la publication d'un dernier article de journal qui finalisera mes recherches. Cet article abordera la problématique de l'évaluation des trajectoires de références accompagnée de celles générées par des algorithmes de cartographie 3D. Il abordera également la gestion de l'incertitude dans ces évaluations et mentionnera l'impact de cette incertitude sur les résultats.

Le calendrier des étapes restantes a été détaillé dans la ???. La rédaction de mon article de journal aura lieu du mois de novembre 2022 au mois de mars 2023. Ensuite sera effectuée la rédaction de ma thèse. Je prévois une rédaction de thèse par articles comme cités dans ce document, à savoir l'article de CRV 2021, l'article de ICRA 2023 et l'article de journal Field Robotics 2023 que je rédigerai. Le dépôt initial de ma thèse aura lieu au mois de mai 2023 et ma défense devrait se tenir durant le mois de juillet 2023. Je prévois ainsi de terminer mon dépôt final durant le mois d'août 2023 après avoir effectué les corrections demandées suite à ma défense.

## References

- [1] J. Van Brummelen, M. O'Brien, D. Gruyer, and H. Najjaran, "Autonomous vehicle perception: The technology of today and tomorrow", *Transportation Research Part C: Emerging Technologies*, vol. 89, no. July 2017, pp. 384–406, 2018.
- [2] D. Baril, V. Grondin, S.-P. Deschenes, *et al.*, "Evaluation of Skid-Steering Kinematic Models for Subarctic Environments", in *2020 17th Conference on Computer and Robot Vision (CRV)*, IEEE, 2020, pp. 198–205.
- [3] A. Mandow, J. L. Martinez, J. Morales, J. L. Blanco, A. Garcia-Cerezo, and J. Gonzalez, "Experimental kinematics for wheeled skid-steer mobile robots", in *2007 IEEE/RSJ International Conference on Intelligent Robots and Systems*, IEEE, 2007, pp. 1222–1227.
- [4] G. Anousaki and K. Kyriakopoulos, "A dead-reckoning scheme for skid-steered vehicles in outdoor environments", in *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA '04. 2004*, IEEE, 2004, 580–585 Vol.1.
- [5] T. Wang, Y. Wu, J. Liang, C. Han, J. Chen, and Q. Zhao, "Analysis and Experimental Kinematics of a Skid-Steering Wheeled Robot Based on a Laser Scanner Sensor", *Sensors*, vol. 15, no. 5, pp. 9681–9702, 2015.
- [6] D. Baril, S.-P. Deschênes, L. Coupal, *et al.*, "Drive: Data-driven robot input vector exploration", *ArXiv preprint, submitted to ICRA 2024*,
- [7] D. Baril, S.-P. Deschênes, O. Gamache, *et al.*, "Kilometer-scale autonomous navigation in subarctic forests: challenges and lessons learned", *Field Robotics*, vol. 2, no. 1, pp. 1628–1660, 2022.
- [8] N. Seegmiller and A. Kelly, "Enhanced 3D Kinematic Modeling of Wheeled Mobile Robots", in *Robotics: Science and Systems X (RSS)*, Robotics: Science and Systems Foundation, 2014.
- [9] C. D. McKinnon and A. P. Schoellig, "Learn Fast, Forget Slow: Safe Predictive Learning Control for Systems With Unknown and Changing Dynamics Performing Repetitive Tasks", *IEEE Robotics and Automation Letters (RA-L)*, vol. 4, no. 2, pp. 2180–2187, 2019.
- [10] G. Huskić, S. Buck, and A. Zell, "A Simple and Efficient Path Following Algorithm for Wheeled Mobile Robots", in *Advances in Intelligent Systems and Computing*, vol. 531, 2017, pp. 375–387.
- [11] S.-P. Deschenes, D. Baril, V. Kubelka, P. Giguere, and F. Pomerleau, "Lidar Scan Registration Robust to Extreme Motions", in *2021 18th Conference on Robots and Vision (CRV)*, IEEE, 2021, pp. 17–24.

- [12] T. Rouček, M. Pecka, P. Čížek, *et al.*, “System for multi-robotic exploration of underground environments CTU-CRAS-NORLAB in the DARPA subterranean challenge”, *Field Robotics*, vol. 2, no. 1, pp. 1779–1818, Mar. 2022.
- [13] C. Courcelle, D. Baril, F. Pomerleau, and J. Laconte, “On the Importance of Quantifying Visibility for Autonomous Vehicles Under Extreme Precipitation”, in *Towards Human-Vehicle Harmonization*, De Gruyter, 2023, pp. 239–250.
- [14] M. Pachter, T. C. Welker, and R. E. Huffman, “Gyro-free INS Theory”, *NAVIGATION*, vol. 60, no. 2, pp. 85–96, 2013.
- [15] F. Djeumou, J. Y. Goh, U. Topcu, and A. Balachandran, “Autonomous Drifting with 3 Minutes of Data via Learned Tire Models”, in *IEEE International Conference on Robotics and Automation (ICRA)*, 2023, pp. 968–974.
- [16] G. Williams, P. Drews, B. Goldfain, J. M. Rehg, and E. A. Theodorou, “Information-Theoretic Model Predictive Control: Theory and Applications to Autonomous Driving”, *IEEE Transactions on Robotics (T-RO)*, vol. 34, no. 6, pp. 1603–1622, 2018.
- [17] L. Hewing, J. Kabzan, and M. N. Zeilinger, “Cautious Model Predictive Control Using Gaussian Process Regression”, *IEEE Transactions on Control Systems Technology (T-CST)*, vol. 28, no. 6, pp. 2736–2743, 2020.