

DRIVE: Data-driven Robot Input Vector Exploration

Dominic Baril¹, Simon-Pierre Deschênes¹, Luc Coupal¹, Cyril Goffin²,

Julien Lépine¹, Philippe Giguère¹, François Pomerleau¹

¹ Northern Robotics Laboratory, Université Laval ² École Polytechnique Fédérale de Lausanne



Context & Motivations

- A motion model is a key component of autonomous navigation systems, but Uncrewed ground vehicles (UGVs) behavior varies significantly depending on terrain and vehicle properties.
- Sensory measurements and information on ground properties are limited.
- Empirical training dataset gathering is energy and time consuming [1], two critical resources for remote deployments.
- Facilitating and automating the task of gathering a training dataset if of high importance for field operations.

Data-driven Robot Input Vector Exploration (DRIVE)




Figure: Vehicle and terrain characterization done through DRIVE. The manufacturer-defined Naive input-space region is drawn in gray. The vehicle's true input-space, characterized through internal measurements, is shown in orange. Typical human driving is shown in red. The resulting body velocities are represented in green for gravel and blue for snow.

- Automated protocol for vehicle input space characterization and training dataset gathering.
- Random uniform input sampling minimized input bias and stimulates dynamic, transitory behavior.
- 6 s intervals to stimulate transitory and steady behavior.
- 46 s required to train a motion model.

Table: Median prediction improvement for all robots and terrains.

Prediction improvement	Husky		HD2		Warthog	
	Tile	Snow	Tile	Snow	Gravel	Ice
Translation (%)	35	10	33	31	50	11
Rotation (%)	18	61	27	51	61	7




Figure: Data-gathering protocol performance for the HD2 on snow experiment. In yellow, we have the linear-focused method. In teal, we have the angular-focused method. In blue-violet is our DRIVE approach. The crosses and regions on the bottom subplot show the medians and interquartile ranges for translational and angular prediction errors.

Experimental setup

- Indoor tile, snow-covered terrain, gravel and surfaced ice.
- Three platforms: (1) the HD2 has a top speed of 1.2 m/s; (2) Husky has a top speed of 1 m/s; and (3) the the Warthog has top speed of 5 m/s.

Figure: Three different commercial platforms that were used for the experimental work: a Superdroid HD2 (1), a Clearpath Robotics Husky (2), and a Clearpath Robotics Warthog mounted on wheels (3). The platforms weigh 80 kg, 75 kg and 470 kg, respectively.



Slip-based Bayesian linear regression (BLR)

- Additive slip model based on dynamics-aware basis functions [2].
- Leveraging Bayesian linear regression (BLR) for learning motion parameters with minimal vehicle and terrain knowledge [3].
- Each dimension of slip (longitudinal, lateral, angular) learned separately.
- First-order plus dead time transient response model for powertrain dynamics.
- Implimented and tested for skid-steering mobile robots (SSMRs).




Figure: Top view drawing of a SSMR. In orange is the commanded body velocity Rf and the resulting body velocity Rv is shown in green. The input-space T is shown in orange and the body velocity space B is shown in green. The difference between commanded and resulting body velocity is represented as the slip velocity Rg in purple.

- Slip-BLR outperforms the most similar model, which performs BLR on UGV actuator dynamics.
- Biggest improvement for Warthog on gravel, which is the highest top speed experiment.
- Model limit reached on surfaced ice, due to extreme slip and long transitory response.




Figure: Translational and rotational prediction errors for all models studied in this work. In yellow is the manufactured-defined naive model, in orange is the powertrain-aware model, in red is the acceleration-based BLR model and in purple is our slip-based BLR model.

Acknowledgments and References

This research was supported by the Fonds de recherche du Québec – Nature et technologies (FRQNT) and by the Natural Sciences and Engineering Research Council of Canada (NSERC) through grant CRDPJ 527642-18 SNOW (Self-driving Navigation Optimized for Winter).

- [1] Grady Williams, Paul Drews, Brian Goldfain, James M. Rehg, and Evangelos A. Theodorou. Information-Theoretic Model Predictive Control: Theory and Applications to Autonomous Driving. *IEEE Transactions on Robotics (T-RO)*, 34(6):1603–1622, 12 2018.
- [2] Neal Seegmiller, Forrest Rogers-Marcovitz, Greg Miller, and Alonzo Kelly. Vehicle model identification by integrated prediction error minimization. *The International Journal of Robotics Research (IJRR)*, 32(8):912–931, 7 2013.
- [3] Christopher D. McKinnon and Angela P. Schoellig. Learn Fast, Forget Slow: Safe Predictive Learning Control for Systems With Unknown and Changing Dynamics Performing Repetitive Tasks. *IEEE Robotics and Automation Letters (RA-L)*, 4(2):2180–2187, 4 2019.