Historical source: SHIP-BUILDING

continued: SHIP-BUILDING

[Margin: Fractical Building]

ends in close contact with, and cooked or dowelled to, the sides of the diagonal timbers. In this state the ~~frame-on~~ **frame-work** in the hold presents various compartments, each representing the figure of a ~~method.~~ **rhomboid.** A ~~T reads timber~~ **truss-timber** is then introduced into each ~~rhombed,~~ **rhomboid,** with an inclination opposite to that of the diagonal timbers, thereby dividing it into two parts. The ~~trust-pieces~~ **truss-pieces** so ~~intended~~ **introduced** into one ~~rhombed,~~ **rhomboid,** are to the diagonal frames where the key-stone is to the arch; for no weight or pressure on the fabric can alter its position in a longitudinal direction till compression takes place at the ~~autumn,~~ **abutments,** and extension of the various ties. ~~"This~~ **This** arch-like property of the diagonal frame not only opposes an alteration of position in a longitudinal direction, but also ~~restate~~ **resists** external pressure on the bottom, either from grounding or any other cause, because ~~so~~ **no** impression can be made in its figure in these directions, without forcing the several parts of which it is composed into a shorter space. The beams are ~~discussed~~ **disposed** in the **new** system nearly as ~~we~~ usual, except that in ~~buildings,~~ **midships,** where a ship necessarily ~~re-quires~~ **requires** the greatest security, two additional beams have been introduced. -• The beams of the several decks are attached to the ~~shiny's~~ **ship's** side in the following manner. 1 Lc by And of pieces internal hoops, distinguished by the letter 2. These shelf-pieces are composed of several lengths of timber, ~~scarded~~ **scarfed** or joined together by coaks or circular ~~downs,~~ **dowels,** so as to form a ~~full~~ **kind** of internal hoop, extending from the hooks forward, to the ~~transons shall —(in~~ **transoms abaft (in** the plate the ~~transons~~ **transoms** are not shown), we have chosen the perfected application of Sir Robert Seapings' system, after the adoption of the circular stem into the service, —to the under side of which, as well as the ~~whole part~~ **under parts** of the beams, they are securely ~~cookies,~~ **coaked,** and being then firmly bolted to the side, instead of becoming a mere local ~~fixer~~ **fixture** of the beam to the ~~shiny's~~ **ship's** exterior frame, as ~~likely~~ **knees** were, they are ~~seen~~ **one** continued and general security. The shelf-piece is also a tie to the top-side in a ~~four~~ **fore** and ~~all~~ **aft** direction, co-operating with the trusted frame, as already explained. 2 Idly. By chocks, represented in Plate CCCCLV. (m.,) which are placed under all the shelf-pieces in walls of the beams, except the drop in such a manner as to receive the up and down arm of the iron knes. The lower ends of those under the span-deck-pipe step on the ends of the otp-bears; and those of the several decks above, step on the projecting part of the splashing beams. The chosen between the they and gun docks, and of their being driven into their respective places very tightly, thereby eating the pillars. Another advantage attending them is the great tendency to stiffen the shiny side, and to prevent the beans-ends from playing on the fasteners when the sihry is rolling or retaining under press of call. ~~"The~~ **The** current non-plate knees for securing the otlop-beans, and the iron frontal knees of the other decks, are described in (a) and (a). Place CCCCLV. ~~"The~~ **The** tendency of the ship to stretch or draw ~~sammber~~ **asunder** in her upper works being by ~~our~~ **no** means ~~advised~~ **obviated** by the short ~~plank-out~~ **planks on** the inside between the ports, a ~~true~~ **truss** piece of plank is substituted in lieu of ~~them,which~~ **them, which** being well ~~secured,~~ **secured** at the ~~altumants,~~ **abutments,** very materially ~~and~~ **aids** the ~~trussal~~ **trussed** frame, and gives great ~~artifacts,~~ **stiffness,** thereby opposing the ~~in-clination~~ **inclination** to arch or ~~log, add."~~ **hog aloft.** These various alterations from the old system of building had the effect of very greatly increasing the strength of the ~~ship~~ **ships** of the ~~boys'l away.~~ **royal navy.** Among ~~us~~ **so** many changes, it is not ~~impossible~~ **improbable** that ~~continuous~~ **erroneous** conclusions may have been drawn as to the relative importance of each. We ~~include~~ **incline** much **to** the opinion that this has been the case **to** a very ~~good-de-gree,~~ **great degree,** and that ~~is~~ **a** part hitherto considered as quite ~~authorinate,~~ **subordinate,** and now wholly discontinued as useless, was one ~~priincipal~~ **principal** cause of the increase of strength which enabled ships to preserve their ~~sheet.~~ **sheers.** This we shall presently endeavour to prove. The lower ranges of riders and trusses, which were brought on the upper surfaces of the floors and the ~~fututets,~~ **futtocks,** could have had little effect in preventing nothing beyond that there, which sense from the additional resistance they offered to compression, and the additional rigidity they pose to the structure in the event of ~~groundning,~~ **grounding,** or of being ~~adore.~~ **ashore.** They certainly served as a firm base upon which to erect a series of riders with ~~diagonally,~~ **diagonally** trusses, which were more advantageous by placed to afford efficient support to the ~~ex-tremities~~ **extremities** of the body. Yet the upper riders only seemed to the countries of the ~~you-decks,~~ **gun-decks,** and therefore not very far above the line of non-action. Presuming, however, that this second series of riders was of considerable utility, as a base for the might probably have been obtained within out so much incumbance to the hold, and consequently without the objective being proved against it, which was to to the diagonal riders, of diminishing the ~~storage.~~ **stowage.** According to the estimate made the IRS of Robert Seapings, the actual inclined contents of the diagonal frame were less than those of the ceiling which is superseded. The ~~trusing~~ **trussing** between the ports has been discontinued in France. ~~He~~ **Her** Majesty's ~~ship.~~ **ships.** We cannot but regret the change, as ~~hetwe would~~ **we consider** this was the most advantageous innovation ~~con-ship-needed~~ **connected** with the diagonal system, and one in which the ~~ke-di~~ **benefit** was ~~uncomfortable~~ **unaccompanied** with compensating inconveniences. In investigating the reasons on which we found this opinion, we shall ~~every~~ **merely**

describe the manner in which we consider this trussing must have acted, to prevent any alteration of form in the upper parts of the ship. We ~~concern when,~~ **commence, then,** with the ~~gun-dedic~~ **gun-deck** of a three-decker. The gun-deck, from its proximity to the line of inaction, from the support of the trussed frame, which extended to the shell and from the ~~walks,~~ **wales,** may be assumed, at least in a new ship, as a most firm base on which to raise a series of supports. At some point on the upper edge of the ~~greck skpirishing a, above,~~ **gun-deck spirketing, a shore,** that is, the truss, firmly closed at its heel, extended upwards and ~~at,~~ **aft,** in the after-body of the ship, to the lower edge of the ~~middle-dock~~ **middle-deck** clamp, where it was ~~secured (denoted),~~ **secured;** immediately above the head of this shore a second was fixed on the upper edge of the ~~middle, deck spiriting,~~ **middle-deck spirketing,** and extended upwards to the lower edge of the main-deck clamp, where it was secured, and ~~immediate ly~~ **immediately** over the head of this shore a third was secured on the edge of the main-deck ~~spiritting,~~ **spirketing,** and extended upwards to the lower edge of the quarter-deck clamp, where it was finally ~~secured to~~ **secured; so** that ~~is~~ **a** point in the ~~power~~ **range** of ~~scientists~~ **securities** to the quarter-deck was continuously and firmly ~~shoel~~ **shored** up from a point in the most rigid and ~~unattereble~~ **unalterable** part of the ship; and, in the same manner, a ~~sister~~ **series** of points along the range of ~~ex-certies~~ **securities** to the ~~counter-deck become shoutp~~ **quarter-deck became shored up** from the same foundation. This is in the after-body. In the ~~first-body~~ **fore-body** a corresponding system of ~~shorting run~~ **shoring ran** in an opposite ~~direction, fun~~ **direction** forward, and in a similar manner supported the range of securities of the ~~forecasts,~~ **forecastle,** while each intervening deck ~~periods,~~ **partook of** the same ~~situation.~~ **advantage.** Radizing as these stores did in opposite direction from the most rigid part of the ship as their lines, they playfished a setter of points of support to the principal longundained ties, they formed with them a system of timeless and the triangular is a figure which admits of no an element of form for at longing as his sides remain the same; the angles are invariable. It might almost be called to impomphether, for the range of quarters-deck and forecast secortiles, by which we mean the clamp, shelf, and water-way, to drop at the extremities excepting to so far as the compressibility of the materials would admit. To adapt another, and perhaps a stronger, view of this system of trussing, we may consider the whole ~~top-side~~ **top-sides** of a ship, with the securities of the gun-deck as a ~~base:~~ **base,** to

Source record

- Page ID: `britannica:309f765b1ecc83e0a7f7762e44b4a927a7555443:train:13`
- Scan: `page-0013-50049db49e8b.jpg`, 600 x 826 px
- Image SHA-256: `50049db49e8b83dc59735eae8cc35e6df733062d4bcb07c5cb4663d51cade012`
- Extraction: `nvidia/nemotron-3.5-parse`, raw reply `artifacts/extract/raw/0013.json`
- Text is Parse OCR output, normalized (long s as s, line-end hyphens joined). It is not corrected by hand.
- ~~Struck-through~~ words are Parse's reading; **bold** words are Super VL's correction, checked against the scan image. Both are model output.