File I/O



Objectives

- See how to read and write multiple file types
- Use deterministic cleanup for files correctly
- Work with in-memory streaming APIs
- Work with paths and directories cross-platform

File I/O in Python

- There are five common types of file operations
 - Text
 - Read / write text of any format
 - · String-based IO
 - Binary
 - · Read / write binary of any format
 - · Stream bytes and bytearray in and out
 - XML
 - · Load XML documents
 - Parse / query documents using XPath
 - JSON
 - Convert JSON to / from dictionaries
 - Convert JSON to / from custom classes
 - Pickling
 - · Serialize object graphs to proprietary binary formats

Text I/O [modes]

- Opening and creating text files
 - Uses open(filename, mode) built-in

r Open text file for reading. Stream is positioned at the beginning of the file. r+ Open for reading and writing. The stream is positioned at the beginning of the file. w Truncate file to zero length or create text file for writing. The stream is positioned at the beginning of the file. w+ Open for reading and writing. The file is created if it does not exist, otherwise it is truncated. The stream is positioned at the beginning of the file. a Open for writing. The file is created if it does not exist. The stream is positioned at the end of the file. a+ Open for reading and writing. The file is created if it does not exist. The stream is positioned at the end of the file.	Mode	Meaning
The stream is positioned at the beginning of the file. W Truncate file to zero length or create text file for writing. The stream is positioned at the beginning of the file. W+ Open for reading and writing. The file is created if it does not exist, otherwise it is truncated. The stream is positioned at the beginning of the file. a Open for writing. The file is created if it does not exist. The stream is positioned at the end of the file. a+ Open for reading and writing. The file is created if it does not exist.	r	
The stream is positioned at the beginning of the file. W+ Open for reading and writing . The file is created if it does not exist, otherwise it is truncated . The stream is positioned at the beginning of the file. Open for writing . The file is created if it does not exist. The stream is positioned at the end of the file. Open for reading and writing . The file is created if it does not exist.	r+	
The file is created if it does not exist, otherwise it is truncated . The stream is positioned at the beginning of the file. a Open for writing . The file is created if it does not exist. The stream is positioned at the end of the file. a+ Open for reading and writing . The file is created if it does not exist.	W	
The file is created if it does not exist. The stream is positioned at the end of the file. a+ Open for reading and writing . The file is created if it does not exist.	W+	The file is created if it does not exist, otherwise it is truncated . The
The file is created if it does not exist.	a	The file is created if it does not exist.
The stream is positioned at the end of the life.	a+	

Text I/O [reading examples] csvFileName = "SomeData.csv" Open file with built-in fin = open(csvFileName, 'r', encoding="utf-8")

lines = fin.readlines()

```
text files easy.
                                                      Loads all data at once
                        csvFileName = "SomeData.csv"
                        fin = open(csvFileName, 'r', encoding="utf-8")
Text file handles are
                        for line in fin: ←
iterable (line by line)-
                             print(line, end='')
```

Uses deferred iteration

open method.

Utility methods make

Text I/O [cleaning up]

```
Files should be
closed ASAP.

fin = open(csvFileName, 'r', encoding="utf-8")
lines = fin.readlines()
fin.close()
```

```
csvFileName = "SomeData.csv"

with open(csvFileName, 'r', encoding="utf-8") as fin:
    for line in fin:
        print(line, end='')
```

The with statement makes this trivial, even in the case of exceptions or early returns.

Create or open text file for appending with a+ mode with open("app.log", 'a+', encoding="utf-8") as fout: fout.write("The application is starting up...\n") fout.write("Everything looks good.\n")

There is no 'writeline' but you can make one.

Text I/O [in-memory stream - reading]

The **io** package has helpful utility classes import io txt = """\ This is my text. There are many words like it But this one is my own\ fin = io.StringIO(txt) for 1 in fin: print(l, end='') We can treat this string as an incoming text-based file # prints stream # This is my text. # There are many words like it # But this one is my own

Text I/O [in-memory stream - writing]

The io package has helpful utility classes

fout = io.StringIO()

fout.write("This is line one!\n")

fout.write("This is line two!\n")

We can treat this in-memory stream as a text file handle, mode w+.

fout.write("This is line two!\n")


fout.seek(0)


print(fout.read())

prints

This is line one!

This is line two!





From Python 3.4 changes: Module __file__ attributes (and related values) should now always contain absolute paths by default, with the sole exception of __main__.__file__ when a script has been executed directly using a relative path. (Contributed by Brett Cannon in <u>issue 18416.)</u>

Binary I/O [reading files]

Incoming data can be stored in **bytearray** or directly processed.

```
bytes = bytearray()
with open(srcFile, 'rb') as fin:
    chunkSize = 1024
    buffer = fin.read(chunkSize)
    while buffer:
        bytes.extend(buffer)
        buffer = fin.read(chunkSize)
```

Read buffer sized chunks and store or process them.

Binary I/O [writing files]

```
Write byte by byte

Memory streams have a simpler method


memStream = getBinaryDataToSave()

# iteratively write (buffered)
with open(destFile, 'wb') as fout:
    for b in memStream:
    fout.write(b)

# write all in one shot
with open(destFile, 'wb') as fout:
    allBytes = memStream.getbuffer()
    fout.write(allBytes)
```

XML Files

- XML file support is built-in to Python
 - Import the xml.etree module
 - The **ElementTree** XML API provides simple DOM-based API



XML Files [querying data]

Given this RSS data, find all titles and related links.

```
<?xml version="1.0" encoding="UTF-8"?>
<rss version="2.0">
   <channel>
       <title>Michael Kennedy on Technology</title>
       <link>http://blog.michaelckennedy.net</link>
       <item>
            <title>Watch Building beautiful web...</title>
            k>http://blog.michaelckennedy.net/...</link>
       </item>
       <item>
            <title>MongoDB for .NET developers</title>
            <link>http://blog.michaelckennedy.net/...</link>
       </item>
       <item>...</item>
     </channel>
</rss>
```

XML Files [querying data]

```
Search for elements using dom.findall()

Extract the data from each item
```

```
from xml.etree import ElementTree
dom = ElementTree.parse("blog.rss.xml")

items = dom.findall('channel/item')
print("Found {0} blog entries.".format(len(items)))

entries = []
for item in items:
   title = item.find('title').text
   link = item.find('link').text
   entries.append( (title, link) )
```

```
Found 50 blog entries.
entries[:3] =>
[
    ('title1', 'link1'),
    ('title2', 'link2'),
    ('title3', 'link3),
]
```

JSON data

- JSON support comes built-in to Python
 - import the **json** module
 - serialize dictionaries
 - serialize custom objects
 - · that have been built to support JSON
 - that do not intentionally support JSON

JSON data [parsing JSON]

- Python dictionaries' and JSON string representations are extremely similar.
 - Converting between them should be easy


Python dictionary

{ 'hobbies': ['biking', 'motocross', 'hiking'], 'name': 'Michael', 'email': '...' }

JSON string


```
{
    "hobbies": [
        "biking",
        "motocross",
        "hiking"],
    "email": "...",
    "name": "Michael"
}
```

JSON data [JSON to dictionaries]



Note: json.load converts a file to a dictionary (pass a file stream as the parameter).

JSON data [dictionaries to JSON]



Note: json.dump converts a dictionary to a file.

JSON data [objects to JSON]

Classes cannot be directly converted to JSON

```
class Person(object):
    def __init__(self, name, hobbies, email):
        self.name = name
        self.email = email
        self.hobbies = hobbies
Not supported
```

```
import json

jeff = Person('Jeff', [], 'j@develop.com')
jsonTxt = json.dumps(jeff)

# TypeError:
<Person object at 0x00000000250CEF0> is not JSON serializable
```

JSON data [objects to JSON]

- Classes cannot be directly converted to JSON
 - But their dictionaries can be
 - Converting back is harder

```
class Person(object):
    def __init__(self, name,\hobbies, email):
        self.name = name
        self.email = email
        self.hobbies = hobbies
import json
jeff = Person('Jeff', [], 'j@develop.com')
jsonTxt = json.dumps(jeff.__dict__)
print(jsonTxt)
# prints:
# {"hobbies": [], "email": "j@develop.com", "name": "Jeff"}
```

JSON data [objects to JSON]

Adding JSON support to our class

```
import json

class Person(object):
    def toJSON(self):
       return json.dumps(self.__dict__)
```

```
jeff = Person('Jeff', [], 'j@develop.com')
jsonTxt = jeff.toJSON()
print(jsonTxt)

# prints:
# {"hobbies": [], "email": "j@develop.com", "name": "Jeff"}
```

JSON data [JSON to objects]

Adding JSON parsing support to our class

```
import json

class Person(object):
    def toJSON(self): ...

    @staticmethod
    def fromJSON(jsonText):
        d = json.loads(jsonText)
        return Person(**d) # requires arg names to match
```

```
jsonTxt = '{"hobbies": [], "email": "j@develop.com", "name": "Jeff"}'
jeff = Person.fromJSON(jsonTxt)
type(jeff) # <class Person>
```

JSON data [for humans]

For nested data, indentation can be a big help

```
import json

d = dict(name="Jeff", age=24, hobbies=['skiing', 'hiking'])

jsonTxt = json.dumps(d, indent=4)
print( jsonTxt )


# prints:
{
    "age": 24,
    "hobbies": [
        "skiing",
        "hiking"
    ],
    "name": "Jeff"
}
```

Binary object serialization

- Python supports a proprietary binary serialization format
 - Called Pickle
 - Good for short-term storage


Binary object serialization [limitations]

- Picking is not good for
 - Code that may change (fields, module names, class names)



Binary object serialization [security]

- Unpickling can result in arbitrary code execution
 - Do not use pickle files for IPC with untrusted clients / services
 - Trusted pickle is a secure version [1]



Summary

- Python has built-in support for text, binary, JSON, XML, and serialization files
- File handles should generally be used within with blocks
- The io module gives a file API to in-memory objects
- The os module enables cross-platform file operations