

# Cheat Sheet for Vim Text Objects / Motions

[Companion YouTube Video](#) [Other Free Documents](#)

**Usage:** `[n]<action>[modifier]<text motion>` or `[n]<action>[text object]`

built-in actions	built-in modifiers	built-in text objects and motions
<b>c</b> (replace) <b>d</b> (delete) <b>v</b> (visual selection) <b>y</b> (yank)	<b>no modifier:</b> from cursor to the end of text object	<b>w</b> (word) <b>s</b> (sentence) <b>p</b> (paragraph) <b>t</b> (tag)
<b>g~</b> (toggle case) <b>gu</b> (lower case) <b>gU</b> (upper case)	<b>i:</b> pick the whole text object excluding the pairs	quotes: ' " `
<b>&lt;</b> (left indent) <b>&gt;</b> (right indent)	<b>a:</b> pick the whole text object including the pairs	pairs (see <code>:h matchpairs</code> ): <b>() [] {} &lt;&gt;</b> <b>b</b> (round bracket) <b>B</b> (curly bracket)
	<b>t T f F [ ]:</b> until	motions: <b>h l j k b e \$ 0 /</b>

## andymass/vim-matchup

- new text object (see `:echo b:match_words`): **%**

## tpope/vim-surround

- new actions: **cs** (change) **ds** (delete) **ys** (add)

## welle/targets.vim

- new text objects:
  - separators: **, . ; : + - = ~ \_ \* # / | \ & \$**
  - b** for bracket (round/square/curly brackets) **q** for quotes
- new modifiers:
  - I**: like **i** but excludes whitespaces at both ends
  - A**: like **a** but includes whitespaces at one end, preferably the trailing end
- seek: **n** for next and **l** for last