


Week 7: Search Trees



Dr. Sirasit Lochanachit



Overall





Outline




Binary Search Trees:


- Definition, properties and methods (search, add, delete)
- Algorithms and Operation examples




Types of Trees (Revisited)



General Tree




Binary Tree



Binary Heap


Types of Binary Trees



What is a Binary Search Tree?




- A **binary search tree (BST)** is a binary tree that stores an ordered sequence of elements or pairs of keys and values and has the following properties [1]:



- All keys/elements in the **left subtree** are **less than** their **root**.
- All keys/items in the **right subtree** are **greater than or equal to** their **root**.
- Each subtree itself is a binary search tree.




Valid/Invalid Binary Search Trees?



Binary Search Tree



- A **binary search tree (BST)** applies the inorder traversal algorithm to insert keys and navigate the tree.
 - Produces a sorted keys in linear time.





BST Node Implementation



```
class BST_Node:
```

```
    def __init__(self, key, val, left=None, right=None, parent=None):
```


```
        self._key = key
```

```
        self._value = val
```

```
        self._leftChild = left
```

```
        self._rightChild = right
```

```
        self._parent = parent
```



```
def ...
```



BST Implementation



```
class BinarySearchTree:
```

```
    def __init__(self):
```

```
        self._root = None
```

```
        self._size = 0
```

```
    def ...
```


```
    def ...
```



Search in Binary Search Tree




- A **binary search tree (BST)** can be used to find whether a given key is stored in a tree by starting at the root.
 - For each position p , the searched *key* are compared with the key stored at position p , which is denoted as p_key .



Search in Binary Search Tree



- A **binary search tree (BST)** can be used to find whether a given value/key is stored in a tree by starting at the root.




- If $value = p_key$, then the value is found and the search is stopped.
- If the search reach an empty tree, the value is not found and the search is also stopped.
- Running time of search operation is proportional to the **height of tree** (i.e. $\log_2 n$ or n) $== O(h)$.

Searching in BST



Three common cases of searching in BST:




Find the Smallest Node



Three common cases of searching in BST:

1. Smallest/Minimum key





Find the Smallest Node



Iterative Version using while loop

Algorithm findMin(root):

Assign currentNode = root

if root is empty, return None because a tree is empty

While left subtree is not empty:

Go to left subtree and update currentNode

return key of currentNode

Find the Smallest Node

Iterative Version - Run through example - Start from 25

findMin(25)

currentNode = Node 25

While left subtree is not empty:

Go to Subtree 20


Go to Subtree 10

Go to Subtree 5

Go to Subtree 1

Cannot go to left subtree further, exit loop

Return currentNode._key # **which is 1**





Find the Smallest Node



Recursive Version

Algorithm findMin_re(root):

if (left subtree is empty):

return root._key

return findMin_re(left subtree)

Find the Smallest Node

Recursive Version - Run through example - Start from 25

findMin_re(25)

left subtree is not empty, recur on left subtree

- **findMin_re(20)**

left subtree is not empty, recur on left subtree


- **findMin_re(10)**

- **findMin_re(5)**

- **findMin_re(1)**

left subtree is empty

Return root._key # which is 1




Find the Largest Node



Three common cases of searching in BST:

1. Smallest/Minimum key
2. Largest/Maximum key




Searching a Target in a BST



Three common cases of searching in BST:

1. Smallest key
2. Largest key
3. Target key - **12**




Searching a Target in a BST



Three common cases of searching in BST:

1. Smallest key
2. Largest key
3. Target key - **18**





Binary Search Tree Algorithm



Algorithm treeSearch(target):

```
if rootNode is not empty then                                     # Root node exists
    result = _treeSearch(rootNode, target)                       # Perform search on the tree
    return result._value                                          # Return the node's value (None if not found)
else:                                                            # Root node not exists
    return None
```



Binary Search Tree Algorithm



Algorithm `_treeSearch`(p, target): # p denotes the current node, starting from the root

if target == p._key **then**

 return p

 # Target is found

else if target < p._key and p._leftChild is not None **then**

 return `_treeSearch`(p._leftChild, target)

 # Recur on left subtree

else if target > p._key and p._rightChild is not None **then**


 return `_treeSearch`(p._rightChild, target)

 # Recur on right subtree

return None

 # Target is not found

BST Construction and Insertion





BST Construction and Insertion



30

22

55

45



BST Insertion Exercise 1



23

18

44

52

12

20

8



BST Construction and Insertion Algorithm



Algorithm `treeInsert(key, value):`

if `rootNode` is not empty **then**

`_treeInsert(key, value, rootNode)` # Root node exists

else:

create a new tree and put key & value as the root #Root node not exists

`self._size = self._size + 1`



BST Construction and Insertion Algorithm



Algorithm `_treeInsert`(key, value, currentNode):

if key < currentNode._key **then**

if # Recur on left subtree

else

else:

if # Recur on right subtree


else



BST Deletion



- The deletion of a key from a BST can be performed on any node.
- Once a target node is found, three cases to consider:





BST Deletion



- Deleting an element from a BST is a bit more challenging than inserting.
 - The deletion of a key can be performed on any node.
 - In contrast, insertion usually occurs at the bottom of a tree path.
- Need to consider whether a tree has only a single node.
 - Removing only the root of the tree if the keys are matched.
 - Otherwise, return None or raise errors
- Once a target node is found, three cases to consider:
 - The node either has zero, one or two children.



BST Deletion Algorithm

Algorithm deleteNode(key):

if self._size > 1 **then**

 node = _treeSearch(self._root, key)

if node is not empty **then**

 _deleteNode(node)

 self._size = self._size - 1

else: **return** None or error

else if self._size == 1 and self._root._key == key:

 self._root = None

 self._size = 0

else: **return** None or error

Tree has >1 nodes

Find the node

Node is found in the tree


Node is not found

Only single node

BST Deletion Case #1




#1: The node has **zero** child.



BST Deletion Case #1



#1: The node has **zero** child.





BST Deletion Algorithm (cont.)



Algorithm _deleteNode(currentNode):

```
if currentNode is a leaf node then           #1: The node has zero child
    if currentNode is the left child of the parent node then
        Set the parent node's left child to None
    else
        Set the parent node's right child to None
```



BST Deletion Case #2



If a node has only a **single** child, the child could be promoted and replace its parent.

- 6 Sub-cases to consider:
 - A node has a left child
 - A node itself is a left child.
 - A node itself is a right child.
 - A node itself is the root node, no parent.



BST Deletion Case #2




- If a node has only a **single** child, the child could be promoted and replace its parent.
- 6 Sub-cases to consider:
 - A node has a left child -> Update its left child to point to its parent
 - A node itself is a left child. -> Update parent's left child
 - A node itself is a right child. -> Update parent's right child
 - A node itself is the root node, no parent. -> replace with the left child
 - A node has a right child -> Update its right child to point to its parent
 - Same as left child case

BST Deletion Case #2



#2: The node has **one** child.




○ A node has a left child

■ A node itself is a left child.

BST Deletion Case #2



#2: The node has **one** child.



- A node has a left child
-> Update its left child to point to its parent


■ A node itself is a left child.

-> Update parent's left child

BST Deletion Case #2



#2: The node has **one** child.





BST Deletion Algorithm (cont.)

Algorithm _deleteNode(currentNode) (*cont.*):

```
elif currentNode.hasAnyChildren():           #2: The node has one child
    if currentNode has a left child then
        if currentNode is the left child of the parent node then
            Update the parent pointer of its left child to currentNode's parent
            Set the parent node's left child to currentNode's left child
        else if currentNode is the right child of the parent node then
            Update the parent pointer of its left child to currentNode's parent
            Set the parent node's right child to currentNode's left child
        else
            Replace the currentNode with the left child
    if currentNode has a right child then
```

...



BST Deletion Case #3



- If a node has **two** children, one of the child could not be simply promoted and replace its parent since the other child would be left out of the tree.



BST Deletion Case #3



- To preserve a binary tree property, need to search the tree for a **successor** node, which is the next largest key after the deleted node:
 - If the successor has one child, it can be removed using case #1 or #2.
 - Then the successor node replaces the deleted node.
- The successor node could be either:
 - The minimum key node in the right subtree. Or
 - The maximum key node in the left subtree.



BST Deletion Case #3




-
- In case of min key, this value is at the leftmost child of the tree.
- To find the successor, follow leftChild references in each node until reaching a node that does not have a left child.

BST Deletion Case #3




#3: The node has **two** child.



BST Deletion Case #3



#3: The node has **two** child.






BST Deletion Algorithm (cont.)



Algorithm `_deleteNode(currentNode)` (*cont.*):

```
elif currentNode.hasBothChildren():      #3: The node has two children
    successor = currentNode._rightChild
    while successor.hasLeftChild():        # find min key in a right subtree
        successor = current._leftChild()
    Update the parent and children (if any) nodes of the minimum key
    node
    Replace the currentNode with the minimum key node
```


BST Deletion Exercise#1




Binary Search Tree



- Running time of inserting node is also proportional to the **height of tree** (i.e. $\log_2 n$ or n) == $O(h)$.
- A **balanced search tree** has the same number of nodes in both left and right subtree.
 - Worst-case performance is $O(\log_2 n)$.
- Inserting keys in sorted order would construct an **imbalanced tree**.
 - Provides poor performance of $O(n)$



Balanced Binary Search Tree



- A **balanced binary search tree (BST)** maintains the balance through a rotation operation which consequently provides a better performance.
- Several types of binary tree that automatically ensure balance
 - AVL tree
 - Splay tree
 - Red black tree