



Chapter 4: Queues

Dr. Sirasit Lochanachit




Queues



Queue is a collection, which keeps objects in a sequence, that are inserted and removed according to the **first-in first-out** (FIFO) principle [1].

- Queue elements can be inserted at any time, but only the element that has been in the queue the longest can be removed at any time.

Queues



- Close “cousin” of the stack.
- Elements enter a queue at the back.
- Elements are removed from the front.


Queues

Real-life examples of queue:




Queues

Examples of queue:



Queue Methods



Formally, there are 2 main operations for queues:


1) enqueue(e)

Insert element e at the back of the queue.

2) dequeue()

Remove and return the first element of the queue;
return error if the queue is empty.


Queue Methods



Additional operations for queues:

- 1) **first()** = Return the first element of the queue without removing it.
- 2) **is_empty()** = Check whether a queue is empty
- 3) **len(Q)** = Return the number of elements in a queue Q

Queues



9

Stacks

How to Implement a Queue?

Array!!

10

Operation Example

Operation	Return Value	Queue [first, ..., last]		
Q.enqueue(9)	-	9		
Q.enqueue(5)	-	9	5	
Q.first()	9	9	5	
Q.enqueue(2)	-	9	5	2
Q.dequeue()	9	5	2	
Q.is_empty()	False	5	2	
len(Q)	2	5	2	

11

Asymptotic Performance

Operation	Running Time
Q.enqueue(e)	$O(1)$
Q.dequeue()	$O(n)$ or $O(1)$
Q.first()	$O(1)$
Q.is_empty()	$O(1)$
len(Q)	$O(1)$


12

Types of Queue

• Queue



• Circular Queue



13

Simple Queue




Suppose a Python list is created.

- Enqueue can be achieved by calling `append(e)`, adding item at the end of the list.
- Dequeue can be executed by using `pop(0)` to remove the first element. *O(?) - inefficient for large number of elements, why?*

14

Simple Queue



- `pop(0)` requires a loop to shift all the elements to the left after removing the first element - $O(n)$.

15

Revised Queue




A better approach is to assign two main pointers to store indices that refer to:

- the first element of the queue, which is called the **Front**,
- and the last element of the queue, which is known as the **Rear**.

16

Revised Queue


• Enqueue



17


Revised Queue

• Dequeue



18

Revised Queue




19

Types of Queue

• Queues



• Circular Queues



20

Drawback:

If enqueue and dequeue is repeatedly executed, then these two pointers will keep shifting rightward.


The size of the list would grow to m where m is the total number of enqueue operations rather than the current number of elements in the queue.

Circular Queue

21


Circular Queue

22



In addition to allowing the pointers to shift rightward, the elements of the queue are wrap around at the end of an array.

When new elements are enqueued at the end of the current queue, the indices are continued at index 0, 1, and so on.




Suppose a queue of length 10,
the front index is at 0, the rear index is at 2.

Circular Queue


23

Circular Queue


24



Empty Queue




Circular Queue




25

Circular Queue



26


Circular Queue



27

Circular Queue


Enqueue



28


Circular Queue

Enqueue



29

Circular Queue in Python



When **enqueue**, the rear index is given by

$$r = (r + 1) \% N$$
 where N is the array length.


* Note: % denotes **modulo** operation in python which provides the remainder after division.

30

Circular Queue in Python

When **enqueue**, the rear index is given by

$$r = (r + 1) \% N$$
 where N is the array length.




For example, given a list length of 5 [0-4], current rear index at 3.
 When an enqueue is called, the new rear index is $(3+1) \% 5 = 4$.

31

Circular Queue


Deque



32

Circular Queue


Dequeue



$O(1)$

33

Circular Queue in Python



When **dequeue**, the front index is given by


$$f = (f + 1) \% N$$
 where N is the array length.

34

Circular Queue in Python

When **dequeue**, the front index is given by

$$f = (f + 1) \% N$$
 where N is the array length.



For example, given a list length of 5 [0-4], current front index at 4.

When a dequeue is called, the new front index is $(4+1) \% 5 = 0$.

35

Extension of Queue ADT

Limitation of queue

- Insertion and deletion of items can only be done at the front and the rear respectively

Double-ended queue (deque) additionally allows:

- Add element at the front of the queue.
- Remove element at the back of the queue.

36

Double-ended Queue

Main Operations for double-ended queues:

1) **add_first(e)**

Insert element *e* at the front of the queue.

2) **add_last(e)** - Same as enqueue(e)

Insert element *e* at the back of the queue.

3) **delete_first()** - Same as dequeue()

Remove and return the first element from the queue;
return error if the queue is empty.

4) **delete_last()**

Remove and return the last element from the queue;
return error if the queue is empty.

37

Double-ended Queue

Additional operations for double-ended queues:

1) **first()** = Return the first element of the queue without removing it.

2) **last()** = Return the last element of the queue without removing it.

38

Individual Assignment

- Assignment#2: Stacks
- Due 09.00 am 25/08/2020.
- Submission
 - Email: sirasit@it.kmitl.ac.th
 - Paper: in classroom next week
- Can be either written by hand or typing.

39