

[Dashboard](#)[my courses](#)[AMCN SS 2022](#)[IEEE 802.11](#)[Quiz: IEEE 802.11 - MAC Management](#)

Started at	Sunday, April 24, 2022, 2:40 p.m
status	Completed
Finished at	Sunday, April 24, 2022, 2:52 p.m
Spent time	11 minutes 54 seconds
feedback	Congratulations, your performance was very good (80%-90%).

question **1**

Complete

Achievable
points: 1.00

Does power saving work in ad hoc mode as well?

Choose one or more answers:

- ☒ a. Yes, stations need to buffer frames for sleeping receivers
- ☒ b. Yes, but there might be collisions between beacons
- ☐ c. No, it is not supported

question **2**

Complete

Achievable
points: 1.00

How are collisions among beacons avoided in ad-hoc mode?

Choose one or more answers:

- ☐ a. Sending of beacon is allowed only for a single station
- ☒ b. Sending of beacon employs a random delay to avoid collisions
- ☐ c. Sending of beacons is explicitly coordinated among stations

question **3**

Complete

Achievable
points: 1.00

How does beaconing work in ad hoc mode?

Choose one or more answers:

- ☒ a. Beacons contain a timestamp and other management information used for power management and roaming
- ☐ b. Beacons may be sent only by a single station
- ☒ c. Local clock is only updated when received timestamp is more recent
- ☒ i.e. Beacons may be sent by any station
- ☐ e. Beacons only contain a timestamp

question **4**

Complete

Achievable
points: 1.00

What is correct for a DTIM?

Choose one or more answers:

- ☒ a. DTIM contains a list of multicast receivers
- ☒ b. DTIM contains a list of broadcast receivers



Frage 5

Vollständig

Erreichbare
Punkte: 1,00

What is correct for a TIM?

Wählen Sie eine oder mehrere Antworten:

- ☐ a. TIM contains a list of broadcast / multicast receivers
- ☒ b. TIM contains a list of unicast receivers
- ☒ c. TIM is used to notify the stations about frames buffered in the AP

Frage 6

Vollständig

Erreichbare
Punkte: 1,00

What's the idea behind energy saving in 802.11?

Wählen Sie eine oder mehrere Antworten:

- ☐ a. All stations sleep at the same time
- ☒ b. Station has two states: low-power and full-power
- ☐ c. Station has two states: sleep and awake
- ☐ d. Stations need to increase the transmission power at times, defined by Timing Synchronization Function (TSF)
- ☒ e. Stations need to buffer frames for sleeping receivers

Frage 7

Vollständig

Erreichbare
Punkte: 1,00

Which steps are required for a handover in 802.11?

Wählen Sie eine oder mehrere Antworten:

- ☒ a. Association to the new AP
- ☒ b. Scanning of channels

Frage 8

Vollständig

Erreichbare
Punkte: 1,00

Why is a handover in 802.11 slow, compared to GSM or UMTS?

Wählen Sie eine oder mehrere Antworten:

- ☒ a. During scanning for another AP, a station needs to wait in each channel for beacons
- ☒ b. Because it is not possible to monitor several channels with a singleband receiver at the same time
- ☒ c. The station does not start the scanning before the old association is lost

Vorhergehende Aktivität

◀ Quiz: IEEE 802.11 -
MAC

Direkt zu:



Nächste Aktivität

Quiz: IEEE 802.11 - Newer
Developments and Physical
Variants ▶

[imprint](#)

How to reach us:

 <https://www.tu-ilmenau.de>

 [+49 3677 69-1111](tel:+493677691111)

 1111@tu-ilmenau.de

