### (5a)

#### Bloom Imagos


Trans Scale Amage => Pixel typically takes

=> Binary amage => Pixel can take only 0 on 1.

> Application ( ) OCR, masking etc...


b(i,i) = { 1, if there is an object of (i,i) } o, otherwise

\* Neighboshood in Gids



NY Neighborhod

Nu (i, i)




N8 Meighbushood

Ng (1,1)

\* Connected Components

=> Two points A and B and Commetted if there exists a path from A to B that goo only mough same Component.



## \* Determining Connected components via a

edges according to N8 neighbors.

## \* Labeling Approach

- 1. Select an unlobeled node and origin a new !
- 2. For each unlabeled neighbors of a labeled mode, assign the same label.
- 3. Repeat Step 2 until all neighbors agre Idseled.
- 4. Rope at Step 1 until all modes are labeled.

Also Called: a "borushfire" approach.

\* Comacted Components (Algorithm)

Input: Dinary Amage b (1,i) E [0,1)

Output: O Number of Components K

@ Component amage K(i,i) @ (0:K)

The second of the contract of


and the control of th

the set but of the are the add in the interest of


the of the Her will be for the or a specific

```
"Composed Mumber K=0, Composed in ege K(i,i)=0
  2 stopact
       find (1,3) | {b(1,3) = 1, K(1,3) = 0};
        S:=\{(i,j)\};
       K: = K+1
        k(i,i) = K)
        nepeat
           find unliabled foreground meighbors
           N(S(b(i,i)) = 1, K(i,i) = 0);
           label all (i,i) @ N(s) with K: K(i,i)=K;
          S = SUN(s)
        Until no neighbor exists: N(s) = 0;
  12 Until no unlabeled forgooned paxel exists.
  13 grotum K, K(i,j);
 * Properties of the algorithm.
 => The Set of noighboss may become large
 => Provides the Connected Components
* Imporound Labeling by Exploiting the Good
             Structure of the Image
  Idoa
 -> Porocass the amage in one pass.
  * Gocess the amage Gom left to sight, top to bottom.
  = If none of its (lop on left) neighbor is 1,
         assign now lobel
If all neighboring (top on left) labels are identical
         , copy to label.
      List label differ, copy the one label and update
        me convidence table.
```


```
= Re- label with the Smallest of equivalent
     1 docts.
  => Extends trivelly for N8 neighborhoods.
   Algorithm: Commerted Component in binary amage.
   Input => bin any Amorge b(ii) E (0,1)
   Output => Component number K, (umponed image K(ii) E(o:K)
 Composent number K=0, equivalence table E=0;
 7 for i=1: I do all onows
      for j=1: I do all Colones
        if b(i,i) = 1 the~
           A = N(i,i) all labeled neighbors;
 5
           & 1A1=0 then
              K:= K+1
            K(i,i)=K_i
           if IAI > 1 them
             K(i,i):= min(K(A));
              for all the xin A with K(x) \= K(i,i) do
 11
                extend equivalence table:
 17
                  E:= EU(K(1,3), K(2))5,
 13
 14
              and
           e~d
 13
         e~d
19
  and
3
is Compute Connected Components of E wing Algo 1
   grapha (K(i,i), i EI, JE; with smallest number of the Component in equivalence graph.
21 510th- K, K(13);
```




background (white) pixel if it has a bakgnard pixal abits Ny neighbor.



$$O_{N}((n,c),(u,v)) = |u-n|+|v-c|$$
 $O_{N}((n,c),(u,v)) = \max(|u-n|,|v-c|)$ 





- => The DT can be Computed Smilen to the
- => Two passes through the image
  - 1st: top-down, left-sight
  - · 2nd: down-up, sight-lift
- => Always Stone the minimum distance.
- \* Nu Vs N8 Neighborhoud
- => The Nu neighborhood overestimates the Euclidean distance.
- => The N8 neighborhood underestimates the Euclidean distance
- => The Sum Du + Do Parovides a better approximation for twice the distacci.

Do= 1 (On+ D8) SAppor Pullidian

=> By win & Do = (On+ Do), we can emploit integer computations.

# Binay Image

#### \* Skeleton

-> A Skeleton can be seen as a Simplification of the amage.

- => Three Views of a Skeleton:
  - 1) A point is a part of the Skeleton if it has the same minimum distance to at least two different points on the bonder.
- The Sot of contain of Circle, which lie fully inside the boarder and touches the boarder and touches the boarder at lost twice.
- 3 The Sot of all points in which the bonder meets.

## Compating the Skeleton

- => Eliminate all pixels at the bonder that
  - i.e. do not brock a component and,
  - wim loss the M No neighbors).

> For Pixels of N.S.E.W border.

×

->

-

\* /

\* I

=

 $\Rightarrow$ 

⋆

\* Issues or Not protetiend Annaid = Complexity O(N2d) 2d= widt of found -> Problems with soull objects. \* Skeleton Via Distance Transform Idea -> Compute the distance transform => Search for local maxima in the DT -> Maxima Sound via local gold-patterns. \* Dinary Image Features => A footune describes certain properties of an image. > We look :- to two types of features: 1 Topological features. [ Dosanbe neighborhood nelations) & Germetric Peatures [ Doscite the shopa} \* Topological Feature => They are invariant under most transformation. Prample -> Number of components K. -> Number of holes L. -> Eulen characteristic is one topological features defined as E= K-L

\* Cramatric Factors \* M => Features that diskibe the geometry of the figure => Two Simple geometric fectures are: # Amag · Parimeter Algorithm: Compuling Aren and Penimeter Initilize U=0, F=0 fon 1=0,... I-2 do for j=0,..., J-2 do M:= b(1,3)+2b(1,3+1)+4b(1+1.3)+8b(1+1,3+1) U:= U+ LUT\_du(M); F := F+ LUT\_dF(M) \* ( \* Goom etric Feature: Farm Factor => Form factor K combines area and × Parimeter ising K= U >1 => Cincle have: K=1 => Aroa and perimeter anse invariant to traslation (not to solchions!) => Form factor invariant to scale changes

\* Center of Mass

=> The moments mio and me, can be word with mos to compute the contex of mass in iadi.

\* Contral Moments of a Binors Image

=> Given the Center of mals, we can compute the Central moments.

$$M_{KD} = \sum_{i=1}^{K} (i-\bar{I})^{K} (i-\bar{I})^{D} b(i,i)$$

\* 2nd Control Momont

=> The -masmalized by the and -second Control moment lead to the matrix

Control moment lette
$$M = \frac{1}{m_{00}} \left[ \frac{\mathcal{U}_{10}}{\mathcal{U}_{11}} \frac{\mathcal{U}_{11}}{\mathcal{U}_{01}} \right] = \left[ \frac{6\chi^2}{6\chi^2} \frac{6\chi^2}{6\chi^2} \right]$$

→ Mis the Covariace matrix of the Probability distribution over the image.

