

Aim:

Smith is enhancing the record management system to use quadratic probing for handling collisions while hashing with a fixed-size hash table. The records are identified by four-digit keys, and Smith wants to efficiently insert these records into the hash table. Your task is to help Smith to write a C program which creates a hash table, inserts records using quadratic probing, and displays the contents.

Input Format:

- First line of input contains two space separated integers N , m representing number of keys and size of the hash table
- Second line of input contains N space separated four-digit integers representing the values.

Output Format:

- If the hash table is empty after all operations, print:

Hash Table is empty

- Otherwise, for each index i of the hash table (from 0 to $m-1$), print:

T[i] -> <value>

where value is the value stored at index i .

- If the hash table becomes full and a key cannot be inserted, print:

Hash table is full. Cannot insert records from key {X}

where X is the 1-based position of the key that couldn't be inserted.

Note:

- Refer to the sample test cases for better understanding of input and output formats.

Source Code:

HashTable1.c

```
// Type your content here...
#include <stdio.h>
#include <stdlib.h>
void insert(int ht[], int m, int key, int count){
    int index = key % m;
    int orgi = index;
    while(ht[index]!=-1){
        index = (index+1)%m;
        if(index == orgi){
            printf("Hash table is full. Cannot insert records from key %d\n", count);
            return;
        }
    }
    ht[index] = key;
}
int main(){
    int n,m;
```

```

int count = 0;
scanf("%d %d", &n, &m);
if(n==0){
    printf("Hash Table is empty\n");
    return 0;
}
int keys[n];
for(int i = 0; i<n; i++){
    scanf("%d", &keys[i]);
}
int ht[m];
for(int i = 0; i<m; i++)
    ht[i]=-1;
for(int i = 0; i<n; i++){
    count++;
    insert(ht, m, keys[i], count);
    if(count > m)
        break;
}
for(int i = 0; i<m; i++){
    printf("T[%d] -> %d\n", i, ht[i]);
}
printf("\n");

return 0;
}

```

Execution Results - All test cases have succeeded!

Test Case - 1

User Output

5 5

1596 3574 9512 7532 4268

T[0] -> 4268

T[1] -> 1596

T[2] -> 9512

T[3] -> 7532

T[4] -> 3574

Test Case - 2

User Output

6 4

4587 6589 4521 6523 5824 6548

Hash table is full. Cannot insert records from key 5

T[0] -> 6523

T[1] -> 6589

T[2] -> 4521

T[3] -> 4587

Test Case - 3

User Output

0 5
Hash Table is empty