

Neutrinos API & Integration Guide

1. Overview

This guide covers how to authenticate against the Neutrinos API, the available Connector types, rate limits, and fixes for the most common integration errors.

2. Authentication

The Neutrinos REST API supports two authentication modes:

- **API Key** — a static key generated per project, passed as a header: `X-Neutrinos-Key`. Suitable for server-to-server integrations.
- **OAuth 2.0 (Client Credentials)** — recommended for production integrations; tokens expire after 60 minutes and must be refreshed.

```
POST /oauth/token
Content-Type: application/x-www-form-urlencoded

grant_type=client_credentials
&client_id=YOUR_CLIENT_ID
&client_secret=YOUR_CLIENT_SECRET
```

3. Connector Types

- **REST Connector** — generic HTTP connector; supports GET/POST/PUT/DELETE and custom headers.
- **Database Connector** — supports PostgreSQL, MySQL, and MSSQL out of the box via a managed connection pool.
- **Webhook Connector** — exposes a Flow as an inbound webhook endpoint; used to trigger flows from external systems (e.g., a Discourse `post_created` event).
- **SaaS Connectors** — pre-built connectors for common tools (Slack, email/SMTP, Salesforce, ServiceNow).

4. Rate Limits

The standard API rate limit is 100 requests/minute per API key, with a burst allowance of 20 additional requests. Exceeding the limit returns a 429 response with a `Retry-After` header.

Webhook Connectors used as inbound triggers are not subject to the outbound rate limit, but the receiving Flow's own Action nodes (e.g., calls back out to a third-party system) are.

5. Common Integration Errors

- **401 Unauthorized** — invalid or expired API key/token. Regenerate the key from Project Settings > API Access.
- **429 Too Many Requests** — rate limit exceeded; implement client-side backoff and respect the Retry-After header.
- **Webhook not firing** — most commonly caused by the external system not matching the expected payload signature. Verify the webhook secret configured on both sides matches exactly.
- **Data type mismatch on inbound webhook** — the external system sent a payload field as a string where Neutrinos expected a number/boolean. Add a Data Mapper transform immediately after the Webhook Trigger node to coerce types before further processing.

6. Sample Request/Response

```
GET /api/v1/flows/{flow_id}/runs?status=failed
```

Response 200:

```
{
  "runs": [
    {
      "run_id": "run_8841",
      "status": "failed",
      "failed_node": "Send-Confirmation-Email",
      "error_code": 504,
      "timestamp": "2026-07-01T09:12:00Z"
    }
  ]
}
```