

PS1 — Compound Interest

Source: MIT OpenCourseWare, 6.100L *Introduction to CS and Programming Using Python*, Fall 2022, Problem Set 1. Adapted for this course under the Creative Commons **CC BY-NC-SA 4.0** license (<https://ocw.mit.edu/terms>). This adaptation is likewise shared under CC BY-NC-SA 4.0.

1) Assignment Overview

Item	Value
Original assignment	MIT 6.100L Fall 2022, Problem Set 1: Compound Interest
Topic	Control flow (loops, conditionals); formulating a computational solution; bisection search
Assigned week	Week 2
Files provided	<code>ps1a.py</code> , <code>ps1b.py</code> , <code>ps1c.py</code> , <code>ps1_tester.py</code> , <code>put_in_function.py</code> (from the original OCW code zip)
Point split across parts	Part A 30% · Part B 30% · Part C 40% (3 problems)

Objectives

- Introduction to control flow in Python
- Formulating a computational solution to a problem
- Exploring bisection search

Overview

- Complete each of the **three** problems in the respective Python files: **`ps1a.py`**, **`ps1b.py`**, **`ps1c.py`**.
- Include **comments** to help the grader understand your code.
- **`ps1_tester.py`** is a tester file that you may run to test your code. Make sure `ps1_tester.py` is in the same folder as `ps1a.py`, `ps1b.py`, `ps1c.py`, and `put_in_function.py`.

Important Notes

- **Do not delete any of the comments in the provided template, and use the variable names specified below to get full credit.**
 - Get user input and declare variables under the correct comment headers in `ps1a.py`, `ps1b.py`, and `ps1c.py`. Failure to do so (e.g. using different variable names where specified or declaring them under the wrong comment headers) will result in a 0 by the grader.
 - If you get an error like `ModuleNotFoundError: No module named 'ps1b_in_function'`, restart your Python session/terminal.
-

2) Problems (original text preserved)

Problem A: Saving for a House (30%)

You have just graduated and have a job! You move to a big city and decide that you want to start saving for a home. Houses are fairly expensive, so you start saving up for the down payment on your dream home.

Your goal is to **find the number of months it takes to save up for a down payment**. The cost of your down payment is calculated by **multiplying the total cost of your dream house by the down payment percentage**.

User Inputs. Ask the user to enter the following variables and cast them as **floats**. They must be initialized in the following order at the beginning of your program, before declaring other variables.

1. The starting yearly salary (`yearly_salary`)
2. The portion of salary to be saved (`portion_saved`). This variable should be in decimal form (e.g. 0.1 for 10%).
3. The cost of your dream home (`cost_of_dream_home`)

Writing the Program. You will need to determine how many months it will take given the following information:

1. `yearly_salary`, as described above.
2. `portion_saved`, as described above.
3. `cost_of_dream_home`, as described above.
4. `portion_down_payment`, the percentage of the total cost needed for a down payment. **Assume `portion_down_payment = 0.25` (25%).**
5. The amount that you have saved thus far is `amount_saved`, which starts at \$0.
6. You get an annual rate of return `r`. In other words, at the **end of each month**, you receive an additional `amount_saved * (r/12)` funds for your savings (the 12 is because `r` is an annual rate). **Assume `r = 0.05` (5%).**
7. At the end of each month, your savings increase by (1) a percentage of your monthly salary and (2) the monthly return on your investment. **(Note: The investment amount used to calculate the monthly return is the amount you had saved at the start of each month.)**

Output.

1. Your program should store the number of months required to save for the down payment using a variable called `months`.

Notes

- Be careful about values that represent **annual** amounts versus **monthly** amounts.
- If the number of months your program returns is off by one, reread the highlighted text above.
- Assume that users enter valid inputs (e.g. no string inputs when expecting a float).
- Your program should print outputs in the same format as the test cases below.

Manual Test Cases

```
Test Case 1
Enter your yearly salary: 112000
Enter the percent of your salary to save, as a decimal: .17
Enter the cost of your dream home: 750000
Number of months: 97

Test Case 2
Enter your yearly salary: 65000
Enter the percent of your salary to save, as a decimal: .20
Enter the cost of your dream home: 400000
Number of months: 79

Test Case 3
Enter your yearly salary: 350000
Enter the percent of your salary to save, as a decimal: .3
Enter the cost of your dream home: 1000000
Number of months: 189
```

Student Tester. Run `ps1_tester.py` in the same folder as `ps1a.py` and `put_in_function.py`. You should pass the first 3 test cases.

Problem B: Saving with a Raise (30%)

In Part A, we assumed that your salary did not change over time. However, clearly you are going to be worth more to your company over time! In this part, we will build on your solution to Part A by **adding a salary raise every six months**. Copy over your solution from Part A into the corresponding sections in `ps1b.py`.

User Inputs. There is one additional user input in Part B. Remember to cast these inputs as floats and in the following order before declaring other variables.

1. The starting yearly salary (`yearly_salary`)
2. The portion of salary to be saved (`portion_saved`)
3. The cost of your dream home (`cost_of_dream_home`)
4. The semi-annual salary raise (`semi_annual_raise`), which is a decimal percentage (e.g. 0.1 for 10%)

Writing the Program. Write a program to calculate how many months it will take for you to save up for a down payment. You can reuse much of the code from Part A. Like before, assume that your investments earn an annual rate of return `r = 0.05` (or 5%) and that `portion_down_payment = 0.25` (or 25%). In this version, `yearly_salary` increases by `semi_annual_raise` at the **end of every six months**.

Output.

1. Like Part A, your program should store the number of months required to save up for your down payment using a variable called `months`.

Notes

- Like Part A, **the investment amount used to calculate the monthly return is the amount you had saved at the *start* of each month.**
- Be careful about values that represent **annual** amounts versus **monthly** amounts.
- Raises should only happen at the end of the 6th, 12th, 18th month, and so on.
- Assume that users enter valid inputs.

Manual Test Cases

Test Case 1

Enter your starting yearly salary: 110000
Enter the percent of your salary to save, as a decimal: .15
Enter the cost of your dream home: 750000
Enter the semi-annual raise, as a decimal: .03
Number of months: 92

Test Case 2

Enter your starting yearly salary: 350000
Enter the percent of your salary to save, as a decimal: .3
Enter the cost of your dream home: 1000000
Enter the semi-annual raise, as a decimal: .05
Number of months: 131

Student Tester. Run `ps1_tester.py` in the same folder as `ps1b.py` and `put_in_function.py`. You should now pass the first 5 test cases.

Problem C: Choosing an Interest Rate (40%)

In Part A and B, you explored how (1) the percentage of your salary saved each month and (2) a semi-annual raise affects how long it takes to save for a down payment given a **fixed rate of return**, `r`.

In Part C, we will have a **fixed initial amount** and the ability to choose a value for the rate of return, `r`. Given an initial deposit amount, our goal is to find the **lowest** rate of return that enables us to save enough money for the down payment in 3 years.

User Inputs. Cast the user input as a **float** in the beginning of your program.

1. The initial amount in your savings account (`initial_deposit`)

Writing the Program. Write a program to calculate the minimum rate of return `r` needed in order to reach your goal of a sufficient down payment in 3 years, given an `initial_deposit`. To simplify things, assume:

1. The cost of the house that you are saving for is \$800,000.
2. The down payment is 25% of the cost of the house.

Use the following formula for compound interest in order to calculate the predicted savings amount given a rate of return `r`, an `initial_deposit`, and `months`:

```
amount_saved = initial_deposit * (1 + r/12) ** months
```

You will use **bisection search** to determine the **lowest** rate of return `r` that is needed to achieve a down payment on an \$800,000 house in 36 months. Since hitting this exact amount is a bit of a challenge, we only require that your savings be within \$100 of the required down payment. For example, if the down payment is \$1000, the total amount saved should be between \$900 and \$1100 (exclusive).

Your bisection search should update the value of `r` until it represents the lowest rate of return that allows you to save enough for the down payment in 3 years. `r` should be a **float** (e.g. 0.0704 for 7.04%). Assume that `r` lies somewhere between 0% and 100% (inclusive).

Outputs.

1. The variable `steps` should reflect the number of steps your bisection search took to get the best `r` value (i.e. `steps` should equal the number of times that you bisect the testing interval).
2. The variable `r` should be the lowest rate of return that allows you to save enough for the down payment in 3 years.

Notes

- There may be multiple rates of return that yield a savings amount that is within \$100 of the required down payment on an \$800,000 house. The grader will accept any of these values of `r`.
- **If the initial deposit amount is greater than or equal to the required down payment minus \$100, then the best savings rate is `0.0`.**
- **If it is not possible to save within \$100 of the required down payment in 3 years given the initial deposit and a rate of return between 0% and 100%, `r` should be assigned the value `None`.**
 - Note: the value `None` is different than `"None"`. The former is Python's version of a null value, and the latter is a string.
- Depending on your stopping condition and how you compute the amount saved for your bisection search, your number of steps may vary slightly from the example test cases. Running `ps1_tester.py` should give you a good indication of whether or not your number of steps is close enough to the expected solution.
- If a test is taking a long time, you might have an infinite loop! Check your stopping condition.

Manual Test Cases

```
Test Case 1
Enter the initial deposit: 65000
Best savings rate: 0.380615234375 [or very close to this number]
Steps in bisection search: 12 [or very close to this number]

Test Case 2
Enter the initial deposit: 150000
Best savings rate: 0.09619140625 [or very close to this number]
Steps in bisection search: 11 [May vary based on how you implemented your bisection
search]

Test Case 3
Enter the initial deposit: 1000
Best savings rate: None
Steps in bisection search: 0 [May vary based on how you implemented your bisection
search]
```

Student Tester. Run `ps1_tester.py` in the same folder as `ps1c.py` and `put_in_function.py` and you should pass all 8 test cases.

3) Deliverables

Submit to the course LMS:

1. `ps1a.py`, `ps1b.py`, `ps1c.py` — with the original template comments intact and the specified variable names.
2. At the start of each file, in comments, write your name, collaborators, and time spent:

```
# Problem Set 1A
# Name: Hong Gildong
# Collaborators: ...
# Time Spent: ...
```

3. A **screenshot or text capture of the `ps1_tester.py` output** showing how many of the 8 tests pass (this is your "student tests" evidence).
4. A short comment block (3–5 lines) at the bottom of `ps1c.py` explaining *how your bisection search decides to move left or right* (this is your "explanation" evidence).

Collaboration. Students may work together, but each student should write up and hand in their assignment separately. Students may not submit the exact same code, and are not permitted to look at or copy each other's code or code structure. Include the names of your collaborators in a comment at the start of each file.

4) Grading Rubric Summary (course common rubric)

Criterion	Weight	Applied to PS1 as
Correctness & edge cases	45%	Tester test cases (8) + hidden edge cases (Part C: <code>r = 0.0</code> case, <code>None</code> case, off-by-one months)
Problem decomposition	20%	Correct variable initialization order; clean loop structure; Part A code reused sensibly in Part B
Student-written tests	15%	Tester run evidence + at least 1 extra manual test case of your own per part
Explanation	10%	Bisection search explanation block; meaningful comments
Code clarity & style	10%	Naming, no dead code, template comments preserved

5) [Instructor Checklist]

Changes from the original (MIT 6.100L F22 PS1):

1. Intro sentence "You have just graduated from MIT... move to the Bay Area" generalized to "You have just graduated and have a job! You move to a big city" (institution-specific reference only; all numbers, variable names, and logic unchanged).
2. MIT-specific logistics removed: Pset Buddy notice, half-way submission (Sep 21) and final submission (Oct 5) dates, MIT upload boxes. Replaced by course LMS deliverables (§3).
3. Deliverables 3–4 (tester evidence, explanation block) added to support the course rubric; they add no new problem content.
4. All three problems, all user-input orders, all constants (`portion_down_payment = 0.25`, `r = 0.05`, \$800,000 house, \$100 tolerance, 36 months), all test cases, and the compound-interest formula — **preserved unchanged**.

Problem count: original 3 (Parts A, B, C) → packet 3 (equal).

Prerequisite check: ☒ Confirmed — no items beyond Week 2 prerequisites (variables, `input` / casting, arithmetic, `while` / `for` loops, conditionals; bisection search is introduced by this pset itself as in the

original).