



2024-2025

ELEC-H504 - Network Security

Deception & Honeypot for Attack Profiling

SUNDARESAN Sankara
CHOUGULE Gaurav
MESSAOUDI Leila
BOTTON David

Pr. Jean-Michel Dricot
Navid Ladner

June 2025



Contents

1	Introduction	2
1.1	Problem Statement	2
1.2	Research Questions	2
2	SSH Isolation & System Hardening	3
2.1	Administrative Controlled Access	3
2.2	Fail2ban Configuration	3
2.3	IPtables Redirection	4
2.4	Validation Metrics	5
3	Cowrie Honeypot Setup	5
3.1	System Requirements	5
3.2	Functional Configuration	5
4	Maximizing Engagement with Deception	6
<hr/>		
A	Annex: Validation for SSH Isolation & Fail2ban Hardening	7
B	Annex: Cowrie Operational Validation	8
C	Annex: LLM Usage in this Project	9

ABSTRACT

This paper shows an operational deployment of the SSH honeypot using `cowrie` on an Ubuntu `EC2` instance to capture attacker activity in real-world circumstances. By exposing a knowingly open SSH port on the Internet and securing legitimate access with a cryptographic key on a different port, the study observes and inspects adversary tactics, techniques, and procedures (TTPs). Key steps include isolating the honeypot space from production access using `fail2ban`, redirecting malicious traffic to `cowrie` via `iptables`, and forging artifacts to track attacker activity. A walkthrough of the settings is covered to demonstrate a complete implementation in `cowrie`, as this paper remains focused on the hands-on aspect of honeypot-based deception. Additionally, cloud provider configurations (e.g., IAM, networking) are not included as implementation-specific and beyond the scope of this paper. This project's public `git` repository is available at that location.

1 Introduction

Lance Spitzner, a seminal researcher and Senior Instructor for SANS Cybersecurity Leadership, established foundational principles in his 2002 book *Honeypots: Tracking Hackers*. Despite its age, Spitzner’s core thesis retains striking relevance in modern threat intelligence; Honeypots derive value from “being probed, attacked, or compromised” (p. 23). Our Cowrie implementation on AWS positions itself onto that continuity, demonstrating that Spitzner’s “gaining value from data” challenge (Ch.4) persists against contemporary attacks. In addition, the attacker behaviors documented in 2002 remain prevalent even today. Furthermore, Spitzner’s risk mitigation framework (Ch.12) comprises a wide set of obstacles one encounters when building such deceptive system, mainly signature-based detection tools that inform attackers about the underlying nature of our operation; “a system designed to be attacked” (p. 298).

With more advanced automated SSH-based attacks, empirical analysis of attacker processes has been crucial in strengthening defenses. By mimicking realistic infrastructure while isolating malicious activity from legitimate administrative access, this proof of concept applies Spitzner’s principles of honeypot deployment, specifically leveraging **medium-interaction design** (Ch.5) to find the correct trade-off between risk containment and attacker engagement. Through silent redirection of open-to-the-public SSH traffic to the honeypot and restriction of legitimate access with key-based authentication, the study allows the monitoring of attacker activities in fine granularity without compromising the security of systems, proving Spitzner’s assertion that honeypots provide «*small amounts of high-value data*» without production noise.

1.1 Problem Statement

Public SSH services are some of the most frequent targets of credential stuffing and post-compromise persistence attacks (e.g., SSH key injection, cronjob exploitation). Conventional defenses measures lack visibility of attacker’s TTPs (Techniques, Tactics & Procedures). A gap Spitzner attributes their inability to naturally distinguish between legitimate and hostile activity (Ch. 4). This research addresses three significant challenges:

- **Safe isolation of production access:** Mitigating Spitzner’s identified risk of collateral system compromise through architectural “separation of honeypot lures from administrative channels” (Ch. 3, 12).
- **Deception efficacy for engagement:** Designing credible system emulations (e.g., service banners, file structures, false credentials) to prolong attacker interaction and avoid detection as a honeypot.
- **High-fidelity TTP capture:** Engineering logging mechanisms that overcome environmental distortion in production systems. Able to capture attackers’ behavior without affecting environmental integrity.

1.2 Research Questions

In order to learn about attacker motives and organization through research honeypots, this study investigates:

- **Credential exploitation patterns:** Which username/password pairs dominate automated brute-force campaigns against internet-exposed SSH? (Extending Spitzner’s analysis of “targets of opportunity” and scripted tools in Ch. 4.)

- **Persistence mechanism prioritization:** How do attackers strategically deploy backdoors (e.g., key injections, cronjobs) post-compromise? “Persistence, not advanced technical skills, is how these attackers successfully break into a system.” (Ch. 2, p. 35)
- **Decoy efficacy for intelligence gathering:** To what extent do fabricated system artifacts (e.g., */etc/shadow* entries) prolong attacker engagement to enhance TTP profiling? (Testing Spitzner’s concept of deception as “psychological weapons used to mess with and confuse a human attacker” in Ch. 4, p. 74).

2 SSH Isolation & System Hardening

Clear goal-setting, suitable interaction levels, reliable data collection, and risk mitigation are all highlighted in Spitzner’s honeypot deployment framework (Ch. 12). In order to study automated SSH-based attacks, in this section we concentrate on segregating legitimate SSH access with cryptographic controls and configuring a simple intrusion prevention system called *fail2ban*. Making sure that these techniques are in line with Spitzner’s recommendations for safe and efficient honeypot operation.

2.1 Administrative Controlled Access

Administrative SSH access is limited to key-based authentication on a non-standard port (e.g.: 2223) in accordance with Spitzner’s advice to reduce risk through secure configurations (Ch. 12). By removing password-based vulnerabilities, this reduces the attack surface and is consistent with the idea of protecting the underlying platform. The setup ensures strong isolation of authorized access by enforcing contemporary cryptographic standards to stop downgrade attacks.

```
# /etc/ssh/sshd_config
Port 2223
Protocol 2
HostKeyAlgorithms ssh-ed25519,rsa-sha2-512
KexAlgorithms curve25519-sha256
Ciphers chacha20-poly1305@openssh.com,aes256-gcm@openssh.com
MACs hmac-sha2-512-etm@openssh.com
PermitRootLogin no
PasswordAuthentication no
AllowUsers ubuntu
LoginGraceTime 30s
MaxAuthTries 2
PubkeyAuthentication yes
X11Forwarding no
```

Listing 1: Securing Legitimate Access

2.2 Fail2ban Configuration

To improve detection of unauthorized access attempts, Fail2Ban is set up to monitor key-based authentication failures on port 2223 and following Spitzner’s assertion that detection is a central function of a honeypot (Ch. 12), this configuration targets repeat public key failures, which can be facilitated through credential-stuffing attacks. Potentially malicious SSH connections

will have fair, high-fidelity logging of attempts to authenticate via public keys. Given that the honeypot contains a deliberately misleading environment, the configuration will not interfere with coded logging and will be able to detect ongoing attacks. This configuration does not monitor any password attempts, as password-based administrative access has been disabled, to avoid receiving false positive logging data.

```
# /etc/fail2ban/jail.d/ssh-admin.conf
[ssh-admin]
enabled = true
port = 2223
filter = sshd
maxretry = 3
findtime = 10m
bantime = 30m
```

Listing 2: Custom Jail Rules

```
# /etc/fail2ban/filter.d/sshd.conf
failregex = %(cmnfailre)s
            <mdre-<mode>>
            ~%(__prefix_line)s(?: Received disconnect from <HOST> port \d+: Too many
            → authentication failures | Disconnected from <HOST> port \d+ due to: Authentication
            → failed for .* publickey )
            %(cfooterre)s
```

Listing 3: Regex Filter Against Key-Based Attacks

2.3 IPtables Redirection

Using Spitzner’s idea of port forwarding through Network Address Translation (NAT) (Ch. 12), all traffic to the standard SSH port (22) is re-routed to the Cowrie honeypot on port 2222. This helps separate the malicious activity from the legitimate usage taking place on port 2223, and helps support Spitzner’s idea of compartmentalization to separate the honeypot from the production systems and avoid any conflicts (Ch. 12, p. 317). Additionally, our group collaborators’ IP addresses could be whitelisted for a much tighter defense.

The `sshd` to `cowrie` (ports `22` → `2222`) redirection is a security design with multiple benefits: both processes avoid conflicting with each other as they can restart separately, binding to high ports does not require root privileges, also, `fail2ban` needs an explicit target to be effective. Compartmentalization is a key principle for any deceptive operation, we also ensure an appropriate foundation for clean and comprehensive post-attack analysis.

```
sudo apt install iptables-persistent netfilter-persistent
sudo iptables -t nat -A PREROUTING -p tcp --dport 22 -j REDIRECT --to-port 2222
sudo ip6tables -t nat -A PREROUTING -p tcp --dport 22 -j REDIRECT --to-port 2222
sudo netfilter-persistent save
```

Listing 4: Traffic Redirection to Cowrie

2.4 Validation Metrics

To ensure rigorous validation, we verify component functionality and isolation using cybersecurity tools. The following Annex align with Spitzner’s focus on testing processes to validate functionality. Validation for network isolation occurs with nmap and iptables to verify traffic is being redirected. Fail2Ban regex exactness is tested against simulated brute-forcing of SSH keys. SSH configuration is validated for compliance to cryptography and resist downgrade attacks.

3 Cowrie Honeypot Setup

Honeybots differ by level of interaction: low-interaction emulates the minimal service much of the time to detect attackers; medium-interaction such as Cowrie employ a controlled environment withstanding an attacker’s impact; high-interaction (like Honeybots) provides access to fully functioning Operating Systems allowing as much dynamic information gathering as possible. Spitzner emphasizes the importance of tailoring honeybots to specific needs: “Developing your own honeybot is not as complicated as it might seem. Using a variety of commonly found security tools, some basic code, and a lot of creativity, you can create many different honeybots” (Ch.9). Cowrie’s configuration leverages this flexibility, allowing customization of emulated services to capture specific attacker behaviors. This section details the deployment of the medium-interaction Honeybot Cowrie on a AWS EC2 instance.

3.1 System Requirements

Cowrie runs under a privileged account that’s not root, with timed-out sudo privileges to ensure least privilege principle. Attack surface minimization is offered by authbind on port binding, eliminating traditional root escalation threats by privileged port allocation. Compartmentalization is used to isolate dependencies through Python virtual environments, which help hide each of the libraries and potential exploits from one another, no conflicts may arise. These measures specifically address reducing lateral movement possibilities in case of compromise.

```
sudo apt-get install -y git python3-venv python3-pip libssl-dev libffi-dev build-essential
↳ libpython3-dev authbind
sudo adduser --disabled-password --gecos "" cowrie # Prevents password-based connections
```

Listing 5: Cowrie User Creation

3.2 Functional Configuration

The following commands compartmentalize Cowrie within a virtual environment and enforce port isolation. Find the latest Cowrie official documentation at docs.cowrie.org.

```
# Operate as cowrie user
sudo su - cowrie
git clone https://github.com/cowrie/cowrie
cd cowrie

# Isolate dependencies using Python venv
python3 -m venv cowrie-env
source cowrie-env/bin/activate
```



```
pip install --upgrade -r requirements.txt

# Configure listener port (2222) to align with iptables redirection (section 2.3)
sed -i 's/tcp:6415:interface=127.0.0.1/tcp:2222:interface=0.0.0.0/' etc/cowrie.cfg
```

Listing 6: Cowrie Honeypot Setup

4 Maximizing Engagement with Deception

As Spitzner points out with respect to the psychological effects of deception, “This can confuse an attacker and potentially waste his time and resources” (Ch. 9), but he also cautions that deception is ineffective against automated threats: “Automated tools such as worms or auto-rooters will not be deceived”. This suggests deception can be useful against human attackers, though it has limitations against automated attacks.

Security Disclaimer

This setup only serves academic purposes; adversarial activities are welcomed, but no offensive counteraction shall be taken in return. “The greater the level of interaction, the more functionality provided to the attacker, and the greater the complexity. Combined, these elements can introduce a great deal of risk” (Ch. 5).

A Annex: Validation for SSH Isolation & Fail2ban Hardening

```
# Verify port 22 redirects to Cowrie (2222) and admin port (2223) is exclusive
sudo nmap -sV -Pn -p 22,2222,2223 $EC2_PUBLIC_IP

# Check iptables NAT rules for redirect (should show 22 to 2222)
sudo iptables -t nat -L PREROUTING -v -n

# Ensure no SSH service binds to port 22 (only Cowrie on 2222)
sudo ss -tulpn | grep -E ':22|:2222|:2223'
```

Listing 7: Network Isolation Verification

```
# Simulate key-based brute-forcing to trigger fail2ban
for i in {1..5}; do ssh -i /path/fake_key ubuntu@localhost -p 2223; done

# Verify fail2ban logged the bans (look for 'ssh-admin' jail)
sudo grep "ssh-admin" /var/log/fail2ban.log

# Check active bans (should list test IP)
sudo fail2ban-client status ssh-admin
```

Listing 8: Fail2ban Efficacy Testing

```
# 1. Verify active SSH configuration matches hardening intent (no fallback to weak
    ↪ protocols)
sudo sshd -T | grep -E '^ciphers|^kexalgorithms|^macs|^hostkeyalgorithms'

# 2. Test SSH service for protocol/cipher negotiation weaknesses
nmap -Pn -p 2223 --script ssh2-enum-algos $EC2_PUBLIC_IP | grep -A 10 "algorithm
    ↪ negotiation"

# 3. Confirm password authentication is globally disabled (even if bypass attempted)
ssh -o PubkeyAuthentication=no -o PreferredAuthentications=password ubuntu@$EC2_PUBLIC_IP
    ↪ -p 2223
```

Listing 9: SSH Service Hardening Validation

B Annex: Cowrie Operational Validation

```
# 1. Validate iptables NAT rules
sudo iptables -t nat -L PREROUTING -nv | grep 'tcp dpt:22 redir ports 2222'

# Confirm no direct binding to port 22
sudo nmap -sV -Pn -p 22,2222 $EC2_IP | grep -E '22/tcp|2222/tcp'
```

Listing 10: Traffic Redirection Verification

```
# 2. Simulate attacker connection
ssh -o StrictHostKeyChecking=no invalid_user@$EC2_IP -p 22

# Verify session capture in logs
sudo journalctl -u cowrie -f | grep 'SSH connection closed'
```

Listing 11: Honeypot Engagement Testing

```
# 3. Confirm execution context
ps -ef | grep cowrie | grep -v grep | awk '{print $1}' | uniq
```

Listing 12: Process Isolation Validation

C Annex: LLM Usage in this Project

Large language models (LLMs) provided targeted support during this honeypot deployment, strictly limited to non-operational tasks. For documentation, LLMs assisted in drafting initial LaTeX templates for technical sections such as SSH hardening (2.1) and iptables redirection (2.3), with all configurations manually validated against AWS and Cowrie documentation. During troubleshooting, models proposed diagnostic commands for SSH permission conflicts (e.g., 'chmod' adjustments in §3.2), which were later tested in isolated Docker environments before EC2 implementation. LLMs were explicitly excluded from security-critical decisions: firewall rules, Fail2ban thresholds, and cryptographic settings in '/etc/ssh/sshd_config' derived exclusively from NIST guidelines and Mozilla Infosec recommendations. No model influenced attacker engagement strategies, log analysis of captured TTPs, or live system interactions. All AI-generated content underwent peer review by the project's cybersecurity team, with particular scrutiny applied to network redirection mechanics and user permission workflows. Final configurations reflect human expertise, with LLMs serving solely as productivity accelerators for non-sensitive administrative tasks.