

API Documentation

Route: <http://localhost:3000/api/v1/apply/countries>

Method: GET

json output:

```
{
  "status": String,
  "statusCode": Number,
  "message": String,
  "data": [
    {
      "country_id": Number (primary id),
      "country_name": String,
      "country_code": String
    },
  ],
  "error": String
}
```

Example with dummy data:

```
{
  "status": "Success",
  "statusCode": 200,
  "message": null,
  "data": [
    {
      "country_id": 1,
      "country_name": "United States",
      "country_code": "US"
    },
  ],
  "error": null
}
```

Route: `http://localhost:3000/api/v1/apply/sates/: country_code`

Method: GET

Input parameters: Country_code – from the countries route.

example: `http://localhost:3000/api/v1/apply/states/US`

json output:

```
{
  "status": String,
  "statusCode": Number,
  "message": String,
  "data": [
    {
      "state_id": Number (Primary ID),
      "state_name": String,
      "state_code": String,
      "country_code": String
    },
  ]
  "error": String
}
```

Example with dummy data:

```
{
  "status": "Success",
  "statusCode": 200,
  "message": null,
  "data": [
    {
      "state_id": 1,
      "state_name": "Puerto Rico",
      "state_code": "PR",
      "country_code": "US"
    },
  ],
  "error": null
}
```

Route: `http://localhost:3000/api/v1/apply/cities/:state_code`

Method: GET

Input parameters: State_code – from the states route.

example: `http://localhost:3000/api/v1/apply/cities/CA`

json output:

```
{
  "status": String,
  "statusCode": Number,
  "message": String,
  "data": [
    {
      "city_id": Number (Primary ID),
      "city_name": String,
      "state_code": String,
    },
  ],
  "error": String
}
```

Example with dummy data:

```
{
  "status": "Success",
  "statusCode": 200,
  "message": null,
  "data": [
    {
      "city_id": 25778,
      "city_name": "Los Angeles",
      "state_code": "CA"
    },
  ],
  "error": null
}
```

Route: <http://localhost:3000/api/v1/apply/countryPhoneCodes>

Method: GET

json output:

```
{
  "status": String,
  "statusCode": Number,
  "message": String,
  "data": [
    {
      "country_id": Number (Primary ID),
      "country_name": String,
      "country_code_phone": String
    },
  ],
  "error": String
}
```

Example with dummy data:

```
{
  "status": "Success",
  "statusCode": 200,
  "message": null,
  "data": [
    {
      "country_id": 1,
      "country_name": "United States",
      "country_code_phone": "+1"
    },
  ],
  "error": null
}
```

Route: <http://localhost:3000/api/v1/apply/employee/>

Method: Post

Input Json:

```
{
  "first_name": String,
  "middle_name": String,
  "last_name": String,
  "birth_date": Format: yyyy-mm-dd,
  "linkedin_url": URL,
  "personal_email": Email,
  "country_code_phone": String,
  "phone": String,
  "phonetype": Enum('Mobile', 'Home', 'Work'),
  "address_line_1": String,
  "address_line_2": String,
  "city_id": Number (Primary ID),
  "state_id": Number (Primary ID),
  "zipcode": String,
  "homecountry_id": Number (Primary ID),
  "time_zone": String,
  "gender": Enum('Male', 'Female', 'Non-binary', 'Prefer not to say'),
  "opt_support": Enum('Yes, the OPT period has started', 'Yes, approved but have not
received the EAD card', 'No'),
  "desired_start_date": Format: yyyy-mm-dd,
  "hours_commitment": Number,
  "why_kworks": String,
  "visa_status": Enum('Citizen', 'Permanent Resident', 'Student Visa', 'Work Visa', 'Other'),
  "additional_websites": URL,
  "additional_info": String,

  "educations": [
    {
      "institution_name": String,
      "degree": String,
      "major": String,
      "start_date": Format: yyyy-mm-dd,
      "end_date": Format: yyyy-mm-dd or null
    }
  ],

  "employments": [
    {
```

```
"company_name": String,  
"job_title": String,  
"location": String,  
"start_date": Format: yyyy-mm-dd,  
"end_date": Format: yyyy-mm-dd or null,  
"responsibilities": String  
}  
],
```

```
"sexual_orientation": Enum('Heterosexual', 'Homosexual', 'Bisexual', 'Asexual', 'Prefer not  
to say'),  
"disability": Enum('Yes', 'No', 'Prefer not to say')  
}
```

Input example with dummy data:

```
{  
  "first_name": "Joe ",  
  "middle_name": "F",  
  "last_name": "Doe",  
  "birth_date": "1990-01-01",  
  "linkedin_url": "https://www.linkedin.com/in/johnfdoe",  
  "personal_email": "johnFDoe2@example.com",  
  "country_code_phone": "+1",  
  "phone": "1234567894",  
  "phonetype": "Mobile",  
  "address_line_1": "123 Main Street",  
  "address_line_2": "Apt 4B",  
  "city_id": 1,  
  "state_id": 1,  
  "zipcode": "12345",  
  "homecountry_id": 1,  
  "time_zone": "America/New_York",  
  "gender": "Male",  
  "opt_support": "No ",  
  "desired_start_date": "2025-02-01",  
  "hours_commitment": 40,  
  "why_kworks": "I am passionate about contributing to meaningful projects.",  
  "visa_status": "Student Visa",  
  "additional_websites": "https://portfolio.johndoe.com",  
  "additional_info": "Looking forward to collaborating with talented teams.",  
  "educations": [  
    {  
      "institution_name": "University of XYZ",  
      "degree": "Bachelor's",
```

```
    "major": "Computer Science",
    "start_date": "2010-08-15",
    "end_date": "2014-05-15"
  },
  {
    "institution_name": "University of ABC",
    "degree": "gggf",
    "major": "Software Engineering",
    "start_date": "2015-09-01",
    "end_date": "2017-05-15"
  }
],
"employments": [
  {
    "company_name": "Tech Corp",
    "job_title": "Software Developer",
    "location": "San Francisco, CA",
    "start_date": "2018-06-01",
    "end_date": "2019-05-13",
    "responsibilities": "Lead development of APIs"
  },
  {
    "company_name": "Innovative Solutions",
    "job_title": "Senior Developer",
    "location": "New York, NY",
    "start_date": "2022-01-01",
    "end_date": null,
    "responsibilities": "Led a team of developers in building cloud-native microservices."
  }
],
"sexual_orientation": "Bisexual",
"disability": "No"
}
```

OUTPUT:

Success Response example:

```
{
  "status": "success",
  "statusCode": 201,
  "message": "Employee created successfully",
  "data": {
    "employee": {
      "userId": 4
    }
  },
  "error": null
}
```

Error output example:

```
{
  "status": "bad request",
  "statusCode": 400,
  "message": null,
  "data": null,
  "error": "error message"
}
```