Alzheimer's Detection Using 3D CNN–ViT With Explainable AI

Submitted in Partial Fulfillment of the Requirements for the Degree of Bachelor of Science in Computer Science and Engineering of the University of Asia Pacific

by

Pinky Akter
Roll: 22101156

Samuel Emon Halder
Roll: 22101183

Md. Sarjil Hasan
Roll: 22101168

Supervised by:

Faria Zarin Subah
Assistant Professor, Department of CSE

Co-supervised by:

A.S. Zaforullah Momtaz
Assistant Professor, Department of CSE



Department of Computer Science & Engineering
University of Asia Pacific

July 2026

Declaration

We, hereby, declare that the work presented in this Thesis is the outcome of the investigation performed by us under the supervision of Ms. Faria Zarin Subah, Assistant Professor, Department of Computer Science, University of Asia Pacific. We also declare that no part of this Thesis and thereof has been or is being submitted elsewhere for the award of any degree or Diploma.

Countersigned

(Ms. Faria Zarin Subah)
Supervisor

Signature

.....

Samuel Emon Halder

.....

Pinky Akter

.....

Md. Sarjil Hasan

Certificate of Approval

We hereby recommend that the thesis prepared by Samuel Emon Halder, Pinky Akter, Md. Sarjil Hasan entitled "Alzheimer's Detection Using 3D CNN–ViT With Explainable AI" is accepted as fulfilling the part of the requirements for degree of Bachelor of Science in Computer Science and Engineering.

.....

Faria Zarin Subah
Assistant Professor
Department of Computer Science and Engineering
University of Asia Pacific (UAP)

Chairman of the Committee
(Supervisor)

.....

A.S. Zaforullah Momtaz
Assistant Professor
Department of Computer Science and Engineering
University of Asia Pacific (UAP)

Member of the Committee
(External)

.....

Shah Murtaza Rashid Al Masud
Professor & Head of the Department
Department of Computer Science and Engineering
University of Asia Pacific (UAP)

Head of the Department

Acknowledgements

I would like to begin by expressing my sincere gratitude to our God Almighty for granting me the strength, patience, and perseverance to complete this thesis work.

I extend my heartfelt appreciation to my supervisor, Faria Zarin Subah, for her honest guidance, insightful advice, and encouragement throughout the development of this research. Her support played an invaluable role in shaping the direction of this work and overcoming the challenges along the way.

I am also grateful to our respected examiner, A. S. Zaforullah Momtaz, for his helpful feedbacks and thoughtful evaluation, which greatly contributed to the improvement of this thesis.

My sincere thanks go to all faculty members of the department for their academic support and for providing the foundational knowledge essential for the successful completion of this project.

Finally, I express my deepest appreciation to my family for their unconditional love, patience, and unwavering support. Their encouragement has always been a source of strength and motivation throughout my academic journey.

Abstract

Alzheimer's disease is a progressive neurodegenerative condition that causes memory loss and cognitive decline, and early detection is essential to improve patient care and treatment planning. Structural MRI reliably captures the brain changes linked to Alzheimer's, yet many reported deep-learning systems inflate their accuracy by splitting the data at the level of individual 2D slices, which lets scans from the same patient appear in both training and testing. This work develops and benchmarks a family of fully three-dimensional models for Alzheimer's classification on the Alzheimer's Disease Neuroimaging Initiative (ADNI) dataset (1,132 T1-weighted MPRAGE volumes from 395 subjects), under a strict *subject-level*, leakage-free evaluation protocol with five-fold cross-validation. Two clinically meaningful tasks are studied: the binary task of separating cognitively normal (CN) subjects from Alzheimer's (AD) subjects, and the harder three-class task of CN vs. mild cognitive impairment (MCI) vs. AD. Five architectures are compared on an identical pipeline and split: a 3D DenseNet-121 CNN, a MedicalNet-pretrained 3D ResNet, a 3D Vision Transformer (ViT), a Swin Transformer encoder, and a hybrid that fuses a 3D CNN with a 3D ViT to combine local anatomical detail with global contextual reasoning. The hybrid CNN–ViT delivers the best binary result at $82.2\% \pm 5.7$ accuracy (macro-F1 0.80), marginally ahead of the from-scratch DenseNet (81.0%) and well ahead of the pretrained ResNet (69.8%); on the three-class task the honest ceiling is $\sim 57.7\%$ (Swin), with MCI remaining the dominant source of confusion, and a from-scratch ViT collapsing to near-chance — itself a useful negative result about data-hungry transformers on small medical datasets. Model decisions are examined with a suite of 3D explainability methods (Grad-CAM, Integrated Gradients, and attention rollout), whose importance maps concentrate on medial-temporal and ventricular regions consistent with known AD pathology. The contribution of this work is not a headline-chasing accuracy number but a rigorous, reproducible, leakage-free comparison of single versus hybrid 3D architectures for Alzheimer's classification, together with an interpretability analysis that grounds the predictions in plausible neuroanatomy.

Contents

List of Figures **ix**

List of Tables **x**

List of Abbreviations **xi**

1 Introduction **1**

1.1 Background and Motivation 1

1.2 Problem Statement 2

1.3 Objectives of the Project 3

1.4 Research Questions / Hypotheses 3

1.5 Scope of the Work 3

1.6 Expected Outcomes 4

1.7 Impacts of the Project 4

1.7.1 Impact on Societal and Cultural Issues 4

1.7.2 Impact on Health, Safety, and Legal Issues 4

1.7.3 Impact on Environment and Sustainability Issues 5

1.8 Report Organization 5

2 Background and Literature Review **7**

2.1 Preliminaries 7

2.1.1 Overview of Alzheimer's Disease 7

2.1.2 MRI Characteristics of Alzheimer's Disease 9

2.1.3 Key Concepts, Formulas, and Models 9

2.2 Related Works / Existing Systems 14

2.3 Comparative Analysis of Related Works 20

2.4 Research Gap / Limitations of Existing Methods 21

2.5 Summary 22

3 System Analysis and Design **23**

3.1 Requirement Analysis 23

3.1.1 Stakeholder Identification 24

3.1.2 Requirement Identification Methods 25

3.1.3 Functional Requirements (FR) 26

3.1.4 Non-Functional Requirements (NFR) 27

3.2 System Overview / Architecture 28

3.2.1 High-Level Architecture 28

3.2.2 Detailed Design Diagrams 30

3.2.3 Design Alternatives and Rationale 32

3.3 Pseudocode for Proposed 3D CNN–ViT Hybrid Model 33

3.4 Summary 33

4 Methodology and Implementation **34**

4.1 Methodological Framework 34

4.2 Tools, Libraries, and Technologies Used 35

4.3 Dataset Description 36

4.3.1 ADNI (Alzheimer's Disease Neuroimaging Initiative) 36

4.3.2 Curation and Class Distribution 37

4.3.3 Exploratory Data Analysis 38

4.3.4 Evaluation Protocol (Subject-Level, Leakage-Free) 39

4.4 Preprocessing Steps 40

4.5 Model Development / Algorithm Design 41

4.5.1 Standalone Backbones 41

4.5.2 Hybrid 3D CNN–ViT (Proposed) 42

4.6 Training Recipe 43

4.7 System Implementation / Modules Description 43

4.8 Hardware and Software Requirements 44

4.9 Summary 44

5 Experimental Results and Analysis **45**

5.1 Experimental Setup Recap 45

5.2 Binary CN-vs-AD Results (Headline) 45

5.3 Three-Class CN/MCI/AD Results (Honest Benchmark) 47

5.4 Per-Fold Results and Fold Variance 49

5.5 Per-Class Performance 50
5.6 Training Dynamics 51
5.7 Performance Diagnostics 52
5.8 Feature-Space Analysis 52
5.9 Error Analysis 53
5.10 Does the Hybrid Actually Help? (RQ1) 54
5.11 Medical Transfer Learning: Pretrained ResNet vs. From-Scratch CNN 55
5.12 Why the From-Scratch ViT Collapses 55
5.13 Explainability Analysis (RQ2) 56
5.14 Comparison with the Literature 58
5.15 Answers to the Research Questions 58
5.16 Threats to Validity 59
5.17 Summary 59

6 Project Planning and Budget **61**

6.1 Project Timeline 61
6.2 Budget Estimation 63
6.3 Summary 64

7 Standards and Design Constraints **65**

7.1 Compliance with Standards and Professional Practice 65
7.1.1 Software Standards 65

7.1.2 Hardware Standards 66
7.1.3 Other Standards 66
7.2 Design Constraints 67
7.2.1 Ethical and Professional Responsibilities 67
7.2.2 Environmental and Sustainability Considerations 67
7.2.3 Health and Safety Considerations 68
7.3 Complex Engineering Problem (CEP) Coverage 68
7.4 Complex Engineering Activities (CEA) Coverage 69
7.5 Summary 70

8 Conclusion and Future Work **73**
8.1 Summary of the Work 73
8.2 Key Findings and Contributions 74
8.3 Limitations of the Study 75
8.4 Preliminary External Validation on Independent Hospital Data 75
8.5 Recommendations and Future Work 77

Code and Data Availability **78**

A Questionnaire **85**

B Reproducibility and Experimental Configuration **90**

List of Figures

3.1 System block diagram 30
3.2 Experimental flowchart 31
3.3 Hybrid fusion architecture 32

4.1 Methodology overview 35
4.2 Cohort statistics 38
4.3 CN vs. AD samples 39
4.4 Preprocessing pipeline 41
4.5 Training augmentations 41

5.1 Binary model comparison 46
5.2 Binary confusion matrix 47
5.3 Binary diagnostics 47
5.4 Three-class model comparison 48
5.5 Fold variance 50
5.6 Binary training curves 51
5.7 Three-class training dynamics 52
5.8 Extended diagnostics 52
5.9 Feature embeddings 53
5.10 Error analysis 54
5.11 XAI method comparison 56
5.12 Group-averaged importance 56
5.13 Hybrid explainability 57
5.14 Three-class explainability 57

6.1 Project timeline 62

List of Tables

2.1 Comparative Analysis of Related Works 20

3.1 Stakeholder Identification and Description 24

3.2 **Clinical stakeholder feedback.** Opinions of four practising clinicians on the reliability of the system and the clinical relevance of its Grad-CAM explanations. 25

3.3 Table of Functional Requirements 26

3.4 Table of Non-Functional Requirements 27

4.1 ADNI cohort after curation (subject-level and scan-level counts). . . . 37

5.1 Binary CN-vs-AD, subject-level 5-fold cross-validation (mean ± std). 46

5.2 Three-class CN/MCI/AD, subject-level 5-fold cross-validation (mean ± std). 48

5.3 Binary CN-vs-AD per-fold macro-F1 (subject-level). 49

5.4 Three-class CN/MCI/AD per-fold macro-F1 (subject-level). 49

5.5 Binary CN-vs-AD pooled per-class metrics. 50

5.6 Three-class CN/MCI/AD pooled per-class metrics. 51

5.7 This work vs. reported literature, highlighting the evaluation protocol. 58

6.1 Table of Budget 63

7.1 Complex Engineering Problems (Ps): mapping with Knowledge Profiles (K), CLOs, and PLOs 69

7.2 Complex Engineering Activities (As): mapping with CLOs and PLOs 70

8.1 **Preliminary hospital external-testing results.** Each ADNI-trained model applied to the hospital pilot set ($n = 8$: 4 CN, 4 MCI; no AD cases). "Hosp AUC*" is CN-vs-MCI ranking quality on the pilot set. . 76

B.1 Configuration of the main experimental runs. 91

List of Abbreviations

AD	Alzheimer's Disease
ADNI	Alzheimer's Disease Neuroimaging Initiative
AMP	Automatic Mixed Precision
AUC / AUROC	Area Under the (Receiver Operating Characteristic) Curve
CE	Cross-Entropy (loss)
CN	Cognitively Normal
CNN	Convolutional Neural Network
CV	Cross-Validation
DenseNet	Densely Connected Convolutional Network
F1	F1-score (harmonic mean of precision and recall)
GAP	Global Average Pooling
Grad-CAM	Gradient-weighted Class Activation Mapping
IG	Integrated Gradients
MCI	Mild Cognitive Impairment
MONAI	Medical Open Network for Artificial Intelligence
MPRAGE	Magnetization-Prepared Rapid Gradient-Echo
MRI	Magnetic Resonance Imaging
NIfTI	Neuroimaging Informatics Technology Initiative (file format)
RAS	Right–Anterior–Superior (canonical image orientation)
ReLU	Rectified Linear Unit

ResNet	Residual Network
ROC	Receiver Operating Characteristic
ROI	Region of Interest
Swin	Shifted-Window Transformer
ViT	Vision Transformer
VRAM	Video Random-Access Memory
XAI	Explainable Artificial Intelligence

Chapter 1

Introduction

This chapter presents an overview of the research problem, motivation, and goals underlying the development of a deep-learning–based Alzheimer's disease detection system using 3D MRI data. It outlines the clinical significance of early Alzheimer's diagnosis, the challenges faced by existing methods, and the rationale for adopting and benchmarking a hybrid 3D CNN–Vision Transformer approach under a rigorous, leakage-free evaluation. The chapter also defines the problem statement, research objectives, research questions, scope of the work, expected outcomes, and the broader societal, ethical, and healthcare impacts associated with this project.

1.1 Background and Motivation

Alzheimer's disease (AD) is a progressive neurodegenerative disorder that affects memory, cognition, and daily functioning [38]. With the global rise in aging populations, Alzheimer's has become a major medical and social challenge. Early and accurate diagnosis is essential, as timely intervention can slow cognitive decline and improve patient outcomes. Structural Magnetic Resonance Imaging (MRI) is one of the most effective non-invasive modalities for identifying early brain changes, particularly in regions such as the hippocampus and medial temporal lobe.

Recent advances in deep learning—especially Convolutional Neural Networks (CNNs) and Vision Transformers (ViTs)—have shown great promise in automated medical image analysis [21, 23]. However, two problems recur in the literature. First, most existing Alzheimer's classification systems operate on 2D slices, which discards the full volumetric context of the scan. Second, and more seriously, many report very

high accuracies obtained by splitting the data at the level of individual slices, so that different slices of the *same* patient appear in both training and testing; this data leakage inflates results and makes them unreliable on new patients [44,45]. Distinguishing the transitional mild-cognitive-impairment (MCI) stage from cognitively normal (CN) and full AD remains genuinely hard. These issues motivate a fully volumetric, hybrid deep-learning framework evaluated under a strict subject-level protocol.

This research builds and benchmarks a family of 3D MRI-based models—a 3D CNN, a pretrained 3D ResNet, a 3D ViT, a Swin Transformer, and a hybrid that fuses a 3D CNN (local spatial features) with a 3D ViT (global contextual features)—on the ADNI dataset, and uses Grad-CAM and related 3D explainability methods for interpretability. The central question is whether such hybridization measurably improves Alzheimer's classification over single models when the evaluation is honest.

1.2 Problem Statement

Despite significant progress in deep learning for Alzheimer's disease detection, several challenges remain. Most models rely on 2D MRI slices, losing three-dimensional spatial context. CNN-based architectures capture local features well but model global relationships weakly, whereas transformer-only approaches need large datasets and struggle on small medical cohorts. Crucially, a large share of the reported high accuracies stem from evaluation protocols that leak patient data across the train/test boundary, so the numbers do not reflect real generalization. The lack of interpretability further reduces clinical trust, and class imbalance (especially the scarce MCI group) hinders multi-class performance.

There is therefore a need for a system that (i) processes full 3D MRI volumes, (ii) combines local and global feature extraction, (iii) is evaluated *subject-level* so results are trustworthy, and (iv) provides interpretable outputs.

Accordingly, this work proposes and benchmarks a hybrid 3D CNN–ViT architecture against strong single-model baselines, on both binary (CN-vs-AD) and three-class (CN/MCI/AD) tasks, with Grad-CAM-based explainability.

1.3 Objectives of the Project

1. To develop a hybrid 3D CNN + 3D Vision Transformer model that fuses local and global structural features for Alzheimer's classification from full 3D MRI volumes.

2. To benchmark this hybrid against strong single-model baselines (3D CNN, pre-trained 3D ResNet, 3D ViT, Swin Transformer) on the same ADNI data and subject-level splits, and thereby determine whether hybridization actually improves accuracy.

3. To evaluate both the binary CN-vs-AD task and the harder three-class CN/MCI/AD task under a leakage-free, subject-level five-fold protocol.

4. To integrate 3D Grad-CAM and related explainability methods for visualizing the brain regions influencing predictions.

1.4 Research Questions / Hypotheses

This project is guided by the following research questions:

- **RQ1:** Does fusing local feature extraction (3D CNN) with global contextual modeling (3D Vision Transformer) improve Alzheimer's classification accuracy over single-model architectures, under a subject-level, leakage-free evaluation?
- **RQ2:** Can 3D Grad-CAM / attribution-based interpretability provide clinically meaningful and anatomically consistent explanations for the model's decisions?

1.5 Scope of the Work

The scope covers 3D T1-weighted MRI volumes from the ADNI dataset and the design, training, and evaluation of a hybrid 3D CNN–ViT architecture alongside single-model baselines. Two classification tasks are addressed: binary CN-vs-AD and three-class CN/MCI/AD. All models are compared on identical subject-level five-fold splits,

with local and global explainability. The study focuses exclusively on structural 3D MRI–based classification and does not extend to clinical deployment; other modalities (e.g., PET, cognitive scores) and additional datasets are left to future work.

1.6 Expected Outcomes

The expected outcomes of this project include:

1. A working hybrid 3D CNN–ViT model and a set of single-model baselines for Alzheimer's classification.
2. A rigorous, leakage-free subject-level benchmark quantifying whether the hybrid outperforms single models on binary and three-class tasks.
3. A reproducible 3D MRI preprocessing and training pipeline.
4. Visual explanations using Grad-CAM and related methods, highlighting the affected brain regions.

1.7 Impacts of the Project

1.7.1 Impact on Societal and Cultural Issues

The project promotes early diagnosis and awareness of Alzheimer's, helping families and caregivers prepare for long-term support. It contributes to reducing stigma through improved understanding and detection. By providing automated diagnostic support, the system also reduces dependency on specialized radiologists, making cognitive health screening more accessible.

1.7.2 Impact on Health, Safety, and Legal Issues

The project promotes safer clinical decision support by providing transparent, explainable predictions. It is intended strictly as a research and decision-support tool,

not an autonomous diagnostic device. Handling MRI data raises privacy and ethical concerns, addressed here through the use of already-anonymized, ethically approved data and honest reporting of performance.

1.7.3 Impact on Environment and Sustainability Issues

The design favours computational efficiency—cached preprocessing, mixed-precision training on a single GPU, and compact models—reducing energy use compared with large, transformer-only systems trained on massive data.

1.8 Report Organization

The report is structured as follows:

1. **Chapter 1** introduces the project: background, motivation, problem statement, objectives, research questions, scope, expected outcomes, and impacts.
2. **Chapter 2** provides the theoretical background and literature review—Alzheimer's disease, MRI biomarkers, CNN/ViT fundamentals, and a comparative analysis of related work with the research gap.
3. **Chapter 3** describes the system analysis and architectural design: requirements, the proposed 3D CNN–ViT architecture, design diagrams, algorithmic flow, and design rationale.
4. **Chapter 4** details the methodology and implementation: the ADNI dataset and curation, the subject-level evaluation protocol, preprocessing, the five 3D models, and the training recipe.
5. **Chapter 5** presents the experimental results and analysis: binary and three-class benchmarks, the single-vs-hybrid comparison, transfer-learning and transformer findings, explainability, and a comparison with the literature.
6. **Chapter 6** presents project planning, timeline, and budget.

7. **Chapter 7** outlines the standards, design constraints, and professional practices, including CEP/CEA coverage.

8. **Chapter 8** concludes the thesis—key findings, contributions, limitations, and future work.

Chapter 2

Background and Literature Review

This chapter provides the theoretical foundation of Alzheimer's disease detection and a review of related research. Section 2.1 introduces basic concepts, medical background, and machine learning techniques used in the field. Section 2.2 discusses existing systems and important research papers similar to our topic. Section 2.3 analyzes their strengths and weaknesses. Section 2.4 identifies research gaps that motivate our proposed CNN–ViT fusion system. Finally, Section 2.5 summarizes the chapter.

2.1 Preliminaries

This section explains the fundamental theories and concepts needed to understand our project. It covers the medical background of Alzheimer's Disease, MRI characteristics, preprocessing techniques, and deep-learning models such as CNNs, Vision Transformers, and explainability methods. Definitions, formulas, and technical acronyms used later in the thesis are also introduced.

2.1.1 Overview of Alzheimer's Disease

Alzheimer's Disease (AD) is a progressive neurodegenerative disorder and the leading cause of dementia worldwide [29,38]. It slowly damages memory, reasoning, and daily functioning. As the global population ages, millions of people are at risk, making early detection extremely important for timely treatment, slowing brain decline, and improving quality of life.

Traditionally, diagnosing AD involves memory assessments and manual MRI evalua-

tion by neurologists. This process is slow, subjective, and heavily dependent on expert availability. With the growing number of elderly individuals, there is an urgent need for automated and reliable systems for Alzheimer's detection.AD develops gradually and spreads through specific brain regions over time:

Hippocampus (Memory Center): The hippocampus is one of the earliest regions affected in Alzheimer's disease. It plays a central role in forming new memories and supporting spatial navigation. As the disease progresses, the hippocampus undergoes shrinkage, known as hippocampal atrophy, which is a strong early biomarker clearly visible in MRI scans [7, 14].

Temporal Lobe: The temporal lobe is responsible for language processing, facial recognition, and understanding meaning. Degeneration in this region leads to difficulty remembering names, recognizing familiar people, and comprehending spoken or written language. These symptoms commonly appear in the early stages of Alzheimer's.

Parietal Lobe: The parietal lobe contributes to spatial awareness, coordination, and the ability to perform daily tasks. When Alzheimer's affects this region, individuals may struggle with navigation, become disoriented even in familiar environments, and find it difficult to carry out routine activities.

Frontal Lobe: The frontal lobe governs decision-making, planning, behavior regulation, and social judgment. In later stages of Alzheimer's disease, deterioration of this area results in personality changes, impaired judgment, reduced problem-solving abilities, and noticeable shifts in behavior.

Cerebral Cortex: The cerebral cortex, which is responsible for higher-level thinking and reasoning, becomes progressively thinner due to widespread neuron loss. This cortical thinning significantly contributes to cognitive decline and difficulties with planning, reasoning, and complex thought processes.

Ventricles: The ventricles are fluid-filled spaces within the brain that enlarge as Alzheimer's progresses. This enlargement occurs because surrounding brain tissues shrink, making ventricular expansion a key MRI indicator of overall brain atrophy

and structural degeneration.

2.1.2 MRI Characteristics of Alzheimer's Disease

MRI scans provide structural information that strongly correlates with Alzheimer's progression. Common MRI biomarkers include [14, 18]:

- Hippocampal atrophy
- Enlarged ventricles
- Temporal lobe shrinkage
- Cortical thinning
- Reduced gray matter volume in parietal and frontal lobes

2.1.3 Key Concepts, Formulas, and Models

This subsection introduces the technical machinery used throughout the thesis: MRI preprocessing, the three deep-learning model families (CNN, Vision Transformer, Swin Transformer) and their fusion, transfer learning, the evaluation metrics, and the explainability methods. Because this work operates on *full 3D volumes*, the formulas below are given in their volumetric form.

MRI Preprocessing

Preprocessing standardizes raw scans into a common orientation, physical resolution, and intensity range before they enter the network.

1. **Intensity (z-score) normalization** rescales each volume to zero mean and unit variance over its non-zero voxels, removing scanner-dependent brightness offsets:

$$x' = \frac{x - \mu}{\sigma}.$$

2. **Spatial resampling and resizing.** Volumes are resampled to an isotropic spacing (here 1.5 mm) and resized/padded to a fixed tensor (here 128^3 or 96^3) so that every input has identical dimensions.

3. **Foreground cropping** removes empty background around the head, focusing the model on tissue.

4. **Data augmentation** (train only) — random flips, small rotations/scalings, noise, and intensity perturbations — expands effective dataset size and reduces overfitting.

Convolutional Neural Networks (CNNs)

CNNs extract local spatial features (edges, textures, shapes) by sliding learnable 3D kernels over the volume, interleaved with non-linear activations (e.g. ReLU) and pooling. A 3D convolution at position (i, j, k) is

$$y_{i,j,k} = \sum_a \sum_b \sum_c w_{a,b,c}\, x_{i+a,\, j+b,\, k+c} + b,$$

and stacking many such layers yields a hierarchy from low-level texture to high-level anatomy. This work uses **DenseNet-121** [17], in which each layer receives the feature maps of all preceding layers, improving gradient flow and parameter efficiency — well suited to small medical datasets. CNNs excel at local patterns but have a limited receptive field, so they can miss long-range relationships between distant brain regions.

Vision Transformers (ViT)

ViTs split an input into fixed-size patches, embed each as a token, and model *global* relationships with self-attention [12, 42]. For a 3D volume of size $H \times W \times D$ and cubic patches of side p, the number of tokens is

$$N = \frac{H \times W \times D}{p^3},$$

each patch x_p^i is linearly projected and given a positional encoding,

$$z_0 = \left[x_p^1 E;\, x_p^2 E;\, \ldots;\, x_p^N E\right] + E_{\text{pos}},$$

and every transformer layer applies multi-head self-attention,

$$Q = XW_q, \quad K = XW_k, \quad V = XW_v, \qquad \text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right) V,$$

where Q, K, V are the query, key, and value projections and d_k the key dimension. ViTs capture how distant regions relate — useful because AD affects multiple connected areas — but they have weak inductive bias and are notoriously data-hungry, which (as shown in Chapter 5) causes a from-scratch 3D ViT to underperform on a few-hundred-subject cohort.

Swin Transformer

The Swin Transformer restores some of the CNN's locality by computing attention within local *shifted windows* and building a hierarchical, multi-scale feature pyramid. This makes it far more efficient than a plain ViT on 3D data and the strongest transformer option for volumetric medical imaging [24]; here the SwinUNETR-style encoder [15] is used as a classification backbone.

Hybrid CNN–ViT Fusion

A hybrid model runs a CNN and a transformer branch on the same volume and fuses their feature vectors, combining local texture with global context. Two fusion strategies are considered: **late concatenation**, $z = [f_{\text{cnn}} \,\|\, f_{\text{vit}}]$, followed by a classifier head; and **cross-attention**, in which the CNN feature acts as the query attending to the transformer feature. Whether this fusion beats either branch alone is the central research question of this thesis.

Transfer Learning

Because medical datasets are small, weights pretrained on large corpora are often reused. This work evaluates a 3D ResNet [16] initialized with **MedicalNet** weights [11] (pretrained on 23 medical datasets) against training from scratch; the outcome (Chapter 5) is a useful cautionary tale about when medical pretraining does and does not transfer.

Evaluation Metrics

Because the cohort is imbalanced (CN is the majority; MCI the minority), overall accuracy alone is misleading — a model can look good simply by favouring the majority class — so per-class and *averaged* F1 scores are central [35]. Every metric below is derived from the confusion-matrix counts: true positives (TP), true negatives (TN), false positives (FP), and false negatives (FN).

Overall correctness is the **accuracy**, the fraction of all scans classified correctly:

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN}.$$

For each class, **precision** is the fraction of predicted positives that are correct, **recall** (sensitivity) is the fraction of actual positives that are recovered, and the **F1-score** is their harmonic mean — high only when *both* precision and recall are high:

$$\text{Precision} = \frac{TP}{TP + FP}, \qquad \text{Recall} = \frac{TP}{TP + FN}, \qquad F1 = \frac{2\,\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}.$$

Specificity (the true-negative rate), important in a screening setting, is

$$\text{Specificity} = \frac{TN}{TN + FP}.$$

For the multi-class task the per-class F1 scores are aggregated in two ways. The **macro-F1** is the *unweighted* mean of the per-class F1 over the C classes, whereas the **weighted-F1** averages them in proportion to each class's support n_c (with $N =$

$\sum_c n_c$):

$$\text{macro-F1} = \frac{1}{C}\sum_{c=1}^{C} F1_c, \qquad \text{weighted-F1} = \sum_{c=1}^{C} \frac{n_c}{N} F1_c.$$

Macro-F1 is adopted as the primary metric of this thesis. Because it gives every class equal weight regardless of how many samples it has, it refuses to let strong performance on the large CN class mask weak performance on the scarce MCI class; weighted-F1 and accuracy, which are both dominated by the majority class, are reported alongside for completeness but are treated as secondary. Finally, the **ROC-AUC** — computed one-vs-rest for the three-class task — summarizes ranking quality across *all* decision thresholds and is therefore threshold-independent. All metrics are computed at both scan level and, by averaging the softmax outputs of a subject's multiple scans, at subject level, the latter being the clinically meaningful figure.

A note on the "z-score". Where this thesis mentions a *z-score*, it refers to the intensity-normalization transform applied to every MRI volume during preprocessing, $x' = (x - \mu)/\sigma$, which standardizes each voxel intensity to zero mean μ and unit standard deviation σ over the non-zero voxels and removes scanner-dependent brightness differences. It is a data-preparation step (Section 2.1.3), not a classification metric, and is noted here only to distinguish it from the evaluation metrics above.

Cross-Validation and Data Leakage

A recurring, critical flaw in the literature is **data leakage** [6,44,45]: when a dataset is split at the level of individual 2D slices, different slices of the *same* patient land in both training and test sets, so the model effectively memorizes patients and reports inflated accuracy that will not hold on new patients. The correct protocol is a **subject-level split**, in which all scans of a subject are kept entirely within one fold. This thesis enforces subject-level, stratified k**-fold cross-validation**, reporting mean $\pm$ standard deviation across folds — a more honest estimate of generalization than a single split.

Explainable AI (XAI)

Interpretability is essential for clinical acceptance. Several complementary methods are used:

- **Grad-CAM / Grad-CAM++ / Score-CAM** [10, 39]: class-discriminative heatmaps from convolutional feature-map gradients; coarse but robust.
- **Integrated Gradients / SmoothGrad / Saliency** [40, 41]: voxel-level attributions along the input–baseline path; fine-grained.
- **Occlusion sensitivity**: measures the drop in confidence when regions are masked.
- **Attention rollout** [1]: aggregates transformer attention across layers.
- **LIME / SHAP** [27, 36]: model-agnostic local explanations.

Agreement between these methods on AD-relevant anatomy (hippocampus, medial temporal lobe, ventricles) is evidence that a model has learned biology rather than artefacts.

2.2 Related Works / Existing Systems

Automated Alzheimer's Disease (AD) detection using MRI has gained significant attention as deep learning models continue to improve diagnostic accuracy. Recent studies have adopted Vision Transformers (ViT), recurrent networks, and hybrid attention-based architectures to classify AD stages more effectively. This section reviews two key studies relevant to our research, detailing their contributions, methodologies, results, and limitations.

The study in [20] explored the use of Vision Transformers (ViTs) for MRI-based Alzheimer's classification using a ViT-Base Patch-16 model across four stages: ND,

VMD, MD, and MOD. The authors applied standard preprocessing, including intensity normalization and resizing to 224×224, before treating MRI slices as patch tokens processed through multi-head self-attention. The model achieved 98.19% accuracy, showing ViTs' strength in capturing global structural features. However, the approach relied solely on 2D slices rather than full 3D MRI volumes, limiting volumetric understanding. The dataset size was also small, and early-stage differentiation (ND vs. VMD) remained challenging. Additionally, no explainability methods (e.g., Grad-CAM) were used, making the model's decisions difficult to interpret. Overall, the study demonstrates ViT's potential but highlights key gaps in data depth, volumetric modeling, and interpretability.

The study in [28] introduced a hybrid ViT–GRU model for Alzheimer's classification, evaluating it across multiple datasets including Kaggle (binary and four-class) and ADNI (three-class). The pipeline used standard preprocessing before extracting ViT patch embeddings, which were then passed through a GRU to capture sequential dependencies. Explainability was incorporated via LIME, SHAP, and attention maps. The model achieved excellent results—99.69% (binary), 99.53% (four-class), and 99.26% (ADNI)—showing the strength of combining transformer-based spatial features with recurrent temporal modeling. However, the approach remained computationally heavy, relied on 2D slices rather than full 3D MRI volumes, and faced class imbalance issues in early-stage categories. Overall, the study presents a strong hybrid architecture but still lacks volumetric modeling and efficient scalability.

The study in [4] proposed a hybrid approach where ResNet-50 is used for CNN-based feature extraction and the resulting features are classified using Softmax, SVM, and Random Forest. The MRI data (from ADNI and MIRIAD) underwent skull stripping, smoothing, resizing, augmentation, and conversion of 3D volumes into 2D slices before feature extraction. Among the classifiers, ResNet-50 + Softmax achieved the best results, reaching 99% accuracy on ADNI and 96% on MIRIAD, outperforming SVM and Random Forest by a large margin. The study shows that Softmax aligns best with the deep features learned by ResNet-50, producing more stable decision

boundaries. However, the method still relies on 2D slices rather than full 3D MRI volumes, and the use of classical ML classifiers limits end-to-end optimization.

The study in [5] proposed a ViT-based model for multi-class Alzheimer's detection using T1-weighted MRI scans across ND, VMD, MD, and MoD categories. After normalization, resizing, skull removal, and augmentation, the authors used the ViT-Base-Patch16-224 architecture to divide MRI slices into patches and process them through transformer encoder layers, enabling strong global feature modeling. The system achieved 99.83% accuracy, with sensitivity, specificity, and F1-scores above 99% for most classes, showing particularly strong performance in identifying mild and moderate dementia. Although early-stage separation (ND vs. VMD) remained slightly more challenging, the results were still above 98%. Overall, the study demonstrates ViT's effectiveness for multi-class AD detection, though it remains limited to 2D slices rather than full 3D volumes.

The study in [32] proposed a ViT-based model for four-class Alzheimer's classification using a small Kaggle MRI dataset of 576 images. After cropping, resizing to 224×224, normalization, and augmentation, the authors used a ViT-Base Patch16 model to process MRI slices as patch embeddings through multi-head self-attention, followed by a Softmax classifier. The model achieved around 71% accuracy, performing better on ND and MOD classes than on VMD and MD, where subtle structural differences caused misclassification. Although the ViT outperformed CNN baselines like VGG19 and DenseNet169, the study was constrained by limited and imbalanced data, reliance on 2D slices, and the absence of explainability techniques. Overall, the work shows the potential of ViT for MRI-based AD detection but highlights the need for larger datasets and more advanced architectures for reliable performance.

The study in [3] proposed an AI framework combining MRI synthesis, deep learning, and interpretability techniques to improve early-stage Alzheimer's prediction using ADNI data. The authors generated synthetic MRI scans with GANs to address class imbalance and applied preprocessing steps such as bias correction, skull stripping, and

spatial normalization. A deep-learning classifier was then used alongside Grad-CAM to identify subtle structural changes in regions vulnerable to AD. The inclusion of synthetic data improved early-risk detection, and the explainability analysis highlighted clinically meaningful areas. However, the approach depended heavily on synthetic image quality, suffered from inconsistency in GAN outputs, and required significant computational resources for generating 3D MRI volumes. Overall, the study shows the promise of combining generative modeling with interpretable deep learning but also underscores its practical limitations.

The study in [2] introduced a multi-stage framework for long-term Alzheimer's progression prediction using longitudinal ADNI MRI data. The pipeline combined ensemble transfer learning for CN→MCI prediction, a 3D ViT-based GAN for generating synthetic future MRI scans, and Grad-CAM–guided ROI extraction for MCI→AD classification, ultimately estimating CN→AD risk through probability fusion. The model achieved 0.85 accuracy and 0.86 F1-score, outperforming CNN-only baselines and providing interpretable ROI visualizations. However, the approach was limited by the small number of progressive CN subjects, the heavy computational demands of the 3D ViT-GAN, and its dependence on two-year intervals due to restricted longitudinal data. Overall, the study shows the potential of combining 3D deep learning and generative modeling for progression forecasting but highlights scalability and data limitations.

The study in [13] proposed a dual-branch CNN for multi-class Alzheimer's classification, where 3×3 and 5×5 convolutional branches captured fine and coarse structural features before concatenation and Softmax classification. Trained on ADNI MRI data with augmentation and ADASYN oversampling, the model achieved strong results—99.43% (3-way), 99.57% (4-way), and 99.30% (5-way)—outperforming ResNet, Xception, and Inception-V3. Grad-CAM visualizations highlighted clinically relevant regions such as hippocampal and cortical atrophy. However, the method relied on 2D slices, required substantial computational resources, and was trained on a single dataset, limiting generalizability. Overall, the work demonstrates that multi-scale

CNN branches can significantly enhance MRI-based AD detection.

The study in [37] proposed an ROI-based 3D ViT ensemble for early Alzheimer's detection, training 138 region-specific ViT models and combining their outputs using a DBN meta-classifier. Evaluated on ADNI MRI data, the framework achieved strong results in binary tasks—90% accuracy (AD vs CN) and 94% (pMCI vs sMCI)—while three-class performance remained moderate at 60%. The ROI-based approach improved interpretability by highlighting key regions such as the hippocampus, amygdala, and insula. However, the method was extremely computationally heavy and relied on precise ROI segmentation, which can limit scalability and robustness. Overall, the study shows the potential of region-wise 3D ViT models but also reveals challenges in multiclass generalization and efficiency.

The study in [30] presented a ViT-Base Patch-16 model for four-class Alzheimer's classification using the OASIS-1 MRI dataset. After normalization, resizing to 224×224, and contrast enhancement, MRI slices were divided into fixed-size patches and processed using multi-head self-attention. The model achieved 97.08% accuracy, outperforming CNN baselines due to its ability to capture global spatial relationships. However, it relied solely on 2D slices, limiting volumetric context, and the small dataset led to weaker performance in early-stage differentiation (ND vs VMD). The absence of explainability tools further reduced clinical interpretability. Overall, the work shows strong ViT capability for MRI feature extraction but highlights ongoing challenges in dataset size, 3D modeling, and explainability.

The study in [43] proposed a hybrid EfficientNet-B0 + Swin Transformer model (with DCGAN-based augmentation) for Alzheimer's disease prediction using structural MRI from the OASIS dataset, augmented to 2,600 images per class. After standard preprocessing and augmentation, the CNN extracted low-level spatial features while the Swin Transformer applied shifted-window attention to capture broader contextual information. The model achieved 95.34% accuracy, outperforming CNN-only baselines, but relied on 2D slices, was not validated on any external dataset, and its DCGAN-

synthesized images risk distorting the data distribution. The authors also noted weaker performance in early-stage discrimination and the absence of interpretability methods, highlighting ongoing challenges in dataset size, 3D structural modeling, and explainability.

The study in [8] reviewed 44 deep learning models—including 3D CNNs, Vision Transformers, and hybrid CNN–ViT architectures—for Alzheimer's disease classification using 3D MRI. The authors found that CNNs remain dominant, with models like 3D-sVoxCNN and BG-3DM2F achieving accuracies above 98% by capturing fine-grained anatomical changes. ViT-based models showed rapidly improving performance, often exceeding 95% due to their strength in modeling global structural patterns, while hybrid systems effectively combined both feature types and reached 90–97% accuracy. The review concludes that all three model families are highly effective but still face challenges related to dataset imbalance, limited multimodal data, and inconsistent evaluation practices.

2.3 Comparative Analysis of Related Works

Table 2.1: Comparative Analysis of Related Works

Paper	**Model Type Used**	**Dataset Used**	**Limitations**	**Accuracy / Performance**
Pandey et al. (2025) [32]	Pretrained ViT	Kaggle Alzheimer MRI (5760 images)	Strong dataset imbalance; no Grad-CAM explainability; not a true 3D volumetric MRI approach	Train 82%, Val 72%
Yagis et al. (2021) [45]	2D CNNs — VGG16 (frozen + fine-tuned)	ADNI (100 AD + 100 CN), OASIS, PPMI	Slice-level train/test split leaks slices of the same subject into both sets	Slice-level 95.2–96.9%; subject-level 66.5–70.1%
Aghaei & Moghaddam (2025) [2]	Ensemble Transfer Learning + 3D models + ViT-GAN + 3D-CNN	ADNI T1-weighted MRI + demographic data	Limited progressive CN samples; high computational cost due to 3D ViT-GAN	Accuracy 0.85; F1 0.86

Wen et al. (2020) [44]	2D-slice, 3D-patch, ROI & 3D-subject CNNs	ADNI + AIBL (T1-weighted MRI)	Survey found >50% of reviewed papers had data leakage (slice-level / augmentation); results not reproducible	Subject-level AD-vs-CN 85–88%; leaky pipelines overestimate
Saoud & AlMarzouqi (2024) [37]	138 × 3D ViTs + Deep Belief Network ensemble	MALPEM-ADNI (532 MRI)	Small dataset; slice-level split; only 60% accuracy for 3-class	AD-vs-CN 90%; sMCI-vs-pMCI AUROC 95%
Velu & Jaisankar (2025) [43]	EfficientNet-B0 + Swin Transformer + DCGAN	OASIS (augmented to 2600/class)	2D slice-based; no external dataset testing; synthetic-data bias due to DCGAN	95.34% accuracy

2.4 Research Gap / Limitations of Existing Methods

The reviewed works report very high accuracies, but a closer reading of their evaluation protocols reveals several limitations that this thesis directly targets:

1. **Evaluation is often not leakage-free.** The majority of the highest-scoring systems (98–99%) split the data at the level of 2D slices or use the curated Kaggle 2D set, allowing a patient's slices to appear in both training and testing. The one clearly subject-level comparator [37] reports a far more sober 90% (AD-vs-CN) and 60% (three-class), suggesting the headline numbers are inflated by leakage. A rigorous, subject-level benchmark is therefore missing.

2. **Full-volume 3D CNN–ViT fusion is underexplored.** Most studies use

either 2D slices or a single model family; genuine 3D fusion of local (CNN) and global (transformer) features on whole volumes, evaluated fairly against single-model baselines, is rare.

3. **The MCI / early stage is the real bottleneck** and is frequently sidestepped by reporting only binary or slice-level multi-class numbers, obscuring how hard the transitional stage actually is.

4. **Explainability is inconsistently applied**, especially for transformer models, and rarely reported honestly with respect to preprocessing (e.g. whether the volumes are skull-stripped or atlas-registered).

5. **Transformer models are computationally heavy and data-hungry**, and their behaviour on small 3D cohorts — where they often fail without large-scale pretraining — is seldom reported as an explicit finding.

These gaps motivate the design of this thesis: a single-source, subject-level, leakage-free benchmark that fairly compares single and hybrid 3D architectures and reports honest accuracies together with anatomically grounded explanations.

2.5 Summary

This chapter presented the medical and technical background for Alzheimer's detection from MRI — AD pathology and affected regions, MRI biomarkers, 3D preprocessing, the CNN / ViT / Swin / hybrid model families, transfer learning, evaluation metrics, the crucial issue of data leakage, and explainability methods. It then reviewed twelve recent studies and compared their models, datasets, strengths, and limitations. The analysis exposed a key gap: reported accuracies are often inflated by slice-level leakage, and fair subject-level comparisons of 3D single-vs-hybrid models are scarce. This directly motivates the proposed CNN–ViT fusion system and the leakage-free evaluation protocol developed in the following chapters.

Chapter 3

System Analysis and Design

This chapter presents the requirement analysis and system architecture of the proposed Alzheimer's disease detection system. The system integrates 3D CNN-based local feature extraction with Vision-Transformer-based global attention, fuses the two, classifies the result, and explains it with 3D attribution methods — all evaluated on the ADNI dataset under a leakage-free, subject-level protocol.

3.1 Requirement Analysis

Requirement analysis was conducted by reviewing:

- Alzheimer's disease–related clinical and imaging literature
- Data characteristics and methodology from the reference papers
- Observed limitations (especially evaluation leakage) and performance metrics

3.1.1 Stakeholder Identification

Table 3.1: Stakeholder Identification and Description

Stakeholder	**Role in System**	**Interest**
Neurologists / Clinicians	Use the system's predictions and visual explanations to support diagnosis and decision-making.	Want accurate, reliable, and interpretable outputs that improve clinical confidence.
Researchers / Data Scientists	Develop, train, and evaluate the deep-learning models and ensure scientific validity.	Need transparent workflows, reproducible results, and honest performance insights.
Patients / Families	Indirect beneficiaries who receive improved diagnostic support through the system.	Prefer early detection, reduced uncertainty, and clinically meaningful outputs.
University Supervisors	Assess the methodology, implementation, and scientific contribution of the system.	Expect clear documentation, proper justification of methods, and strong research outcomes.
System Developers(Team)	Design, implement, and optimize the full pipeline from preprocessing to evaluation.	Need modular structure, maintainability, and reproducibility for future expansion.

In addition to the roles above, this project engaged four practising clinicians as expert stakeholders to review the system's outputs and judge its clinical reliability; their consolidated feedback is summarised in Table 3.2. In particular, **Dr. Ziaur Rahman** (Physician & Surgeon, **Comfort Diagnostic Center**) guided the labelling of the hospital scans used in the preliminary external-validation study (Section 8.4); those labels were derived from routine radiology reports and are therefore treated as *weak*

labels rather than research-protocol diagnoses. These clinicians are key stakeholders for assessing the system's real-world, cross-site applicability and the clinical value of its explainability outputs.

Table 3.2: **Clinical stakeholder feedback.** Opinions of four practising clinicians on the reliability of the system and the clinical relevance of its Grad-CAM explanations.

Name	**Specialization**	**Clinical Reliability Opinion**	**Grad-CAM Clinically Relevant?**	**Helpful for Diagnosis?**
Dr. Ziaur Rahman	Physician & Surgeon	Reliable	Yes, highly relevant	Yes
Dr. Abul Latif	Radiologist	Reliable	Yes, improves interpretability	Yes
Dr. Tania Kabir	Radiologist	Reliable	Partially relevant	Yes
Dr. Subir Chandra Das	Neurologist	Technically reliable	Yes, essential for model transparency	Yes

3.1.2 Requirement Identification Methods

- Analysis of existing research papers (CNN, ViT, Swin, and hybrid AD classification)
- Comparative study of dataset characteristics and, critically, evaluation protocols
- Workflow observation from 3D preprocessing pipelines (reorientation, resampling, normalization)
- Evaluation metrics from the literature (accuracy, macro-F1, AUROC)

These sources provided the core requirements for the system functionality.

3.1.3 Functional Requirements (FR)

This is the list of Functional Requirements(FR):

Table 3.3: Table of Functional Requirements

Requirement ID	**Functional Requirement**	**Description**
FR1	MRI Input Handling	The system must accept 3D T1-weighted MRI volumes (NIfTI).
FR2	Preprocessing Pipeline	Reorient to RAS, resample to isotropic spacing, foreground-crop, z-score normalize, and resize to a fixed tensor; augment during training.
FR3	Subject-Level Splitting	Build stratified, subject-disjoint cross-validation folds so no subject's scans cross the train/test boundary.
FR4	Feature Extraction	Provide 3D CNN, ResNet, ViT, and Swin backbones behind a common interface for extracting spatial/contextual features.
FR5	Classification Module	Classify binary CN-vs-AD and three-class CN/MCI/AD using a shared softmax head.
FR6	Explainable AI	Generate Grad-CAM, Integrated-Gradients, and attention-rollout overlays for interpretability.

FR7	Performance Evaluation	Compute accuracy, macro/weighted-F1, per-class precision/recall, ROC-AUC, and confusion matrices at scan and subject level.

3.1.4 Non-Functional Requirements (NFR)

Below is a list of Non-Functional Requirements(NFR):

Table 3.4: Table of Non-Functional Requirements

Requirement ID	**Non-Functional Requirement**	**Description**
NFR1	Accuracy	Achieve a strong, *honest* subject-level result (target: high-70s to low-80s% accuracy / $\geq$ 0.78 macro-F1 on binary CN-vs-AD), rather than an inflated leakage-based number.
NFR2	Reliability	Produce consistent results across folds; report mean $\pm$ std, not a single lucky split.
NFR3	Performance	Support GPU-accelerated training within a 16 GB VRAM budget; inference is fast.
NFR4	Reproducibility	Fixed seeds, saved configs and splits, and one-command regeneration of results and figures.
NFR5	Usability	Clinician-friendly, interpretable heatmap outputs.

NFR6	Maintainability	Modular pipelines for data, models, training, evaluation, and explainability.
NFR7	Security	Use only anonymized, ethically approved data; protect MRI privacy.

3.2 System Overview / Architecture

The proposed system follows a modular deep-learning pipeline that combines convolution-based local feature extraction with transformer-based global attention. It preprocesses raw 3D MRI, extracts local and global features through a dual-path network, fuses the representations, classifies the Alzheimer's status, and explains the decision — all under a subject-level evaluation that keeps the reported accuracy honest.

3.2.1 High-Level Architecture

The system consists of five major modules:

1. Data Acquisition and Curation Module

This module ingests 3D T1-weighted MRI volumes from ADNI, indexes them by image ID, attaches the CN/MCI/AD labels, and removes off-pipeline scans. It builds the stratified, subject-level cross-validation folds that guarantee leakage-free evaluation.

2. Preprocessing Module

This component reorients volumes to RAS, resamples them to 1.5 mm isotropic spacing, crops the foreground, applies z-score intensity normalization over non-zero voxels, and resizes to a fixed 128^3 (CNN/ResNet) or 96^3 (ViT/Swin/hybrid) tensor. Deterministic outputs are cached; training augmentation (flips, affine, noise, intensity jitter) is applied on the fly.

3. Feature Extraction and Classification Module

- **CNN backbone** — 3D DenseNet-121 (local features).
- **Pretrained CNN** — MedicalNet 3D ResNet (transfer-learning baseline).
- **Transformer backbones** — 3D ViT and Swin (global features).
- **Hybrid** — CNN+ViT with late-concatenation or cross-attention fusion.
- **Classifier** — a shared dropout+linear+softmax head over the backbone/fused features.

4. Explainability Module (XAI)

This module produces Grad-CAM / Grad-CAM++ / Score-CAM heatmaps, Integrated-Gradients and SmoothGrad attributions, occlusion sensitivity, and attention rollout for the transformer branch, overlaid on the MRI for clinical interpretation.

5. Model Evaluation and Reporting Module

This component computes accuracy, macro/weighted-F1, sensitivity, specificity, ROC-AUC, and confusion matrices at both scan and subject level, and aggregates the five folds into mean $\pm$ std summaries with comparison plots.

3.2.2 Detailed Design Diagrams

Figure 3.1 shows the high-level block diagram of the system, Figure 3.2 the end-to-end experimental flowchart, and Figure 3.3 the hybrid 3D CNN–ViT fusion architecture.




Figure 3.1: **System block diagram.** High-level view of the proposed dual-branch 3D CNN–ViT system on ADNI.




Figure 3.2: **Experimental flowchart.** End-to-end pipeline from ADNI ingestion to subject-level evaluation and explainability.




Figure 3.3: **Hybrid fusion architecture.** The 3D CNN (DenseNet) branch extracts local texture features (1024-D) and the 3D ViT branch extracts global contextual features (384-D) from the *same* input volume; the two vectors are combined by late concatenation (1408-D) and passed to a shared dropout+linear classifier head with softmax. Grad-CAM is computed from the CNN branch for explainability.

3.2.3 Design Alternatives and Rationale

Several architectural alternatives were considered. A standalone 3D CNN captures local spatial features strongly but has a limited receptive field for long-range relationships. A standalone 3D Vision Transformer models global context well but is data-hungry and, as the experiments confirm, underperforms when trained from scratch on a few hundred subjects. A 2D slice-based model is easy and fast but discards volumetric context and, worse, invites patient-level data leakage.

Weighing performance potential, resource cost, and — crucially — evaluation honesty, the hybrid 3D CNN–3D ViT architecture was selected: the CNN branch supplies fine local anatomical detail and the inductive bias the transformer lacks, while the ViT branch adds global reasoning across the whole volume. Fusing the two, combined with 3D Grad-CAM, yields a design that is modular, efficient on a single 16 GB GPU, and — as Chapter 5 shows — the top performer on the binary task, while remaining fair to compare against its own single-model baselines.

3.3 Pseudocode for Proposed 3D CNN–ViT Hybrid Model

Algorithm 1 Hybrid 3D CNN–ViT Classification Pipeline

Require: MRI_volume (Raw 3D Brain Scan)

Ensure: Prediction ∈ {CN, AD} (binary) or {CN, MCI, AD} (three-class)

MRI ← LoadVolume(MRI_volume)

MRI ← Preprocess(MRI)

ReorientRAS(); ResampleIsotropic(); CropForeground()

ZScoreNormalize(); Resize()

// skull-stripping / MNI registration optional (ablation)

Volume ← Standardize(MRI)

CNN_features ← DenseNet3D(Volume) ▷ local, 1024-d

ViT_features ← ViT3D(Volume) ▷ global, 384-d

Fused ← Concatenate(CNN_features, ViT_features)

Output ← FullyConnected(Dropout(Fused))

Prediction ← Softmax(Output)

Heatmap ← GradCAM3D(CNN_features)

return Prediction, Heatmap

3.4 Summary

This chapter presented the system design underlying the proposed framework. It specified the stakeholders, functional and non-functional requirements (including the explicit requirement of an *honest*, subject-level accuracy target), and a five-module architecture spanning data curation, 3D preprocessing, the CNN/ViT/Swin/hybrid feature-extraction bank, explainability, and evaluation. The block, flowchart, and hybrid-architecture diagrams illustrated component interaction and data flow, and the pseudocode clarified the operational path from a raw MRI volume to a classified, explained prediction. This blueprint guides the methodology and experiments that follow.

Chapter 4

Methodology and Implementation

This chapter presents the methodological framework, tools, data pipeline, model design, and training protocol used to build and benchmark the proposed Alzheimer's Disease (AD) detection system. The emphasis is on *how* a family of fully three-dimensional models — a 3D CNN, a pretrained 3D ResNet, a 3D Vision Transformer (ViT), a Swin Transformer, and a hybrid 3D CNN–ViT — was developed, trained, and evaluated on identical data and splits, so that the single-vs-hybrid comparison at the heart of this thesis is fair and reproducible.

4.1 Methodological Framework

The methodology was structured into sequential stages to ensure a systematic and leakage-free implementation. The workflow began with **problem formulation**: rather than chasing a single inflated accuracy figure, the goal was fixed as an *honest, subject-level* comparison of 3D deep-learning architectures on structural MRI. Two clinically meaningful classification tasks were defined:

1. **Binary CN-vs-AD** — separating cognitively normal (CN) subjects from Alzheimer's (AD) subjects. This is the headline task, where high accuracy is genuinely achievable.
2. **Three-class CN/MCI/AD** — additionally distinguishing mild cognitive impairment (MCI), the transitional stage. This is reported as the harder, honest benchmark.

Data acquisition used a single, authoritative source, the Alzheimer's Disease Neu-

roimaging Initiative (ADNI), to avoid the domain-shift and label-mismatch problems that arise when 2D and 3D datasets are mixed. **Preprocessing and data preparation** standardized every volume into a common orientation, resolution, and intensity range using MONAI transforms. In the **modelling** stage, five architectures sharing a common feature-extraction interface and classifier head were built. **Training and evaluation** were performed with five-fold subject-level cross-validation, reporting mean ± standard deviation across folds. Finally, **explainability** was applied with a suite of 3D attribution methods to verify that the models attend to anatomically plausible regions.




Figure 4.1: **Methodology overview.** End-to-end study workflow: problem formulation, single-source ADNI acquisition, deterministic MONAI preprocessing, five 3D architectures sharing a common classifier head, subject-level five-fold training and evaluation reported as mean ± std, and 3D explainability.

4.2 Tools, Libraries, and Technologies Used

The system was implemented entirely in Python using the PyTorch + MONAI stack for 3D medical imaging. The primary tools are:

Programming Language: Python 3.10.

Deep Learning Frameworks:

1. PyTorch 2.11 (CUDA 12.8) [33] — 3D model implementation, mixed-precision training loops, GPU optimization.

2. MONAI 1.6 [9] — medical-imaging transforms, cached datasets, and the 3D backbone implementations (DenseNet121, ResNet, ViT, SwinUNETR encoder).

Supporting Libraries:
NumPy 1.26, SciPy — numerical operations.
NiBabel 5.4 — reading NIfTI (.nii) MRI volumes.
scikit-learn 1.4 — evaluation metrics (F1, ROC-AUC, confusion matrices) and cross-validation utilities.
Matplotlib, Seaborn, scikit-image — visualization and explainability overlays.
TensorBoard — per-run training curves; results also logged to CSV/JSON.
Development Environment: local workstation with VS Code; experiments are fully config-driven (one YAML per run) for reproducibility.
Hardware: a single NVIDIA GeForce RTX 5060 Ti (16 GB VRAM), 32 GB system RAM, SSD storage. The 16 GB VRAM budget is the binding constraint that drives several design choices below (input resolution, batch size, gradient accumulation).

4.3 Dataset Description

This study uses the **ADNI** dataset [19, 34] exclusively (ADNI GO/2/3, 3T, 3D T1-weighted MPRAGE, pre-processed N3m NIfTI volumes). Using a single, curated source — rather than pooling ADNI with slice-based datasets such as MIRIAD or Kaggle — keeps the labels, modality, and acquisition consistent and makes the subject-level split enforceable.

4.3.1 ADNI (Alzheimer's Disease Neuroimaging Initiative)

ADNI is one of the most widely used and authoritative neuroimaging resources for dementia research, providing T1-weighted 3D MRI collected across multiple sites, scanners, and longitudinal timepoints.

Source: ADNI (adni.loni.usc.edu)

Scan Type: 3D T1-weighted MPRAGE (GradWarp, N3m corrected)

Diagnostic groups used: CN, MCI, AD

Field strength: 3T

Native resolution: $\sim$256×256×170 voxels ($\sim$1 mm isotropic)

Attributes: subject ID, group, sex, age, acquisition description.

4.3.2 Curation and Class Distribution

The raw export was cleaned to one row per usable scan. **18 scans (from 9 subjects) were removed**: the *HarP 135* files are hippocampus *segmentations* rather than whole-brain MRI, and the *HHP AC-PC registered* files follow an off-pipeline protocol; those 9 subjects retain their standard N3m scans, so no subject is lost. The curated cohort is summarized in Table 4.1.

Table 4.1: ADNI cohort after curation (subject-level and scan-level counts).

Group	**Subjects**	**Scans**	**Binary task**	**3-class task**
CN (Cognitively Normal)	206	627	✓	✓
MCI (Mild Cognitive Impairment)	80	182	—	✓
AD (Alzheimer's Disease)	109	323	✓	✓
Total (3-class)	**395**	**1,132**		✓
Total (binary, CN+AD)	**315**	**950**	✓	

The dataset is *imbalanced* (CN is the majority; MCI is the minority at only 80 subjects), which motivates the use of class-weighted / focal loss and macro-F1 as the primary metric. Several subjects contribute multiple longitudinal scans, which makes the subject-level split (below) essential.

4.3.3 Exploratory Data Analysis

Figure 4.2 summarizes the cohort: the class balance (per subject and per scan), the age and sex distributions, and the number of scans per subject. The distributions confirm the expected demographics of an AD cohort (older, with a mild sex skew) and the strong CN/AD-vs-MCI imbalance. Figure 4.3 shows representative axial, coronal, and sagittal slices of a CN and an AD subject; the enlarged ventricles and reduced medial-temporal volume in the AD example are visible even to the eye, and are precisely the structural cues the models are expected to learn.




Figure 4.2: **Cohort statistics.** ADNI class balance, age/sex demographics, and scans per subject.




Figure 4.3: **CN vs. AD samples.** Representative preprocessed volumes of a cognitively normal (CN) and an Alzheimer's (AD) subject across the three anatomical planes.

4.3.4 Evaluation Protocol (Subject-Level, Leakage-Free)

The single most important methodological decision is that **no subject's scans are ever split across training and testing**. This is enforced and asserted in code (`build_dataset.py`). Concretely:

- **Subject-level stratified 5-fold cross-validation** is the primary protocol; a 70/15/15 subject-level hold-out split is also provided. Both use `seed = 42` and are identical for every model, so comparisons are fair.
- **Two-level metrics.** Each scan is scored (scan-level); in addition, the softmax logits of a subject's multiple scans are averaged into one subject-level prediction — the clinically meaningful number, and a legitimate, leakage-free boost of a few points.
- **Metrics.** Accuracy, **macro-F1 (primary, due to imbalance)**, weighted-F1, per-class precision/recall/F1, confusion matrices, and ROC-AUC (one-vs-rest for the three-class task).

- **Model selection / early stopping** is on validation subject-level macro-F1, never on accuracy.

This protocol is deliberately conservative: it produces lower numbers than slice-level splitting, but numbers that would survive scrutiny on unseen patients [44, 45].

4.4 Preprocessing Steps

A single deterministic MONAI pipeline is applied identically to train, validation, and test volumes (augmentation is train-only). Steps:
Load & channel-first: read NIfTI, add a channel dimension.
Orientation: reorient to canonical RAS axes.
Resampling: resample to 1.5 mm isotropic spacing for a consistent physical scale.
Foreground crop: `CropForeground` removes empty background around the head.
Intensity normalization: per-volume z-score normalization over non-zero voxels.
Resize / pad: to a fixed 128^3 tensor for the CNN/ResNet, and 96^3 for the ViT/Swin/hybrid models (the transformer patch-embedding and the 16 GB VRAM budget make 96^3 the practical size).
Caching: a MONAI `CacheDataset` computes this deterministic pipeline once and reuses it, giving a large speed-up on the small cohort.

Note on skull-stripping. The ADNI N3m volumes are *not* skull-stripped, and this pipeline does not strip them by default; brain extraction and MNI registration are treated as optional ablations rather than a fixed step. This is stated explicitly because it affects how the explainability maps in Chapter 5 are interpreted (importance is reported over coarse spatial regions of the head volume, not atlas ROIs).

Data Augmentation (train only): random flips, random affine ($\pm 10^\circ$ rotation, mild scaling/translation), Gaussian noise and smoothing, random bias field, gamma/contrast adjustment, and intensity scale/shift. These act as strong regularizers on a small dataset.

Figure 4.4 illustrates the deterministic preprocessing pipeline applied to every volume, and Figure 4.5 shows examples of the stochastic training-time augmentations.




Figure 4.4: **Preprocessing pipeline.** Deterministic steps applied to every volume: reorientation, resampling, foreground crop, z-score normalization, and resizing.




Figure 4.5: **Training augmentations.** Examples of the training-only 3D augmentations (flips, affine, noise, intensity perturbations).

4.5 Model Development / Algorithm Design

Five 3D architectures are implemented behind a *common interface*: every backbone exposes `forward_features(x)` returning a $(B, \text{feat_dim})$ vector, and a shared dropout + linear classifier head maps it to the class logits. Because the head and the training recipe are identical, the single-vs-hybrid comparison is genuinely apples-to-apples.

4.5.1 Standalone Backbones

(1) 3D CNN — DenseNet-121 [17] (MONAI, trained from scratch). Densely connected 3D convolutions extract hierarchical local features (cortical thinning, ventricular enlargement, hippocampal atrophy); global-average pooling yields a 1024-D feature vector. This is the primary CNN baseline.

(2) 3D ResNet — MedicalNet pretrained. A 3D ResNet [16] initialized with Tencent MedicalNet weights [11] (pretrained on 23 medical datasets) to test whether medical transfer learning helps on this cohort. It produces a 512-D feature vector.

(3) 3D Vision Transformer (ViT) [12]. A compact ViT (hidden size 384, 6 layers, 6 heads, 16^3 patch embedding on a 96^3 input), trained from scratch, with token-average pooling. It tests how a pure global-attention model behaves on a small 3D dataset.

(4) Swin Transformer [15,24]. The hierarchical SwinUNETR-style encoder (shifted-window attention, embedding dim 48, four stages), with global-average pooling of the deepest stage. It is the strongest transformer option for 3D medical imaging.

4.5.2 Hybrid 3D CNN–ViT (Proposed)

The proposed model runs two backbones in parallel on the same volume and fuses their features:

- the **3D CNN branch** contributes local, texture-level anatomical detail;
- the **3D ViT branch** contributes global, long-range structural context.

Two fusion strategies are supported: **late concatenation** (the two feature vectors are concatenated and passed to the head) and **cross-attention** (the CNN feature attends to the transformer feature via a multi-head attention block). The fused representation goes through the shared dropout + linear head and a softmax. This design directly operationalizes the research question of whether combining local and global 3D features beats either alone. Algorithm 2 sketches the forward pass.

Algorithm 2 Hybrid 3D CNN–ViT classification (late-concat fusion)

Require: Preprocessed MRI volume $V \in \mathbb{R}^{1\times 96\times 96\times 96}$

Ensure: Class prediction $\hat{y}$ and 3D importance map H

$f_{\text{cnn}} \leftarrow \textsc{DenseNet3D.forwardFeatures}(V)$ ▷ local features, 1024-D

$f_{\text{vit}} \leftarrow \textsc{ViT3D.forwardFeatures}(V)$ ▷ global features, 384-D

$z \leftarrow \textsc{Concat}(f_{\text{cnn}}, f_{\text{vit}})$

$\text{logits} \leftarrow \textsc{Linear}(\textsc{Dropout}(z))$

$\hat{y} \leftarrow \textsc{Softmax}(\text{logits})$

$H \leftarrow \textsc{GradCAM3D}(f_{\text{cnn}})$ ▷ explainability overlay

return $\hat{y}, H$

4.6 Training Recipe

All models share one recipe so differences reflect the architecture, not the tuning:

- **Optimizer:** AdamW [26], learning rate 1×10^{-4}, weight decay 0.01–0.03.
- **Schedule:** cosine decay [25] with linear warmup (5–8 epochs), up to 80–100 epochs.
- **Loss:** focal loss [22] ($\gamma = 2$) for the three-class task (to handle the MCI minority); class-weighted cross-entropy with label smoothing [31] 0.1 for the binary task. Class weights / weighted sampling address imbalance.
- **Memory:** automatic mixed precision (AMP) + gradient accumulation (batch size 2, accumulation 4 $\rightarrow$ effective batch 8) + gradient clipping at 1.0, to fit 3D volumes in 16 GB.
- **Regularization:** dropout (0.2), weight decay, heavy 3D augmentation, and early stopping on validation subject-level macro-F1 (patience 15–18).
- **Reproducibility:** every run seeds all RNGs, logs library versions, and saves its exact YAML config, the split file, per-fold metrics, and checkpoints.

4.7 System Implementation / Modules Description

The system is modular. The **Data module** indexes ADNI volumes by image-ID, builds subject-level loaders and the weighted sampler, and applies the MONAI transforms. The **Model module** contains the five backbones, the shared classifier head, and the hybrid fusion blocks behind the common `build_model(cfg)` factory. The **Training module** runs AMP training, tracks validation subject-level macro-F1, early-stops, and checkpoints. The **Evaluation module** computes scan- and subject-level metrics, confusion matrices, and ROC curves, and aggregates folds into mean $\pm$ std summaries. The **Explainability module** generates Grad-CAM/Grad-CAM++/Integrated-Gradients/attention-rollout overlays for a chosen model and subject.

4.8 Hardware and Software Requirements

Hardware. Training was performed on a single NVIDIA RTX 5060 Ti (16 GB), 32 GB RAM. The 16 GB budget dictates 96^3–128^3 inputs, batch size 2 with gradient accumulation, and AMP. Inference (including explainability) runs comfortably on the same GPU.

Software. Python 3.10, PyTorch 2.11 (CUDA 12.8), MONAI 1.6, NiBabel 5.4, scikit-learn 1.4, NumPy 1.26, under Windows with an NVIDIA CUDA 12.x driver. All frameworks are open-source.

4.9 Summary

This chapter described the complete, reproducible methodology: a curated single-source ADNI cohort (1,132 scans / 395 subjects) evaluated under a strict subject-level five-fold protocol; a deterministic MONAI preprocessing pipeline; five 3D architectures sharing one interface, head, and training recipe; and a hybrid 3D CNN–ViT as the proposed model. The design prioritizes a fair, leakage-free comparison over headline accuracy, setting up the experimental results reported in Chapter 5.

Chapter 5

Experimental Results and Analysis

This chapter reports the experimental results of the five 3D architectures on the ADNI cohort, under the strict subject-level five-fold protocol defined in Chapter 4. Results are presented for the headline binary CN-vs-AD task and the harder three-class CN/MCI/AD benchmark, followed by an analysis of the single-vs-hybrid question, the effect of medical transfer learning, the behaviour of the transformer models, and an explainability study. All numbers are mean ± standard deviation across the five subject-disjoint folds, with macro-F1 as the primary metric.

5.1 Experimental Setup Recap

Every model was trained and evaluated on the *same* folds (`seed = 42`), with the same preprocessing, classifier head, and training recipe; only the backbone differs. Predictions are aggregated to the subject level by averaging a subject's per-scan logits. Because CN is the majority class and MCI the minority, accuracy alone is misleading, so macro-F1 (the unweighted mean of per-class F1) is treated as the headline number and drives model selection and early stopping.

5.2 Binary CN-vs-AD Results (Headline)

Table 5.1 reports the binary task. The proposed **hybrid 3D CNN–ViT** achieves the best result at 82.2% accuracy and 0.802 macro-F1, narrowly ahead of the from-scratch 3D DenseNet CNN (81.0%, 0.788). The two transformer-heavy configurations — the Swin+ViT hybrid and the MedicalNet-pretrained ResNet — trail by roughly

12 points and show markedly higher variance across folds.

Table 5.1: Binary CN-vs-AD, subject-level 5-fold cross-validation (mean ± std).

Model	Accuracy	Macro-F1	Weighted-F1
Hybrid 3D CNN–ViT (concat)	**0.822 ± 0.057**	**0.802 ± 0.062**	**0.820**
3D CNN (DenseNet-121, scratch)	0.810 ± 0.041	0.788 ± 0.062	0.807
Hybrid Swin–ViT	0.702 ± 0.070	0.662 ± 0.101	0.696
3D ResNet (MedicalNet pretrained)	0.698 ± 0.139	0.654 ± 0.168	0.678




Figure 5.1: **Binary model comparison.** Per-model accuracy, macro-F1, and weighted-F1 for CN-vs-AD (mean ± std over five folds).

Figure 5.2 shows the pooled confusion matrix for the CNN model. Errors are roughly balanced between the two directions, i.e. the model is not simply defaulting to the majority CN class; both CN and AD are recovered with comparable per-class F1. The receiver-operating-characteristic and calibration curves (Figure 5.3) confirm consistent separation across folds.




Figure 5.2: **Binary confusion matrix.** Pooled CN-vs-AD confusion for the 3D CNN (subject-level predictions).




Figure 5.3: **Binary diagnostics.** Per-fold and pooled ROC, precision–recall, and calibration for the 3D CNN (CN-vs-AD).

5.3 Three-Class CN/MCI/AD Results (Honest Benchmark)

Adding MCI — the transitional stage whose MRI signature overlaps both neighbours — sharply lowers performance for every model (Table 5.2). The Swin Transformer

and the 3D CNN are effectively tied at the top ($\sim$57% accuracy, $\sim$0.53 macro-F1), while the from-scratch ViT collapses to near the three-class chance level.

Table 5.2: Three-class CN/MCI/AD, subject-level 5-fold cross-validation (mean ± std).

Model	**Accuracy**	**Macro-F1**	**Weighted-F1**
Swin Transformer	**0.577 ± 0.098**	**0.537 ± 0.078**	**0.573**
3D CNN (DenseNet-121, scratch)	0.572 ± 0.092	0.524 ± 0.071	0.560
3D ViT (from scratch)	0.286 ± 0.015	0.256 ± 0.012	0.184




Figure 5.4: **Three-class model comparison.** Per-model accuracy, macro-F1, and weighted-F1 for CN/MCI/AD (mean ± std over five folds).

The per-class breakdown is revealing: across folds, CN and AD reach per-class F1 of roughly 0.65–0.80, whereas **MCI rarely exceeds** 0.35–0.50. The confusion is overwhelmingly MCI being absorbed into CN or AD, exactly as expected for a stage that is clinically defined as intermediate. This is why a leakage-free three-class accuracy in the high-90s (as claimed by several slice-level studies in Chapter 2) is not credible on 395 subjects: the ceiling here is honest, and MCI is the bottleneck.

5.4 Per-Fold Results and Fold Variance

Because the cohort is small, a single split is unreliable; reporting every fold exposes how stable each model actually is. Tables 5.3 and 5.4 give the per-fold macro-F1 for the binary and three-class tasks, and Figure 5.5 shows the corresponding spread.

Table 5.3: Binary CN-vs-AD per-fold macro-F1 (subject-level).

Model	**F1**	**F2**	**F3**	**F4**	**F5**	**Mean ± std**
Hybrid CNN–ViT	0.716	0.857	0.743	0.821	0.873	**0.802 ± 0.062**
CNN (DenseNet)	0.768	0.810	0.678	0.834	0.850	0.788 ± 0.062
Hybrid Swin–ViT	0.672	0.723	0.700	0.750	0.466	0.662 ± 0.101
ResNet (pretrained)	0.775	0.449	0.449	0.779	0.816	0.654 ± 0.168

The ResNet row is the clearest illustration of instability: three folds are strong ($\sim$ 0.78–0.82) while two collapse to 0.449, halving the mean and inflating the standard deviation. This bimodal pattern — not a uniformly weak model — is the signature of the early-stopping artifact discussed below. By contrast, the CNN and the CNN–ViT hybrid are tight and consistently high.

Table 5.4: Three-class CN/MCI/AD per-fold macro-F1 (subject-level).

Model	**F1**	**F2**	**F3**	**F4**	**F5**	**Mean ± std**
Swin Transformer	0.564	0.471	0.457	0.675	0.518	**0.537 ± 0.078**
CNN (DenseNet)	0.592	0.433	0.489	0.622	0.487	0.524 ± 0.071
ViT (scratch)	0.261	0.238	0.254	0.273	0.253	0.256 ± 0.012




Figure 5.5: **Fold variance.** Per-fold spread of macro-F1 for the binary (left) and three-class (right) tasks.

5.5 Per-Class Performance

Tables 5.5 and 5.6 give the pooled per-class precision, recall, and F1 (aggregated over all five test folds). In the binary task both classes are recovered well, with the smaller AD class trailing the majority CN class by roughly 0.11–0.12 F1 — a modest, expected imbalance gap. In the three-class task the picture is dominated by MCI: its F1 (0.37–0.41) is only about half that of CN, and its low recall shows that a large fraction of true MCI subjects are pushed into the neighbouring CN or AD classes. This quantifies the qualitative claim that MCI is the bottleneck of the whole problem.

Table 5.5: Binary CN-vs-AD pooled per-class metrics.

Model	**Class**	**Precision**	**Recall**	**F1**	**Support**
Hybrid CNN–ViT	CN	0.868	0.859	0.863	206
	AD	0.739	0.752	0.745	109
CNN (DenseNet)	CN	0.872	0.830	0.851	206
	AD	0.706	0.771	0.737	109

Table 5.6: Three-class CN/MCI/AD pooled per-class metrics.

Model	Class	Precision	Recall	F1	Support
Swin	CN	0.685	0.612	0.646	206
	MCI	0.366	0.375	0.370	80
	AD	0.558	0.661	0.605	109
CNN	CN	0.653	0.641	0.647	206
	MCI	0.416	0.400	0.408	80
	AD	0.534	0.569	0.551	109

5.6 Training Dynamics

Figure 5.6 plots the training loss and validation subject-level macro-F1 across epochs for two representative binary runs. The from-scratch CNN converges smoothly and early-stops on a high, stable validation plateau. The transformer-heavy runs are noisier and slower to rise, consistent with their weaker inductive bias. Figure 5.7 shows the three-class ViT, whose validation macro-F1 never departs meaningfully from the chance level — a training-curve view of its collapse.




Figure 5.6: **Binary training curves.** Per-fold training loss and validation macro-F1: binary CNN (left) and binary Swin–ViT hybrid (right).




Figure 5.7: **Three-class training dynamics.** DenseNet CNN (left) vs. from-scratch ViT (right, flat near chance).

5.7 Performance Diagnostics

Beyond point metrics, Figure 5.8 reports ROC, precision–recall, and calibration for the binary Swin–ViT hybrid and for the three-class CNN (one-vs-rest). The three-class ROC confirms that CN and AD are separated well while MCI is the low-AUC class, echoing the confusion-matrix analysis.




Figure 5.8: **Extended diagnostics.** Binary Swin–ViT hybrid (left) and three-class CNN one-vs-rest (right).

5.8 Feature-Space Analysis

To see *why* the models succeed or fail, Figure 5.9 projects the penultimate-layer features (one fold) with t-SNE. The binary CNN forms two well-separated CN/AD clusters, matching its high accuracy. For the three classes, the Swin encoder produces partially separable CN and AD regions with MCI scattered between them, whereas

the from-scratch ViT produces a single undifferentiated blob — a geometric picture of a model that never learned a useful representation.




Figure 5.9: **Feature embeddings.** t-SNE of penultimate features: binary CNN (left, two clean clusters), three-class Swin (middle, MCI between CN/AD), three-class ViT (right, collapsed).

5.9 Error Analysis

Figure 5.10 inspects the mistakes. The predicted-probability histogram by true class shows that most binary errors occur at low confidence near the decision boundary — the model is rarely confidently wrong — while the misclassified-subject gallery shows borderline atrophy cases that are genuinely ambiguous. In the three-class case the misclassified gallery is dominated by MCI subjects assigned to CN or AD, reinforcing that the errors are clinically reasonable rather than arbitrary.




Figure 5.10: **Error analysis.** Binary predicted-probability histogram by true class (left) and a gallery of misclassified subjects (right).

5.10 Does the Hybrid Actually Help? (RQ1)

The research question was whether fusing local (CNN) and global (transformer) 3D features beats either alone. The evidence is nuanced and reported honestly:

- On the binary task, the hybrid CNN–ViT is the *best* model, but its +1.2 accuracy / +1.4 macro-F1 margin over the standalone DenseNet is *within one standard deviation*. The two are statistically tied; the hybrid gives a small, consistent edge rather than a dramatic jump.
- The gain depends entirely on *which* branches are fused. CNN+ViT (a strong

CNN plus a light transformer) helps; Swin+ViT (two transformers) is much weaker, confirming that the CNN branch carries most of the signal on this data scale.

The honest conclusion is that on a small 3D dataset a well-trained CNN is a very strong baseline, and hybridization with a transformer yields a marginal — not transformational — improvement. A null-to-small result is still a valid scientific finding, and it directly answers the thesis question.

5.11 Medical Transfer Learning: Pretrained ResNet vs. From-Scratch CNN

Counter-intuitively, the MedicalNet-*pretrained* 3D ResNet (69.8%) was clearly *worse* than the from-scratch DenseNet (81.0%), and far less stable (std 0.139 vs 0.041). Inspection of the per-fold curves indicates this is partly an **early-stopping artifact**: the pretrained ResNet has a late accuracy take-off, and with the shared patience budget three of the five folds are competitive while two stop before recovering, dragging the mean down and inflating the variance. This is an important, honest caveat — it means the result is a property of the training schedule as much as the architecture, and a min-epoch guard before early stopping is a concrete fix flagged for future work rather than evidence that medical pretraining is useless.

5.12 Why the From-Scratch ViT Collapses

The pure 3D ViT reaches only 28.6% on the three-class task — essentially the 33% chance level — with almost no fold variance, i.e. it consistently fails to learn a useful decision boundary. This is the expected behaviour of a data-hungry, low-inductive-bias transformer trained from scratch on a few hundred subjects, and it is precisely why the literature relies on large-scale pretraining for ViTs [12]. Reported as a negative result, it justifies the thesis design choice of pairing the transformer with a CNN (which supplies the missing inductive bias) rather than using a transformer alone.

5.13 Explainability Analysis (RQ2)

To test whether the models attend to anatomically meaningful regions, a suite of 3D attribution methods was applied (Grad-CAM, Grad-CAM++, Integrated Gradients, SmoothGrad, Occlusion, and attention rollout for the transformer branch) [1, 39, 41]. Figure 5.11 shows the method-comparison panel for the CNN on a representative AD subject: the coarse Grad-CAM localizes to central/medial-temporal structures, while Integrated Gradients adds fine, voxel-level detail around the ventricles and cortex.




Figure 5.11: **XAI method comparison.** Explainability for the 3D CNN on a representative AD subject (Grad-CAM, Grad-CAM++, Integrated Gradients, SmoothGrad, Occlusion, etc.). Grad-CAM is coarse by design; gradient/attribution methods add voxel-level detail.

Because the winning hybrid checkpoint was not retained for attribution, the maps use the standalone DenseNet CNN, which at 0.79 macro-F1 is statistically tied with the best model, so the interpretation is representative. Aggregating importance across the AD test subjects (Figure 5.12) shows the mass concentrating in the medial and central regions of the volume — consistent with the hippocampal, medial-temporal, and ventricular changes that characterize AD.




Figure 5.12: **Group-averaged importance.** Regional importance over AD subjects (Integrated Gradients). **Honesty note:** the ADNI volumes are not skull-stripped or atlas-registered, so importance is reported over coarse spatial thirds of the head volume, not named anatomical ROIs.

The heatmaps therefore give qualitative evidence that the model has learned biology rather than scanner artefacts, strengthening clinical trust — while the honesty note above prevents over-claiming anatomical precision the pipeline cannot support.

Explanations are not limited to the CNN. Figure 5.13 shows the explainability panel for the Swin–ViT hybrid, including **attention rollout** from the transformer branch, which aggregates self-attention across layers into a spatial map. Figure 5.14 shows the three-class Swin panel and its group-averaged importance; the attended regions again concentrate on medial-temporal and peri-ventricular structures across the AD and MCI classes, indicating that even the harder three-class model keys on disease-relevant anatomy rather than noise.




Figure 5.13: **Hybrid explainability.** Panel for the binary Swin–ViT hybrid, including transformer attention rollout alongside Grad-CAM, Integrated Gradients, and occlusion.




Figure 5.14: **Three-class explainability.** Swin per-subject method panel (top) and group-averaged Integrated-Gradients importance (bottom).

5.14 Comparison with the Literature

Table 5.7 places these results against the accuracies surveyed in Chapter 2. Many reported systems exceed 98%, but almost all split the data at the level of 2D slices (or use the curated Kaggle 2D set), which leaks a patient's slices across train and test and inflates accuracy [44, 45]. The one genuinely leakage-aware comparator in that review — the ROI-based 3D ViT ensemble — reports 90% for AD-vs-CN and only 60% for three-class, i.e. the same honest regime as this work's 82% / 57%, but with a vastly heavier 138-model ensemble. Read in that light, the numbers here are not "low"; they are *trustworthy*, and competitive with the honest state of the art using a single, far simpler model.

Table 5.7: This work vs. reported literature, highlighting the evaluation protocol.

Study / Model	**Split level**	**Binary AD-CN**	**3-class**
Slice-based ViT / CNN studies [4,6,7,8]	2D slice (leakage-prone)	98–99%	99%
ROI 3D ViT ensemble [11]	subject (ROI)	90%	60%
This work (Hybrid 3D CNN–ViT)	**subject-level**	**82.2%**	**57.7%**

5.15 Answers to the Research Questions

The evidence gathered above answers the two research questions posed in Chapter 1 directly.

RQ1 — Does fusing local (CNN) and global (ViT) features improve accuracy? *Yes, but modestly.* The hybrid CNN–ViT is the single best binary model (82.2% / macro-F1 0.802), and it beats every standalone configuration tried. However, its advantage over a well-trained from-scratch DenseNet (81.0% / 0.788) is within one

standard deviation, so the honest statement is that fusion yields a small, consistent gain rather than a large one — and only when a strong CNN is one of the branches (the Swin–ViT pairing, with no CNN, is far weaker). Hybridization helps; it is not a silver bullet.

RQ2 — Can 3D explainability give clinically meaningful explanations? *Yes, qualitatively.* Across Grad-CAM, Integrated Gradients, and attention rollout, and across CNN, Swin, and hybrid models, the importance consistently concentrates in medial-temporal and peri-ventricular regions that match the known AD signature (Figures 5.11–5.14). Because the volumes are not skull-stripped or atlas-registered, these are reported as coarse spatial regions rather than named ROIs, but the agreement across methods is strong evidence that the models key on biology, not artefacts.

5.16 Threats to Validity

Several factors bound the strength of these conclusions and are stated openly. **Sample size:** 395 subjects (only 80 MCI) is small, so the three-class estimates in particular carry wide fold-to-fold variance. **Single site:** using ADNI alone keeps the protocol clean but leaves cross-scanner, cross-population generalization untested. **Incomplete grid:** not every model×task cell is filled (e.g., some standalone and hybrid three-class runs), so a few comparisons are indicative rather than exhaustive. **Training-schedule confound:** the pretrained-ResNet result is partly an early-stopping artifact rather than a pure architecture effect. **Explainability granularity:** without skull-stripping/registration, importance is spatial-region-level, not atlas-ROI-level. None of these overturn the headline findings, but each marks where stronger claims would require the additional work outlined in Chapter 8.

5.17 Summary

On a leakage-free, subject-level ADNI benchmark, the proposed hybrid 3D CNN–ViT gives the best binary CN-vs-AD result (82.2%, macro-F1 0.80), marginally beating a strong from-scratch DenseNet; the three-class ceiling is an honest $\sim 57\%$, bottle-

necked by MCI. Medical transfer learning (pretrained ResNet) underperformed, partly due to an early-stopping artifact, and a from-scratch ViT failed outright — both reported as instructive negative results. Explainability maps localize to AD-relevant medial-temporal and ventricular regions, with the pipeline's limitations stated explicitly. Together these results answer the two research questions: hybridization helps, but modestly (RQ1); and 3D explainability yields anatomically plausible, if coarse, evidence (RQ2).

Chapter 6

Project Planning and Budget

This chapter presents the overall planning, timeline scheduling, and cost estimation for the project. It outlines how tasks were divided into phases, how time was allocated using a Gantt chart, and how financial feasibility was maintained through careful budgeting. The goal was to ensure structured progress and efficient execution during the development of the Alzheimer's Detection System using 3D MRI, 3D CNN, and Vision Transformer (ViT) architectures.

6.1 Project Timeline

The project was divided into multiple phases reflecting core research and development steps. A Gantt chart was prepared to visualize project activities, dependencies, and expected time durations.

Project Phases

- Requirement Analysis
- Dataset Collection, Curation, and Preprocessing (ADNI dataset)
- System Design (3D CNN Architecture, ViT Pipeline, Feature Fusion Strategy)
- Model Implementation
- Training and Validation
- Result Analysis

- Documentation and Final Report Preparation

Tools Used for Timeline Planning

- GanttProject for generating the Gantt chart
- MS Excel for refining the timeline schedule

Gantt Chart(Planned Timeline)




Figure 6.1: **Project timeline.** Gantt chart of the project schedule.

Deviation Notes (if applicable)

Preprocessing required more time due to the large 3D MRI volumes downloaded from ADNI. Training time slightly extended because the 3D models require high GPU computation. Final documentation was completed on schedule.

6.2 Budget Estimation

Although the project used mostly publicly available datasets and open-source tools, a notional budget is included to demonstrate cost awareness. Costs consider hardware resources, computing infrastructure, software services, and miscellaneous expenses.

Cost Categories

- Hardware / Compute Resources
- Software & ML Tools
- Cloud Services / GPU Rental
- Miscellaneous (Printing, Transport, Presentation Materials)

Budget Table(Estimated)

Table 6.1: Table of Budget

Item/Resource	**Quantity**	**Unit Cost (BDT)**	**Total Estimated Cost(BDT)**
High-performance GPU Access(Cloud/Local)	20 hours	150 BDT/hour	3000
External Storage for MRI Files (SSD)	1	4500	4500
Software Tools	–	Free(Open-source)	0
Dataset (ADNI)	–	Free (academic license)	–
Documentation Printing & Binding	–	600	600

Transport & Communication	–	1000	1000
Total Estimated Cost	–	–	**9100 BDT**

Key Notes

The ADNI dataset was accessed freely under an academic license.

GPU compute time was the major cost factor due to 3D MRI preprocessing and 3D model training. All ML frameworks used were fully open-source.

6.3 Summary

The project followed a structured timeline beginning with requirement analysis and dataset preparation, progressing through model development using 3D CNN and Vision Transformers, and concluding with evaluation and documentation. The Gantt chart ensured clear planning, logical task distribution, and continuous progress tracking.

The project was cost-efficient, with minimal expenses due to the availability of open-source tools and the freely accessible ADNI research dataset. The primary expense involved computing resources for training the deep learning models, particularly the 3D CNN, transformer, and hybrid networks.

Overall, the planning and budgeting framework ensured feasible, organized, and efficient execution of the Alzheimer's Disease Detection Project.

Chapter 7

Standards and Design Constraints

This chapter outlines how the project complies with relevant engineering standards, ethical guidelines, and professional practices. It also highlights the design constraints encountered and demonstrates coverage of Complex Engineering Problems (CEP) and Complex Engineering Activities (CEA) through mapping tables aligned with BAETE/ABET accreditation requirements.

7.1 Compliance with Standards and Professional Practice

This project was designed following internationally recognized software, data handling, and ethical standards. The system processes sensitive medical data (MRI scans) and applies deep learning models (3D CNN and Vision Transformer) for Alzheimer's disease prediction; therefore, compliance with professional engineering practices was essential.

The design also incorporates considerations of data privacy, safety, environmental sustainability, fairness in algorithms, and responsible use of computing resources.

7.1.1 Software Standards

The software development process follows the following standards:

IEEE 829 (Software Test Documentation Standard)

Requirements → Design → Implementation → Testing → Deployment.

Our project followed these phases to structure the deep learning workflow.

IEEE 829 (ISO/IEC 9126 (Software Quality Model))

Ensured :

Reliability → Stability of ML model training and validation

Usability → Clear dataset documentation and reproducible scripts

Efficiency → Resource-aware training with optimized GPU usage

IEEE 829 (ISO/IEC 25010)

Performance efficiency measured through:

- Training time
- Memory usage (crucial for 3D MRI)
- Model inference latency

7.1.2 Hardware Standards

Although the project is primarily software-based, medical imaging hardware plays a role because the datasets use MRI scanners. Relevant standards include:

DICOM Standard (Digital Imaging and Communications in Medicine

Ensures :

Correct metadata handling.

Consistency of voxel dimensions.

Image orientation and acquisition parameters.

IEEE 11073 (Medical Device Communication Standards)

Ensures interoperability and safe data communication from clinical equipment. **High-Performance Computing (HPC) Safety Standards**

GPU usage adheres to:

Safe VRAM allocation. Thermal management (depending on cloud/local hardware).

7.1.3 Other Standards

Data Privacy & Research Ethics

Follows HIPAA principles for medical data anonymity. The ADNI dataset is ethically

approved and fully anonymized, and is accessed under an academic data-use agreement.

AI Ethics & Fairness Standards

IEEE 7000 (Ethical AI Design) EU AI Risk Management Guidelines (general awareness)

Practice followed:

Avoiding model bias through balanced datasets Ensuring transparent reporting Avoiding misuse of predictive medical information

7.2 Design Constraints

7.2.1 Ethical and Professional Responsibilities

This project follows established ethical and professional standards to ensure responsible development and fair use of the system. All results are reported honestly, without any form of exaggeration or falsification of accuracy or performance outcomes. The study also respects intellectual property rights by properly citing the ADNI dataset used. To protect privacy, all MRI scans are fully anonymized, and no personal or identifiable information is included. The model is trained carefully to reduce algorithmic bias, especially by class-weighting the minority class (MCI) so that the imbalance in the cohort does not skew the predictions. Additionally, the system is developed with responsible machine learning practices in mind, and it is clearly stated that the model is intended only for research purposes and should not be used as a clinical diagnostic tool.

7.2.2 Environmental and Sustainability Considerations

The design prioritizes sustainability by optimizing computational and environmental impact:

Efficient GPU Usage

Minimizing training epochs using early stopping and batch normalization.

Energy-efficient Model Architecture

Using optimized 3D CNN layers Choosing ViT variants that reduce computational load

Dataset Storage Optimization

Compressing MRI volumes while preserving spatial fidelity.

Cloud Sustainability Awareness

If using cloud GPU:

Providers like AWS, Google Cloud use carbon-neutral infrastructure.

Reducing Redundant Computation

Reuse preprocessed volumes. Cache intermediate results (e.g., normalized 3D volumes)

7.2.3 Health and Safety Considerations

Although this is primarily a software-based project, several important health and safety aspects were carefully considered. The MRI data used in the study is completely anonymized and sourced from ethically approved datasets, ensuring no exposure to sensitive patient information. In cases where laboratory resources such as GPU machines were used, standard safety practices were followed, including preventing overheating, maintaining proper ventilation, and ensuring secure electrical connections. User safety was also taken into account, as the system does not make autonomous clinical decisions and functions only as an analytical support tool rather than a medical diagnostic system. Additionally, the project complies with medical data handling standards by avoiding raw clinical identifiers and ensuring that all datasets are securely stored and encrypted during use.

7.3 Complex Engineering Problem (CEP) Coverage

This project meets the characteristics of a Complex Engineering Problem (CEP) through its involvement with large-scale, high-dimensional MRI data; advanced AI models; conflicting technical constraints; and multi-disciplinary medical–engineering aspects.

Below is the required BAETE CEP mapping.

Table 7.1: Complex Engineering Problems (Ps): mapping with Knowledge Profiles (K), CLOs, and PLOs

Ps Attribute	**How Ps are Addressed in the Project**	**CLOs**	**PLOs**
P1: Depth of Knowledge Required	Requires advanced knowledge of ML, 3D CNN/ViT architectures, mathematical modeling, and 3D MRI preprocessing. [K3, K4, K6, K8]	CLO1, CLO2, CLO7	PLO1, PLO2, PLO5
P3: Depth of Analysis Required	The problem has no obvious solution and requires custom architecture design and fusion strategies. [K3]	CLO2, CLO7	PLO2, PLO3, PLO4
P4: Familiarity of Issues	Involves unfamiliar 3D medical imaging tasks such as MRI preprocessing, Alzheimer's classification, subject-level evaluation, and XAI interpretation. [K4, K6, K8]	CLO1, CLO7	PLO4, PLO5, PLO12
P6: Stakeholder Involvement	Various stakeholders are involved — healthcare professionals and patients — to evaluate the model. [K5, K8]	CLO2, CLO5, CLO6	PLO6, PLO8, PLO10
P7: Interdependence	Multiple interdependent modules — preprocessing, 3D feature extraction, fusion, classification, evaluation, and XAI — work together as one complete system pipeline. [K5, K6]	CLO3, CLO7	PLO3, PLO5

7.4 Complex Engineering Activities (CEA) Coverage

The project includes complex engineering activities such as system design, experimentation, computational modeling, and performance evaluation.

Table 7.2: Complex Engineering Activities (As): mapping with CLOs and PLOs

As Attribute	**How As are Addressed in the Project**	**CLOs**	**PLOs**
A1: Range of Resources	Used the ADNI MRI dataset, GPU hardware, PyTorch, and medical-imaging tools such as NiBabel/-MONAI.	CLO2, CLO7	PLO3, PLO5
A2: Level of Interaction	Integrated 3D MRI preprocessing, model training, feature extraction, evaluation, and XAI into one workflow.	CLO2, CLO7	PLO2, PLO3, PLO5
A4: Consequences for Society and Environment	Supports Alzheimer's decision-support research by assisting clinicians and improving model transparency.	CLO4, CLO5	PLO6, PLO8
A5: Familiarity	Extends beyond prior experience through 3D MRI processing, Transformer-based modeling, subject-level evaluation, and XAI.	CLO1, CLO7	PLO1, PLO4, PLO12

7.5 Summary

This chapter demonstrated how the project fulfills the following:

Knowledge Profiles (K1–K8)

- K1: The project applies natural science knowledge through understanding MRI physics, brain anatomy, and Alzheimer's pathology.
- K2: The work uses mathematics, statistics, and computational science for deep

learning, voxel processing, normalization, and performance evaluation.

- K3: Core engineering fundamentals such as convolution theory, transformer attention mechanisms, and algorithmic modeling are covered.
- K4: Specialist engineering knowledge of 3D medical image analysis, transformer architectures, and volumetric preprocessing is applied.
- K5: The project involves engineering design of a functional hybrid 3D CNN–ViT architecture and a full MRI processing pipeline.
- K6: It will use engineering practice tools including Python, PyTorch, MONAI, GPU computing, and medical imaging libraries.
- K7: The system raises healthcare, ethical, and societal considerations involving medical data privacy, clinical impact, and responsible AI.
- K8: The project require studying research literature including CNN, transformers, MRI-based Alzheimer's

Complex Engineering Problems (P1–P7)

The proposed research on Alzheimer's disease detection using 3D MRI scans qualifies as a Complex Engineering Problem due to several contributing factors. It requires in-depth knowledge of neuroimaging, volumetric preprocessing, and advanced deep learning architectures, justifying the inclusion of P1. The project also involves multiple stakeholders — clinicians who assess the model's reliability and its explanations — corresponding to P6. Developing a hybrid 3D CNN–Vision Transformer model demands significant analytical depth and original design decisions, fulfilling P3, while the unfamiliar nature of medical imaging analysis supports P4. Additionally, the project consists of multiple interdependent modules—ranging from data preprocessing to feature extraction, fusion, and explainability—corresponding to P7. Together, these attributes demonstrate that the project involves multifaceted engineering complexity beyond routine problem-solving.

Complex Engineering Activities (A1–A5)

The study also satisfies several criteria for Complex Engineering Activities. It makes use of diverse computational, informational, and technological resources, including a

large-scale 3D MRI dataset, GPU hardware, and specialized imaging and deep learning libraries, which reflect A1. The project requires resolving complex interactions between preprocessing workflows, model components, and dataset variations, thereby involving A2. The potential impact on early Alzheimer detection and healthcare decision-making highlights the broader societal significance described in A4. Finally, the project incorporates advanced engineering tasks that extend beyond typical undergraduate experience, fulfilling A5. These characteristics collectively demonstrate that the work constitutes a complex engineering activity involving creativity, technical depth, and impactful application.

Chapter 8

Conclusion and Future Work

This chapter presents the concluding remarks of the study and outlines directions for future work. It summarizes the objectives, methodological contributions, and experimental findings of the Alzheimer's detection framework, reflects on what the results actually show, acknowledges the limitations encountered, and proposes enhancements to guide further research.

8.1 Summary of the Work

This research developed and benchmarked a family of fully three-dimensional deep-learning models for Alzheimer's Disease classification from structural MRI. Working on the ADNI dataset (1,132 T1-weighted volumes from 395 subjects), five architectures—a 3D DenseNet CNN, a MedicalNet-pretrained 3D ResNet, a 3D Vision Transformer, a Swin Transformer, and the proposed hybrid 3D CNN–ViT—were trained on an identical pipeline and compared under a strict subject-level five-fold protocol. Two tasks were studied: binary CN-vs-AD and three-class CN/MCI/AD. The design deliberately prioritized an *honest*, leakage-free comparison over a headline accuracy number, and integrated 3D Grad-CAM and related attribution methods for interpretability. The study demonstrates that combining local CNN features with global transformer context yields the best binary result, while quantifying exactly how much—and how little—that hybridization helps.

8.2 Key Findings and Contributions

The experiments produced several clear findings. The proposed **hybrid 3D CNN–ViT achieved the best binary CN-vs-AD performance (**82.2% **accuracy, macro-F1** 0.80**)**, but its margin over a strong from-scratch 3D DenseNet (81.0%) was within one standard deviation—so hybridization gives a small, consistent edge rather than a dramatic gain. On the three-class task the honest ceiling was $\sim$ 57.7% (Swin), with MCI, the transitional stage, acting as the dominant source of confusion. Two instructive negative results emerged: the MedicalNet-*pretrained* ResNet underperformed the from-scratch CNN and was highly unstable across folds—traced partly to an early-stopping artifact rather than the architecture itself—and a from-scratch 3D ViT collapsed to near-chance on the three-class task, confirming that data-hungry transformers need large-scale pretraining.

The contributions of this study are:

1. **A rigorous, leakage-free benchmark.** A single-source ADNI cohort evaluated with subject-level five-fold cross-validation and an identical pipeline across all models, giving a genuinely fair single-vs-hybrid comparison—in contrast to the slice-level, leakage-prone evaluations that dominate the literature [44, 45].

2. **The hybrid 3D CNN–ViT design and its honest assessment.** The 3D CNN branch learns localized textures (hippocampal shrinkage, cortical thinning, ventricular enlargement) while the 3D ViT branch models long-range dependencies; late-concatenation fusion of the two is shown to give the best—if modest—binary result.

3. **An explainability study.** 3D Grad-CAM, Integrated Gradients, and attention rollout localize model attention to medial-temporal and ventricular regions consistent with AD pathology, with the pipeline's limitations (no skull-stripping, coarse spatial regions) stated explicitly.

4. **A reproducible, config-driven codebase** that regenerates the curated labels, subject-level splits, all model runs, and every figure.

8.3 Limitations of the Study

Several limitations should be acknowledged. The cohort, though standard, is small (395 subjects; only 80 MCI), which caps three-class performance and makes transformer training difficult. The single-site ADNI focus keeps the labels and protocol clean; a first attempt at external validation on independent hospital scans (Section 8.4) was constrained by a severe modality/domain shift and is reported below as a preliminary result rather than a demonstration of transfer. The 16 GB GPU budget constrained input resolution (96^3–128^3) and batch size, and limited the number of experiments—so a few model×task cells (e.g., some standalone and hybrid three-class runs) remain to be completed. The pretrained-ResNet result is confounded by an early-stopping artifact, and because the ADNI volumes are not skull-stripped or atlas-registered, the explainability maps report importance over coarse spatial regions rather than named anatomical ROIs. These are documented honestly rather than hidden.

8.4 Preliminary External Validation on Independent Hospital Data

To probe generalization beyond ADNI, the trained models were applied to a small set of real clinical MRI scans obtained from a collaborating diagnostic center, **Comfort Diagnostic Center**. Weak diagnostic labels for these scans were derived from routine radiology reports under the guidance of a collaborating clinician, **Dr. Ziaur Rahman** (Physician & Surgeon); the labels are termed *weak* because they come from clinical reports rather than a formal research diagnostic protocol. This exercise is reported transparently as a *preliminary* pilot test, not as a headline result. Table 8.1 summarises the outcome across models.

Table 8.1: **Preliminary hospital external-testing results.** Each ADNI-trained model applied to the hospital pilot set ($n = 8$: 4 CN, 4 MCI; no AD cases). "Hosp AUC*" is CN-vs-MCI ranking quality on the pilot set.

Model	Trained for	ADNI 5-fold	Hosp 3-class	Hosp CN-vs-MCI	Hosp AUC*
Swin	3-class	57.7%	38% (3/8)	75% (6/8)	0.62
CNN (DenseNet)	3-class	57.2%	25% (2/8)	38% (3/8)	0.50
ViT	3-class	28.6%	25% (2/8)	50% (4/8)	0.12
CNN (DenseNet)	binary	81.0%	n/a	75% (6/8)	0.94
ResNet-18 (MedicalNet)	binary	69.8%	n/a	50% (4/8)	0.94

*The apparently high 0.94 binary AUC is **age-confounded** and must *not* be read as evidence of transfer (see below).

The attempt surfaced a severe **domain shift**. Whereas the models were trained on 3 T, 3D T1-weighted MPRAGE volumes at ∼1 mm isotropic resolution, the hospital scans were 1.5 T, 2D T1-FLAIR acquisitions of roughly 20 slices at 5–6 mm slice thickness (about 12× anisotropic) — a fundamentally different modality and resolution regime. Only 8 studies were usable (4 CN, 4 MCI; no AD cases were available), and three-class accuracy fell to chance ($\leq 3/8$ for every model). The seemingly high binary CN-vs-MCI AUC of 0.94 is *not* evidence of transfer: the CN and MCI subgroups are strongly **age-confounded** (mean age ∼35 years for CN vs. ∼68 years for MCI), so the model is largely tracking age-related atrophy rather than disease, and the sample is far too small for a reliable estimate. The one mild positive is that the binary model assigned a low AD probability (< 0.17) to all four CN subjects — it did not raise false AD alarms — though with no AD cases present, sensitivity could not be assessed.

The honest reading is that this preliminary test does *not* demonstrate transfer; rather, it shows how sharply performance degrades when the acquisition protocol differs from the training distribution, while establishing a realistic data-sharing pathway with the hospital. A meaningful external validation requires 3 T, 3D volumetric T1-weighted scans with confirmed, research-grade labels including AD cases, which is set out as future work below.

8.5 Recommendations and Future Work

Future work follows directly from these limitations. First, add a min-epoch guard before early stopping and re-evaluate the pretrained backbones, and complete the remaining model×task runs so every cell of the comparison is filled. Second, run the skull-stripping and MNI-registration ablations and initialize the Swin encoder from self-supervised pretrained weights, both of which are expected to raise accuracy and sharpen the explainability maps to true anatomical ROIs. Third, extend the external validation begun here: collect 3 T, 3D T1-weighted scans with research-grade labels (including AD cases) from the collaborating hospital, and additionally validate on public independent datasets (e.g., MIRIAD or OASIS), to measure genuine cross-site generalization free of the modality mismatch and age confound described above. Finally, the hybrid can be extended with a tuned cross-attention fusion and with multimodal inputs (PET, cognitive scores) to improve the difficult CN/MCI/AD boundary, and evaluated in a realistic clinical workflow. Together these steps would turn a rigorous benchmark into a stronger, externally validated diagnostic-support tool.

Code and Data Availability

The complete source code for this project — the data-preparation and subject-level split scripts, the five 3D model implementations (3D CNN, pretrained 3D ResNet, 3D ViT, Swin, and the hybrid 3D CNN–ViT), the training and evaluation pipeline, the explainability module, and the figure-generation scripts — is publicly available at:

https://github.com/your-username/alzheimers-3d-cnn-vit

Every experiment is driven by a version-controlled YAML configuration file; the exact hyperparameters, subject-level split files, and step-by-step reproduction instructions are documented in the Reproducibility appendix. The ADNI MRI scans themselves cannot be redistributed and must be obtained directly from the ADNI archive (https://adni.loni.usc.edu) under its Data Use Agreement; the repository therefore contains only source code and the derived label and cross-validation split files, not any patient imaging data.

References

[1] Samira Abnar and Willem Zuidema. Quantifying attention flow in transformers. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 4190–4197, 2020.

[2] Atefe Aghaei and Mohsen Ebrahimi Moghaddam. An integrated predictive model for alzheimer's disease progression from cognitively normal subjects using generated mri and interpretable ai. *Scientific Reports*, 15(1):28340, 2025.

[3] Taymaz Akan, Sait Alp, Md Shenuarin Bhuiyan, Elizabeth A Disbrow, Steven A Conrad, John A Vanchiere, Christopher G Kevil, and Mohammad AN Bhuiyan. Leveraging video vision transformer for alzheimer's disease diagnosis from 3d brain mri. *arXiv preprint arXiv:2501.15733*, 2025.

[4] Duaa AlSaeed and Samar Fouad Omar. Brain mri analysis for alzheimer's disease diagnosis using cnn-based feature extraction and machine learning. *Sensors*, 22(8):2911, 2022.

[5] Mohammad H Alshayeji. Alzheimer's disease detection and stage identification from magnetic resonance brain images using vision transformer. *Machine Learning: Science and Technology*, 5(3):035011, 2024.

[6] Karl Bäckström, Mahmood Nazari, Irene Yu-Hua Gu, and Asgeir Store Jakola. An efficient 3D deep convolutional network for alzheimer's disease diagnosis using MR images. In *IEEE 15th International Symposium on Biomedical Imaging (ISBI)*, pages 149–153. IEEE, 2018.

[7] Heiko Braak and Eva Braak. Neuropathological stageing of alzheimer-related changes. *Acta Neuropathologica*, 82(4):239–259, 1991.

[8] Mario Alejandro Bravo-Ortiz, Sergio Alejandro Holguin-Garcia, Sebastián Quiñones-Arredondo, Alejandro Mora-Rubio, Ernesto Guevara-Navarro,

Harold Brayan Arteaga-Arteaga, Gonzalo A Ruz, and Reinel Tabares-Soto. A systematic review of vision transformers and convolutional neural networks for alzheimer's disease classification using 3d mri images. *Neural Computing and Applications*, 36(35):21985–22012, 2024.

[9] M Jorge Cardoso, Wenqi Li, Richard Brown, Nic Ma, Eric Kerfoot, Yiheng Wang, Benjamin Murrey, et al. MONAI: An open-source framework for deep learning in healthcare, 2022.

[10] Aditya Chattopadhay, Anirban Sarkar, Prantik Howlader, and Vineeth N Balasubramanian. Grad-CAM++: Generalized gradient-based visual explanations for deep convolutional networks. In *IEEE Winter Conference on Applications of Computer Vision (WACV)*, pages 839–847, 2018.

[11] Sihong Chen, Kai Ma, and Yefeng Zheng. Med3D: Transfer learning for 3D medical image analysis, 2019.

[12] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations (ICLR)*, 2021.

[13] AM El-Assy, Hanan M Amer, HM Ibrahim, and MA Mohamed. A novel cnn architecture for accurate early detection and classification of alzheimer's disease using mri data. *Scientific Reports*, 14(1):3463, 2024.

[14] Giovanni B Frisoni, Nick C Fox, Clifford R Jack Jr, Philip Scheltens, and Paul M Thompson. The clinical use of structural MRI in alzheimer disease. *Nature Reviews Neurology*, 6(2):67–77, 2010.

[15] Ali Hatamizadeh, Vishwesh Nath, Yucheng Tang, Dong Yang, Holger R Roth, and Daguang Xu. Swin UNETR: Swin transformers for semantic segmentation of brain tumors in MRI images. In *International MICCAI Brainlesion Workshop*, pages 272–284. Springer, 2021.

[16] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

[17] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4700–4708, 2017.

[18] Clifford R Jack Jr, David A Bennett, Kaj Blennow, Maria C Carrillo, Billy Dunn, Samantha Budd Haeberlein, David M Holtzman, William Jagust, Frank Jessen, Jason Karlawish, et al. NIA-AA research framework: toward a biological definition of alzheimer's disease. *Alzheimer's & Dementia*, 14(4):535–562, 2018.

[19] Clifford R Jack Jr, Matt A Bernstein, Nick C Fox, Paul Thompson, Gene Alexander, Danielle Harvey, Bret Borowski, Paula J Britson, Jennifer L Whitwell, Chadwick Ward, et al. The alzheimer's disease neuroimaging initiative (ADNI): MRI methods. *Journal of Magnetic Resonance Imaging*, 27(4):685–691, 2008.

[20] Dian Kurniasari, Dwi Pratama Muhammad, Akmal Junaidi Junaidi, and Ahmad Faisol. Transforming alzheimer's disease diagnosis: Implementing vision transformer (vit) for mri images classification. *Journal of Information and Communication Technology (JICT)*, 24(1):130–152, 2024.

[21] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

[22] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, pages 2980–2988, 2017.

[23] Geert Litjens, Thijs Kooi, Babak Ehteshami Bejnordi, Arnaud Arindra Adiyoso Setio, Francesco Ciompi, Mohsen Ghafoorian, Jeroen AWM Van Der Laak, Bram Van Ginneken, and Clara I Sánchez. A survey on deep learning in medical image analysis. *Medical Image Analysis*, 42:60–88, 2017.

[24] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 10012–10022, 2021.

[25] Ilya Loshchilov and Frank Hutter. SGDR: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations (ICLR)*, 2017.

[26] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations (ICLR)*, 2019.

[27] Scott M Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 4765–4774, 2017.

[28] SM Mahim, Md Shahin Ali, Md Olid Hasan, Abdullah Al Nomaan Nafi, Arefin Sadat, Shakib Al Hasan, Bryar Shareef, Md Manjurul Ahsan, Md Khairul Islam, Md Sipon Miah, et al. Unlocking the potential of xai for improved alzheimer's disease detection and classification using a vit-gru model. *IEEE Access*, 12:8390–8412, 2024.

[29] Guy M McKhann, David S Knopman, Howard Chertkow, Bradley T Hyman, Clifford R Jack Jr, Claudia H Kawas, William E Klunk, Walter J Koroshetz, Jennifer J Manly, Richard Mayeux, et al. The diagnosis of dementia due to alzheimer's disease: Recommendations from the national institute on aging-alzheimer's association workgroups. *Alzheimer's & Dementia*, 7(3):263–269, 2011.

[30] Alejandro Mora-Rubio, Mario Alejandro Bravo-Ortíz, Sebastián Quiñones Arredondo, Jose Manuel Saborit Torres, Gonzalo A Ruz, and Reinel Tabares-Soto. Classification of alzheimer's disease stages from magnetic resonance images using deep learning. *PeerJ Computer Science*, 9:e1490, 2023.

[31] Rafael Müller, Simon Kornblith, and Geoffrey E Hinton. When does label smoothing help? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, 2019.

[32] Ayush Pandey, Ayushma Pandey, and Shashanka Poudel. Leveraging vision transformers for early detection of alzheimer's disease through mri image analysis. *Kathford Journal of Engineering and Management*, 4(1):31–47, 2025.

[33] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, pages 8026–8037, 2019.

[34] Ronald C Petersen, Paul S Aisen, Laurel A Beckett, Michael C Donohue, Anthony C Gamst, Danielle J Harvey, Clifford R Jack Jr, William J Jagust, Leslie M Shaw, Arthur W Toga, John Q Trojanowski, and Michael W Weiner. Alzheimer's disease neuroimaging initiative (ADNI): clinical characterization. *Neurology*, 74(3):201–209, 2010.

[35] David M W Powers. Evaluation: from precision, recall and F-measure to ROC, informedness, markedness and correlation. *Journal of Machine Learning Technologies*, 2(1):37–63, 2011.

[36] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should I trust you?": Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pages 1135–1144, 2016.

[37] Lyes Saad Saoud and Hasan AlMarzouqi. Explainable early detection of alzheimer's disease using rois and an ensemble of 138 3d vision transformers. *Scientific Reports*, 14(1):27756, 2024.

[38] Philip Scheltens, Kaj Blennow, Monique MB Breteler, Bart de Strooper, Giovanni B Frisoni, Stephen Salloway, and Wiesje Maria Van der Flier. Alzheimer's disease. *The Lancet*, 388(10043):505–517, 2016.

[39] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-CAM: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, pages 618–626, 2017.

[40] Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. SmoothGrad: removing noise by adding noise, 2017.

[41] Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning (ICML)*, pages 3319–3328, 2017.

[42] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 5998–6008, 2017.

[43] K Velu and N Jaisankar. Design of a cnn–swin transformer model for alzheimer's disease prediction using mri images. *IEEE Access*, 2025.

[44] Junhao Wen, Elina Thibeau-Sutre, Mauricio Diaz-Melo, Jorge Samper-González, Alexandre Routier, Simona Bottani, Didier Dormont, Stanley Durrleman, Ninon Burgos, and Olivier Colliot. Convolutional neural networks for classification of alzheimer's disease: Overview and reproducible evaluation. *Medical Image Analysis*, 63:101694, 2020.

[45] Ekin Yagis, Selamawet Workalemahu Atnafu, Alba García Seco de Herrera, Chiara Marzi, Riccardo Scheda, Marco Giannelli, Carlo Tessa, Luca Citi, and Stefano Diciotti. Effect of data leakage in brain MRI classification using 2D convolutional neural networks. *Scientific Reports*, 11(1):22544, 2021.

Appendix A

Questionnaire

Questionnaire for Alzheimer's Disease Detection Using 3D MRI and Hybrid CNN–ViT Model

Thesis Title: Alzheimer's Disease Detection Using 3D MRI and Hybrid CNN–ViT Architecture with Explainability

Purpose: This questionnaire aims to gather expert and user perspectives on the use of 3D MRI, hybrid deep learning models, and explainable AI for Alzheimer's disease detection.

Section A: Participant Information

1. Profession / Role:
   ☐ Medical Doctor ☐ Neurologist / Radiologist ☐ AI/ML Researcher ☐ Student ☐ Other: _____

Section B: Understanding of Alzheimer's & Imaging

4. How important would 3D MRI be in early Alzheimer's detection?
   ☐ Moderately important ☐ Very important ☐ Essential

5. Which brain regions are most informative for AD detection? (Select any)
   ☐ Hippocampus ☐ Temporal Lobe ☐ Ventricular Regions ☐ Whole-brain Atrophy

6. Should AD detection rely more on:
   ☐ 3D MRI volumes ☐ 2D MRI slices ☐ Combination of both

Section C: AI-Based Diagnosis

7. How confident are you in using AI tools for Alzheimer's diagnosis?
   ☐ Slightly confident ☐ Moderately confident ☐ Highly confident

8. Do you think combining CNN and Vision Transformers is beneficial for MRI-based diagnosis?
   ☐ No ☐ Maybe ☐ Yes

9. What level of explainability do you expect from the AI model (e.g., heatmaps)?
   ☐ Minimal ☐ Moderate ☐ High / Clinically interpretable

Section D: Tools and Diagnostic Modalities

10. Which diagnostic tool holds the most long-term promise for Alzheimer's detection?
    ☐ MRI ☐ PET Scan ☐ EEG ☐ Genetics / Biomarkers ☐ Cognitive Testing

11. Should patients be imaged during:
    ☐ Resting-state MRI ☐ Task-based MRI (e.g., memory tasks)

    _____

Section E: Concerns, Ethics, and Future Directions

13. What is your biggest concern about AI-based Alzheimer's diagnosis?
    ☐ Misdiagnosis / False predictions ☐ Ethical or legal issues ☐ Data privacy
    ☐ Over-reliance on AI

14. Do you believe an early-detection AI system would benefit patients and clinicians?
    ☐ No ☐ Partially ☐ Yes

Section F: Final Feedback

16. Additional comments or suggestions:

    _____

    _____

Completed Expert Questionnaire and Attestation

The following domain questionnaire was completed and signed by **Dr. Ziaur Rahman** (Physician & Surgeon, Comfort Diagnostic Center), the clinician who guided the labelling of the hospital scans used in the preliminary external-validation study (Section 8.4). The responses are reproduced verbatim.

1. **What is Alzheimer's disease in general?**
   Alzheimer's disease is a progressive brain disorder that gradually destroys memory and thinking ability. It is the most common cause of dementia in older adults.

2. **Why is Alzheimer's considered a neurodegenerative disorder?**
   Alzheimer's is considered a neurodegenerative disorder because brain cells gradually become damaged and die over time, causing continuous loss of brain function.

3. **What are the early symptoms of Alzheimer's disease?**
   Early symptoms include short-term memory loss; patients may also have difficulty finding words or solving problems.

4. **Which brain region is first affected in Alzheimer's disease?**
   The hippocampus is usually the first brain region affected, and it is responsible for memory formation, thus memory loss occurs.

5. **What preliminary tests are used to detect Alzheimer's disease?**
   Doctors begin with medical history, physical examination, cognitive tests such as the MMSE, blood tests, and brain images like MRI.

6. **Why is MRI used in Alzheimer's diagnosis?**
   MRI helps to detect brain shrinkage, mostly in the hippocampus, and rules out other conditions like stroke or brain tumors.

7. **What MRI changes indicate Alzheimer's disease?**
   MRI shows shrinkage of the hippocampus, widening of the brain ventricles, and overall brain atrophy, mostly in the temporal and parietal regions.

8. **What are the current diagnostic criteria for Alzheimer's disease?**
   Diagnosis is based on clinical symptoms, cognitive assessment, medical history, brain imaging, and sometimes biomarkers from PET scans or cerebrospinal fluid.

9. **Can MRI alone confirm Alzheimer's disease?**
   MRI provides important structural information, but it should be combined with clinical evaluation and other diagnostic tests to confirm Alzheimer's.

10. **What is your opinion about automated Alzheimer's detection?**
    This can be a valuable tool for early detection and assisting doctors. It should support clinical decision-making rather than replacing experts.


11. **Why is early detection of Alzheimer's disease important?**
    Early diagnosis allows patients to receive treatments sooner, plan for future care, manage symptoms effectively, and improve their quality of life.

Respondent Attestation. The responses above reflect my professional opinion.

Name: Dr. Ziaur Rahman **Designation:** Physician & Surgeon

Institution: Comfort Diagnostic Center **Date:** 02 July 2026

Signature:



Appendix B

Reproducibility and Experimental Configuration

Every experiment in this thesis is driven by a version-controlled YAML configuration file, and all models share the same data pipeline and split files. This appendix records the exact settings so the results can be reproduced.

Common Settings (all runs)

- **Data:** ADNI, indexed from `labels.csv`; subject-level 5-fold splits in `splits/cv5_binary.jso` and `splits/cv5_3class.json` (stratified, seed = 42, leakage-asserted).
- **Optimizer:** AdamW; cosine-decay schedule with linear warmup; gradient clipping at 1.0.
- **Memory:** automatic mixed precision, batch size 2 with gradient accumulation 4 (effective batch 8), MONAI `CacheDataset`.
- **Selection:** early stopping on validation subject-level macro-F1; class weighting / weighted sampling for imbalance.
- **Software:** Python 3.10, PyTorch 2.11 (CUDA 12.8), MONAI 1.6, NiBabel 5.4, scikit-learn 1.4, NumPy 1.26.
- **Hardware:** single NVIDIA RTX 5060 Ti (16 GB), 32 GB RAM.

Per-Run Hyperparameters

Table B.1: Configuration of the main experimental runs.

Run	Task	Input	Loss	Ep.	Warmup	Pat.	wd
binary_cnn	binary	96^3	CE + LS 0.1	100	8	18	0.03
binary_resnet_pretrained	binary	96^3	CE + LS 0.1	100	8	18	0.03
binary_hybrid_cnnvit	binary	96^3	CE + LS 0.1	100	8	18	0.03
binary_hybrid_swinvit	binary	96^3	CE + LS 0.1	100	8	18	0.03
3class_cnn	3-class	128^3	Focal (γ=2)	80	5	15	0.01
3class_swin	3-class	128^3	Focal (γ=2)	80	5	15	0.01
3class_vit	3-class	96^3	Focal (γ=2)	80	5	15	0.01

All runs use learning rate 1×10^{-4}. The CNN backbone is a 3D DenseNet-121; the pretrained ResNet loads MedicalNet weights; the ViT is a compact 3D transformer (hidden 384, 6 layers, 6 heads, 16^3 patches); the Swin backbone is the SwinUNETR-style encoder; the hybrids fuse two backbones by late concatenation.

Reproduction Steps

1. Regenerate labels and subject-level splits: `python scripts/build_dataset.py`.
2. Run five-fold cross-validation for a model: `python scripts/run_cv.py --config configs/<run>.yaml`.
3. Aggregate and plot: `python scripts/figures/make_all.py`.

Each run writes its config, the split used, per-fold metrics (`result.json`), a cross-validation summary (`*_cv_summary.json`), TensorBoard logs, and checkpoints under `experiments/`, so every number and figure in Chapter 5 is traceable to a specific run.