

EdgeGuard / ShrikeFi

AI-Powered Personal Health Companion & Edge Disaster Monitor

A secure, offline medical wearable fusing physiological vitals with environmental disaster telemetry on custom silicon to predict fatal heat stroke, toxic air inhalation, and cold-shock hypothermia before collapse.

⚡ 20 ns FPGA Timing

🧠 91% INT8 TinyML

🏥 92% MIMIC-III Validated

Team Name: CHIPSTERS | Team ID: 01 | Category: Hardware



Problem & Solution — The Deadly 'Smartwatch Blind Spot'

✗ The Problem: Why Current Tech Fails in Disasters

Wearables Are Environmentally Blind: Smartwatches only track fitness steps or resting pulse. They have zero awareness if ambient air is toxic (AQI 500+) or if 48°C heat is causing heat exhaustion.

Environmental Sensors Ignore the Body: Weather apps report regional city forecasts, not what an individual worker's cardiovascular system is actually enduring at street level.

Cloud Dependency Trap: Commercial AI health platforms require mobile networks. During severe storms, floods, or grid failures, cell towers collapse and cloud apps die completely.

Software Jitter Destroys HRV: Operating system scheduling delays on standard CPUs jitter by 5-20 ms, severely distorting heart rate variability (HRV) metrics.

✓ The Solution: EdgeGuard Heterogeneous Companion

Biometric & Environmental Fusion: Simultaneously acquires dual-wavelength optical PPG pulses along with hyper-local ambient temperature, humidity, and laser PM2.5 particulate matter on the wrist.


Cycle-Accurate FPGA Silicon: Custom Verilog 8-tap filter and peak-detector FSM runs on 50 MHz hardware with 20 ns resolution, completely bypassing OS scheduling jitter.

Zero-Cloud On-Device TinyML: Deep neural network fits in only 619 bytes SRAM and evaluates risks in 42 μ s, providing 100% offline continuous triage during infrastructure blackouts.

Early Preventive Warnings: Predicts heat stroke collapse, acute pollution-induced vagal suppression, and cold-water immersion shock 15-20 minutes before medical emergencies.

💡 **Core Innovation:** Turning dumb wearable sensors into an autonomous, offline clinical life-saver that detects physiological collapse before symptoms turn fatal.


Technical Approach — 4-Stage Autonomous Dataflow Pipeline



Hardware Acceleration — 20 ns Cycle-Accurate Verilog RTL

💡 **Layman Analogy: Why FPGA?** Software CPUs have OS jitter — like timing a sprint with a loose, flickering stopwatch. An FPGA is a custom physical circuit: it gives us 20 billionths of a second (20 ns) timing accuracy with zero lag.

⚡ Renesas ForgeFPGA Silicon Synthesis & Floorplan



17.4%

LUT5 Logic Used
(195 / 1120)


**0 DSP / 0
BRAM**

Pure Logic Gates
(Lowest Cost BOM)

+5.603 ns

WNS Timing Slack
(STA Met at 69 MHz)

📊 Verified GTKWave Cycle-Accurate Timing Simulation



Noise Filtering Convergence: Raw optical signals are smoothed by the 8-tap pipeline into filter_red_out[7:0] with 0 multiplier delay.

Systolic Peak Detection: FSM transitions ARMED -> RISING -> PEAK_FOUND with a 250 ms refractory lock-out window.

Interrupt & IBI Latch: A single-cycle irq_beat fires, latching the 32-bit heartbeat interval count with 20.0 ns resolution.

Clinical Intelligence — 91% TinyML & MIMIC-III ICU Validation

91.00%

Synthetic Multi-Hazard Accuracy
(10,000 extreme edge condition test vectors)

92.05%

Clinical Concordance on MIMIC-III
(16,387 gold-standard patient ICU records)

619 Bytes

Ultra-Low SRAM Memory Footprint
(Executes in 42 μ s with zero cloud)

On-Device TinyML INT8 Micro-Engine

Deep Micro-Architecture: 6 Inputs -> 24 Hidden (ReLU) -> 16 Hidden (ReLU) -> 3 Multi-Hazard Outputs (Logistic Sigmoid).

Quantization-Aware Training (QAT): Converted to fixed-point INT8 arithmetic. Zero floating-point math prevents battery drain on edge microcontrollers.

Multi-Disaster Risk Outputs: Independent continuous threat probabilities:

1. Heat Stroke Risk (Cardiovascular drift + thermal index)
2. Smog Distress Risk (PM2.5 inhalation + HRV vagal drop)
3. Flood Hypothermia Risk (Cold shock + bradycardia)

Peer-Reviewed Clinical Foundations

mNEWS2 Triage Protocol: Royal College of Physicians clinical early warning system scoring respiration, blood oxygen, and heart rate for hospital-grade triage.

Karlen & Elgendi SQI (Signal Quality): Algorithms compute skewness, perfusion index, and waveform entropy to eliminate false alarms from arm motion.

Moran's Physiological Strain Index (PSI): Gold-standard cardio-thermal formula quantifying heat exhaustion strain on a scale of 0-10.

AHA Brook Autonomic Stress Model: American Heart Association scientific formula linking acute fine particulate (PM2.5) exposure to vagal heart rate suppression.

Working System — Live GUI Dashboard & Wearable Hardware

Standalone 60 FPS Desktop GUI Dashboard

Real-Time Optical Oscilloscope: Visualizes raw & filtered systolic pulses at 60 frames per second using high-performance Win32 GDI graphics (0 external dependencies).


Dual-Mode Hardware Connectivity: Auto-connects to ESP32-S3 USB COM port at 115,200 baud for live streaming, or switches to 6 simulated disaster profiles for offline demonstrations.

Comprehensive Digital Biomarkers: Displays continuous digital readouts: Heart Rate (BPM), SpO2 (%), Respiratory Rate (RPM), RMSSD HRV (ms), and PM2.5 (ug/m3).

Live Clinical & TinyML Meters: Color-coded dynamic meters for Royal College mNEWS2 clinical triage alongside the 3 on-device AI disaster hazard risk scores.

One-Click Instant Execution: Self-compiles with GCC and launches instantly via `launch_dashboard.bat` from the repository root.

Physical Wearable CAD & Bill of Materials



Custom Ergonomic Enclosure: Engineered in Autodesk CAD with optical skin aperture, strap clips, and airflow ventilation for thermal & PM2.5 sensors.

KiCad PCB & Routing: Complete dual-layer hardware PCB designed in hardware/shrikefi/pcb/ for compact Zero PCB / wearable assembly.

Commercial Mass-Production BOM: • Renesas ForgeFPGA (\$1.80) + ESP32-S3 (\$2.20)

- MAX30102 + BME280 + PM2.5 Sensors (\$5.80)

- OLED + Battery + Enclosure (\$4.20)

=> Total Bulk Unit BOM: <\$15 (~₹1,250)

National Impact & Production Roadmap (India 2026)

IN Tailored for Extreme Indian Climate Emergencies

 **Severe North India Heatwaves (May-June):** Protects 380+ million construction laborers, agricultural workers, and delivery personnel from fatal heat exhaustion by issuing warnings 15-20 minutes before collapse.

 **Winter Toxic Smog in Indo-Gangetic Plains:** Warns traffic police, elderly individuals, and asthmatic patients when hyper-local PM2.5 triggers dangerous autonomic cardiac vagal suppression.

 **Monsoon Flash Floods (Mumbai / Assam):** Detects cold-water immersion, hyperventilation, and bradycardia when citizens or rescue teams are stranded during electric grid and mobile network blackouts.

Commercial Production: Qualcomm Snapdragon Wear

Hardware Challenge Silicon Roadmap: While prototyped on Renesas ForgeFPGA + ESP32-S3 for hackathon accessibility, our architecture is designed for direct migration to Qualcomm Snapdragon Wear W5+ Gen 1.

Qualcomm Hexagon™ DSP Acceleration: The synthesizable Verilog 8-tap filter algorithms map directly to Hexagon Vector eXtensions (HVX) on the Snapdragon Low-Power Island (<5 mW continuous power).

Qualcomm AI Engine (SNPE / QNN): The quantized INT8 neural network compiles natively via Snapdragon Neural Processing Engine (SNPE) for microsecond hardware acceleration.

Enterprise & Defense Readiness: Targeted for National Disaster Response Force (NDRF), municipal sanitation departments, traffic police, and commercial health insurance deployments.