

## Products Family


- **Architecture**
- **Installation**
- **Administration**
- **Maintenance and Support**

## Components

- **Nova.BotConnector**
- **Nova.ChatProxy.Genesys.PureConnect.ICWS**
- **Nova.ChatProxy.Genesys.PureConnect.IWT**
- **Nova.ChatProxy.Genesys.PureEngage**
- **Nova.ChatProxy.Genesys.PureCloud**
- **Nova.ChatProxy.Cisco.ECE**
- **Nova.ChatRouter.Omilia**

## Architecture

Workflow Nova.ChatsConnector



## Installation

## Disable SE Linux

1. Check status # `sestatus`
2. # `sudo setenforce 0`
3. Open the `/etc/selinux/config` file and set the SELINUX mod to `disabled`
4. Restart and check

## MongoDB Installation

1. Add MongoDB repo # `vi /etc/yum.repos.d/mongodb.repo`

```
[MongoDB]
name=MongoDB Repository
baseurl=http://repo.mongodb.org/yum/redhat/$releasever/mongodb-
org/4.2/$basearch/
gpgcheck=1
enabled=1
gpgkey=https://www.mongodb.org/static/pgp/server-4.2.asc
```

2. Install daemon # `yum install mongodb-org`
3. Start daemon # `systemctl start mongod.service`
4. Check TCP Port 27017 is listened `netstat -anp | grep 27017` and try to connect through Robo 3T Client (ssh tunnel needed)

## Nginx Installation

1. Install # `yum install nginx`
2. Updating Diffie-Hellman Parameters

If you test your server using the SSL Labs Server Test now, it will only get a B grade due to weak Diffie-Hellman parameters. This effects the security of the initial key exchange between our server and its users. We can fix this by creating a new `dhparam.pem` file and adding it to our server block.

```
# sudo openssl dhparam -out /etc/ssl/certs/dhparam.pem 2048
```

3. Create and modify config per site:

```
# vim /etc/nginx/conf.d/newsite.conf

server {
    server_name  newsite.com;
    listen 443 ssl;
```

```

ssl_protocols TLSv1.1 TLSv1.2;
ssl_certificate "/etc/pki/nginx/..";
ssl_certificate_key "/etc/pki/nginx/..";
ssl_dhparam "/etc/ssl/certs/dhparam.pem";
ssl_session_cache shared:SSL:1m;
ssl_session_timeout 10m;
ssl_ciphers HIGH:!aNULL:!MD5;
ssl_prefer_server_ciphers on;

access_log /var/log/nginx/newsite.com.acces.log main;

# Nova.ChatsConnector BotConnector Webhooks
location /webhook {
    proxy_set_header    Host $host;
    proxy_set_header    X-Real-IP $remote_addr;
    proxy_set_header    X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header    X-Forwarded-Proto $scheme;
    proxy_pass           http://127.0.0.1:8080;
    proxy_read_timeout  30;
}

# Nova.ChatsConnector BotConnector Download Files
location / {
    root                /var/lib/nginx/nova.chatsconnector;
    try_files           $uri @defaulthome;

    expires             max;
    #access_log         off;
}

# Nova.ChatsConnector BotConnector Default Home
location @defaulthome {
    root                /usr/share/nginx/html;
    try_files           $uri $uri/index.html $uri.html index.html =404;

    expires             max;
}

error_page 404 /404.html;
location = /40x.html {
}

error_page 500 502 503 504 /50x.html;
location = /50x.html {
}

server {
    server_name  newsite.com;
    listen      80;

```

```
    return 301 https://$host$request_uri;
}
```

#### 4. Modify standart config:

```
# vim /etc/nginx/nginx.conf

user nginx;
worker_processes auto;
error_log /var/log/nginx/error.log;
pid /run/nginx.pid;

# Load dynamic modules. See /usr/share/nginx/README.dynamic.
include /usr/share/nginx/modules/*.conf;

events {
    worker_connections 1024;
}

http {
    log_format main '$remote_addr - $remote_user [$time_local]
"$request" '
                    '$status $body_bytes_sent "$http_referer" '
                    '"$http_user_agent" "$http_x_forwarded_for"';

    access_log /var/log/nginx/access.log main;
    # Security
    server_tokens off;

    sendfile            on;
    tcp_nopush          on;
    tcp_nodelay         on;
    keepalive_timeout   65;
    types_hash_max_size 2048;

    # Optimization
    gzip on;
    gzip_types application/javascript image/* text/css;
    gunzip on;

    include              /etc/nginx/mime.types;
    default_type         application/octet-stream;

    # Load modular configuration files from the /etc/nginx/conf.d
    directory.
    # See http://nginx.org/en/docs/nginx\_core\_module.html#include
    # for more information.
    include /etc/nginx/conf.d/*.conf;
```

```
}
```

## 5. Validate nginx configuration

```
# nginx -t
```

## 6. Check nginx functionality.

# Node.JS Installation

## 1. Install *Stable* Release

```
# yum install -y gcc-c++ make
# curl -sL https://rpm.nodesource.com/setup_12.x | sudo -E bash -
# sudo yum install nodejs
```

## 2. Check versions

```
# node -v
# npm -v
```

# .Net CORE Installation (PureConnect Only)

[Prerequisites 2.0.x Core \(Microsoft article\)](#)

[Install 2.0.x Core \(Microsoft article\)](#)

## 1. Add Repos and dependencies

```
# rpm -Uvh https://packages.microsoft.com/config/rhel/7/packages-microsoft-
prod.rpm
# yum install dotnet-sdk-2.0.3
```

```
=====
=====
Package                        Arch      Version
Repository                    Size
=====
=====
Installing:
dotnet-sdk-2.0.3              x86_64    2.0.3-1
```

```

packages-microsoft-com-prod      86 M
Installing for dependencies:
aspnetcore-store-2.0.0           x86_64      2.0.0-1
packages-microsoft-com-prod      24 M
aspnetcore-store-2.0.3           x86_64      2.0.3-1
packages-microsoft-com-prod      7.9 M
dotnet-host                       x86_64      2.2.5-1
packages-microsoft-com-prod      44 k
dotnet-hostfxr-2.0.3            x86_64      2.0.3-1
packages-microsoft-com-prod      182 k
dotnet-runtime-2.0.3            x86_64      2.0.3-1
packages-microsoft-com-prod      24 M

```

#### Transaction Summary

```

=====
=====
Install 1 Package (+5 Dependent packages)

```

## 2. Validate Installation

Try to RUN PureConnect IWT ChatProxy

### ***NovaChatsConnector Components Installation***

All of Packages install from RPM.

```
# rpm -ivh ${nova-component}.rpm
```

Update for all Packages install from RPM. Before updating backup is recommended.

```
# rpm -Uvh ${nova-component}.rpm
```

## Administration

Chatproxy manages by **systemd**. Some commands:

Operation	Command
status	<code>systemctl status \${daemon}.service</code>
restart	<code>systemctl restart \${daemon}.service</code>
stop	<code>systemctl stop \${daemon}.service</code>
start	<code>systemctl start \${daemon}.service</code>
view service logs	<code>journalctl -xe -u \${daemon}.service</code>

Operation	Command
check net use	<code>netstat -anp   grep LISTEN</code>

Maintenance and Support

---

## Setup Components

---

### Nova.BotConnector

- *Introduction*

Nova.BotConnector allows you to connect your bot to multiple messaging channels.

- **Core** component. Provides routing messages from outside to the another components and back. Works as a Linux daemon behind Reverse-proxy.
- The **Core** is requested by Webhook from outside (from Messengers).
- The **Core** is requested by `POST` | `PUT` | `DELETE` requests from inside (e.g. `curl`, another components).

- *Installation*

#### 1. Install Component

```
# rpm -ivh $HOME/nova-botconnector-2020_R1-1.x86_64.rpm
```

#### 2. Modify and enable service

```
# systemctl enable nova-botconnector.service
# vim /etc/systemd/system/multi-user.target.wants/nova-
botconnector.service

[Unit]
Description=Nova.BotConnector service
After=network.target mongodb.service

[Service]
ExecStart=/usr/bin/node /opt/nova-botconnector/src/index.js
WorkingDirectory=/opt/nova-botconnector
Restart=on-failure
StandardOutput=syslog
StandardError=syslog
SyslogIdentifier=botconnector
User=botconnector
Group=botconnector
```

```
Environment=NODE_ENV=production
```

```
[Install]
```

```
WantedBy=multi-user.target
```

The last option **Environment** in **[Service]** section means what config service have to use Production or Development config file.

### 3. Configure your Nova.BotConnector

```
#vim /opt/nova-botconnector/conf/production.js
```

Section	Parameter	Value	Explanation
db	uri	URL	connection to Mongo. Replica-set Supported
db	options	JSON	default
server	port	int	application bind port
server	host	string	application bind IP
server	base_url	URL	base URL for webhook, must be FQDN
server	cleanOlder	int	remove conversations older than x day

```
module.exports = {
  db: {
    uri: 'mongodb://127.0.0.1:27017/nova-botconnector',
    debugMode: false,
    options: {
      useNewUrlParser: true,
      reconnectTries: Number.MAX_VALUE,
      reconnectInterval: 1000,
      poolSize: 10,
      connectTimeoutMS: 5000,
      family: 4,
      keepAlive: true,
      keepAliveInitialDelay: 300000,
    },
  },
  server: {
    port: '8080',
    host: '127.0.0.1',
    base_url: 'https://yourservername.com',
    cleanOlder: 7
  },
  logging: { // log4js-node configuration
```



```

    appenders: {
      file: {
        type: 'file',
        filename: '/var/log/nova-botconnector/nova-botconnector.log',
        maxLogSize: 52428800, // 50 MB
        backups: 5,
        compress: true,
        keepFileExt: true
      }
    },
    categories: {
      default: {appenders: ['file'], level: 'debug'}
    }
  },
}

```

#### 4. Start your service

```

# systemctl start nova-botconnector
# systemctl status nova-botconnector

```

#### 5. Create **New Connector Instance** of Nova.BotConnector

- *Administration*

##### 1. New Connector Instance

You have to decide what TCP Port will be used and set into request

```

# curl -X POST 'http://localhost:8080/connectors' --data
'url=http://localhost:5000'

```

You will receive response with UUID `${CONNECTOR_ID}` of new Connector. Remember this value (or found in mongodb).

In case with Genesys PureConnect command will be:

```

# curl -X POST 'http://localhost:8080/connectors' --data
'url=http://localhost:5000/api/message'

```

##### 2. Add Channels

- *Trough Nova Chats API (WhatsApp, Skype, Instagram)*

Before adding channel, you have to Create it on [Nova.Chats](#)

- **Nova Chats**

```
curl -X POST \
--data "slug=WhatsappPureConnect" \
--data "type=novachats" \
--data "token=c4436e57856ff976e9473b75f1bbe2" \
--data "isActivated=true" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

- **Direct API**

- **Telegram**

```
curl -X POST \
--data "isActivated=true" \
--data "slug=TelegramSlug" \
--data "token=652278712:AAGI8FqQwGPa_K4Gf-smLvZXx4zbqk8Q4is" \
--data "type=telegram" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

- **Viber**

```
curl -X POST \
--data "isActivated=true" \
--data "slug=BiberSlug" \
--data "token=49674f056da7d074-c09d50d64d30605e-2e3da1df1adaa0ac" \
--data "type=viber" \
--data "userName=NovaIT" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

- **Twilio**

```
curl -X POST \
--data "isActivated=true" \
--data "slug=WhatsAppSlug" \
--data "phoneNumber=whatsapp:+14155238886" \
--data "clientId=id" \
--data "clientSecret=secret" \
--data "type=whatsapp" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

- **Nexmo**

```
curl -X POST \
--data "slug=NexmoDemo" \
--data "isActivated=true" \
--data "type=nexmo" \
--data "token=811ntawuntawun0qxt" \
--data "phoneNumber=447418342149" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

- **Infobip**

```
curl -X POST \
--data "slug=InfobipSlug" \
--data "isActivated=true" \
--data "type=infobip" \
--data "userName=Nova-It" \
--data "password=GRvsQfdFU22frs6U" \
--data "phoneNumber=447491163530" \
--data "accountKey=C6321E1DCFB76208EA8CEB665FA1D48A" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

- **WeChat**

```
curl -X POST \
--data "slug=WeChat" \
--data "isActivated=true" \
--data "type=wechat" \
--data "appId=appId" \
--data "appSecret=secret" \
--data "token=12345678901" \
--data "userName=wechat" \
"http://localhost:8080/connectors/{CONNECTOR_ID}/channels"
```

- **WebChat**

```
curl -X POST \
--data "slug=WebChat" \
--data "isActivated=true" \
--data "type=webchat" \
"http://localhost:8080/connectors/${CONNECTOR_ID}/channels"
```

### 3. Send test message and view logs according to *production/development.js*

More information see in next section.

#### 4. Connectivity checking

First of all, check that all the needed service started and successfully run.

- Nginx (or another reverse-proxy)
- BotConnector
- ChatProxy

Also, check that bound Ports are LISTENING.

The right way to check how it works - register one of the simplest channel, Telegram, and write a few messages to bot.

After that you can check the logs:

1. First logs can be **Nginx** logs. You can see how messages arrive and request a webhook.
2. BotConnector log **\$LOG/nova-botconnector.log**.
3. ChatProxy log **\$LOG/nova-chatproxy.log**.

If the log doesn't give clear/detailed information - try to change Log Level, according to using Logger Specs (log4js, nlog ).

UUIDs that help to track messaging.

Entity	Meaning
ConnectorID	First UUID in one log string, ID of Connector Instance
conversation	ID of conversation on kept trough all logs
source	type of channel

#### 5. Some commands

ChatpRouter manages by **systemd**. Usefull commands are:

Operation	Command
check status	<b>systemctl status nova-botconnector.service</b>
restart	<b>systemctl restart nova-botconnector.service</b>
restart	<b>systemctl stop nova-botconnector.service systemctl start nova-botconnector.service</b>
view service logs	<b>journalctl -xe -u nova-botconnector.service</b>
check net use	<b>netstat -anp   grep LISTEN</b>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service
2. Copy current release with all files into another place:

```
# cp /opt/nova-botconnector/ $HOME/backup
```

3. Install update from by RPM

```
# rpm -Uvh nova-botconnector-2020_R1-1.x86_64.rpm
```

4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.
5. Start service and check connectivity

## Nova.ChatProxy.Genesys.PureConnect.ICWS

- *Introduction*

Nova.ChatProxy.Genesys.PureConnect allows you to connect Nova.BotConnector with Genesys PureConnect by using ICWS API.

- *Installation*

1. Install Component

```
# rpm -ivh $HOME/nova-chatproxy-genesys-pureeconnect-2020_R1-1.x86_64.rpm
```

2. Configure your Nova.ChatProxy

```
# cd /opt/nova-chatproxy-genesys-pureeconnect/config/  
# cp chatproxy.js nova-chatproxy-genesys-pureeconnect.js
```

Component's Settings:

Section	Parameter	Value	Explanation
db	uri	URL	connection to Mongo. Replica-set Supported
db	options	JSON	default

Section	Parameter	Value	Explanation
genesys	endpoint	URL	
chat	targetName	string	Target Genesys Workgroup
chat	firstName lastName	string	from Who you will be see chat-session
chat	additionalAttributes	JSON	A collection of any additional attributes associated with the interaction. These can be standard CIC attribute names or custom attribute names to support custom handlers / integrations
chat	pollingInterval	int	Pooling timeout in miliseconds
chat	systemMessages	boolean	enable or disable
chat	welcomeMessage waitForAgentMessage chatEndMessage	string	enables messages from internal settings <code>/opt/nova-chatproxy-cisco-ece/resources/messages.json</code> ; filename must be like Enviroment variable in SYSTEMD.
app	host	string	own host
app	port	int	own port
app	endQueuedSessions	int	how quickly QUEUED session have will be deleted, in <i>min</i>
app	endDeadSessions	int	how quickly DEAD session have will be deleted in <i>min</i>
app	downloadFolder	string	local directory where media will be stored
app	downloadURLPrefix	string	prefix for formation full URL of stored media
app	downloadMaxSize	int	max size of download media. in <i>Bytes</i>
connector	url	URL	Internal BotConnector's URL
connector	connectorId	UUID	The ID of Botconnector Instance what have to process messages from ChatProxy

```

module.exports = {
  db: {
    uri: 'mongodb://127.0.0.1:27017/nova-chatproxy-genesys-pureconnect-icws',
    debugMode: false,
    options: {
      useUrlParser: true,
      useFindAndModify: false,
      reconnectTries: Number.MAX_VALUE,
      reconnectInterval: 5000,
    }
  }
}

```

```
    poolSize: 10,
    connectTimeoutMS: 5000,
    family: 4,
    keepAlive: true,
    keepAliveInitialDelay: 300000,
  },
},
genesys: {
  endpoint: 'https://site.com/api/site.inin.local',
  timeout: 5000
},
chat: {
  targetName: 'Workgroup',
  firstName: 'Nova',
  lastName: 'ChatProxy',
  additionalAttributes: {
    chatApplication: 'Nova.ChatProxy',
  },
  pollingInterval: 2000,
  systemMessages: true,
  welcomeMessage: false,
  waitForAgentMessage: false,
  chatEndMessage: false,
},
app: {
  host: '127.0.0.1',
  port: 5000,
  endQueuedSessions: 3,
  endDeadSessions: 1440,
  downloadFolder: '/var/lib/nginx/downloads/',
  downloadURLPrefix: 'https://yourservername.com/',
  downloadMaxSize: 52428800 // 50 MB
},
connector: {
  url: 'http://127.0.0.1:8080/connectors/',
  connectorId: '01b74904-71c9-4dec-9a0c-def2115989ca',
  timeout: 5000
},
logging: { // log4js-node configuration
  appenders: {
    file: {
      type: 'file',
      filename: '/var/log/nova-chatproxy-genesys-
pureconnect/chatproxy.log',
      maxLogSize: 52428800, // 50 MB
      backups: 5,
      compress: true,
      keepFileExt: true
    }
  },
  categories: {
```

```
        default: {appenders: ['file'], level: 'trace'}
    }
}
}
```

### 3. Modify and enable service

```
# cd /etc/systemd/system/
# vim /etc/systemd/system/nova-chatproxy-genesys-pureconnect.service

[Unit]
Description=Genesys PureConnect using ICWS API proxy for Nova.BotConnector.
After=network.target mongod.service

[Service]
ExecStart=/usr/bin/node /opt/nova-chatproxy-genesys-pureconnect/src/index.js
WorkingDirectory=/opt/nova-chatproxy-genesys-pureconnect
Restart=on-failure
RestartSec=30
StandardOutput=syslog
StandardError=syslog
SyslogIdentifier=nova-chatproxy-genesys-pureconnect
User=botconnector
Group=botconnector
Environment=CHATPROXY_INSTANCE=nova-chatproxy-genesys-pureconnect

[Install]
WantedBy=multi-user.target

# systemctl enable nova-chatproxy-genesys-pureconnect.service
# chown botconnector.botconnector /etc/systemd/system/nova-chatproxy-genesys-pureconnect.service
# chown botconnector.botconnector -R /opt/nova-chatproxy-genesys-pureconnect/config/
# systemctl start nova-chatproxy-genesys-pureconnect.service
```

The last option **Environment** in **[Service]** section means what config service have to use from config files.

- *Administration*

#### **Connectivity checking**

First of all, check that the needed ChatProxy service started and successfully run.

Check bound Port is LISTEN.



Check ChatProxy log and systemd unit log (`journalctl -xe -u nova-chatproxy-genesys-pureconnect.service`)

If the log doesn't give clear/have detailed information - try to change Log Level, according to using Logger Specs (log4js).

UUIDs that help to track messaging.

Entity	Meaning
ConnectorID	First UUID in one log string, ID of Connector Instance
conversation	ID of conversation on kept trough all logs
source	type of channel

### Some commands

ChatpRouter manages by `systemd`. Usefull commands are:

Operation	Command
check status	<code>systemctl status nova-chatproxy.service</code>
restart	<code>systemctl restart nova-chatproxy.service</code>
restart	<code>systemctl stop nova-chatproxy.service systemctl start nova-chatproxy.service</code>
view service logs	<code>journalctl -xe -u nova-chatproxy.service</code>
check net use	<code>netstat -anp   grep LISTEN</code>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service
2. Copy current release with all files into another place:

```
# cp /opt/nova-chatproxy-genesys-pureconnect/ $HOME/backup
```

3. Install update from by RPM

```
# rpm -Uvh nova-chatproxy-genesys-pureconnect-2020_R1-1.x86_64.rpm
```

4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.
5. Start service and check connectivity

## Nova.ChatProxy.Genesys.PureConnect.IWT

- *Introduction*

Nova.ChatProxy.Genesys.PureConnect allows you to connect Nova.BotConnector with Genesys PureConnect by using Interaction Web Tools API.

- *Installation*

Nova.ChatProxy.Genesys.PureConnect.IWT developed by .NET. RPM doesn't supported. Each brand new Instance of Chatproxy IWT copied from tar.gz.

Before deploying Instance you have to Install .Net Core.

1. Untar Nova.ChatProxy\_v1.7.0.0.zip into /opt/chatProxyPureConnectIWT
2. Configure Port.

You have to decide, what port it will be. This port only for Internal user between components.

```
# vim /opt/chatProxyPureConnectIWT/hosting.json
{
  "urls": "http://127.0.0.1:5000"
}
```

3. Configure Logs.

You have to decide where it will be. For Logging solution uses NLog and have XML structure. Modify **nlog variables** for defining place for logs.

```
<?xml version="1.0" encoding="utf-8" ?>
<nlog xmlns="http://www.nlog-project.org/schemas/NLog.xsd"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      autoReload="true"
      internalLogLevel="Warn"
      internalLogFile="internal-nlog.txt">

  <!-- Load the ASP.NET Core plugin -->
  <extensions>
    <add assembly="NLog.Web.AspNetCore"/>
  </extensions>

  <variable name="logDirectory" value="logs/${shortdate}" />
  <variable name="logRootDirectory" value="./logs" />
```

```

<!-- the targets to write to -->
<targets>
  <!-- write logs to file -->
  <target xsi:type="File"
    name="allfile"
    archiveEvery ="Hour"
    createDirs="True"
    archiveFileName="${logRootDirectory}/archive/nlog-all_{##}.log"
    archiveNumbering="Rolling"
    maxArchiveFiles="5"
    fileName="${logRootDirectory}/nlog-all.log"
    layout="${longdate}|${uppercase:${level}}|${event-
properties:item=EventId.Id}|${logger}|${message} ${exception}" />

  <!-- another file log, only own logs. Uses some ASP.NET core renderers
-->
  <target xsi:type="File"
    name="ownFile-web"
    archiveEvery ="Hour"
    archiveFileName="${logRootDirectory}/archive/nlog-all_{##}.log"
    createDirs="True"
    archiveNumbering="Rolling"
    maxArchiveFiles="5"
    fileName="${logRootDirectory}/nlog-chatProxy.log"
    layout="${longdate}| ${uppercase:${level}}| ${callsite} |
${message} ${exception}" />

  <!-- write to the void aka just remove -->
  <target xsi:type="Null" name="blackhole" />
</targets>

<!-- rules to map from logger name to target -->
<rules>

```

#### 4. Configure ChatProxy

Component's Settings:

Section	Parameter	Value	Explanation
MongoDB	Client	URI	connection to Mongo. Replica-set Supported
MongoDB	Database	string	DB name
BotConnector	Url	URL	from BotConnector settings. Where the BotConnector LISTEN as a Daemon

Section	Parameter	Value	Explanation
BotConnector	ConnectorId	UUID	To which BotConnector ChatProxy have to route messages from Genesys side
BotConnector	Timeout	int	how long wait response from BotConnector
BotConnector	FirstHandler	int	default
BotConnector	DownloadFolder	int	Where sended media will be stored
BotConnector	DownloadURLPrefix	int	Places this address for full URL in Response to Customer
InternalConnectors	Connector.Url	string	Main Route. Can be directly to CIC. HTTP or HTTPS
InternalConnectors	Connector.UrlAlternative	string	Backup Route. Can be directly to CIC. HTTP or HTTPS
InternalConnectors	Connector.Workgroup	string	Workgroup on Genesys side
InternalConnectors	Connector.InactiveIntervalMinutes	int	How long keep connection to Genesys side
InternalConnectors	Connector.UserNamePattern	string	What data can be transfer into Name on Genesys Side

```
{
  "Configuration": {
    "MongoDB": {
      "Client": "mongodb://localhost:27017",
      "Database": "ChatProxyNovaPureConnect"
    },
    "BotConnector": {
      "Url": "http://127.0.0.1:8080",
      "ConnectorId": "786b4297-e5aa-439c-a8f7-37d8dd61c836",

```

```

    "Timeout": 10,
    "FirstHandler": "Genesys_PureConnect_Ex_Chat_Queue",
    "DownloadFolder": "/var/lib/nginx/downloads/",
    "DownloadURLPrefix": "https://novachatsconnector.demo.novait.com.ua"
  },

  "InternalConnectors": [
  {
    "Name": "Genesys_PureConnect_Ex_Chat_Queue",
    "Type": "Genesys.PureConnect.Ex",
    "Connector": {
      "Url": "https://192.168.1.1/I3Root/Server1",
      "UrlAlternative": "https://192.168.1.2/I3Root/Server1",
      "Workgroup": "W_Nova.ChatsConnector_Queue",
      "InactiveIntervalMinutes": 1,
      "UserNamePattern": "{chatid}, {senderid}, {__v}, {_id},
{participant}, {conversation}, {receivedat}, {userid}, {username},
{lastname}, {firstname}, {source}, {type}"

    }
  }
]
}
}

```

## 5. Create Service

```

# cd /etc/systemd/system/
# vim /etc/systemd/system/nova-chatproxy-iwt.service

[Unit]
Description=Chat Proxy for bot connector. Customer: IWT

[Service]
WorkingDirectory=/opt/chatProxyPureConnectIWT
ExecStart=/usr/bin/dotnet /opt/chatProxyPureConnectIWT/ChatProxy.dll
Restart=always
RestartSec=10 # Restart service after 10 seconds if dotnet service crashes
SyslogIdentifier=chatproxy-pivotalgroup
User=root
Environment=ASPNETCORE_ENVIRONMENT=Production
Environment=DOTNET_PRINT_TELEMETRY_MESSAGE=false

[Install]
WantedBy=multi-user.target

# systemctl enable nova-chatproxy-iwt.service
# chown botconnector.botconnector /etc/systemd/system/nova-chatproxy-

```

```
iwt.service
# chown botconnector.botconnector -R /opt/nova-chatproxy-iwt/config/
# systemctl start nova-chatproxy-iwt.service
```

The last option **Environment** in **[Service]** section means what config service have to use from config files.

- *Administration*

### Connectivity checking

First of all, check that the needed ChatRouter service started and successfully run.

Check bound Port is LISTEN.

Check ChatProxy log and systemd unit log (`journalctl -xe -u nova-cahtrouter.service`)

If the log doesn't give clear/have detailed information - try to change Log Level, according to using Logger Specs (nlog).

UUIDs that help to track messaging.

Entity	Meaning
ConnectorID	First UUID in one log string, ID of Connector Instance
conversation	ID of conversation on kept trough all logs
source	type of channel

### Some commands

ChatpRouter manages by **systemd**. Usefull commands are:

Operation	Command
check status	<code>systemctl status nova-chatproxy.service</code>
restart	<code>systemctl restart nova-chatproxy.service</code>
restart	<code>systemctl stop nova-chatproxy.service systemctl start nova-chatproxy.service</code>
view service logs	<code>journalctl -xe -u nova-chatproxy.service</code>
check net use	<code>netstat -anp   grep LISTEN</code>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service
2. Copy current release with all files into another place:

```
# cp /opt/nhatProxyPureConnectIWT/ $HOME/backup
```

3. Install update by coping from tat.gz to working directory.
4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.
5. Start service and check connectivity

## Nova.ChatProxy.Genesys.PureEngage

- *Introduction*

Nova.ChatProxy.Genesys.PureEngage allows you to connect Nova.BotConnector with Genesys PureEngage.

- *Installation*

1. Install Component

```
# rpm -ivh $HOME/nova-chatproxy-genesys-pureengage-2020_R2-1.x86_64.rpm
```

2. Configure your Nova.ChatProxy

```
# cd /opt/nova-chatproxy-genesys-pureengage/config/  
# cp chatproxy.js nova-chatproxy-genesys-pureengage.js
```

Component's Settings:

Section	Parameter	Value	Explanation
db	uri	URL	connection to Mongo. Replica-set Supported
db	options	JSON	default
genesys	endpoint	URL	Path to internal or external endpoint
chat	serviceName	string	Service Name on Genesys endpoint (Queue)
chat	firstname	string	see the example below. Can be Pattern for sending channel info to end system
chat	lastname	sstring	see the example below. Can be Pattern for sending channel info to end system

Section	Parameter	Value	Explanation
chat	attachedUserData	JSON	Could be added additional custom parameters for sending into Genesys
chat	memberInfo	JSON	patterns, that can be send to customer side
chat	welcomeMessage waitForAgentMessage chatEndMessage systemMessages	boolean	enables messages from internal settings /opt/nova-chatproxy-genesys-purecloud/messages.json; filename must be like Enviroment variable in SYSTEMD
chat	pollingInterval	int	how frequently endpoint will be requested (in milisec)
app	host	string	own host
app	port	int	own port
app	downloadFolder	string	local directory where media will be stored
app	downloadURLPrefix	string	prefix for formation full URL of stored media
app	downloadMaxSize	int	max size of download media. in Bytes
connector	url	URL	Internal BotConnector's URL
connector	connectorId	UUID	The ID of Botconnector Instance what have to proccess messages from ChatProxy

```

module.exports = {
  db: {
    uri: 'mongodb://127.0.0.1:27017/nova-chatproxy-genesys-pureengage',
    debugMode: false,
    options: {
      useUrlParser: true,
      useFindAndModify: false,
      reconnectTries: Number.MAX_VALUE,
      reconnectInterval: 5000,
      poolSize: 10,
      connectTimeoutMS: 5000,
      family: 4,
      keepAlive: true,
      keepAliveInitialDelay: 300000,
    }
  },
  genesys: {
    endpoint: 'https://gbank.demo.genesys.com/gms_port_8010',
    timeout: 5000,
  },
  chat: {
    serviceName: 'customer-support',
    firstName: '{userid}',
  }
}

```



```

        lastName: 'ChatProxy | {source}',
        attachedUserData: {
          pfs_id: '380672189796',
          channel: '{source}',
        },
        pollingInterval: 3000,
        welcomeMessage: false,
        waitForAgentMessage: false,
        chatEndMessage: false,
      },
      app: {
        host: '127.0.0.1',
        port: 5000,
        downloadFolder: '/var/lib/nginx/downloads/nccpengage',
        downloadURLPrefix:
'https://novachatsconnector.demo.novait.com.ua/nccpengage',
        downloadMaxSize: 52428800 // 50 MB
      },
      connector: {
        url: 'http://127.0.0.1:8080/connectors/',
        connectorId: 'd4e38610-ac6a-43f3-8222-78e44fb46512',
        timeout: 5000
      },
      logging: { // log4js-node configuration
        appenders: {
          file: {
            type: 'file',
            filename: '/var/log/nova-chatproxy-genesys-
pureengage/gdemo/nova-chatproxy.log',
            maxLogSize: 52428800, // 50 MB
            backups: 5,
            compress: true,
            keepFileExt: true
          }
        },
        categories: {
          default: {appenders: ['file'], level: 'trace'}
        }
      }
    }
  }
}

```

### 3. Modify and enable service

```

# cd /etc/systemd/system/
# vim /etc/systemd/system/nova-chatproxy-genesys-pureengage.service

[Unit]
Description=Genesys PureEngage proxy for Nova.BotConnector
After=network.target mongodb.service

```

```

[Service]
ExecStart=/usr/bin/node /opt/nova-chatproxy-genesys-pureengage/src/index.js
WorkingDirectory=/opt/nova-chatproxy-genesys-pureengage
Restart=on-failure
RestartSec=30
StandardOutput=syslog
StandardError=syslog
SyslogIdentifier=nova-chatproxy-genesys-pureengage
User=botconnector
Group=botconnector
Environment=CHATPROXY_INSTANCE=nova-chatproxy-genesys-pureengage

[Install]
WantedBy=multi-user.target

# systemctl enable nova-chatproxy-genesys-pureengage.service
# chown botconnector.botconnector /etc/systemd/system/nova-chatproxy-
genesys-pureengage.service
# chown botconnector.botconnector -R /opt/nova-chatproxy-genesys-
pureengage/config/
# systemctl start nova-chatproxy-genesys-pureengage.service

```

The last option **Environment** in **[Service]** section means what config service have to use from config files.

- *Administration*

### Connectivity checking

First of all, check that the needed ChatProxy service started and successfully run.

Check bound Port is LISTEN.

Check ChatProxy log and systemd unit log (**journalctl -xe -u nova-chatproxy-genesys-pureengage.service**)

If the log doesn't give clear/have detailed information - try to change Log Level, according to using Logger Specs (log4js).

UUIDs that help to track messaging.

Entity	Meaning
ConnectorID	First UUID in one log string, ID of Connector Instance
conversation	ID of conversation on kept trough all logs
source	type of channel

### Some commands

ChatpRouter manages by **systemd**. Usefull commands are:

Operation	Command
check status	<code>systemctl status nova-chatproxy-genesys-purecloud.service</code>
restart	<code>systemctl restart nova-chatproxy-genesys-pureengage.service</code>
restart	<code>systemctl stop nova-chatproxy-genesys-pureengage.service systemctl start nova-chatproxy-genesys-pureengage.service</code>
view service logs	<code>journalctl -xe -u nova-chatproxy-genesys-pureengage.service</code>
check net use	<code>netstat -anp   grep LISTEN</code>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service
2. Copy current release with all files into another place:

```
# cp /opt/nova-chatproxy-genesys-pureengage/ $HOME/backup
```

3. Install update from by RPM

```
# rpm -Uvh nova-chatproxy-genesys-pureengage-2020_R3-1.x86_64.rpm
```

4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.
5. Start service and check connectivity

## Nova.ChatProxy.Genesys.PureCloud

- *Introduction*

Nova.ChatProxy.Genesys.PureCloud allows you to connect Nova.BotConnector with Genesys PureCloud WebChat.

- *Installation*

1. Install Component

```
# rpm -ivh $HOME/nova-chatproxy-genesys-purecloud-2020_R1-1.x86_64.rpm
```

## 2. Configure your Nova.ChatProxy

```
# cd /opt/nova-chatproxy-genesys-purecloud/config/  
# cp chatproxy.js nova-chatproxy-genesys-purecloud.js
```

Component's Settings:

Section	Parameter	Value	Explanation
db	uri	URL	connection to Mongo. Replica-set Supported
db	options	JSON	default
genesys	endpoint	URL	<a href="#">Australia/New Zealand</a> , <a href="#">EU Ireland</a> , <a href="#">EU Frankfurt</a> , <a href="#">Japan</a>
genesys	welcomeMessage waitForAgentMessage chatEndMessage unsupportedContentMessage	boolean	enables messages from internal settings <code>/opt/nova-chatproxy-genesys-purecloud/messages.json</code> ; filename must be like Enviroment variable in SYSTEMD
genesys	purecloud	JSON	see the example below
genesys	memberInfo	JSON	patterns, that can be send to customer side
app	host	string	own host
app	port	int	own port
app	endQueuedSessions	int	how quickly QUEUED session have will be deleted, in <i>min</i>
app	endDeadSessions	int	how quickly DEAD session have will be deleted in <i>min</i>
app	downloadFolder	string	local directory where media will be stored
app	downloadURLPrefix	string	prefix for formation full URL of stored media
app	downloadMaxSize	int	max size of download media. in <i>Bytes</i>
app	connector.url	URL	Internal BotConnector's URL

Section	Parameter	Value	Explanation
app	connector.connectorId	UUID	The ID of Botconnector Instance what have to process messages from ChatProxy

```

module.exports = {
  db: {
    uri: 'mongodb://127.0.0.1:27017/nova-chatproxy-genesys-purecloud',
    debugMode: false,
    options: {
      useUrlParser: true,
      useFindAndModify: false,
      reconnectTries: 999999,
      reconnectInterval: 5000,
      poolSize: 10,
      connectTimeoutMS: 5000,
      family: 4,
      keepAlive: true,
      keepAliveInitialDelay: 300000,
    }
  },
  genesys: {
    endpoint: 'https://api.mypurecloud.ie',
    timeout: 50000,
    welcomeMessage: false,
    waitForAgentMessage: true,
    chatEndMessage: false,
    unsupportedContentMessage: true,
    defaultDisplayName: 'Nova.ChatsConnector',
    purecloud: {
      organizationId: '7d3b1626-0152-4568-98e4-900512803047',
      deploymentId: '329215a2-b571-4073-8489-baf44824795d',
      routingTarget: {
        targetType: 'queue',
        targetAddress: 'ChatQueue',
      },
    },
    memberInfo: { // can be customized
      displayName: "{firstname} {lastname}",
      lastName: "{firstname}",
      firstName: "{lastname}",
      customFields: {
        origin: '{source}',
        userid: '{userid}',
      }
    },
  },
},
app: {

```

```

        host: '127.0.0.1',
        port: 5000,
        endQueuedSessions: 1,
        endDeadSessions: 1440,
        downloadFolder: '/var/lib/nginx/downloads/tmp',
        downloadURLPrefix: 'https://yourservername.com/tmp',
        downloadMaxSize: 52428800 // 50 MB
    },
    connector: {
        url: 'http://127.0.0.1:8080/connectors/',
        connectorId: 'c019973d-f8e9-4c9c-b8ed-a688115b48f0',
        timeout: 5000
    },
    logging: { // log4js-node configuration
        appenders: {
            file: {
                type: 'file',
                filename: '/var/log/nova-chatproxy-genesys-
purecloud/nova/nova-chatproxy.log',
                maxLogSize: 52428800, // 50 MB
                backups: 5,
                compress: true,
                keepFileExt: true
            }
        },
        categories: {
            default: {appenders: ['file'], level: 'ALL'}
        }
    }
}

```

### 3. Modify and enable service

```

# cd /etc/systemd/system/
# vim /etc/systemd/system/nova-chatproxy-genesys-purecloud.service

[Unit]
Description=Genesys PureCloud proxy for Nova.BotConnector
After=network.target mongod.service

[Service]
ExecStart=/usr/bin/node /opt/nova-chatproxy-genesys-purecloud/src/index.js
WorkingDirectory=/opt/nova-chatproxy-genesys-purecloud
Restart=on-failure
RestartSec=30
StandardOutput=syslog
StandardError=syslog
SyslogIdentifier=nova-chatproxy-genesys-purecloud
User=botconnector
Group=botconnector

```

```

Environment=CHATPROXY_INSTANCE=nova-chatproxy-genesys-purecloud

[Install]
WantedBy=multi-user.target

# systemctl enable nova-chatproxy-genesys-purecloud.service
# chown botconnector.botconnector /etc/systemd/system/nova-chatproxy-
genesys-purecloud.service
# chown botconnector.botconnector -R /opt/nova-chatproxy-genesys-
purecloud/config/
# systemctl start nova-chatproxy-genesys-purecloud.service

```

The last option **Environment** in **[Service]** section means what config service have to use from config files.

- *Administration*

### Connectivity checking

First of all, check that the needed ChatProxy service started and successfully run.

Check bound Port is LISTEN.

Check ChatProxy log and systemd unit log (`journalctl -xe -u nova-chatproxy-genesys-purecloud.service`)

If the log doesn't give clear/have detailed information - try to change Log Level, according to using Logger Specs (log4js).

UUIDs that help to track messaging.

Entity	Meaning
<b>ConnectorID</b>	First UUID in one log string, ID of Connector Instance
<b>conversation</b>	ID of conversation on kept trough all logs
<b>source</b>	type of channel

### Some commands

ChatpRouter manages by **systemd**. Usefull commands are:

Operation	Command
check status	<code>systemctl status nova-chatproxy-genesys-purecloud.service</code>
restart	<code>systemctl restart nova-chatproxy-genesys-purecloud.service</code>
restart	<code>systemctl stop nova-chatproxy-genesys-purecloud.service systemctl start nova-chatproxy-genesys-purecloud.service</code>

Operation	Command
view service logs	<code>journalctl -xe -u nova-chatproxy-genesys-purecloud.service</code>
check net use	<code>netstat -anp   grep LISTEN</code>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service
2. Copy current release with all files into another place:

```
# cp /opt/nova-chatproxy-genesys-purecloud/ $HOME/backup
```

3. Install update from by RPM

```
# rpm -Uvh nova-chatproxy-genesys-purecloud-2020_R1-1.x86_64.rpm
```

4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.
5. Start service and check connectivity

## Nova.ChatProxy.Cisco.ECE

- *Introduction*

Nova.ChatProxy.Cisco.ECE allows you to connect Nova.BotConnector with Cisco Enterprise Chat and Email (ECE).

- *Installation*

1. Install Component

```
# rpm -ivh $HOME/nova-chatproxy-cisco-ece-2020_R1-1.x86_64.rpm
```

2. Configure your Nova.ChatProxy



```
# cd /opt/nova-chatproxy-cisco-ece/config/
# cp chatproxy.js nova-chatproxy-cisco-ece.js
```

Component's Settings:

Section	Parameter	Value	Explanation
db	uri	URL	connection to Mongo. Replica-set Supported
db	options	JSON	default
egain	corsHost	URL	FQDN for chat
chat	entryPointId	int	Entry Point ID from Cisco settings
chat	locale	string	settings from Cisco Chat settings
chat	templateName	string	settings from Cisco Chat settings
chat	firstName lastName	string	from Who you will be see chat-session
chat	systemMessages	boolean	enable or disable
chat	welcomeMessage waitForAgentMessage chatEndMessage	string	enables messages from internal settings /opt/nova-chatproxy-cisco-ece/resources/messages.json; filename must be like Enviroment variable in SYSTEMD.
app	host	string	own host
app	port	int	own port
app	cleanChatOlder	int	
connector	url	URL	Nova.BotConnector Internal URL
connector	connectorId	UUID	Nova.BotConnector ID in MongoDB, where we will be connect channels

Tune main config:

```
# vim /opt/nova-chatproxy-cisco-ece/config/nova-chatproxy-cisco-ece.js

module.exports = {
  db: {
    uri: 'mongodb://127.0.0.1:27017/nova-chatproxy-cisco-ece',
    debugMode: false,
    options: {
      useUrlParser: true,
      poolSize: 10,
      connectTimeoutMS: 5000,
      useUnifiedTopology: true,
    }
  }
}
```

```

        useFindAndModify: false,
        family: 4,
        keepAlive: true,
        keepAliveInitialDelay: 300000
    }
},
again: {
    corsHost: 'https://chat.com/system',
    isDevelopmentModeOn: false,
    eGainContextPath: './',
    isDebugOn: false,
    chatPauseInSec: 30
},
chat: {
    entryPointId: 1004,
    locale: 'ru_RU',
    templateName: 'aqua-al-ukc',
    firstName: 'Nova',
    lastName: 'ChatProxy',
    systemMessages: true,
    welcomeMessage: false,
    waitForAgentMessage: false,
    chatEndMessage: false
},
app: {
    host: '127.0.0.1',
    port: 8888,
    cleanChatOlder: 24
},
connector: {
    url: 'http://127.0.0.1:8080/connectors/',
    connectorId: '7d56d98b-b28b-4b22-a875-5d9b434fc2a7',
    timeout: 5000
},
logging: { // log4js-node configuration
    appenders: {
        file: {
            type: 'file',
            filename: '/var/log/nova-chatproxy-cisco-ece/chatproxy.log',
            maxLogSize: 52428800, // 50 MB
            backups: 5,
            compress: true,
            keepFileExt: true
        }
    },
    categories: {
        default: {appenders: ['file'], level: 'debug'}
    }
}
}
}

```

### 3. Modify and enable service

```
# cd /etc/systemd/system/multi-user.target.wants
# cp /etc/systemd/system/multi-user.target.wants/nova-chatproxy-cisco-
ece.service ../
# vim /etc/systemd/system/nova-chatproxy-cisco-ece.service

[Unit]
Description=Cisco ECE proxy for Nova.BotConnector. UKC_Help.
After=network.target mongod.service

[Service]
ExecStart=/usr/bin/node /opt/nova-chatproxy-cisco-ece/src/index.js
WorkingDirectory=/opt/nova-chatproxy-cisco-ece
Restart=on-failure
RestartSec=30
StandardOutput=syslog
StandardError=syslog
SyslogIdentifier=nova-chatproxy-cisco-ece
User=botconnector
Group=botconnector
Environment=CHATPROXY_INSTANCE=nova-chatproxy-cisco-ece

[Install]
WantedBy=multi-user.target

# systemctl enable nova-chatproxy-cisco-ece.service
# chown botconnector.botconnector /etc/systemd/system/nova-chatproxy-cisco-
ece.service
# chown botconnector.botconnector -R /opt/nova-chatproxy-cisco-ece/config/
# systemctl start nova-chatproxy-cisco-ece.service
```

The last option **Environment** in **[Service]** section means what config service have to use from config files.

- *Administration*

#### **Connectivity checking**

First of all, check that the needed ChatProxy service started and successfully run.

Check bound Port is LISTEN.

Check ChatProxy log and systemd unit log (**journalctl -xe -u nova-chatproxy-cisco-ece.service**)

If the log doesn't give clear/have detailed information - try to change Log Level, according to using Logger Specs (log4js).

UUIDs that help to track messaging.

Entity	Meaning
ConnectorID	First UUID in one log string, ID of Connector Instance
conversation	ID of conversation on kept trough all logs
source	type of channel

### Some commands

Chatproxy manages by `systemd`. Usefull commands are:

Operation	Command
check status	<code>systemctl status nova-chatproxy-cisco-ece.service</code>
restart	<code>systemctl restart nova-chatproxy-cisco-ece.service</code>
restart	<code>systemctl stop nova-chatproxy-cisco-ece.service systemctl start nova-chatproxy-cisco-ece.service</code>
view service logs	<code>journalctl -xe -u nova-chatproxy-cisco-ece.service</code>
check net use	<code>netstat -anp   grep LISTEN</code>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service
2. Copy current release with all files into another place:

```
# cp /opt/nova-chatproxy-cisco-ece/ $HOME/backup
```

3. Install update from by RPM

```
# rpm -Uvh nova-chatproxy-cisco-ece-2020_R1-1.x86_64.rpm
```

4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.
5. Start service and check connectivity

# Nova.ChatRouter.Omilia

- *Introduction*

Nova.ChatRouter allows you to connect Nova.BotConnector with Omilia Solution or Google Dialog Flow solution.

- *Installation*

## 1. Install Component

```
# rpm -ivh $HOME/nova-chatrouter-2020_R1-1.x86_64.rpm
```

## 2. Configure ChatRouter

```
# cd /opt/nova-chatrouter/config/  
# cp chatrouter.js nova-chatrouter-omilia.js
```

Component's Settings:

Section	Parameter	Value	Explanation
db	uri	URL	connection to Mongo. Replica-set Supported
db	options	JSON	default
app	host	string	own host
app	port	int	own port
app	endDeadSessions	int	how frequently need to delete ended session. Recomenend value 24 hours
app	endBasedOnChatProxySessions	boolean	Chatrouter must end session bassing on session state of ChatProxy or not
omilia	enabled	boolean	enabled or disabled
omilia	url	URL	URL to Omilia host
omilia	application	string	Tne name of Omilia's Application handles chat
omilia	sessionRefreshTimeout	int	in miliseconds, how long will be <i>NoInput</i> timeout.
omilia	attachHistory	boolean	send Omilia's dialog history

Section	Parameter	Value	Explanation
omilia	surveyEnabled	boolean	enable Application <i>after</i> ChatProxy Session
omilia	surveyApplicatonId	string	The name of Omilia's Application handles chat <i>after</i> ChatProxy Session (i.e. questionnaire)
omilia	drtviewer	JSON	connection parameters for <i>omilia.attachHistory</i> . Required only if <i>attachHistory</i> is enabled.
omilia	sendGreetingMessage	boolean	first message from Omilia after session creation
omilia	ignoreFailure	boolean	session will be transferred to ChatProxy if Omilia fails
dialogflow	enabled	boolean	enabled or disabled
dialogflow	projectId	string	The project ID from the Google Developer's Console
dialogflow	languageCode	string	The language to retrieve training phrases, parameters and rich messages for
dialogflow	endIntent	string	The Intent indicates about ending Chat Session
dialogflow	transferIntent	string	The Intent indicates about starting ChatProxy Session
dialogflow	ignoreFailure	boolean	
chatproxy	url	URL	Internal ChatProxy's URL
botconnector	url	URL	Internal BotConnector's URL
botconnector	connectorId	UUID	The ID of Botconnector Instance what have to proccess messages from ChatRouter

Tune main config:

```
# vim /opt/nova-chatrouter/config/nova-chatrouter-omilia.js

module.exports = {
  db: {
    uri: 'mongodb://127.0.0.1:27017/nova-chatrouter-omilia',
    debugMode: false,
```

```
options: {
  useUrlParser: true,
  useFindAndModify: false,
  useUnifiedTopology: true,
  reconnectTries: 999999,
  reconnectInterval: 5000,
  poolSize: 10,
  connectTimeoutMS: 5000,
  family: 4,
  keepAlive: true,
  keepAliveInitialDelay: 300000,
  bufferMaxEntries: 0
}
},
app: {
  host: '127.0.0.1',
  port: 6789,
  endDeadSessions: 1440,
  endBasedOnChatProxySessions: false
},
omilia: {
  enabled: false,
  url: 'https://192.168.1.1:8443/',
  applicationId: 'TEST_APP',
  sessionRefreshTimeout: 30000,
  attachHistory: true,
  surveyEnabled: true,
  surveyApplicationId: 'Demo_Feedback',
  drtviewer: { // r
    url: 'https://192.168.1.1',
    username: 'drtviewer',
    password: 'drtviewer',
    clientSecret: '28ac0167-22c9-422d-acea-00cdf1bbcc16'
  },
  sendGreetingMessage: true,
  ignoreFailure: true,
  timeout: 5000
},
dialogflow: {
  enabled: true,
  projectId: 'chatrouterdemoapp-nxnlhq',
  languageCode: 'en-EN',
  endIntent: 'No_Help_Not_Needed',
  transferIntent: 'Operator',
  ignoreFailure: true,
  timeout: 10000
},
chatproxy: {
  url: 'http://127.0.0.1:5000/',
  timeout: 5000
},
```

```

botconnector: {
  url: 'http://127.0.0.1:8080/connectors/',
  connectorId: '3be1660b-0b70-49b4-964a-bc6667fd6f4f',
  timeout: 5000
},
logging: {
  appenders: {
    file: {
      type: 'file',
      filename: '/var/log/nova-chatrouter/chatrouter.log',
      maxLogSize: 52428800,
      backups: 5,
      compress: true,
      keepFileExt: true
    }
  },
  categories: {
    default: {appenders: ['file'], level: 'debug'}
  }
}
}

```

### 3. Modify and enable service

```

# cd /etc/systemd/system/
# vim /etc/systemd/system/nova-chatrouter-omilia.service

[Unit]
Description=Chat routing application.

[Service]
ExecStart=/usr/bin/node /opt/nova-chatrouter/src/index.js
WorkingDirectory=/opt/nova-chatrouter
Restart=on-failure
RestartSec=30
StandardOutput=syslog
StandardError=syslog
SyslogIdentifier=nova-chatrouter-omilia
User=botconnector
Group=botconnector
Environment=CHATROUTER_INSTANCE=nova-chatrouter-omilia

[Install]
WantedBy=multi-user.target

# systemctl enable nova-chatrouter-omilia.service
# chown botconnector.botconnector /etc/systemd/system/nova-chatrouter-
omilia.service
# chown botconnector.botconnector -R /etc/systemd/system/nova-

```



```
chatrouter/config/  
# systemctl start nova-chatrouter-omilia.service
```

The last option **Environment** in **[Service]** section means what config service have to use from config files.

- *Administration*

### Connectivity checking

First of all, check that the needed ChatRouter service started and successfully run.

Check bound Port is LISTEN.

Check ChatProxy log and systemd unit log (`journalctl -xe -u nova-cahtrouter.service`)

If the log doesn't give clear/have detailed information - try to change Log Level, according to using Logger Specs (log4js).

UUIDs that help to track messaging.

Entity	Meaning
ConnectorID	First UUID in one log string, ID of Connector Instance
conversation	ID of conversation on kept trough all logs
source	type of channel

### Some commands

ChatpRouter manages by **systemd**. Usefull commands are:

Operation	Command
check status	<code>systemctl status nova-chatrouter.service</code>
restart	<code>systemctl restart nova-chatrouter.service</code>
restart	<code>systemctl stop nova-chatrouter.service systemctl start nova-chatrouter.service</code>
view service logs	<code>journalctl -xe -u nova-chatrouter.service</code>
check net use	<code>netstat -anp   grep LISTEN</code>

- *Maintenance and Support*

### Updating. Installing new release

1. Stop service

2. Copy current release with all files into another place:

```
# cp /opt/nova-chatrouter/ $HOME/backup
```

3. Install update from by RPM

```
# rpm -Uvh nova-chatrouter-2020_R1-1.x86_64.rpm
```

4. Compare new configs with old one, add a new setting, if they exist and copy modified configs into folder with new installation.

5. Start service and check connectivity

---