



SP-2 — HVET / EIR / RGAC Cryptographic Standard

NOVAK Protocol Standards Series — SP-2

Version 1.0 — January 2025

Status: Open Draft

Author: Matthew Novak

Category: PBAS-02 (Proof-Before-Action Systems — Cryptographic Core)



NOVAK SP-2 — CRYPTOGRAPHIC STANDARD

Formal Specification for Hash-Verified Execution Traces (HVET), Execution Identity Receipts (EIR), and the Recursive Global Audit Chain (RGAC)

This is the core mathematical and cryptographic definition of NOVAK.

SP-2 is the equivalent of:

- Bitcoin's Block Structure specification
- TLS 1.3's handshake protocol definition
- Signal's Double Ratchet formal spec
- NIST FIPS-180 hash standard structure

SP-2 defines the *canonical format* and *cryptographic commitments* that make NOVAK possible.

Table of Contents

1. Introduction
 2. Purpose & Scope
 3. Cryptographic Primitives
 4. Canonical Serialization
 5. HVET Structure
 6. Execution Identity Receipt (EIR) Spec
 7. Recursive Global Audit Chain (RGAC) Spec
 8. Generation Algorithms
 9. Verification Algorithms
 10. Failure Modes
 11. Security Considerations
 12. Compliance Levels
 13. References
-

1. Introduction

SP-2 defines the cryptographic core of the NOVAK Protocol:

- **HVET** — Hash-Verified Execution Trace
- **EIR** — Execution Identity Receipt
- **RGAC** — Recursive Global Audit Chain

This standard guarantees that every action, decision, or automated process is:

- deterministic
- tamper-evident
- identity-bound
- timestamped
- reproducible
- globally verifiable

SP-2 is the mathematical backbone of Proof-Before-Action Systems (PBAS).

2. Purpose & Scope

SP-2 formalizes all cryptographic structures required by SP-1 (Execution Integrity Standard), including:

- canonical serialization
- hash constructions
- digital identity binding
- RGAC chain-extension logic
- tamper detection guarantees

SP-2 **does not** prescribe how systems must store or transmit these objects; it defines only the cryptographic truth conditions required for NOVAK compliance.

3. Cryptographic Primitives

SP-2 requires the following primitives:

3.1 Hash Function

- **SHA-256** (mandatory)
- SHA-512, BLAKE3 (optional)

Collision resistance is assumed.

3.2 Randomness

- A CSPRNG is recommended for UUID or entropy fields.

3.3 Digital Signatures (Optional but Recommended)

Allowed algorithms:

- ECDSA-P256
- Ed25519
- RSA-2048+

SP-2 permits unsigned EIRs for offline/local-only systems.

4. Canonical Serialization

NOVAK uses a deterministic serialization format called **NOVAK-CANONICAL-1**.

Rules:

1. UTF-8 encoding only
2. No whitespace normalization
3. Fields sorted lexicographically by key
4. All numbers serialized as strings

- 5. No optional fields omitted
- 6. No floating-point representations

Canonicalization is required to guarantee deterministic hashing.

Serialization examples are included later.

5. HVET Structure

Hash-Verified Execution Trace (HVET) is the cryptographic binding of:

- HR (Rule Hash)
- HD (Data/Input Hash)
- HO (Output Hash)
- T (Timestamp)

5.1 HVET Fields

Field	Type	Description
HR	hex	SHA-256 hash of the ruleset
HD	hex	SHA-256 hash of the attested input data
HO	hex	SHA-256 hash of the output produced
timestamp	RFC3339 string	ISO8601 timestamp
HVET	hex	SHA-256(HR

5.2 HVET Generation Algorithm

```
function GenerateHVET(ruleset, input, output):  
    HR = SHA256(CANON(ruleset))  
    HD = SHA256(CANON(input))  
    HO = SHA256(CANON(output))  
    T = CURRENT_TIMESTAMP()  
    HVET = SHA256(HR || HD || HO || T)  
    return {HR, HD, HO, timestamp: T, HVET}
```

5.3 HVET Verification Algorithm

```
function VerifyHVET(hvetObj):  
    recomputed = SHA256(  
        hvetObj.HR ||  
        hvetObj.HD ||  
        hvetObj.HO ||  
        hvetObj.timestamp  
    )  
    return (recomputed == hvetObj.HVET)
```

Verification MUST NOT depend on external context.

6. Execution Identity Receipt (EIR)

EIR is the authoritative pre-execution proof required by SP-1.

It binds:

- identity
- rules
- input

- output
- HVET
- timestamp
- optional signature
- versioning
- metadata

6.1 EIR Format

Field	Type	Description
<code>eir_id</code>	UUIDv4	Unique identifier
<code>version</code>	string	Always <code>"NOVAK-EIR-v1"</code>
<code>HR</code>	hex	Rule hash
<code>HD</code>	hex	Input hash
<code>H0</code>	hex	Output hash
<code>timestamp</code>	RFC3339	When execution proof was created
<code>HVET</code>	hex	Final hash binding
<code>executor_identity</code>	string	Machine or human identity
<code>rule_version</code>	string	Version of ruleset used
<code>signature</code>	hex (optional)	Digital signature over HVET
<code>metadata</code>	object	Additional canonical metadata

6.2 EIR Generation Algorithm

```
function CreateEIR(hvet, identity, ruleVersion, metadata):
    id = UUID()
    signature = SIGN(identity.privateKey, hvet.HVET)
    return {
        eir_id: id,
        version: "NOVAK-EIR-v1",
        HR: hvet.HR,
        HD: hvet.HD,
        HO: hvet.HO,
        timestamp: hvet.timestamp,
        HVET: hvet.HVET,
        executor_identity: identity.public,
        rule_version: ruleVersion,
        signature: signature,
        metadata: CANON(metadata)
    }
```

6.3 EIR Verification Algorithm

```
function VerifyEIR(eir):
    if !VerifyHVET(eir) return false
    if eir.signature exists:
        if !VERIFY_SIGNATURE(eir.executor_identity, eir.signature,
            eir.HVET):
            return false
    return true
```

7. Recursive Global Audit Chain (RGAC)

A tamper-evident, append-only hash chain.

RGAC is NOT a blockchain:

- no miners
- no consensus
- no network
- no blocks
- no shared ledger

It is a **local, deterministic, ordered audit chain**.

7.1 RGAC Entry Format

Field	Type	Description
<code>eir</code>	object	The full validated EIR
<code>prev_hvet</code>	hex	Previous HVET or "GENESIS"
<code>chain_hash</code>	hex	SHA256(prev_hvet)
<code>position</code>	integer	Sequence number

7.2 RGAC Append Algorithm

```
function RGAC_Append(chain, eir):
    prev = chain.last().eir.HVET OR "GENESIS"
    link = SHA256(prev || eir.HVET)
    entry = {
        eir: eir,
        prev_hvet: prev,
        chain_hash: link,
        position: chain.length + 1
    }
    chain.push(entry)
```

```
return entry
```

7.3 RGAC Verification Algorithm

```
function RGAC_Verify(chain):
    prev = "GENESIS"
    for entry in chain:
        if SHA256(prev || entry.eir.HVET) != entry.chain_hash:
            return false
        prev = entry.eir.HVET
    return true
```

8. Generation/Verification Summary

Component	Generated By	Verified By	Standard
HVET	SP-2	SP-2	SP-2
EIR	SP-2	SP-2	SP-1
RGAC	SP-2	SP-2	SP-1
Safety Gate	SP-3	SP-3	SP-3

9. Failure Modes

SP-2 guarantees detection of:

- Modified input
- Modified rule
- Modified output

- Timestamp manipulation
 - EIR tampering
 - Identity spoofing
 - RGAC chain rewrites
 - Corrupted historical state
 - Cross-boundary replay attacks
 - Partial serialization attacks
-

10. Security Considerations

SP-2 anticipates:

- hash collision attempts
- preimage attacks
- signature forgeries
- replays
- partial canonicalization errors
- silent memory corruption
- rule-substitution attacks
- adversarial AI manipulations

PL-X and PS-X from SP-3 further expand the protection surface.

11. Compliance Levels

Level	Definition
CL-1	Basic HVET generation
CL-2	Full EIR binding
CL-3	Full RGAC chain
CL-4	Signature support
CL-5	Full NOVAK SP-2 compliance

NOVAK-compliant systems must support **CL-3 or higher**.

12. References

- NOVAK SP-1
- NOVAK SP-3
- PBAS Category Definition
- IBF Formal Specification
- NIST SP-800-90B
- RFC 4648, RFC 8446
- Bitcoin: A Peer-to-Peer Electronic Cash System