

according to Regulation (EC) No. 1907/2006

Revision Date 27.07.2015

Version 9.0

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

REACH Registration Number 01-2119486657-20-XXXX

CAS-No. 67-66-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

In compliance with the conditions described in the annex to this safety

data sheet.

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone:+49 6151 72-0

Responsible Department EQ-RS * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone

number

Please contact the regional company representation in your country.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4, Oral, H302

Acute toxicity, Category 3, Inhalation, H331

Skin irritation, Category 2, H315

Eye irritation, Category 2, H319

Carcinogenicity, Category 2, H351

Reproductive toxicity, Category 2, H361d

Specific target organ toxicity - repeated exposure, Category 1, Liver, Kidney, H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification (67/548/EEC or 1999/45/EC)

Carc.Cat.3 Carcinogenic Category 3 R40
Repr.Cat.3 Toxic to Reproduction Category 3 R63
Xi Irritant R36/38

Xn Harmful R20/22 - 48/20

For the full text of the R-phrases mentioned in this Section, see Section 16.

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word

Danger

Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.

Precautionary statements

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Reduced labelling (≤125 ml)

Hazard pictograms





Signal word Danger

Hazard statements

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.

Precautionary statements

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

Index-No. 602-006-00-4

2.3 Other hazards

None known.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

SECTION 3. Composition/information on ingredients

3.1 Substance

Formula CHCl₃ CHCl₃ (Hill)

 Index-No.
 602-006-00-4

 EC-No.
 200-663-8

 Molar mass
 119,38 g/mol

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical Name (Concentration)

CAS-No. Registration number Classification

Chloroform (>= 50 % - <= 100 %)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

67-66-3 01-2119486657-20- Carcinogenicity, Category 2, H351

XXXX Reproductive toxicity, Category 2, H361d

Acute toxicity, Category 3, H331 Acute toxicity, Category 4, H302

Specific target organ toxicity - repeated exposure, Category 1,

H372

Eye irritation, Category 2, H319 Skin irritation, Category 2, H315

For the full text of the H-Statements mentioned in this Section, see Section 16.

Hazardous components (1999/45/EC)

Chemical Name (Concentration)
CAS-No. Classification
Chloroform (>= 50 % - <= 100 %)

67-66-3 Xn, Harmful; Carc.Cat.3; R40

Xn, Harmful; Repr.Cat.3; R63

Xi, Irritant; Xi; R36/38

Xn, Harmful; Xn; R20/22-48/20

For the full text of the R-phrases mentioned in this Section, see Section 16.

3.2 Mixture

Not applicable

SECTION 4. First aid measures

4.1 Description of first aid measures

General advice

First aider needs to protect himself.

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower. Consult a physician.

After eye contact: rinse out with plenty of water. Call in ophthalmologist.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

After swallowing: caution if victim vomits. Risk of aspiration! Keep respiratory tract clear. Pulmonary failure possible after aspiration of vomit. Call a physician immediately. Subsequently administer: activated charcoal (20 - 40 g in 10% slurry).

4.2 Most important symptoms and effects, both acute and delayed

irritant effects, Cough, Shortness of breath, respiratory arrest, Dizziness, narcosis, agitation, spasms, inebriation, Nausea, Vomiting, Stomach/intestinal disorders, cardiovascular disorders, Headache, ataxia (impaired locomotor coordination)

Drying-out effect resulting in rough and chapped skin.

4.3 Indication of any immediate medical attention and special treatment needed

Laxative: Sodium sulfate (1 tablespoon/1/4 I water).

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Not combustible.

Ambient fire may liberate hazardous vapours.

Fire may cause evolution of:

Hydrogen chloride gas, Phosgene

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

6.2 Environmental precautions

Do not empty into drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area. Do not inhale vapours.

6.4 Reference to other sections

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Observe label precautions.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Protected from light. Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons.

Recommended storage temperature see product label.

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Worker DNEL, acute	Systemic effects	inhalation	333 mg/m³
Worker DNEL, longterm	Systemic effects	inhalation	2,5 mg/m³
Worker DNEL, longterm	Systemic effects	dermal	0,94 mg/kg Body weight

Worker DNEL, longterm Local effects inhalation 2,5 mg/m³

Consumer DNEL, longterm Systemic effects inhalation 0,18 mg/m³

Predicted No Effect Concentration (PNEC)

PNEC Fresh water	0,146 mg/l
PNEC Fresh water sediment	0,45 mg/kg
PNEC Marine water	0,015 mg/l
PNEC Marine sediment	0,09 mg/kg
PNEC Aquatic intermittent release	0,133 mg/l
PNEC Soil	0,56 mg/kg
PNEC Sewage treatment plant	0,048 mg/l

8.2 Exposure controls

Engineering measures

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection Safety glasses

Hand protection

full contact:

Glove material: Viton (R)
Glove thickness: 0,70 mm
Break through time: > 480 min

splash contact:

Glove material: butyl-rubber
Glove thickness: 0,7 mm
Break through time: > 10 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 890 Vitoject® (full contact), KCL 898 Butoject® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter AX (EN 371)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not empty into drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Colour colourless

Odour sweet

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Odour Threshold 84,9 - 201,5 ppm

pH No information available.

Melting point -63 °C

Boiling point/boiling range ca. 61 °C

at 1.013 hPa

Flash point Method: DIN 51755 Part 1

does not flash

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit Not applicable

Upper explosion limit Not applicable

Vapour pressure 211 hPa

at 20 °C

Relative vapour density 4,25

Density 1,48 g/cm3

at 20 °C

Relative density No information available.

Water solubility 8 g/l

at 20 °C

Partition coefficient: n-

octanol/water

log Pow: 2 (25 °C) (experimental)

(IUCLID) Bioaccumulation is not expected.

Auto-ignition temperature No information available.

Decomposition temperature Distillable in an undecomposed state at normal pressure.

Viscosity, dynamic 0,56 mPa.s

at 20 °C

Explosive properties Not classified as explosive.

Oxidizing properties none

9.2 Other data

Ignition temperature not combustible

SECTION 10. Stability and reactivity

10.1 Reactivity

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

See section 10.3

10.2 Chemical stability

heat-sensitive Sensitivity to light

Stabilizer ethanol

10.3 Possibility of hazardous reactions

Risk of explosion with:

Ammonia, Amines, nitrogen oxides, bases, Oxygen, alkali amides, organic nitro compounds, Alcohols, alkali hydroxides, strong alkalis, Fluorine, peroxi compounds, Alkaline earth metals, Alkali metals. Powdered metals

Methanol, with, alcoholates

Methanol, with, strong alkalis

Iron, in powder form

various alloys, sensitive to shock

Methanol, with, Sodium hydroxide

magnesium, in powder form

Oxygen, with, alkali compounds

Aluminium, in powder form

Acetone, with, alkali compounds

Potassium, sensitive to shock

sodium, sensitive to shock

Violent reactions possible with:

phosphines, bis(dimethylamino)dimethyl tin, nonmetallic hydrogen compounds, Powdered metals, Light metals, Ketones, mineral acids, Strong oxidizing agents, semimetallic hydrogen compounds

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity LD50 Rat: 695 mg/kg

(RTECS)

Symptoms: Nausea, Vomiting, Risk of aspiration upon vomiting., Aspiration may cause pulmonary oedema and pneumonitis.

absorption

Acute inhalation toxicity

Acute toxicity estimate: 0,5 mg/l; aerosol

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Symptoms: Cough, Shortness of breath, Possible damages:, mucosal irritations

absorption

Acute dermal toxicity

LD50 Rabbit: > 3.980 mg/kg

(IUCLID)

absorption

Skin irritation

Rabbit

Result: slight irritation

(IUCLID)

Drying-out effect resulting in rough and chapped skin.

Causes skin irritation.

Eye irritation

Causes serious eye irritation.

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

CMR effects

Carcinogenicity:

Suspected of causing cancer.

Teratogenicity:

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

Target Organs: Liver, Kidney

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

This information is not available.

11.2 Further information

Systemic effects:

After absorption:

Dizziness, inebriation, agitation, spasms, narcosis, respiratory arrest

After long-term exposure to the chemical:

drop in blood pressure, Headache, ataxia (impaired locomotor coordination), Stomach/intestinal disorders, cardiovascular disorders

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Damage to:

Liver, Kidney, Cardiac

Effect potentiated by: ethanol

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

Toxicity to fish

LC50 Lepomis macrochirus (Bluegill sunfish): 18 mg/l; 96 h

(IUCLID)

Toxicity to daphnia and other aquatic invertebrates EC50 Daphnia magna (Water flea): 79 mg/l; 48 h (IUCLID)

TOE E avilantum > 6 F60

EC5 E.sulcatum: > 6.560 mg/l; 72 h

(IUCLID) (maximum permissible toxic concentration)

Toxicity to algae

IC5 Scenedesmus quadricauda (Green algae): 1.100 mg/l; 8 d

(IUCLID) (maximum permissible toxic concentration)

Toxicity to bacteria

EC5 Pseudomonas putida: 125 mg/l; 16 h

(IUCLID) (maximum permissible toxic concentration)

EC50 activated sludge: 1.010 mg/l; 3 h

OECD Test Guideline 209

12.2 Persistence and degradability

Biodegradability

0 %: 14 d

OECD Test Guideline 301C Not readily biodegradable.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: 2 (25 °C) (experimental)

(IUCLID) Bioaccumulation is not expected.

12.4 Mobility in soil

Distribution among environmental compartments

Adsorption/Soil log Koc: 1,72 (experimental)

Mobile in soils

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

12.6 Other adverse effects

Henry constant 14084 Pa*m³/mol Method: (experimental)

(IUCLID) Distribution preferentially in air.

Discharge into the environment must be avoided.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number UN 1888

14.2 Proper shipping name CHLOROFORM

14.3 Class6.114.4 Packing groupIII14.5 Environmentally hazardous--14.6 Special precautions foryes

user

Tunnel restriction code E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number UN 1888

14.2 Proper shipping name CHLOROFORM

14.3 Class6.114.4 Packing groupIII14.5 Environmentally hazardous--14.6 Special precautions forno

user

Sea transport (IMDG)

14.1 UN number UN 1888

14.2 Proper shipping name CHLOROFORM

14.3 Class6.114.4 Packing groupIII14.5 Environmentally hazardous--14.6 Special precautions foryes

user

EmS F-A S-A

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Major Accident Hazard

Legislation

SEVESO III ACUTE TOXIC

H2

Quantity 1: 50 t Quantity 2: 200 t

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at

work.

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where

applicable.

Regulation (EC) No 1005/2009 on substances that not regulated

deplete the ozone layer

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending

Directive 79/117/EEC

not regulated

Regulation (EC) No 689/2008 concerning the export The following ingredients are regulated

and import of dangerous chemicals

under Regulation (EC) No 689/2008

Contains: Chloroform

Substances of very high concern (SVHC)

This product does not contain substances

of very high concern according to

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of \geq 0.1 % (w/w).

National legislation

Storage class 6.1 D

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H302 Harmful if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated

exposure.

Full text of R-phrases referred to under sections 2 and 3

R20/22 Harmful by inhalation and if swallowed.

R36/38 Irritating to eyes and skin.

R40 Limited evidence of a carcinogenic effect.

R48/20 Harmful: danger of serious damage to health by prolonged

exposure through inhalation.

R63 Possible risk of harm to the unborn child.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms





Signal word Danger

Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.

Precautionary statements

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Labelling (67/548/EEC or 1999/45/EC)

Symbol(s)	Xn	Harmful
R-phrase(s)	20/22-36/38-40- 48/20-63	Harmful by inhalation and if swallowed. Irritating to eyes and skin. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure
S-phrase(s)	36/37	through inhalation. Possible risk of harm to the unborn child. Wear suitable protective clothing and gloves.

Further information

Only for research, development, analysis or specific industrial processes (76/769/EEC).

EC-No.	200-663-8	EC Label
Reduced labelling (≤125 ml) Symbol(s) Xn		Harmful
R-phrase(s) S-phrase(s)	40-48/20/22-20/22-63 36/37	Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. Harmful by inhalation and if swallowed. Possible risk of harm to the unborn child. Wear suitable protective clothing and gloves.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

SAFETY DATA SHEET - Annex

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

EXPOSURE SCENARIO 1 (Industrial use)

1. Industrial use (Reagent for analysis)

Sectors of end-use

SU 3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU9 Manufacture of fine chemicals

SU 10 Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Chemical product category

PC19 Intermediate

PC21 Laboratory chemicals

Process categories

PROC1 Use in closed process, no likelihood of exposure

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC3 Use in closed batch process (synthesis or formulation)

PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large

containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large

containers at dedicated facilities

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including

weighing)

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC1 Manufacture of substances

ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC1

Amount used

Daily amount per site (Msafe) 829.589 kg

Environment factors not influenced by risk management

Dilution Factor (River) 10
Dilution Factor (Coastal Areas) 100

Other given operational conditions affecting environmental exposure

Number of emission days per year 365
Emission or Release Factor: Air 0,07 %
Emission or Release Factor: Water 0,006 %

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant Municipal sewage treatment plant

Flow rate of sewage treatment 10.000 m3/d

plant effluent

Percentage removed from waste 85,6 %

water

Sludge Treatment Sewage sludge should not be applied to natural soils.

Conditions and measures related to external treatment of waste for disposal

Disposal methods All liquid and solid waste should be incinerated.

SAFETY DATA SHEET – Annex

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

2.2 Contributing scenario controlling environmental exposure for: ERC6a

Amount used

Daily amount per site (Msafe) 4.800 kg

Environment factors not influenced by risk management

Dilution Factor (River) 10
Dilution Factor (Coastal Areas) 100

Other given operational conditions affecting environmental exposure

Number of emission days per year 300 Emission or Release Factor: Air 0,5 % Emission or Release Factor: Water 0,7 %

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant Municipal sewage treatment plant

Flow rate of sewage treatment 10.000 m3/d

plant effluent

Percentage removed from waste

water

85,6 %

Sludge Treatment Sewage sludge should not be applied to natural soils.

Conditions and measures related to external treatment of waste for disposal

Disposal methods All liquid and solid waste should be incinerated.

2.3 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9. PROC15

Product characteristics

Concentration of the Substance in Covers the percentage of the substance in the product up to

Mixture/Article 100 %.

High volatile liquid

Frequency and duration of use

Physical Form (at time of use)

Frequency of use 8 hours/day

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor with local exhaust ventilation (LEV)

Outdoor / Indoor Outdoor

Technical conditions and measures

Provide extraction ventilation at points where emissions occur.

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves (tested to EN374), coverall and eye protection. Wear respiratory protection.

3. Exposure estimation and reference to its source

SAFETY DATA SHEET – Annex according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC1	829589 kg/day	All compartments	< 1	EUSES
2.2	ERC6a	4800 kg/day	All compartments	< 1	EUSES

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC1	longterm, combined, systemic	< 1	ECETOC TRA
2.3	PROC2	longterm, combined, systemic	< 1	ECETOC TRA
2.3	PROC3	longterm, combined, systemic	< 1	ECETOC TRA
2.3	PROC8a	longterm, combined, systemic	< 1	ECETOC TRA
2.3	PROC8b	longterm, combined, systemic	< 1	ECETOC TRA
2.3	PROC9	longterm, combined, systemic	< 1	ECETOC TRA
2.3	PROC15	longterm, combined, systemic	< 1	ECETOC TRA

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

SAFETY DATA SHEET - Annex

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

EXPOSURE SCENARIO 2 (Professional use)

1. Professional use (Reagent for analysis)

Sectors of end-use

SU 22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

ERC8a Wide dispersive indoor use of processing aids in open systems

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC6a

Amount used

Daily amount per site (Msafe) 4.800 kg

Environment factors not influenced by risk management

Dilution Factor (River) 10
Dilution Factor (Coastal Areas) 100

Other given operational conditions affecting environmental exposure

Number of emission days per year 300 Emission or Release Factor: Air 0,5 % Emission or Release Factor: Water 0,7 %

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant Municipal sewage treatment plant

Flow rate of sewage treatment 10.000 m3/d

plant effluent

Percentage removed from waste 85,6 %

water

Sludge Treatment Sewage sludge should not be applied to natural soils.

Conditions and measures related to external treatment of waste for disposal

Disposal methods All liquid and solid waste should be incinerated.

2.2 Contributing scenario controlling environmental exposure for: ERC8b

Amount used

Daily amount per site (Msafe) 5 kg

Environment factors not influenced by risk management

Dilution Factor (River) 10
Dilution Factor (Coastal Areas) 100

Other given operational conditions affecting environmental exposure

Number of emission days per year 365

SAFETY DATA SHEET - Annex

according to Regulation (EC) No. 1907/2006

Catalogue No. 107024

Product name Chloroform for analysis EMPARTA® ACS

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant none

Conditions and measures related to external treatment of waste for disposal

Disposal methods All liquid and solid waste should be incinerated.

2.3 Contributing scenario controlling worker exposure for: PROC15

Product characteristics

Concentration of the Substance in Covers the percentage of the substance in the product up to

Mixture/Article 100 %

Physical Form (at time of use) High volatile liquid

Frequency and duration of use

Frequency of use 8 hours/day

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor with local exhaust ventilation (LEV)

Technical conditions and measures

Provide extraction ventilation at points where emissions occur.

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves (tested to EN374), coverall and eye protection.

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC6a	4800 kg/day	All compartments	< 1	EUSES
2.2	ERC8b	< 5 l/day	All compartments	< 1	EUSES

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC15	longterm, combined, systemic	< 1	ECETOC TRA

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).