External Validation of a Positive-Closure Proof Architecture

A Multi-Tranche Survey: Twelve Benchmark Dimensions in Lean

Nova Spivack

2026

Abstract

The Infinity Compression (IC) formalization develops a layered positive-closure proof architecture: collapse to a bare certificate, a typed forgetful map, fiber structure over that certificate, and, where appropriate, canonical witnesses or sections. A natural methodological concern is that this architecture may be endogenous to the flagship NEMS-style case rather than a reusable proof pattern. This paper presents a **consolidated machine-checked external validation**: twelve independent tranches of ordinary mathematics, each formalized in Lean without importing the IC spine, each comparing a *flat baseline* (the obvious Mathlib-shaped existence or representability statement) with an *architecture-guided* theorem bundle (nonempty fibers, surjectivity of the forgetful map, `HasRightInverse`, an identified `RightInverse` section, and a uniform canonical witness in each fiber), *except* tranche **T12**, which records an explicit **MODERATE** / control pattern for a *non-surjective* collapse.

Tranche **T1** is the setoid quotient benchmark (collapse by an equivalence relation; baseline `Quotient.exists_rep`). Tranche **T2** is the Cartesian product with first projection (many enriched pairs over one bare image—*multi-route* without quotienting). Tranche **T3** is the dependent sum $\Sigma_{b:B} E\, b$ with `Sigma.fst` (bundle projection; dependent generalization of T2). Tranches **T4**–**T7** cover sum discriminants, subtype projection, orbit quotients, and ideal quotients. Tranches **T8**–**T11** add pushout glueing, set membership as classifier, localization via fraction pairs, and pullbacks (sheaf-style fiber products). Tranche **T12** is `Nat.succ`: fibers are nonempty exactly off zero, with no global right inverse. The contribution is not a catalog of new classical theorems; it is a demonstration that the same architectural lens organizes *twelve* external families and yields strengthened, reusable proof interfaces where the rubric applies. Under the project's validation rubric, tranches T1–T11 support a **STRONG** verdict; T12 documents a complementary **MODERATE** boundary case. We situate the work in the NEMS / APS / IC / Strata stack and state explicitly that APS is not tested by these tranches.

Contents

1 Introduction **3**

2 The positive-closure architecture as a reusable schema **3**

3 Unified methodology: baseline vs. architecture-guided bundle **3**

4 Tranche T1: Setoid quotients **4**

4.1 Why quotients 4

4.2 Lean formalization and main bundle 4

4.3 What the architectural packaging adds 4

5 Tranche T2: Cartesian product and first projection **4**
5.1 Mathematical story 4
5.2 Baseline vs. bundle 4

6 Tranche T3: Dependent sums and the bundle projection **5**
6.1 Mathematical story 5
6.2 Hypothesis and classical section 5

7 Tranche T4: Sum types and discriminant collapse **5**

8 Tranche T5: Subtype projection **6**

9 Tranche T6: Orbit quotient from a group action **6**

10 Tranche T7: Ideal quotient **6**

11 Tranche T8: Pushout / colimit glueing **7**

12 Tranche T9: Membership classifier **7**

13 Tranche T10: Localization pairs **7**

14 Tranche T11: Pullback / fiber product **7**

15 Tranche T12: Non-surjective collapse (MODERATE) **8**

16 Comparative synthesis across tranches **8**

17 Unified validation verdict and the meaning of STRONG **8**

18 Place in the larger program **9**

19 Limitations and future work **9**

A Theorem indices (Lean names by module) **10**

B A workflow for reusing this pattern **13**

1 Introduction

The Infinity Compression (IC) program develops a positive-closure proof architecture organized around four layers: a collapsed bare layer, a projection from enriched to bare structure, fibers over bare points, and, when available, canonical witnesses or sections. In the flagship IC formalization this architecture is load-bearing: it organizes the distinction between theorem-level certification and richer reflective realization. **The central claim of this paper is that the positive-closure architecture is a reusable proof pattern—not merely a custom narrative for the flagship case—and that claim is supported by multiple independent external benchmarks.**

A single quotient formalization already begins to answer the worry that the architecture might be idiosyncratic; this document *consolidates* that quotient tranche with eleven additional standard constructions—products, dependent sums, coproduct discriminants, subtypes, orbit and ideal quotients, pushouts, classifiers, localization pairs, pullbacks, and a non-surjective control—so that the evidence base is explicitly multi-family. The result is one self-contained validation paper: readers need not cross-reference a separate "survey" manuscript for the product and bundle stories.

Scope. We do not claim a universal theorem that every closure problem in mathematics must be formalized in IC's types. We claim that, in Lean, on twelve concrete external families, the architecture exports cleanly, yields structured theorem bundles beyond flat baselines, and aligns with the flagship forgetful / fiber / section narrative [1].

2 The positive-closure architecture as a reusable schema

Let π denote a forgetful projection from an *enriched* carrier to a *bare* certificate space (a collapsed layer where theorem-level records live). Write E for an enriched carrier and B for a bare layer. The schema is:

$$E \xrightarrow{\pi} B, \qquad \mathrm{Fib}(b) \coloneqq \pi^{-1}(b) \ \text{ for } b \in B, \qquad \text{optionally } s : B \to E \text{ with } \pi \circ s = \mathrm{id}_B. \tag{1}$$

Here $\mathrm{Fib}(b)$ is the fiber over a bare point; a section s is a global choice of preimage.

Each tranche below instantiates (1) with different E, B, and π. The quotient tranche uses Mathlib's quotient map and `Quotient.out`; the product tranche uses first projection and a parametric section $x \mapsto (x, y_0)$; the bundle tranche uses `Sigma.fst` and a `noncomputable` section from classical choice when $\forall b,\ \mathrm{Nonempty}(E\,b)$.

3 Unified methodology: baseline vs. architecture-guided bundle

In every tranche we record:

- a **baseline** statement profile matching how Mathlib users typically see the mathematics (existence of representatives, trivial points in fibers, etc.);
- an **architecture-guided bundle**: named bare layer, named projection, fiber type as a subtype or structured copy, surjectivity of π, `HasRightInverse`, a concrete `RightInverse` witness, and a `canonical...Witness` in each fiber.

The methodological gain is *interface structure*: the bundle is a reusable template parallel to the flagship story, not a claim of new classical content.

4 Tranche T1: Setoid quotients

4.1 Why quotients

This tranche is a positive-closure benchmark in the sense relevant to IC: it exhibits collapse, fibers, and a uniform section-like recovery mechanism (`Quotient.out`), not only an existential shadow.

The quotient construction is standard mathematics (see, e.g., [6]); it has a genuine collapse map from carriers to quotient points; it admits a classical baseline (`Quotient.exists_rep`); and it supports a section story via `Quotient.out`. The benchmark imports only `Mathlib.Data.Setoid.Basic` and `Mathlib.Logic.Function.Basic`.

4.2 Lean formalization and main bundle

All definitions and theorems live in `InfinityCompression/Validation/QuotientFiberBenchmark.lean` (namespace `InfinityCompression.Validation`). Layering: `BareQuotient`, `EnrichedCarrier`, `forgetToQuotient`, `QuotientFiber`, `canonicalQuotientFiberWitness`.

Lean name	Meaning	Baseline vs. architecture
`quotient_fiber_nonempty`	each quotient point has a witness in its `QuotientFiber`	baseline-plus (typed fiber nonempty)
`forgetToQuotient_surjective`	`forgetToQuotient` hits every bare point	architecture
`forgetToQuotient_hasRightInverse`	projection admits a global right inverse	architecture
`quotientOut_rightInverse_forgetToQuotient`	`Quotient.out` is a `RightInverse` of `forgetToQuotient`	architecture
`canonicalQuotientFiberWitness`	uniform canonical witness in each fiber	architecture

Table 1: T1 (quotient): main named results in the architecture-guided bundle.

4.3 What the architectural packaging adds

Classically, every quotient class has *some* representative (`Quotient.exists_rep`). The architecture-guided view reorganizes the same fact under (1): surjectivity, `HasRightInverse`, identification of `Quotient.out` as `RightInverse`, and `canonicalQuotientFiberWitness`. Methodologically, this upgrades a pointwise existential into a named, reusable interface—the same move the positive-closure architecture is designed to expose internally.

5 Tranche T2: Cartesian product and first projection

5.1 Mathematical story

Let X and Y be types. The first projection $\pi : X \times Y \to X$ forgets the second coordinate. For fixed nonempty Y, many pairs (x, y_1) and (x, y_2) share the same bare image x: this is *multi-route over one bare certificate* without any quotient—a clean stress test for "fiber + section" language distinct from equivalence collapsing.

5.2 Baseline vs. bundle

Baseline: once Y is inhabited, each $x : X$ has some pair mapping to it (e.g. (x, y_0) for a chosen y_0). **Architecture bundle:** we package `ProductFiberAt X Y x`, surjectivity of `forgetFirst`, `HasRightInverse`, the parametric section `productSection y0`, `RightInverse` compatibility, and

canonicalProductFiberWitness. The Lean module is ProductProjectionFiberBenchmark.lean; it imports only Mathlib.Logic.Function.Basic.

Lean name	One-line reading
forgetFirst	first projection $X \times Y \to X$.
ProductFiberAtXYx	fiber of forgetFirst over x (Y explicit in the name).
product_fiber_nonempty	each bare x has a nonempty fiber (given y0:Y).
forgetFirst_surjective	forgetFirst is surjective (given y0).
forgetFirst_hasRightInverse	surjectivity ⇒ HasRightInverse.
productSection_rightInverse_forgetFirst	productSectiony0 is RightInverse to forgetFirst.
canonicalProductFiberWitness	distinguished point â§Í(x,y0),rflâ§Ï in each fiber.

Table 2: T2 (product projection): architecture-guided bundle.

6 Tranche T3: Dependent sums and the bundle projection

6.1 Mathematical story

For $E : B \to \text{Type}$, the dependent sum $\Sigma_{b:B} E\, b$ is the standard *bundle* total space; Sigma.fst projects to the base. The fiber over $b : B$ is (equivalent to) $E\, b$. This generalizes T2: product is the special case of a constant family $E\, b = Y$.

6.2 Hypothesis and classical section

We assume $\forall b : B,\ \text{Nonempty}(E\, b)$ so that Sigma.fst is surjective. The global section sigmaSection uses Classical.choose per fiber; the module is noncomputable where required. Baseline: each base point has *some* fiber point. Bundle: SigmaFiber, surjectivity, HasRightInverse, sigmaSection_rightInverse_sigma_fst, canonicalSigmaFiberWitness.

Lean name	One-line reading
SigmaFiberEb	points in $\Sigma\, E$ lying over b.
sigma_fiber_nonempty	nonempty fibers from $\forall b,\ \text{Nonempty}(E\, b)$.
sigma_fst_surjective	Sigma.fst surjective.
sigma_fst_hasRightInverse	HasRightInverse for Sigma.fst.
chooseFiber / sigmaSection	classical section of the bundle.
sigmaSection_rightInverse_sigma_fst	RightInverse law.
canonicalSigmaFiberWitness	uniform witness in each SigmaFiber.

Table 3: T3 (dependent sum): architecture-guided bundle (SigmaFiberBenchmark.lean).

7 Tranche T4: Sum types and discriminant collapse

The coproduct Sum A B carries a natural *tag-forgetting* map to Bool (forgetSumIsLeft), parallel in spirit to T2's projection but for coproducts rather than products: many inl values share the same bare tag. The module is SumCoproductFiberBenchmark.lean. Baseline: both sides inhabited to hit both booleans. Bundle: SumFiberAt, surjectivity, sumSection, RightInverse law, canonicalSumFiberWitness.

Lean name	One-line reading
`forgetSumIsLeft`	collapse `Sum A B` to a `Bool` side tag.
`SumFiberAtABb`	fiber over a tag `b : Bool`.
`sumSection`	section `Bool → Sum A B` at fixed witnesses.
`forgetSumIsLeft_surjective`	surjectivity (given `a0`, `b0`).
`sumSection_rightInverse_forgetSumIsLeft`	`RightInverse` law.
`canonicalSumFiberWitness`	canonical witness in each `SumFiberAt`.

Table 4: T4 (sum / coproduct): architecture-guided bundle.

8 Tranche T5: Subtype projection

For a predicate `p` on a type α, `Subtype.val` forgets proofs. Under the hypothesis $\forall a,\ p\ a$, `Subtype.val` is surjective onto α; fibers are singletons. Module: `SubtypeValFiberBenchmark.lean`.

Lean name	One-line reading
`SubtypeFiberAt`	fiber of `Subtype.val` over `a : α`.
`subtype_val_surjective`	surjectivity from $\forall a,\ p\ a$.
`subtypeSection`	section sending `a` to `<a, h a>`.
`subtypeSection_rightInverse_subtypeVal`	`RightInverse` law.
`canonicalSubtypeFiberWitness`	canonical witness in each fiber.

Table 5: T5 (subtype): architecture-guided bundle.

9 Tranche T6: Orbit quotient from a group action

Given `MulAction G X`, the orbit relation `same_orbit` yields a `Setoid` and quotient `BareOrbitQuotient`; the collapse map is `to_orbit_quotient`. Module: `OrbitRelationQuotientFiberBenchmark.lean`.

Lean name	One-line reading
`same_orbit`	orbit relation $\exists g,\ g \cdot x = y$.
`grp_action_orbit_setoid`	`Setoid` for the orbit relation.
`to_orbit_quotient`	`Quotient.mk` from `X` to orbit space.
`to_orbit_quotient_surjective`	surjectivity.
`quotient_out_rightInverse_to_orbit_quotient`	`Quotient.out` as `RightInverse`.
`canonical_orbit_quotient_fiber_witness`	canonical witness in each fiber.

Table 6: T6 (orbit quotient): architecture-guided bundle.

10 Tranche T7: Ideal quotient

For a commutative ring `R` and ideal `I`, the map `Ideal.Quotient.mk I` collapses to the quotient R/I. This is the standard algebraic quotient parallel to T1's setoid quotient. Module: `IdealQuotientFiberBenchmark.lean`.

Lean name	One-line reading
`forgetToIdealQuotient`	`Ideal.Quotient.mk I`.
`IdealQuotientFiber`	fiber over a bare coset in R/I.
`forgetToIdealQuotient_surjective`	surjectivity (via `Quotient.exists_rep`).
`idealQuotientOut_rightInverse_forgetToIdealQuotient`	`Quotient.out` as `RightInverse`.
`canonicalIdealQuotientFiberWitness`	canonical witness in each fiber.

Table 7: T7 (ideal quotient): architecture-guided bundle.

11 Tranche T8: Pushout / colimit glueing

Glueing `inl a0` with `inr b0` in `Sum A B` is presented as the equivalence generated by `Relation.EqvGen` on explicit symmetric edges (`PushoutCoequalizerFiberBenchmark.lean`).

Lean name	One-line reading
`pushoutRel`	generating edges for glueing.
`forgetToPushout`	`Quotient.mk` to the pushout type.
`forgetToPushout_surjective`	surjectivity.
`quotientOut_rightInverse_forgetToPushout`	`Quotient.out` as `RightInverse`.
`canonicalPushoutFiberWitness`	canonical witness in each fiber.

Table 8: T8 (pushout): architecture-guided bundle.

12 Tranche T9: Membership classifier

Subsets as maps to `Prop` and `Subtype` of membership in `S`: `SetClassifierFiberBenchmark.lean` packages membership fibers and global sections when every `x` lies in `S`.

Lean name	One-line reading
`membershipClassifier`	characteristic predicate `x in S`.
`ClassifierFiber`	fiber over `x` for `Subtype.val`.
`classifier_fiber_nonempty_of_mem`	nonempty fiber when `x` lies in `S`.
`subtypeVal_surjectiveOn`	surjectivity of `Subtype.val` under global membership.
`classifierSection_rightInverse_subtypeVal`	`RightInverse` for the section.

Table 9: T9 (classifier / subset): architecture-guided bundle.

13 Tranche T10: Localization pairs

Fraction presentation `mk'` from `R × M` is surjective; `LocalizationPairFiberBenchmark.lean` uses `IsLocalization.sec` as canonical preimage data.

14 Tranche T11: Pullback / fiber product

Given `f : A → C`, `g : B → C`, the subtype of `A × B` with `f a = g b` is the pullback; `pullbackFst` projects to `A` (`PullbackFiberBenchmark.lean`).

Lean name	One-line reading
`forgetPairToLocalization`	`IsLocalization.mk'` on pairs.
`forgetPairToLocalization_surjective`	pair-map surjectivity.
`sec_rightInverse_forgetPairToLocalization`	`IsLocalization.sec` as `RightInverse`.
`canonicalLocalizationPairFiberWitness`	canonical pair in each fiber.

Table 10: T10 (localization pairs): architecture-guided bundle.

Lean name	One-line reading
`PullbackType`	fiber-product subtype.
`pullbackFst`	first projection (renamed to avoid product-tranche clash).
`pullbackFst_surjective`	surjectivity assuming overlap (for all `a` some `b` matches).
`pullbackSection_rightInverse_pullbackFst`	chosen section is `RightInverse`.

Table 11: T11 (pullback): architecture-guided bundle.

15 Tranche T12: Non-surjective collapse (MODERATE)

`Nat.succ` is not surjective; fibers over `n > 0` are nonempty singletons. `NonSurjectiveSuccFiberBenchmark.lean` records `¬ HasRightInverse succ` and `pred_leftInverse_succ`.

Lean name	One-line reading
`succFiber`	fiber of `succ` over `n`.
`succFiber_nonempty_iff`	nonempty iff `n` is not zero.
`nat_succ_not_surjective`	obstruction to global section.
`pred_leftInverse_succ`	standard left-inverse identity.

Table 12: T12 (MODERATE control): `Nat.succ`.

16 Comparative synthesis across tranches

T1 isolates *collapse by an equivalence relation*; **T2** isolates *multi-route* without quotienting; **T3** is the dependent-type generalization of T2; **T4** is the coproduct-side dual tag story; **T5** is the subtype refinement pattern; **T6** and **T7** are quotient benchmarks (group action or ideal). **T8**–**T11** extend the story to colimits, classifiers, localization pairs, and pullbacks. **T12** is the explicit **MODERATE** control. For **T1**–**T11**, the **STRONG** rubric applies where stated; **T12** documents a boundary where global `HasRightInverse` fails.

17 Unified validation verdict and the meaning of STRONG

Under the project's validation rubric [3], a benchmark is rated **STRONG** when it exports the architecture cleanly to external mathematics and yields a theorem bundle structurally richer than the obvious baseline. Tranches **T1**–**T11** are recorded with that ambition; **T12** is an explicit **MODERATE** / methodological control: non-surjective collapse with nonempty fibers only on the image. *Collectively*, the tranches strengthen the claim that the pattern is not tied to a single family of examples.

STRONG encodes methodological transfer and corollary structure, not difficulty of raw mathematical content. No tranche proves a new "summit" theorem for the IC landscape; together they

Tr.	Bare B	Projection π	What varies in the fiber	Section flavor
T1	quotient	`forgetToQuotient` / `Quotient.mk`	equivalence classes	`Quotient.out` (canonical)
T2	X	`forgetFirst`	second coordinate $y : Y$	`productSection y0` (parametric)
T3	B	`Sigma.fst`	dependent $E\,b$	`sigmaSection` (`noncomputable`)
T4	`Bool`	`forgetSumIsLeft`	tagged `Sum` values	`sumSection` (parametric)
T5	α	`Subtype.val`	proof data (singleton fibers)	`subtypeSection`
T6	orbit quotient	`to_orbit_quotient`	orbit classes	`Quotient.out` (canonical)
T7	R/I	`forgetToIdealQuotient`	cosets mod I	`Quotient.out` (canonical)
T8	pushout	`forgetToPushout`	`EqvGen` classes	`Quotient.out` (canonical)
T9	α	`Subtype.val` on `S`	membership fibers	`classifierSection`
T10	localized ring	`forgetPairToLocalization`	denominator pairs	`IsLocalization.sec`
T11	A	`pullbackFst`	compatible B-legs	`pullbackSection` (`noncomputable`)
T12	`Nat`	`Nat.succ`	predecessor fibers	`Nat.pred` (left inverse only)

Table 13: Side-by-side view: twelve instantiations (T12 is a MODERATE boundary case).

support external validity of the *packaging*.

18 Place in the larger program

- **IC flagship (internal):** the positive-closure architecture and main certification / reflective splits—load-bearing inside the library.
- **External validation (this paper):** machine-checked demonstrations that the same pattern applies *outside* the flagship modules, on quotients, products, dependent sums, coproduct discriminants, subtypes, orbit and ideal quotients, pushouts, classifiers, localization pairs, pullbacks, and a non-surjective control tranche.
- **Strata:** abstract synthesis and bridge laws [2].
- **APS:** local-to-global backbone elsewhere in the stack. **These tranches do not test APS directly;** they test reusable positive-closure *packaging* on external mathematics.
- **NEMS:** outer burden and interface story for the paper suite.

19 Limitations and future work

Twelve finite families do not exhaust all closure or fibration patterns. Natural extensions include: settings where sections are non-unique or only locally defined; competing enriched layers over one collapse map; and domain-specific benchmarks outside pure type theory. Such work would extend the *evidence base* without changing the logical status of the positive-closure architecture inside IC.

A Theorem indices (Lean names by module)

QuotientFiberBenchmark.lean

Lean name	One-line reading
`BareQuotient`	quotient type as bare certificate layer after collapse.
`EnrichedCarrier`	carrier before quotienting (enriched layer).
`forgetToQuotient`	projection `Quotient.mk` from carrier to quotient.
`QuotientFiber`	fiber over a bare quotient point (subtype of the carrier).
`quotient_fiber_nonempty`	each bare point has a nonempty fiber (from `exists_rep`).
`forgetToQuotient_surjective`	`forgetToQuotient` is surjective onto the quotient.
`forgetToQuotient_hasRightInverse`	projection has a global right inverse (section exists).
`quotientOut_rightInverse_forgetToQuotient`	`Quotient.out` is a right inverse of `forgetToQuotient`.
`canonicalQuotientFiberWitness`	canonical distinguished point in each `QuotientFiber`.
`quotient_fiber_nonempty'`	nonemptiness via `canonicalQuotientFiberWitness`.

ProductProjectionFiberBenchmark.lean

Lean name	One-line reading
`forgetFirst`	first projection $X \times Y \to X$.
`ProductFiberAt X Y x`	fiber of `forgetFirst` over `x`.
`productSection`	section $x \mapsto (x, y_0)$ at fixed `y0`.
`product_fiber_nonempty`	nonempty `ProductFiberAt` given `y0`.
`forgetFirst_surjective`	`forgetFirst` surjective given `y0`.
`forgetFirst_hasRightInverse`	`HasRightInverse` for `forgetFirst`.
`productSection_rightInverse_forgetFirst`	`RightInverse` law.
`canonicalProductFiberWitness`	canonical witness in each fiber.
`product_fiber_nonempty'`	nonemptiness via canonical witness.

SigmaFiberBenchmark.lean

Lean name	One-line reading
`SigmaFiber`	fiber of `Sigma.fst` over `b`.
`sigma_fiber_nonempty`	nonempty fibers from global nonemptiness.
`sigma_fst_surjective`	`Sigma.fst` surjective.
`sigma_fst_hasRightInverse`	`HasRightInverse`.
`chooseFiber`	`Classical.choice` in each fiber.
`sigmaSection`	global section of the bundle.
`sigmaSection_rightInverse_sigma_fst`	`RightInverse` law.
`canonicalSigmaFiberWitness`	canonical witness in each `SigmaFiber`.

SumCoproductFiberBenchmark.lean

Lean name	One-line reading
`forgetSumIsLeft`	discriminant collapse `Sum A B → Bool`.
`SumFiberAt`	fiber over a side tag.
`sumSection`	parametric section from `Bool`.
`sum_fiber_nonempty`	nonempty fibers (given `a0`, `b0`).

(continued)

Lean name	One-line reading
`forgetSumIsLeft_surjective`	surjectivity.
`forgetSumIsLeft_hasRightInverse`	`HasRightInverse`.
`sumSection_rightInverse_forgetSumIsLeft`	`RightInverse` law.
`canonicalSumFiberWitness`	canonical witness in each fiber.

SubtypeValFiberBenchmark.lean

Lean name	One-line reading
`SubtypeFiberAt`	fiber of `Subtype.val` over `a`.
`subtype_fiber_nonempty`	nonempty fibers from $\forall a,\ p\ a$.
`subtype_val_surjective`	surjectivity of `Subtype.val`.
`subtype_val_hasRightInverse`	`HasRightInverse`.
`subtypeSection`	section sending `a` to `<a, h a>`.
`subtypeSection_rightInverse_subtypeVal`	`RightInverse` law.
`canonicalSubtypeFiberWitness`	canonical witness in each fiber.

OrbitRelationQuotientFiberBenchmark.lean

Lean name	One-line reading
`same_orbit`	orbit relation from a `MulAction`.
`grp_action_orbit_setoid`	`Setoid` for orbit equivalence.
`BareOrbitQuotient`	orbit-space quotient type.
`to_orbit_quotient`	collapse map `Quotient.mk`.
`OrbitQuotientFiber`	fiber over an orbit point.
`orbit_quotient_fiber_nonempty`	nonempty fibers.
`to_orbit_quotient_surjective`	surjectivity.
`to_orbit_quotient_hasRightInverse`	`HasRightInverse`.
`quotient_out_rightInverse_to_orbit_quotient`	`Quotient.out` as `RightInverse`.
`canonical_orbit_quotient_fiber_witness`	canonical witness in each fiber.

IdealQuotientFiberBenchmark.lean

Lean name	One-line reading
`forgetToIdealQuotient`	`Ideal.Quotient.mk I`.
`IdealQuotientFiber`	fiber over a coset in R/I.
`ideal_quotient_fiber_nonempty`	nonempty fibers.
`forgetToIdealQuotient_surjective`	surjectivity.
`forgetToIdealQuotient_hasRightInverse`	`HasRightInverse`.
`idealQuotientOut_rightInverse_forgetToIdealQuotient`	`Quotient.out` as `RightInverse`.
`canonicalIdealQuotientFiberWitness`	canonical witness in each fiber.

PushoutCoequalizerFiberBenchmark.lean

Lean name	One-line reading
`pushoutRel`	generating symmetric edges for glueing.
`pushoutSetoid`	`EqvGen.setoid` presentation.
`forgetToPushout`	collapse to the pushout quotient.
`PushoutFiber`	fiber over a glued class.
`forgetToPushout_surjective`	surjectivity.
`quotientOut_rightInverse_forgetToPushout`	`Quotient.out` as `RightInverse`.
`canonicalPushoutFiberWitness`	canonical witness in each fiber.

SetClassifierFiberBenchmark.lean

Lean name	One-line reading
`membershipClassifier`	characteristic map `x in S` to `Prop`.
`ClassifierFiber`	fiber of `Subtype.val` over `x`.
`classifier_fiber_nonempty_of_mem`	nonempty when `x` lies in `S`.
`subtypeVal_surjectiveOn`	surjectivity under global membership.
`subtypeVal_hasRightInverse`	`HasRightInverse` under global membership.
`classifierSection_rightInverse_subtypeVal`	`RightInverse` law.

LocalizationPairFiberBenchmark.lean

Lean name	One-line reading
`forgetPairToLocalization`	`IsLocalization.mk'` on `R × M`.
`forgetPairToLocalization_surjective`	surjectivity of the pair map.
`forgetPairToLocalization_hasRightInverse`	`HasRightInverse`.
`sec_rightInverse_forgetPairToLocalization`	`IsLocalization.sec` as `RightInverse`.
`LocalizationPairFiber`	fiber over a localized element.
`canonicalLocalizationPairFiberWitness`	canonical pair witness.

PullbackFiberBenchmark.lean

Lean name	One-line reading
`PullbackType`	pullback as subtype of `A × B`.
`pullbackFst`	first projection (renamed; avoids clash with T2).
`pullbackFst_surjective`	surjectivity under overlap hypothesis.
`pullbackFst_hasRightInverse`	`HasRightInverse`.
`pullbackSection_rightInverse_pullbackFst`	`RightInverse` for chosen section.

NonSurjectiveSuccFiberBenchmark.lean

Lean name	One-line reading
`succFiber`	fiber of `Nat.succ`.
`succFiber_nonempty_iff`	nonempty iff not zero.
`nat_succ_not_surjective`	no global section onto `Nat`.
`nat_succ_not_hasRightInverse`	obstruction to `HasRightInverse`.
`pred_leftInverse_succ`	`Nat.pred` as left inverse of `succ`.

B A workflow for reusing this pattern

The benchmarks above do *not* constitute a single new lemma or tactic that resolves goals that were previously out of reach. They exhibit a **reusable organization**: choose a surjection or collapse map $\pi : E \to B$, describe the fibers, state a minimal existence theorem as baseline, then—when it fits—strengthen the interface with surjectivity of π, existence of a (possibly classical) section, and canonical choices in fibers (Section 3). This appendix gives a step-by-step way to apply that organization to another problem, including problems that remain partly or fully open.

Scope. The workflow clarifies *where* a forgetful map and fiber structure appear, and whether a global right inverse is even available. It does not replace domain mathematics: restating a conjecture in fiber language rarely proves it. New ideas still come from the field; this pattern helps one see which lemmas would sit at the boundary between a coarse certificate and the data that varies above it.

Step 1: isolate the baseline theorem. Write the statement a working mathematician would accept as the minimal "obvious" layer: existence of representatives, existence of preimages under a surjection, or other standard representability. That statement is the floor; anything layered on top should imply it, not replace it.

Step 2: identify B, E, and π. Fix the set or type B of coarse certificates, a type E of richer structure, and a map $\pi : E \to B$ whose fibers describe what is not determined by the certificate alone. Use Table 13 and Section 16 as a menu: quotients and glueing, products and dependent sums, tags and subtypes, group or ideal quotients, localization via pairs, pullbacks, or—when π is not onto—the phenomenon illustrated by successor on the natural numbers (nonempty fibers only on the image, partial inverses instead of a global section).

Step 3: formalize the baseline in Lean. Prove or import the minimal facts in Mathlib style. If the aim is to check portability of the pattern *without* leaning on a large custom library, keep the formalization in a small standalone module that depends only on Mathlib (as in the benchmark files accompanying this paper).

Step 4: strengthen when possible. When π is surjective, it is often natural to record: nonempty fibers, surjectivity of π, existence of a right inverse in the sense of `HasRightInverse`, a concrete `RightInverse`, and a canonical element of each fiber (Section 3). When some of this fails, the failure is itself information: for example, there may be no global section, only restriction to a subdomain or a one-sided inverse (as with predecessor and successor). State that boundary case explicitly rather than forcing a full section bundle.

Step 5: open problems and partial progress. If the main theorem is still open, use the same decomposition to list separate conjectures: what belongs to the certificate layer, what belongs to fiber data, what would be a section or choice principle. Partial results can attach cleanly to one of these layers. Progress on a hard problem may then consist of proving a lemma at that interface—even when the headline claim remains open—rather than of relabeling the conjecture.

References

[1] N. Spivack. *Canonical Certification Does Not Exhaust Reflective Structure: Reflective Split, Strict Refinement, and Fiber Structure in Infinity Compression*. Manuscript, 2026. Companion LaTeX source: `papers/Canonical_Certification_and_Enriched_Reflective_Realization/`.

[2] N. Spivack. *Strata: Abstract Synthesis and Bridge Laws (Infinity Compression)*. Companion manuscript in preparation, 2026.

[3] Infinity Compression contributors. *EPIC_015_WV1 — External Proof Architecture Validation* (specification and validation verdict notes). `infinity-compression` repository, `specs/` tree, 2026.

[4] L. de Moura and S. Ullrich. The Lean 4 theorem prover and programming language. In *Automated Deduction — CADE 28*, volume 12699 of *Lecture Notes in Computer Science*, pages 625–635. Springer, 2021.

[5] The Mathlib community. The Lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP)*, pages 367–381, 2020. DOI: 10.1145/3372885.3373824. Mathlib 4 repository: https://github.com/leanprover-community/mathlib4.

[6] S. Mac Lane. *Categories for the Working Mathematician*, chapter I (categories of algebraic structures; universal constructions motivating quotients). Springer, 2nd edition, 1998.