

STAR H-232

All-in-One Commercial Storage

CATL LFP 280 Ah

115 kW | **232** kWh

Latest CATL battery technology

CATL is the world's leading battery manufacturer. Over 300 GWh of installed capacity without any safety-related incidents.

Compatible with Consolinno CEMS

For self-consumption optimization, peak shaving, dynamic electricity tariffs and the marketing of surplus capacity.

Scalable and long-lasting

Individually scalable system solution for industry and commerce. Extremely reliable and durable (≥ 10,000 cycles).

Support from our German team

Strong Energy accompanies you from project planning and sizing through to after-sales support.

Technical Data

Star H-232 · 115 kW / 232 kWh

BASICS	
Manufacturer	CNTE Star H-232
Inverter	YUNT MARS-125KT (derated to 115 kW)
Battery modules	CATL, 5 × 46.5 kWh (= 232.5 kWh)
Cells	CATL, 280 Ah
Architecture	1P52S5S

BATTERY MODULES	
Architecture	1P52S
Cell chemistry	LFP
Nominal voltage	166.4 VDC
Cycle life	10,000 cycles

OTHER	
Safety	Smoke detector, gas detector, pressure relief valve, aerosol fire suppression, flood valve
Certificates	VDE-AR-N 4105 / 4110
Communication	Modbus TCP
EMS	Compatible with Consolinno CEMS
Warranty	10 years
Scalability	Up to 12 systems in master/slave operation; freely scalable with switch (CEMS)

INVERTER	
DC INPUT	
Max. DC voltage	1,000 VDC
Min. DC voltage	580 VDC
Charge/discharge rate (C-rate)	0.5
AC INPUT / OUTPUT	
Rated power	115 kW
Max. power	115 kVA
Max. current	166 A
Nominal voltage	230 / 400 VAC
Frequency	50 / 60 Hz
Power factor	adjustable –1 to +1
GENERAL	
Temperature range[1]	–40 °C to +60 °C
Max. altitude above sea level	4,000 m
Weight	58 kg
Ingress protection[2]	IP20

DIMENSIONS AND WEIGHT	
Width	1,500 mm
Depth	1,300 mm
Height	2,050 mm
Weight	2,600 kg

1 Derating from +45 °C

2 Ingress protection: inverter = IP20 · power section of cabinet = IP54 · battery compartment = IP65

Subject to change and errors; all information without guarantee.