SF6012PLUS · LASER TUBE CUTTING MACHINE · 3 – 6 KW

SF6012PLUS
TECHNICAL SPECIFICATION

LASER TUBE CUTTING MACHINE









Ø0.4 – 4.7"	3.3 – 21.3 ft	240 rpm	1.5 G
ROUND TUBE	TUBE LENGTH	CHUCK SPEED	ACCELERATION

FULL TECHNICAL SPECIFICATION · SF6012PLUS · 3 – 6 KW

CONTENTS

01 · Model 03
02 · Technical parameters 04
03 · Precautions 05
04 · Clamping range 06
04 · Cutting parameters — carbon steel 07
05 · Cutting parameters — stainless steel, aluminum alloy 08
06 · Cost-benefit analysis 09
07 · Configuration list 10
08 · Laser source, laser head 11
09 · Chuck 12
10 · Host 13
11 · CNC system 14
12 – 13 · Optional units 15
14 · Automated metal fabrication solutions 17
15 · Personnel training, packaging and transportation 18
16 · Installation and customization 19
17 · Five-star fast service 20
18 · Customer testimonials 21

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

SOLD & SERVICED IN CANADA

by NovoTech Machine Tools — Mississauga, ON

01 · MODEL · LASER TUBE CUTTING MACHINE

SF6012PLUS

Versatile & efficient





Senfeng's campus in Jinan, China

1 SUPERIOR CUTTING STABILITY

2 ULTRA-HIGH CUTTING SPEED

3 AUTOMATED SYSTEM, MORE EFFICIENT

4 PRECISION PNEUMATIC CHUCK

5 OVER-POSITION CUTTING TO MINIMIZE TAIL LENGTH

**The picture is for reference; the actual appearance and size shall prevail.*

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

02 · TECHNICAL PARAMETERS

TECHNICAL PARAMETERS · SF6012PLUS

NO.	ITEM	PARAMETER	NOTE
1	**Tube length range**	3.3 – 21.3 ft (1,000 – 6,500 mm)	
2	**Tube diameter range**	Ø0.4 – 4.7″ (Ø10 – 120 mm)	National standard tube
3	**Side length of square tube**	□0.4 – 4.7″ (10 – 120 mm)	National standard tube
4	**X / Y axis positioning accuracy**	±0.002″ (±0.05 mm)	
5	**X / Y axis repeated positioning accuracy**	±0.001″ (±0.03 mm)	
6	**Maximum rapid speed**	492 ft/min (150 m/min)	As pipe weight increases, processing speed and moving parameters decrease.
7	**Maximum chuck speed**	240 rpm	
8	**Maximum acceleration**	1.5 G	
9	**Weight**	7,716 lb (3,500 kg)	Depends on actual factory delivery
10	**Maximum load**	265 lb (120 kg)	
11	**Dimensions**	29.9 × 7.3 × 7.5 ft (9,100 × 2,230 × 2,300 mm)	
12	**Phase**	Three-phase	
13	**Power supply rated voltage**	380 V — in Canada: 208 / 240 / 480 / 600 V 3-phase 60 Hz through the transformer NovoTech supplies	
14	**Frequency**	50 Hz	
15	**Power supply protection grade**	IP54	

1. The achievable accuracy of the workpiece depends to some extent on factors such as workpiece type, surface, tube specifications and straightness.

2. The technical parameters above are subject to change without notice; the final technical parameters are subject to the order agreement.

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**








03 · TECHNICAL PARAMETERS

PRECAUTIONS · SF6012PLUS

1. Pipes being processed should be free from significant rust, as it can affect the cutting section quality.
2. Pipes should not be stored in the open air and should be placed flat, preferably with a surface oil coating or packaging. Ensure that the front end is even and the burr height at both ends is ≤0.20" (5 mm). Bundled pipes should have consistent lengths, with a deviation of less than 11.8" (300 mm).
3. For welded pipes, the external weld seam should be relatively flat, with a height of less than 0.012" (0.3 mm). The internal weld seam should have a height of less than 0.08" (2 mm).
4. The distortion and bending of the pipe should be lower than the tolerances specified in "GB/T 6728-2002 Dimensions, Shape, Weight, and Permissible Deviations of Cold-formed Hollow Sections for Structural Use."
5. The pipe should be straight, with a bending curvature of less than 0.012" per ft (1 mm/1 m; 3 mm over 6 m).
6. For the lengthwise torsion of the pipe, the total torsion should be less than 0.02 % of the total length.
7. The outer diameter tolerance of the profile should not exceed ±0.5 % of the outer diameter, with a minimum of 0.008" (0.2 mm)(according to the standard deviation level D4 specified in GB/T 17395-1998 for standardized outer diameter deviations).
8. When loading the pipes, ensure the safety of personnel and equipment. Bundle loading should be carried out using cranes operated by qualified and certified professionals. The crane should have both fast and slow speed functions, and slow speed should be used when approaching the loading platform.
9. Considering material errors, the positional error should be within IT12, and the shape and profile error should be within IT12.
10. The surface roughness of the pipe cross-section varies with the material and thickness.
11. Users must perform regular maintenance of the machine as instructed in the manual. Failure to do so may result in damage to the machine, and the manufacturer reserves the right to refuse repairs in such cases.
12. To ensure cutting effectiveness and minimize pipe deformation, the pipe wall thickness should meet the following criteria based on the pipe diameter:
    1. For pipe diameters greater than Ø2" (Ø50 mm): 1/40 ≤ wall thickness ≤ 1/10 of the pipe diameter.
    2. For pipe diameters smaller than Ø2" (Ø50 mm): 0.031" (0.8 mm) ≤ wall thickness ≤ 1/10 of the pipe diameter.
    3. Where the bending deflection exceeds the relevant standards, the cutting quality cannot be guaranteed.
13. Equipment temperature requirements: 32 – 104 °F (0 – 40 °C)(if the ambient temperature at the installation site exceeds this range, the buyer shall give written notice to the supplier at the time of purchase); the laser source should be placed in an environment of 64 – 77 °F (18 – 25 °C). If the ambient temperature at the installation site exceeds this range, air conditioning is recommended.
14. Equipment humidity requirements: ≤70 % (laser source only).
15. Cutting gas purity requirements: nitrogen ≥99.7 %; oxygen ≥99.5 %.

04 · CUTTING PARAMETERS

CLAMPING RANGE · SF6012PLUS

TYPE	CROSS-SECTION	CLAMPING RANGE
Round tube		Ø0.4 – 4.7″ (Ø10 – 120 mm)
Square tube		□0.4 – 4.7″ (10 – 120 mm)
Rectangular tube		0.4″ (10 mm) ≤ diagonal ≤ 4.7″ (120 mm)
I-beam		≤ GB No. 8
H-beam		≤ GB No. 8 (customized)
Channel steel		≤ GB No. 8
Equal angle steel		≤ GB No. 8
Unequal angle steel		≤ GB No. 9/5
Load capacity		265 lb (120 kg)

Clamping ranges of the SF6012PLUS by section, as given in Senfeng's cutting parameters.

04 · CUTTING PARAMETERS · SF6012PLUS

CARBON STEEL

Cutting speed by laser source power in inches per minute, with Senfeng's metres per minute and the assist gas below each value.

Material	Wall thickness	3 kW	6 kW
CARBON STEEL	**0.039″** 1 mm	984 – 1,378 25 – 35 · N_2 / air	1,181 – 1,772 30 – 45 · N_2 / air
	0.079″ 2 mm	512 – 669 13 – 17 · N_2 / air	787 – 984 20 – 25 · N_2 / air
	0.118″ 3 mm	276 – 394 7 – 10 · N_2 / air	472 – 551 12 – 14 · N_2 / air
	0.157″ 4 mm	197 – 315 5 – 8 · N_2 / air	276 – 315 7 – 8 · N_2 / air
	0.197″ 5 mm	118 – 126 3 – 3.2 · O_2	197 – 236 5 – 6 · N_2 / air
	0.236″ 6 mm	91 – 98 2.3 – 2.5 · O_2	177 – 197 4.5 – 5 · N_2 / air
	0.315″ 8 mm	71 – 87 1.8 – 2.2 · O_2	87 – 98 2.2 – 2.5 · O_2
	0.394″ 10 mm	55 – 71 1.4 – 1.8 · O_2	79 – 91 2.0 – 2.3 · O_2
	0.472″ 12 mm	39 – 55 1 – 1.4 · O_2	75 – 83 1.9 – 2.1 · O_2
	0.551″ 14 mm	/	55 – 67 1.4 – 1.7 · O_2
	0.630″ 16 mm	/	47 – 55 1.2 – 1.4 · O_2
	0.709″ 18 mm	/	31 0.8 · O_2
	0.787″ 20 mm	/	/

1. For carbon steel pipes with a wall thickness over 0.197″ (5 mm) and a diameter or side length under 2″ (50 mm), oxygen is not recommended as the assist gas. Contact us for such pipe sizes.

2. There are two types of cutting heads: ① the standard cutting head cuts regular pipes such as square, round, elliptical and triangular pipes without concave angles; ② the PC cutting head makes a significant difference in cutting speed and quality on carbon steel pipes of 0.236″ (6 mm) and thicker — the speed is reduced by 20 – 40 %, but it can process pipes of any shape.

3. Parameters are for reference only. The values above are theoretical; the actual cutting speed may vary with factors such as pipe dimensions and equipment speed.

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

05 · CUTTING PARAMETERS · SF6012PLUS

STAINLESS STEEL · ALUMINUM ALLOY

Cutting speed by laser source power in inches per minute, with Senfeng's metres per minute and the assist gas below each value.

Material	Wall thickness	3 kW	6 kW
STAINLESS STEEL	0.039″ 1 mm	984 – 1,378 25 – 35 · N_2 / air	1,181 – 1,772 30 – 45 · N_2 / air
	0.079″ 2 mm	512 – 669 13 – 17 · N_2 / air	787 – 984 20 – 25 · N_2 / air
	0.118″ 3 mm	236 – 394 6 – 10 · N_2 / air	472 – 709 12 – 18 · N_2 / air
	0.157″ 4 mm	197 – 236 5 – 6 · N_2 / air	394 – 472 10 – 12 · N_2 / air
	0.197″ 5 mm	118 – 157 3 – 4 · N_2 / air	276 – 315 7 – 8 · N_2 / air
	0.236″ 6 mm	91 – 118 2.3 – 3 · N_2 / air	177 – 197 4.5 – 5 · N_2 / air
	0.315″ 8 mm	39 – 59 1.0 – 1.5 · N_2 / air	98 – 138 2.5 – 3.5 · N_2 / air
	0.394″ 10 mm	31 – 39 0.8 – 1 · N_2 / air	47 – 79 1.2 – 2 · N_2 / air
	0.472″ 12 mm	/	39 – 47 1 – 1.2 · N_2 / air
	0.551″ 14 mm	/	31 – 39 0.8 – 1 · N_2 / air
	0.630″ 16 mm	/	20 – 24 0.5 – 0.6 · N_2 / air
ALUMINUM ALLOY	0.039″ 1 mm	984 – 1,378 25 – 35 · N_2 / air	1,181 – 1,772 30 – 45 · N_2 / air
	0.079″ 2 mm	512 – 669 13 – 17 · N_2 / air	787 – 984 20 – 25 · N_2 / air
	0.118″ 3 mm	236 – 315 6 – 8 · N_2 / air	551 – 630 14 – 16 · N_2 / air
	0.157″ 4 mm	157 – 197 4 – 5 · N_2 / air	315 – 394 8 – 10 · N_2 / air
	0.197″ 5 mm	98 – 138 2.5 – 3.5 · N_2 / air	197 – 236 5 – 6 · N_2 / air
	0.236″ 6 mm	79 – 91 2 – 2.3 · N_2 / air	138 – 157 3.5 – 4 · N_2 / air
	0.315″ 8 mm	31 – 51 0.8 – 1.3 · N_2 / air	59 – 79 1.5 – 2 · N_2 / air
	0.394″ 10 mm	/	39 – 47 1 – 1.2 · N_2 / air
	0.472″ 12 mm	/	24 – 28 0.6 – 0.7 · N_2 / air
	0.551″ 14 mm	/	16 – 24 0.4 – 0.6 · N_2 / air

1. For carbon steel pipes with a wall thickness over 0.197″ (5 mm) and a diameter or side length under 2″ (50 mm), oxygen is not recommended as the assist gas. Contact us for such pipe sizes.

2. There are two types of cutting heads: ① the standard cutting head cuts regular pipes such as square, round, elliptical and triangular pipes without concave angles; ② the PC cutting head makes a significant difference in cutting speed and quality on carbon steel pipes of 0.236″ (6 mm) and thicker — the speed is reduced by 20 – 40 %, but it can process pipes of any shape.

3. Parameters are for reference only. The values above are theoretical; the actual cutting speed may vary with factors such as pipe dimensions and equipment speed.

06 · COST-BENEFIT ANALYSIS

COST-BENEFIT ANALYSIS · SF6012PLUS

If the cutting auxiliary gas is dried compressed air, the cost includes the air compressor's electricity, the machine's power consumption and the consumables (protective lenses, cutting nozzles).

Item		3 kW			6 kW		
		Air	O_2	N_2	Air	O_2	N_2
PEAK POWER CONSUMPTION	Laser source (kW)	10			18.5		
	Chiller (kW)	3.5			8.4		
	Air compressor (kW)	22	/	/	22	/	/
	Host (kW)	16.7	16.7	16.7	16.7	16.7	16.7
	Dust removal (kW)	1.5	1.5	1.5	1.5	1.5	1.5
	Semi-automatic loading (kW)	1.5	1.5	1.5	1.5	1.5	1.5
Consumables and gas consumption (CNY/h)		0.5	4.5	60.5	0.5	4.5	60.5
Total power (kW)		55.2	33.2	33.2	68.6	46.6	46.6
Total power consumption (kWh per hour)		33.12	19.92	19.92	41.16	27.96	27.96
Total operating cost (RMB per hour, at 1 RMB/kWh)		33.62	24.42	80.42	41.66	32.46	88.46

1. The electricity and gas prices are Senfeng's reference values in China (RMB) and may vary by region.

2. Auxiliary gas consumption varies with plate thickness. The oxygen data is based on cutting 0.315″ (8 mm) carbon steel and nitrogen on 0.039″ (1 mm) stainless steel; for reference only, actual usage may vary.

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

07 · CONFIGURATION LIST

CONFIGURATION LIST · SF6012PLUS

NO.	ITEM	QTY	BRAND
	LASER SOURCE		
1	Laser source	1	Raycus
	LASER CUTTING HEAD		
1	Laser cutting head	1	BOCI
	MACHINE TOOL & HOST		
1	Transmission system	8	SENFENG
2	Machine tool and accessories	1	SENFENG
3	Reducer	6	TECHMECH
4	Electrical and pneumatic systems	1	SCHNEIDER (France) · SMC (Japan) & AIRTAC (Taiwan)
5	AC servo motor and driver	8	INOVANCE
6	Water chiller	1	TONGFEI
	CNC SYSTEM		
1	CNC system	1	FSCUT 3000DE
	OPTIONAL AUTOMATION SYSTEM		
1	Loading system	1	Optional: fully automatic / basic fully automatic / semi-automatic
2	Unloading system	1	Standard: 6.6 ft (2 m) · customizable: 10 ft (3 m) / 13 ft (4 m)

1. This is Senfeng's optimized configuration. Changes in brand or configuration may cause irreversible effects.

2. The warranty period for the entire machine (excluding consumables, non-force majeure natural disasters, war, improper operation, and human damage) is 1 year.

08 · CORE COMPONENTS

LASER SOURCE · LASER HEAD


SF6012PLUS LASER SOURCE



Raycus RFL-C3000 fiber laser source

1. **Small fiber core:** better beam quality.
2. **Faster cutting speed:** enhanced cutting efficiency.
3. **Improved high-reflection resistance:** new optical components with a multi-layer anti-reflection design for efficient processing of various metals.
4. **Enhanced intelligence:** next-generation software with a smart app mode for real-time monitoring.
5. **High electrical-optical conversion:** over 40 % efficiency, reducing power consumption.
6. **Upgraded components:** new-generation pump sources offer greater reliability and stability, with improved beam quality and 30 – 40 % more brightness thanks to patented nonlinear suppression technology.
7. **Lightweight and compact:** small size and compact design for easier integration.
8. **Enhanced safety:** improved safety features.

SF6012PLUS LASER HEAD




1. **Collision protection for the cutting head:** the collision component is replaced directly, without replacing the cutting head, reducing the likelihood of returns.
2. **Protective lens temperature monitoring:** if contamination is detected during operation, the system immediately raises an alarm and stops the machine to prevent damage to the head or lenses.
3. **Cutting pressure monitoring:** gas pressure is monitored continuously; an alarm is raised at once if it is insufficient, too low or unstable.
4. **Protective lens explosion detection:** the stray light on the protective lens is monitored continuously, with an alarm when it exceeds the threshold.
5. **Pan seal failure detection:** the gas pressure in the lower 1 and lower 2 protective lens chambers is monitored continuously for stable production.
6. **Process monitoring:** automatically re-cuts if the material isn't fully cut through.

09 · CORE COMPONENTS

SF6012PLUS CHUCK



Chuck for straight cutting



Bevel cutting chuck

1. Pneumatic self-centering chuck with high clamping accuracy for more precise cutting.
2. Fast clamping, with gear-driven self-centering for high efficiency.
3. High-precision chuck with good dust-proof performance and a low maintenance frequency.
4. The chuck's tube holding capacity reaches 265 lb (120 kg) — designed for ultra-high-precision cutting of small tubes.
5. The front chuck has a square structure, allowing a wider range of clamping sizes for square and rectangular tubes.
6. Dual-row roller configuration for more stable tube clamping.


INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

10 · HOST MACHINE

SF6012PLUS HOST







1 · Machine bed

1. The bed is welded from rectangular tubes, giving better stability, load capacity, vibration damping and performance.
2. The bed is designed with structural dynamic principles and finite-element variable analysis. After precise welding, stress-relief annealing, secondary aging treatment and precision machining on a large gantry milling machine, it has high rigidity and a long service life.

2 · Follow support

1. Servo control automatically aligns the tube center with the chuck center, ensuring constant contact with the tube surface for more precise lifting movements.
2. The intelligent segmented layout keeps long tubes from sagging, ensuring higher machining accuracy.





3 · Ultra-short tail material

1. **Dimensions:** round tube Ø0.4 – 4.7″ (Ø10 – 120 mm); square tube 0.4 × 0.4 – 4.7 × 4.7″ (10 × 10 – 120 × 120 mm).
2. **Tube types:** round, square and rectangular tubes.
3. The “over-position” cutting process gives an ultra-short tail, making Senfeng one of the few makers of dual-chuck laser tube cutting machines that minimize tail material.

4 · Powerful dynamic performance

A brand-new laser tube cutting machine, offering ultra-high performance matched with high precision to meet customer needs.

11 · CNC SYSTEM

FSCUT3000DE CNC SYSTEM



Quick operation & efficient cutting

FSCUT3000DE is a bus control system specifically designed for processing pipes with a diameter of 4.7" (120 mm) or less. It supports cutting square, round, racetrack-shaped and elliptical tubes with high precision and efficiency. Its key features include:

- Real-time tube center deviation compensation reduces clamping requirements, improves efficiency and enhances piercing accuracy.
- A bus-based real-time system with integrated follow control gives faster corner cutting, more stable following and more reliable cutting quality.
- The support-following function ensures the processing quality of the whole tube.
- Hollow chuck feeding and cutting significantly shortens the overall length of the tube cutting machine, with high automation.
- Supports automatic loading and unloading, continuous processing and standard automated feeding actions.
- Track accuracy 0.0008" (0.02 mm), positioning accuracy 0.00004" (0.001 mm), repeated positioning accuracy 0.0001" (0.003 mm).
- Supports bevel cutting with automatic focusing.
- A pipe process library for easy process export and storage.
- Contactless piercing makes cutting smoother and improves efficiency.
- Compatible with the TubePro cutting software and the TubesT small-tube nesting software.

12 · OPTIONAL UNITS

SF6012PLUS OPTIONAL UNITS

1 · UNLOADING UNIT optional



Dimensions	78.7 × 44.1 × 31.5″ (2,000 × 1,120 × 800 mm)
Maximum tube length	9.8 ft (3,000 mm)

1. The material separation system automatically separates waste from finished tubes without manual intervention; the receiving cart and drop rack are one integrated structure — high integration and space saving.
2. Servo control automatically aligns the tube center with the chuck center so tube sag does not affect machining accuracy. After processing, the plate flips and the finished product slides into the material cart.

2 · FULLY AUTOMATIC LOADING UNIT standard



Tube length	14.8 – 21.3 ft (4,500 – 6,500 mm)
Side length (or diameter) of tube section	0.8 × 0.8 – 4.7 × 4.7″ (20 × 20 – 120 × 120 mm); Ø0.8 – 4.7″ (Ø20 – 120 mm)
Max. load of a single tube	265 lb (120 kg)
Warehouse load bearing	4,409 lb (2 t)


INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

13 · OPTIONAL UNITS

SF6012PLUS OPTIONAL UNITS


3 · BEVEL CUTTING UNIT optional



Chuck diameter	4.7″ (120 mm)
Maximum swing angle	±45°

Suitable for precision bevel cutting of small-diameter tubes. Paired with a high-precision oscillating axis, it improves cutting stability and cuts bevels up to ±45°.

4 · AUTOMATIC SLAG REMOVAL UNIT optional



Maximum tube length	19.7″ (500 mm)
Side length (or diameter) of pipe section	0.8 × 0.8 – 4.7 × 4.7″ (20 × 20 – 120 × 120 mm); Ø0.8 – 4.7″ (Ø20 – 120 mm)

This system effectively reduces the slag left inside the tube, eliminating secondary processing.


INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

14 · AFTER-SALES SERVICE

PROVIDING GLOBAL USERS WITH AUTOMATED METAL FABRICATION SOLUTIONS

Senfeng provides automated metal fabrication solutions globally, integrating cutting, bending, welding, cladding, automation and new energy. With core technologies in laser cutting, welding and cladding, the company also offers intelligent manufacturing systems such as flexible laser processing lines and panel benders. These solutions serve industries including automotive, construction, energy and petrochemicals, and are used in over 100 countries.



03
INTERNATIONAL PCT PATENTS

577
CHINESE TECHNOLOGY PATENTS

Senfeng has developed key components such as laser generators, processing heads, the Feng Cloud system and CNC systems, used in cutting, welding, cladding and automation. The company offers a complete industry chain, including laser cutting, welding, cladding and cleaning machines, bending centers and flexible production lines. These solutions are used in sectors such as power towers, construction machinery, shipbuilding, bridges and aerospace, helping businesses accelerate production and reduce costs for greater economic benefit.

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**

15 · AFTER-SALES SERVICE

TRAINING · PACKAGING · INSTALLATION

TECHNICAL TRAINING TO ENHANCE CUSTOMER PRODUCTION EFFICIENCY

01 BEFORE EQUIPMENT DELIVERY

The buyer can arrange for 1 – 2 operators to attend a one-week training at the Senfeng factory. The dates are confirmed with Senfeng's customer service department.

02 DURING THE WARRANTY PERIOD

The buyer can apply for one more session of free training for 1 – 2 operators at Senfeng.

03 TRAINING

Laser principles, equipment structure, process explanation, equipment maintenance, laser safety protection, operating procedures and basic troubleshooting.

04 REQUIREMENT

Trainees must be mechanical, electrical or optical engineers and pass assessments on equipment operation, laser principles, safety and maintenance before starting work.

PACKAGING & TRANSPORTATION TO ENSURE EQUIPMENT QUALITY







01 PACKAGING

Standard packaging, suitable for long-distance transportation, moisture-proof, rust-proof and shock-resistant. Designed for full lifting, with marked lifting points and center of gravity.

02 TRANSPORTATION

Domestic transportation within China is fully handled by Senfeng, including freight and insurance.

03 PACKING LIST & CERTIFICATE

Each package includes a packing list and a certificate of conformity. The user manual and other documents are inside the box; the packing list is on the outside.

INSTALLATION PROFESSIONAL AND HIGH-QUALITY

01 INSTALLATION

NovoTech engineers, with Senfeng, install the equipment at the customer's site.

02 EQUIPMENT DEBUGGING

After installation, the equipment is debugged for the customer's use.

03 DOOR-TO-DOOR TRAINING

On-site training on equipment maintenance, safety, operating procedures and basic troubleshooting, with 7 days of guaranteed usage.

04 ON-SITE ACCEPTANCE

After the steps above, the engineer leaves the site only after the customer's acceptance (the customer can veto).

16 · AFTER-SALES SERVICE

PREMIUM CUSTOMIZATION


In the digital era, intelligent transformation in metal processing is essential. Building unmanned factories is key to upgrading, with customized automation solutions a top priority.



01 · Senfeng understands the client's industry status and specific production processes, identifies issues and assesses their needs.



02 · Through in-depth on-site communication, metal fabrication automation solutions are customized to the client's pain points and needs.



03 · A tailored solution, different from competitors' standardized models.



04 · A one-stop R&D and production service from design to final machine, with thorough quality checks until customer satisfaction and acceptance.

INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**


17 · AFTER-SALES SERVICE

FIVE-STAR FAST SERVICE



EFFICIENT

- Senfeng's repair hotline is available 24/7.
- A professional engineer responds to customer inquiries within 10 minutes and provides a repair plan within 1 hour.



PROFESSIONAL

- **Custom service:** service plans tailored to the customer's specific needs.
- **Service engineer certification:** each service engineer is rigorously trained and assessed before being certified to work.
- **Common issues training:** a manual of common issues for each equipment model, with certified engineers training customers.
- **Online guidance:** experienced senior engineers support customers by phone or video call.
- **Professional technical support:** the equipment is properly calibrated at the first installation, and similar issues are resolved in one go.





COMPREHENSIVE

- **Pre-service:** theoretical and hands-on operation training, common fault self-diagnosis training, quick repair guidance and usage reminders.
- **Regular service:** regular maintenance reminders, on-site services and periodic promotional activities.
- **Value-added service:** equipment software and hardware upgrades, financing lease services and extended warranty services.



18 · AFTER-SALES SERVICE

CUSTOMER TESTIMONIALS

Senfeng machines and customers around the world.




















NovoTech MACHINE TOOLS Inc.

LET'S FIND THE RIGHT TUBE LASER FOR YOUR SHOP.

Call or visit us for quotes, demonstrations, installation and service. In-stock machines ship fast from our Mississauga, ON location.

PHONE

+1 647 526 5510

WEB & EMAIL

NovoTechMachineTools.com
info@NovoTechMachineTools.com

ADDRESS


1365 Mid-Way Blvd, 26
Mississauga, ON L5T 2J5
Canada


INCLUDED WITH EVERY NOVOTECH MACHINE

- Made in China by Senfeng Laser — CE, FDA and ETL certified and CSA approved
- CSA-approved electrical panel
- 1-year warranty
- **7-day money-back guarantee** (in-stock machines only)
- Spare parts & technical support readily available in Canada
- **Order Today with Just 10% Down — 0% Down Financing Available**
- **Installation and training available**









Specifications subject to change without notice. Imperial values are converted from Senfeng's metric data and rounded: sheet thicknesses in decimal inches, cutting speeds in inches per minute. Model numbers are manufacturer designations. Photos may show optional equipment.